



TEST REPORT

Report Reference No.....	TRE1607018201	R/C.....: 90529
FCC ID.....	2AEKCPR800VHF	
Applicant's name.....	ZTE TRUNKING TECHNOLOGY CORPORATION	
Address.....	4/F, R&D Building 1, ZTE Industrial Park, LiuXian Road, Xili, Nanshan District, Shenzhen, P. R. China	
Manufacturer.....	ZTE TRUNKING TECHNOLOGY CORPORATION	
Address.....	4/F, R&D Building 1, ZTE Industrial Park, LiuXian Road, Xili, Nanshan District, Shenzhen, P. R. China	
Test item description	DIGITAL REPEATER	
Trade Mark	ZTE	
Model/Type reference.....	PR800 VHF	
Listed Model(s)	-	
Standard	FCC Part 90/FCC Part 15B/ FCC Part 2	
Date of receipt of test sample.....	July 27, 2016	
Date of testing.....	July 28, 2016 –September 28, 2016	
Date of issue.....	September 28, 2016	
Result.....	PASS	
Compiled by (position+printed name+signature)...	File administrators Shayne Zhu	
Supervised by (position+printed name+signature)...	Project Engineer Cary Luo	
Approved by (position+printed name+signature)...	RF Manager Hans Hu	
Testing Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Address.....	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.		
This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.		

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Test frequency list	6
3.4.	EUT operation mode	6
3.5.	EUT configuration	6
<u>4.</u>	<u>TEST ENVIRONMENT</u>	<u>7</u>
4.1.	Address of the test laboratory	7
4.2.	Test Facility	7
4.3.	Environmental conditions	8
4.4.	Statement of the measurement uncertainty	8
4.5.	Equipments Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1.	Maximum Transmitter Power	11
5.2.	Occupied Bandwidth	14
5.3.	Emission Mask	17
5.4.	Modulation Limit	19
5.5.	Audio Frequency Response	21
5.6.	Frequency Stability Test	23
5.7.	Transmitter Frequency Behaviour	27
5.8.	Spurious Emission on Antenna Port	30
5.9.	Transmitter Radiated Spurious Emission	32
5.10.	Conducted Emissions Test	36
5.11.	Radiated Emission	39
<u>6.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>43</u>
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>44</u>

1. **TEST STANDARDS AND REPORT VERSION**

1.1. **Test Standards**

The tests were performed according to following standards:

[FCC Rules Part 90: 2016](#) Private land mobile radio services.

[TIA/EIA 603 D: June 2010](#) Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

[FCC Part 15 Subpart B: 2016](#) Unintentional Radiators

[FCC Part 2: 2014](#) Frequency allocations and radio treaty matters, general rules and regulations.

[KDB579009 D03 v01:](#) Applications Part 90 Refarming Bands

1.2. **Report version**

Version No.	Date of issue	Description
00	September 28, 2016	Original
01	October 12, 2016	New
02	October 13, 2016	New

2. TEST DESCRIPTION

Transmitter Requirement			
Test item	Standards requirement	Result	
		Pass	N/A
Maximum Transmitter Power	FCC Part 90.205, FCC Part 2.1046	<input checked="" type="checkbox"/>	
Modulation Characteristic	FCC Part 90.207, FCC Part 2.1047	<input checked="" type="checkbox"/>	
Occupied Bandwidth	FCC Part 90.209, FCC Part 90.210, FCC Part 2.1049	<input checked="" type="checkbox"/>	
Emission Mask	FCC Part 90.209, FCC Part 90.210, FCC Part 2.1049	<input checked="" type="checkbox"/>	
Frequency Stability	FCC Part 90.213, FCC Part 2.1055	<input checked="" type="checkbox"/>	
Transmitter Frequency Behavior	FCC Part 90.214	<input checked="" type="checkbox"/>	
Transmitter Radiated Spurious Emission	FCC Part 90.210, FCC Part 2.1053	<input checked="" type="checkbox"/>	
Spurious Emission On Antenna Port	FCC Part 90.210, FCC Part 2.1051	<input checked="" type="checkbox"/>	
Receiver Requirement			
Test item	Standards requirement	Result	
		Pass	N/A
Conducted Emission	FCC Part 15.107	<input checked="" type="checkbox"/>	
Radiated Emission	FCC Part 15.109	<input checked="" type="checkbox"/>	

3. SUMMARY

3.1. Client Information

Applicant:	ZTE TRUNKING TECHNOLOGY CORPORATION
Address:	4/F, R&D Building 1, ZTE Industrial Park, LiuXian Road, Xili, Nanshan District, Shenzhen, P. R. China
Manufacturer:	ZTE TRUNKING TECHNOLOGY CORPORATION
Address:	4/F, R&D Building 1, ZTE Industrial Park, LiuXian Road, Xili, Nanshan District, Shenzhen, P. R. China

3.2. Product Description

Name of EUT:	DIGITAL REPEATER	
Trade mark:	ZTE	
Model/Type reference:	PR800 VHF	
Listed mode(s):	-	
Power supply:	DC Power: DC 13.6V, or AC Power: AC 120V/60Hz	
Battery information:	-	
Charger information:	-	
Adapter information:	-	
Operation Frequency Range:	From 136MHz to 174MHz	
Rated Output Power:	High Power: 45 W (46.53dBm)/Low Power: 25W (43.98dBm)	
Modulation Type:	Analog Voice:	FM
	Digital Voice /Digital Data:	4FSK
Digital Type:	DMR	
Channel Separation:	Analog Voice:	<input checked="" type="checkbox"/> 12.5kHz
	Digital Voice /Digital Data:	<input checked="" type="checkbox"/> 12.5kHz <input type="checkbox"/> 6.25kHz
Emission Designator:	Analog Voice:	<input checked="" type="checkbox"/> 12.5kHz Channel Separation: 6K88F3E <input type="checkbox"/> 25kHz Channel Separation: ---
	Digital Voice& Data:	<input checked="" type="checkbox"/> 12.5kHz Channel Separation: 7K80FXW <input type="checkbox"/> 6.25kHz Channel Separation: ---
	Digital Data:	<input checked="" type="checkbox"/> 12.5kHz Channel Separation: 7K80FXD <input type="checkbox"/> 6.25kHz Channel Separation: ---
Support data rate:	9.6kbps	
Antenna Type:	External	
Maximum Transmitter Power:	Digital	46.24W for 12.5kHz Channel Separation
	Analog	45.81W for 12.5kHz Channel Separation

Note:

- 1)The product has the same digital working characters when operating in both two digitized voice/data mode. So only one set of test results for digital modulation modes are provided in this test report.
- 2)This equipment is capable of supporting a minimum data rate of 4800 bits per second per 6.25 kHz of channel bandwidth. DMR interphone's bandwidth is 12.5 kHz, and it has a double time slot, one is the speech time slot, one is the data time slot, just language sequence is satisfied with 4800 bps/6.25 kHz BW.

3.3. Test frequency list

Mode	Modulation	Operation Frequency Range (MHz)	Test Frequency (MHz)
Analog	FM	136-174	CH _L 150.0125
			CH _M 162.0000
			CH _H 173.9875
Digital	4FSK	136-174	CH _L 150.0125
			CH _M 162.0000
			CH _H 173.9875

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above listed frequency for testing.

3.4. EUT operation mode

Test mode	Transmitting	Receiving	Power level		Digital	Analog	GPS
			High	Low	12.5kHz	12.5kHz	
TX1	✓		✓		✓		
TX2	✓			✓	✓		
TX3	✓		✓			✓	
TX4	✓			✓		✓	
RX1		✓					✓

✓: is operation mode.

3.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

●	Power Cable	Length (m) :	3m
		Shield :	Unshielded
		Detachable :	Undetachable
○	Multimeter	Manufacturer :	/
		Model No. :	/

4. TEST ENVIRONMENT

4.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd.

Address: 1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Phone: 86-755-26748019 Fax: 86-755-26748089

4.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

A2LA-Lab Cert. No. 3902.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until December 31, 2016.

FCC-Registration No.: 317478

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date Jul. 18, 2014, valid time is until Jul. 18, 2017.

IC-Registration No.: 5377A&5377B

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

Two 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on Dec.03, 2014, valid time is until Dec.03, 2017.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

4.3. Environmental conditions

Normal Condition	
Relative humidity:	20 % to 75 %.
Air Pressure:	950~1050mba
Voltage:	AC 120V/60Hz, or DC 13.6V

4.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Frequency stability	25 Hz	(1)
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.65 dB	(1)
Radiated Emission 1~18GHz	5.16 dB	(1)
Radiated Emission 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)
Emission Mask	-----	(1)
Modulation Characteristic	-----	(1)
Transmitter Frequency Behavior	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

4.5. Equipments Used during the Test

Conducted Emission				
Name of Equipment	Manufacturer	Model	Serial Number	Last Cal.
Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2015/11/2
EMI Test Receiver	Rohde&Schwarz	ESCS 30	100038	2015/11/2
Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2015/11/2
EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	2015/11/2
Artificial Mains	Rohde&Schwarz	ESH3-Z6	100210	2015/11/2
Artificial Mains	Rohde&Schwarz	ESH3-Z6	100211	2015/11/2

Modulation Characteristic				
Name of Equipment	Manufacturer	Model	Serial Number	Last Cal.
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	2015/11/2

Frequency Stability				
Name of Equipment	Manufacturer	Model	Serial Number	Last Cal.
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	2015/11/2
Signal Generator	Rohde&Schwarz	SMT03	100059	2015/11/2
Climate Chamber	ESPEC	EL-10KA	05107008	2015/11/2

Transmitter Radiated Spurious Emission				
Name of Equipment	Manufacturer	Model	Serial Number	Last Cal.
Ultra-Broadband Antenna	Rohde&Schwarz	HL562	100015	2015/11/2
EMI Test Receiver	Rohde&Schwarz	ESI 26	100009	2015/11/2
RF Test Panel	Rohde&Schwarz	TS / RSP	335015/ 0017	N/A
HORN ANTENNA	Rohde&Schwarz	HF906	100039	2015/12/2
Turntable	ETS	2088	2149	N/A
Antenna Mast	ETS	2075	2346	N/A
EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	2015/11/2
Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2015/11/2
Ultra-Broadband Antenna	ShwarzBeck	VULB9163	539	2015/11/2
HORN ANTENNA	ShwarzBeck	9120D	1012	2015/11/2
HORN ANTENNA	ShwarzBeck	9120D	1011	2015/11/2
TURNTABLE	MATURO	TT2.0	----	N/A
ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A

Maximum Transmitter Power & Spurious Emission On Antenna Port & Occupied Bandwidth & Emission Mask				
Name of Equipment	Manufacturer	Model	Serial Number	Last Cal.
Receiver	Rohde&Schwarz	ESI 26	100009	2015/11/2
Attenuator	R&S	ESH3-22	100449	2015/11/2
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	2015/11/2
Digital Radio Test Set	AEROFLEX	3920	299001967	2015/11/2
High-Pass Filter	Anritsu	MP526B	6220875256	2015/11/2
High-Pass Filter	Anritsu	MP526D	6220878392	2015/11/2
Spectrum Analyzer	Agilent	E4407B	MY44210775	2015/11/2
Spectrum Analyzer	Rohde&Schwarz	FSP40	1164.4391.40	2015/11/2
SPECTRUM ANALYZER	Agilent	E4407B	MY44210775	2015/11/2

Transient Frequency Behavior				
Name of Equipment	Manufacturer	Model	Serial Number	Last Cal.
Signal Generator	Rohde&Schwarz	SMT03	100059	2015/11/2
Storage Oscilloscope	Tektronix	TDS3054B	B033027	2015/11/2
RF COMMUNICATION TEST SET	HP	8920A	3813A10206	2015/11/2

The calibration interval was one year.

5. TEST CONDITIONS AND RESULTS

5.1. Maximum Transmitter Power


Applicants for licenses must request and use no more power than the actual power necessary for satisfactory operation.

LIMIT

FCC Part 90.205, FCC Part 2.1046

Maximum ERP is dependent upon the station's antenna HAAT and required service area. The output power shall be within ± 1 dB of the manufacturer's rated power listed in the equipment specifications.

TEST CONFIGURATION



TEST PROCEDURE

- 1 Connect the equipment as test configuration
- 2 Measurements shall be made to establish the radio frequency power delivered by the transmitter the standard output termination.
- 3 The power output shall be monitored and recorded and no adjustment shall be made to the transmitter after the test has begun, except as noted below:
If the power output is adjustable, measurements shall be made for the highest and lowest power levels.

TEST MODE:

Please reference to the section 3.4

TEST RESULTS

Passed **Not Applicable**

AC 120V/60Hz		Conducted output power			
Operation Mode	Test Frequency (MHz)	Measured power (dBm)	Difference (dB)	Limit (dB)	Result
TX1	150.0125	46.65	0.12	-1 ~ +1	Pass
	162	46.59	0.06		
	173.9875	46.49	-0.04		
TX2	150.0125	44.08	0.10	-1 ~ +1	Pass
	162	44.03	0.05		
	173.9875	44.01	0.03		
TX3	150.0125	46.61	0.08	-1 ~ +1	Pass
	162	46.56	0.03		
	173.9875	46.49	-0.04		
TX4	150.0125	44.07	0.09	-1 ~ +1	Pass
	162	44.02	0.04		
	173.9875	44.06	0.08		

AC 120V/60Hz		ERP					
Operation Mode	Test Frequency (MHz)	Measured power (dBm)	Tolerance (dB)	Output Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)
TX1	150.0125	46.65	1.00	47.65	6.35	54.00	251.19
	162	46.59	1.00	47.59	6.35	53.94	247.74
	173.9875	46.49	1.00	47.49	6.35	53.84	242.10
TX2	150.0125	44.08	1.00	45.08	6.35	51.43	139.00
	162	44.03	1.00	45.03	6.35	51.38	137.40
	173.9875	44.01	1.00	45.01	6.35	51.36	136.77
TX3	150.0125	46.61	1.00	47.61	6.35	53.96	248.89
	162	46.56	1.00	47.56	6.35	53.91	246.04
	173.9875	46.49	1.00	47.49	6.35	53.84	242.10
TX4	150.0125	44.07	1.00	45.07	6.35	51.42	138.68
	162	44.02	1.00	45.02	6.35	51.37	137.09
	173.9875	44.06	1.00	45.06	6.35	51.41	138.36

Note:

1. Output Power(dBm)= Measured power(dBm)+ Tolerance(dB)
2. Antenna Gain(dBd)= Antenna Gain(dBi)-2.15, Antenna Gain(dBi)=8.5dBi
3. ERP(dBm)= Output Power (dBm)+ Antenna Gain (dBd)
4. ERP(W)= $\{10^{(ERP/10)}\} / 1000$

DC 13.6V		Conducted output power			
Operation Mode	Test Frequency (MHz)	Measured power (dBm)	Difference (dB)	Limit (dB)	Result
TX1	150.0125	46.44	-0.10	-1 ~ +1	Pass
	162	46.38	-0.15		
	173.9875	46.28	-0.25		
TX2	150.0125	43.88	-0.10	-1 ~ +1	Pass
	162	43.83	-0.15		
	173.9875	43.81	-0.17		
TX3	150.0125	46.40	-0.14	-1 ~ +1	Pass
	162	46.35	-0.18		
	173.9875	46.28	-0.25		
TX4	150.0125	43.87	-0.11	-1 ~ +1	Pass
	162	43.82	-0.16		
	173.9875	43.86	-0.12		

DC 13.6V		ERP					
Operation Mode	Test Frequency (MHz)	Measured power (dBm)	Tolerance (dB)	Output Power (dBm)	Antenna Gain (dBd)	ERP (dBm)	ERP (W)
TX1	150.0125	46.44	1.00	47.44	6.35	53.79	239.16
	162	46.38	1.00	47.38	6.35	53.73	235.89
	173.9875	46.28	1.00	47.28	6.35	53.63	230.55
TX2	150.0125	43.88	1.00	44.88	6.35	51.23	132.70
	162	43.83	1.00	44.83	6.35	51.18	131.19
	173.9875	43.81	1.00	44.81	6.35	51.16	130.59
TX3	150.0125	46.40	1.00	47.40	6.35	53.75	236.98
	162	46.35	1.00	47.35	6.35	53.70	234.28
	173.9875	46.28	1.00	47.28	6.35	53.63	230.55
TX4	150.0125	43.87	1.00	44.87	6.35	51.22	132.39
	162	43.82	1.00	44.82	6.35	51.17	130.89
	173.9875	43.86	1.00	44.86	6.35	51.21	132.09

Note:

1. Output Power(dBm)= Measured power(dBm)+ Tolerance(dB)
2. Antenna Gain(dBd)= Antenna Gain(dBi)-2.15, Antenna Gain(dBi)=8.5dB
3. ERP(dBm)= Output Power (dBm)+ Antenna Gain (dBd)
4. ERP(W)= $\{10^{(ERP/10)}\} /1000$

5.2. Occupied Bandwidth


The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits.

LIMIT

FCC Part 90.209, FCC Part 90.210, FCC Part 2.1049

Frequency band (MHz)	Channel spacing (kHz)	Authorized bandwidth (kHz)
Below 252		
25-50	20	20
72-76	20	20
150-174	17.5	1 320/11.25/6
216-2205	6.25	20/11.25/6
220-222	5	4
406-5122	16.25	1 320/11.25/6
806-809/851-854	12.5	20
809-824/854-869	25	20
896-901/935-940	12.5	13.6
902-9284		
929-930	25	20
1427-14325	12.5	12.5
32450-2483.52		
Above 25002		

TEST CONFIGURATION



TEST PROCEDURE

- 1 The EUT was modulated by 2.5kHz sine wave audio signal; the level of the audio signal employed is 16dB greater than that necessary to produce 50% of rated system deviation.
Rated system deviation is 2.5 kHz for 12.5kHz channel spacing).
- 2 Spectrum set as follow:
Centre frequency = fundamental frequency, span=50kHz for 12.5kHz channel spacing,
RBW=100Hz, VBW=300Hz, Sweep = auto,
Detector function = peak, Trace = max hold
- 3 Set 99% Occupied Bandwidth and 26dB Occupied Bandwidth
- 4 Measure and record the results in the test report.

TEST MODE:

Please reference to the section 3.4


TEST RESULTS

Passed Not Applicable

Note: have pre-tested TX1 to TX4 mode, record the worst case mode TX1 and TX3 on the report.

Operation Mode	Test Frequency (MHz)	Occupied Bandwidth (kHz)		Limit(kHz)	Result
		99%	26dB		
TX1	150.0125	7.80	9.93	≤ 11.25	Pass
	162	7.40	9.75		
	173.9875	7.32	9.78		
TX3	150.0125	6.88	10.24	≤ 11.25	Pass
	162	6.52	9.73		
	173.9875	6.12	9.17		

Operation Mode



5.3. Emission Mask

LIMIT

FCC Part 90.209, FCC Part 90.210, FCC Part 2.1049


Frequency band (MHz)	Mask for equipment with audio low pass filter	Mask for equipment without audio low pass filter
Below 251	A or B	A or C
25-50	B	C
72-76	B	C
150-1742	B, D, or E	C, D or E
150 paging only	B	C
220-222	F	F
421-5122.5	B, D, or E	C, D, or E
450 paging only	B	G
806-809/851-854	B	H
809-824/854-8693.5	B	G
896-901/935-940	I	J
902-928	K	K
929-930	B	G
4940-4990 MHz	L or M	L or M
5850-59254		
All other bands	B	C

(d) Emission Mask D—12.5 kHz channel bandwidth equipment.

For transmitters designed to operate with a 12.5 kHz channel bandwidth, any emission must be attenuated below the power (P) of the highest emission contained within the authorized bandwidth as follows:

- 1) On any frequency from the centre of the authorized bandwidth f_0 to 5.625 kHz removed from f_0 : 0dB
- 2) On any frequency removed from the centre of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 5.625 kHz but no more than 12.5 kHz: At least $7.27(f_d - 2.88)$ dB.
- 3) On any frequency removed from the centre of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz: At least $50 + 10 \log (P)$ dB or 70 dB, whichever is the lesser attenuation.

TEST CONFIGURATION



TEST PROCEDURE

- 1 Connect the equipment as illustrated.
- 2 Spectrum set as follow:
Centre frequency = fundamental frequency, span=50kHz for 12.5kHz channel spacing,
RBW=100Hz, VBW=300Hz, Sweep = auto,
Detector function = peak, Trace = max hold
- 3 Key the transmitter, and set the level of the unmodulated carrier to a full scale reference line. This is the 0dB reference for the measurement.
- 4 Modulate the transmitter with a 2500 Hz sine wave at an input level 16 dB greater than that necessary to produce 50% of rated system deviation(Rated system deviation is 2.5 kHz for 12.5kHz channel spacing). The input level shall be established at the frequency of maximum response of the audio modulating circuit. Transmitters employing digital modulation techniques that bypass the limiter and the audio low-pass filter shall be modulated as specified by the manufacturer
- 5 Measure and record the results in the test report.

TEST MODE:


Please reference to the section 3.4

TEST RESULTS

Passed Not Applicable

Note: have pre-tested TX1 to TX4 mode, record the worst case mode TX1 and TX3 on the report.

Operation Mode




5.4. Modulation Limit

LIMIT

FCC Part 2.1047(b)

2.5 KHz for 12.5 KHz Channel Spacing System

TEST CONFIGURATION



TEST PROCEDURE

- 1) Connect the equipment as illustrated.
- 2) Adjust the transmitter per the manufacturer's procedure for full rated system deviation.
- 3) Set the test receiver to measure peak positive deviation. Set the audio bandwidth for ≤ 0.25 Hz to $\geq 15,000$ Hz. Turn the de-emphasis function off.
- 4) Apply a 1000 Hz modulating signal to the transmitter from the audio frequency generator, and adjust the level to obtain 60% of full rated system deviation, this level is as a reference (0dB) and vary the input level from -20 to +20dB.
- 5) Measure both the instantaneous and steady-state deviation at and after the time of increasing the audio input level
- 6) Repeat step 4-5 with input frequency changing to 300Hz, 1004Hz, 1500Hz and 2500Hz in sequence.

TEST MODE:

Please reference to the section 3.4


TEST RESULTS

Passed Not Applicable

Note: have pre-tested TX3 to TX4 mode, record the worst case mode TX3 on the report.

TX3: 162MHz						
Modulation Level (dB)	Peak frequency deviation (kHz)				Limit (kHz)	Result
	300Hz	1004Hz	1500Hz	2500 Hz		
-20	0.09	0.18	0.27	0.35	2.5	Pass
-15	0.13	0.29	0.44	0.57		
-10	0.18	0.51	0.79	1.01		
-5	0.29	0.84	1.33	1.78		
0	0.49	1.47	2.04	2.04		
5	0.81	2.01	2.03	2.03		
10	1.31	2.02	2.04	2.04		
15	1.64	2.01	2.04	2.05		
20	1.63	2.02	2.04	2.03		


Test plot as follows:



5.5. Audio Frequency Response


LIMIT

2.1047(a): Voice modulated communication equipment. A curve or equivalent data showing the frequency response of the audio modulating circuit over a range of 100 to 5000 Hz shall be submitted. For equipment required to have an audio low-pass filter, a curve showing the frequency response of the filter or of all circuitry installed between the modulation limiter and the modulated stage shall be submitted.



Receiver audio frequency response shall not vary more than +1, -3 dB from a standard 6 dB per octave de-emphasis curve over the frequency range of 300 Hz to 3000 Hz, except for additional attenuation of 6 dB per octave below 500 Hz and 12dB per octave above 2500. The reference frequency shall be 1000 Hz.

TEST CONFIGURATION



TEST PROCEDURE

- 1) Configure the EUT as shown in figure .
- 2) Adjust the audio input for 20% of rated system deviation at 1kHz using this level as a reference.
- 3) Vary the Audio frequency from 300Hz to 3 kHz and record the frequency deviation.
- 4) Audio Frequency Response = $20\log_{10} (V_{FREQ}/V_{REF})$.

TEST MODE:


Please reference to the section 3.4

TEST RESULTS

Passed Not Applicable

Note: have pre-tested TX3 to TX4 mode, record the worst case mode TX3 on the report.

TX3:162MHz			
Frequency (Hz)	Audio Frequency Response (dB)	Frequency (Hz)	Audio Frequency Response (dB)
300	7.21	2000	-6.25
400	6.15	2100	-6.72
500	5.32	2200	-7.13
600	4.23	2300	-7.58
700	3.05	2400	-7.97
800	1.87	2500	-8.30
900	0.88	2600	-8.62
1000	0.00	2700	-8.94
1200	-1.60	2800	-9.28
1400	-2.84	2900	-9.56
1600	-4.07	3000	-9.89
1800	-5.22		



5.6. Frequency Stability Test

The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

LIMIT

FCC Part 90.213, FCC Part 2.1055

Frequency range (MHz)	Fixed and base stations	Mobile stations		200
		Over 2 watts output power	2 watts or less output power	
Below 25	12 3100	100		200
25-50	20	20		50
72-76	5			50
150-174	5 115	65		4 650
216-220	1.0			1.0
220-22212	0.1	1.5		1.5
421-512	7 11 142.5	85		85
806-809	141.0	1.5		1.5
809-824	141.5	2.5		2.5
851-854	1.0	1.5		1.5
854-869	1.5	2.5		2.5
896-901	140.1	1.5		1.5
902-928	2.5	2.5		2.5
902-92813	2.5	2.5		2.5
929-930	1.5			
935-940	0.1	1.5		1.5
1427-1435	9300	300		300
Above 245010				


⁵In the 150-174 MHz band, fixed and base stations with a 12.5 kHz channel bandwidth must have a frequency stability of 2.5 ppm. Fixed and base stations with a 6.25 kHz channel bandwidth must have a frequency stability of 1.0 ppm.

⁷In the 421-512 MHz band, fixed and base stations with a 12.5 kHz channel bandwidth must have a frequency stability of 1.5 ppm. Fixed and base stations with a 6.25 kHz channel bandwidth must have a frequency stability of 0.5 ppm.

¹¹Paging transmitters operating on paging-only frequencies must operate with frequency stability of 5 ppm in the 150-174 MHz band and 2.5 ppm in the 421-512 MHz band.

¹⁴Control stations may operate with the frequency tolerance specified for associated mobile frequencies.

TEST CONFIGURATION



TEST PROCEDURE

1. According to FCC Part 2 Section 2.1055 (a)(1), the frequency stability shall be measured with variation of ambient temperature from -30°C to +50°C.
2. According to FCC Part 2 Section 2.1055 (d) (2), for battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacturer.
3. Vary primary supply voltage from 85 to 115 percent of the nominal value.
4. The EUT was set in the climate chamber and connected to an external DC/AC power supply. The RF output was directly connected to Spectrum Analyzer, The coupling loss of the additional cables was recorded and taken in account for all the measurements. After temperature stabilization (approx. 20 min for each stage), the frequency for the lower, the middle and the highest frequency range was recorded. For Frequency stability Vs. Voltage the EUT was connected to a DC/AC power supply and the voltage was adjusted in the required ranges. The result was recorded.

TEST MODE:

Please reference to the section 3.4

TEST RESULTS

Passed **Not Applicable**

Note: have pre-tested TX1 to TX4 mode, record the worst case mode TX1 and TX3 on the report.

TX1						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage(V)	Temp(°C)	150.0125MHz	162MHz	173.9875MHz		
120	-30	0.29	0.05	0.06	±2.5	Pass
	-20	0.27	0.05	0.06		
	-10	0.28	0.05	0.06		
	0	0.30	0.05	0.06		
	10	0.30	0.05	0.06		
	20	0.30	0.05	0.06		
	30	0.31	0.06	0.06		
	40	0.31	0.06	0.07		
	50	0.33	0.06	0.07		
	102	0.27	0.05	0.06		
138	20	0.30	0.05	0.07		

TX3						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage(V)	Temp(°C)	150.0125MHz	162MHz	173.9875MHz		
120	-30	0.35	0.06	0.09	±2.5	Pass
	-20	0.34	0.07	0.09		
	-10	0.37	0.07	0.09		
	0	0.34	0.07	0.09		
	10	0.34	0.06	0.09		
	20	0.37	0.07	0.09		
	30	0.37	0.07	0.10		
	40	0.38	0.08	0.10		
	50	0.40	0.08	0.11		
	102	0.35	0.06	0.09		
138	20	0.38	0.07	0.10		

TX1						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage(V)	Temp(°C)	150.0125MHz	162MHz	173.9875MHz		
13.6	-30	0.07	0.25	0.14	±2.5	Pass
	-20	0.07	0.24	0.14		
	-10	0.07	0.24	0.14		
	0	0.07	0.24	0.14		
	10	0.07	0.25	0.14		
	20	0.07	0.25	0.14		
	30	0.07	0.26	0.15		
	40	0.08	0.28	0.16		
	50	0.08	0.28	0.18		
	11.56	20	0.07	0.24		
	15.64	20	0.08	0.26		

TX3						
Test conditions		Frequency error (ppm)			Limit (ppm)	Result
Voltage(V)	Temp(°C)	150.0125MHz	162MHz	173.9875MHz		
13.6	-30	0.23	0.24	0.27	±2.5	Pass
	-20	0.24	0.23	0.27		
	-10	0.25	0.23	0.28		
	0	0.24	0.24	0.28		
	10	0.23	0.23	0.28		
	20	0.26	0.24	0.30		
	30	0.27	0.24	0.31		
	40	0.29	0.26	0.33		
	50	0.30	0.27	0.27		
	11.56	20	0.25	0.22		
	15.64	20	0.27	0.25		

5.7. Transmitter Frequency Behaviour

LIMIT

FCC part 90.214


Transmitters designed to operate in the 150-174 MHz and 421-512 MHz frequency bands must maintain transient frequencies within the maximum frequency difference limits during the time intervals indicated:

Time intervals ^{1,2}	Maximum frequency difference ³	All equipment	
		150 to 174 MHz	421 to 512 MHz
Transient Frequency Behavior for Equipment Designed to Operate on 25 kHz Channels			
t_1 ⁴	± 25.0 kHz	5.0 ms	10.0 ms
t_2	± 12.5 kHz	20.0 ms	25.0 ms
t_3 ⁴	± 25.0 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 12.5 kHz Channels			
t_1 ⁴	± 12.5 kHz	5.0 ms	10.0 ms
t_2	± 6.25 kHz	20.0 ms	25.0 ms
t_3 ⁴	± 12.5 kHz	5.0 ms	10.0 ms
Transient Frequency Behavior for Equipment Designed to Operate on 6.25 kHz Channels			
t_1 ⁴	± 6.25 kHz	5.0 ms	10.0 ms
t_2	± 3.125 kHz	20.0 ms	25.0 ms
t_3 ⁴	± 6.25 kHz	5.0 ms	10.0 ms

Note:

1. On is the instant when a 1 kHz test signal is completely suppressed, including any capture time due to phasing.
 - 1) t_1 is the time period immediately following ton.
 - 2) t_2 is the time period immediately following t_1 .
 - 3) t_3 is the time period from the instant when the transmitter is turned off until toff.
 - 4) t_{off} is the instant when the 1 kHz test signal starts to rise.
2. During the time from the end of t_2 to the beginning of t_3 , the frequency difference must not exceed the limits specified in § 90.213.
3. Difference between the actual transmitter frequency and the assigned transmitter frequency.
4. If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency difference for this time period.

TEST CONFIGURATION



TEST PROCEDURE

According to TIA/EIA-603 2.2.19 requirement, as for the product different from PTT, we use test steps as follows:

1. Connect DUT into Test discriminator and Storage Oscilloscope and keep DUT stats ON;
2. Input 1kHz signal into DUT;
3. Set the modulation domain analyzer to trigger on the rising edge of the waveform in order to capture a single-shot turn-on of the transmitter signals;
4. Keep DUT in OFF state and Key the PTT;
5. Observe the stored oscilloscope of modulation domain analyzer. The signal trace shall be maintained within the allowable limits during the periods t_1 and t_2 , and shall also remain within limits following t_2 ;
6. Adjust the modulation domain analyzer to trigger on the falling edge of the transmitter waveform in order to capture a single-shot turn-off transmitter of the transmitter signal.
7. Keep the digital portable radio in ON state and unkey the PTT;
8. Observe the stored oscilloscope of modulation domain analyzer. The signal trace shall be maintained within the allowable limits during the period t_3 .

TEST MODE:


Please reference to the section 3.4

TEST RESULTS


Passed **Not Applicable**

Note: have pre-tested TX3 to TX4 mode, record the worst case mode TX3 on the report.

Modulation Type: FM(TX3)
Transmitter Frequency Behaviour @ 12.5kHz Channel Separation-----Off – On



Transmitter Frequency Behaviour @ 12.5kHz Channel Separation-----On – Off



5.8. Spurious Emission on Antenna Port

Conducted spurious emissions are emissions at the antenna terminals on a frequency or frequencies that are outside a band sufficient to ensure transmission of information of required quality for the class of communication desired

LIMIT

FCC Part 90.210, FCC Part 2.1051 (12.5 kHz Bandwidth only):

On any frequency removed from the center of the authorized bandwidth by a displacement frequency (f_d in kHz) of more than 12.5 kHz at least:

High: $50 + 10 \log (P_{\text{watts}}) = 50 + 10 \log (46.24) = 66.65 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.


Calculation: Limit (dBm) = $EL - 50 - 10 \log_{10} (TP)$

EL is the emission level of the Output Power expressed in dBm,

In this application, the EL is 46.53 dBm.

Limit (dBm) = $46.53 - 50 - 10 \log_{10} (46.24) = -20 \text{ dBm}$

TEST CONFIGURATION



TEST PROCEDURE

1. The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation.
2. The resolution bandwidth of the spectrum analyzer was set to 100 kHz. Sufficient scans were taken to show any out of band emission up to 10th Harmonic for the lower and the highest frequency range.
3. Set RBW 100 kHz, VBW 300 kHz in the frequency band 30MHz to 1GHz, while set RBW=1MHz. VBW=3MHz from the 1GHz to 10th Harmonic.
4. The audio input was set the unmodulated carrier, the resulting picture is print out for each channel separation.


TEST MODE:

Please reference to the section 3.4

TEST RESULTS

Passed Not Applicable

Note: have pre-tested TX1 to TX4 mode, record the worst case mode TX1 and TX3 on the report.



5.9. Transmitter Radiated Spurious Emission

Radiated spurious emissions are emissions from the equipment when transmitting into a nonradiating load on a frequency or frequencies that are outside an occupied band sufficient to ensure transmission of information of required quality for the class of communications desired.

LIMIT

FCC Part 90.210, FCC Part 2.1051 (12.5 kHz Bandwidth only):

On any frequency removed from the center of the authorized bandwidth by a displacement frequency (fd in kHz) of more than 12.5 kHz at least:

High: $50 + 10 \log (P_{\text{watts}}) = 50 + 10 \log (46.24) = 66.65 \text{ dB}$

Note: In general, the worse case attenuation requirement shown above was applied.




Calculation: Limit (dBm) = $EL - 50 - 10 \log_{10} (TP)$

EL is the emission level of the Output Power expressed in dBm,

In this application, the EL is 46.53 dBm.

Limit (dBm) = $46.53 - 50 - 10 \log_{10} (46.24) = -20 \text{ dBm}$

TEST CONFIGURATION



TEST PROCEDURE

1. Standard Transmitter Load with a 50Ω input impedance and an output impedance matched to the test equipment.
2. EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission

measurements. The height of receiving antenna is 1.0 m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in six channels were measured with peak detector.

3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz,VBW=3MHz for above 1GHz and RBW=100kHz,VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (P_r).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (P_{Mea}) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (P_r). The power of signal source (P_{Mea}) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (P_{cl}), the Substitution Antenna Gain (G_a) and the Amplifier Gain (P_{Ag}) should be recorded after test.
The measurement results are obtained as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{Ag} - P_{cl} - G_a$$

We used SMF100A microwave signal generator which signal level can up to 33dBm, so we not used power Amplifier for substitution test; The measurement results are amend as described below:

$$\text{Power(EIRP)} = P_{Mea} - P_{cl} - G_a$$
7. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power.
8. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

TEST MODE:

Please reference to the section 3.4

TEST RESULTS

Passed Not Applicable

Note:

1. In general, the worse case attenuation requirement shown above was applied.
2. The measurement frequency range from 30 MHz to 2 GHz.
3. Absolute Level=SG Level+Cable loss+Antenna Gain, Margin=Limit-Absolute Level
4. We tested TX1 to TX3 for AC 120V and DC 13.6V, recorded worst case TX1 and TX3 for AC 120V.

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G.Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
TX1: 150.0125 MHz								
300.025	H	62.42	-35.24	0	2.43	-37.67	-20	17.67
300.025	V	61.74	-35.13	0	2.43	-37.56	-20	17.56
450.0375	H	60.12	-38.25	8.42	4.16	-33.99	-20	13.99
450.0375	V	63.69	-36.05	8.42	4.16	-31.79	-20	11.79
600.05	H	56.42	-45.20	9.78	4.25	-39.67	-20	19.67
600.05	V	54.55	-47.59	9.78	4.25	-42.06	-20	22.06
TX1:162.0000 MHz								
324	H	62.45	-33.96	0	2.48	-36.44	-20	16.44
324	V	61.36	-36.46	0	2.48	-38.94	-20	18.94
486	H	60.23	-40.39	8.51	4.19	-36.07	-20	16.07
486	V	63.42	-38.24	8.51	4.19	-33.92	-20	13.92
648	H	57.57	-43.90	10.05	4.37	-38.22	-20	18.22
648	V	55.69	-46.30	10.05	4.37	-40.62	-20	20.62
TX1:173.9875 MHz								
347.975	H	62.34	-34.51	0	2.52	-37.03	-20	17.03
347.975	V	60.41	-38.11	0	2.52	-40.63	-20	20.63
521.9625	H	62.29	-39.07	8.53	4.32	-34.86	-20	14.86
521.9625	V	64.36	-36.50	8.53	4.32	-32.29	-20	12.29
695.95	H	57.86	-43.83	10.21	4.48	-38.1	-20	18.1
695.95	V	56.71	-45.98	10.21	4.48	-40.25	-20	20.25

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			S.G.Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
TX3: 150.0125 MHz								
300.025	H	62.42	-35.24	0	2.43	-37.67	-20	17.67
300.025	V	62.62	-34.25	0	2.43	-36.68	-20	16.68
450.0375	H	61.71	-36.66	8.42	4.16	-32.4	-20	12.4
450.0375	V	62.67	-37.07	8.42	4.16	-32.81	-20	12.81
600.05	H	57.59	-44.03	9.78	4.25	-38.5	-20	18.5
600.05	V	55.44	-46.70	9.78	4.25	-41.17	-20	21.17
TX3:162.0000 MHz								
324	H	62.59	-33.82	0	2.48	-36.3	-20	16.3
324	V	60.69	-37.13	0	2.48	-39.61	-20	19.61
486	H	61.62	-39.00	8.51	4.19	-34.68	-20	14.68
486	V	62.74	-38.92	8.51	4.19	-34.6	-20	14.6
648	H	56.85	-44.62	10.05	4.37	-38.94	-20	18.94
648	V	55.71	-46.28	10.05	4.37	-40.6	-20	20.6
TX3:173.9875 MHz								
347.975	H	62.52	-34.33	0	2.52	-36.85	-20	16.85
347.975	V	61.46	-37.06	0	2.52	-39.58	-20	19.58
521.9625	H	62.52	-38.84	8.53	4.32	-34.63	-20	14.63
521.9625	V	65.26	-35.60	8.53	4.32	-31.39	-20	11.39
695.95	H	58.71	-42.98	10.21	4.48	-37.25	-20	17.25
695.95	V	57.74	-44.95	10.21	4.48	-39.22	-20	19.22

5.10. Conducted Emissions Test


The frequency spectrum from 0.15 MHz to 30 MHz was investigated. The LISN used was 50 ohm / 50 u Henry as specified by section 5.1 of ANSI C63.4 - 2009. Cables and peripherals were moved to find the maximum emission levels for each frequency.

Limit

FCC part 15.107(a)

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4-2009.
- 2 Support equipment, if needed, was placed as per ANSI C63.4-2009.
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4-2009.
- 4 If a EUT received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:


Please reference to the section 3.4

TEST RESULTS


Passed Not Applicable

Note:

1. The EUT was tested with the GPS antenna.



Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.366000	38.50	10.2	59	20.1	QP	L1	GND
0.456000	46.00	10.2	57	10.8	QP	L1	GND
0.640500	27.20	10.2	56	28.8	QP	L1	GND
2.652000	22.60	10.3	56	33.4	QP	L1	GND
2.742000	23.50	10.4	56	32.5	QP	L1	GND
18.244500	30.80	10.7	60	29.2	QP	L1	GND
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.366000	34.20	10.2	49	14.4	AV	L1	GND
0.456000	41.10	10.2	47	5.7	AV	L1	GND
0.640500	23.80	10.2	46	22.2	AV	L1	GND
18.244500	27.60	10.7	50	22.4	AV	L1	GND
19.707000	27.80	10.7	50	22.2	AV	L1	GND



Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.181500	39.10	10.3	64	25.3	QP	N	GND
0.366000	38.40	10.2	59	20.2	QP	N	GND
0.456000	46.00	10.2	57	10.8	QP	N	GND
0.546000	33.00	10.2	56	23.0	QP	N	GND
0.640500	27.20	10.2	56	28.8	QP	N	GND
2.647500	28.10	10.3	56	27.9	QP	N	GND
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.186000	28.90	10.3	54	25.3	AV	N	GND
0.366000	35.20	10.2	49	13.4	AV	N	GND
0.456000	42.60	10.2	47	4.2	AV	N	GND
0.546000	26.60	10.2	46	19.4	AV	N	GND
0.640500	23.30	10.2	46	22.7	AV	N	GND
23.127000	28.60	10.8	50	21.4	AV	N	GND
Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.186000	28.90	10.3	54	25.3	AV	N	GND
0.366000	35.20	10.2	49	13.4	AV	N	GND
0.456000	42.60	10.2	47	4.2	AV	N	GND
0.546000	26.60	10.2	46	19.4	AV	N	GND
0.640500	23.30	10.2	46	22.7	AV	N	GND
23.127000	28.60	10.8	50	21.4	AV	N	GND

5.11. Radiated Emission

LIMIT


For unintentional device, according to § 15.109(a) except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

TEST CONFIGURATION

(A) Radiated Emission Test Set-Up, Frequency below 1000MHz



(B) Radiated Emission Test Set-Up, Frequency above 1000MHz



TEST PROCEDURE

- 2 The EUT was placed on a turn table which is 0.8m above ground plane.
- 3 Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT
- 4 And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 5 Repeat above procedures until all frequency measurements have been completed.

TEST MODE:


Please reference to the section 3.4


TEST RESULTS

Passed **Not Applicable**

Note:


1. The EUT shall be scanned from 30 MHz to the 5th harmonic of the highest oscillator frequency in the digital devices or 1 GHz whichever is higher.
2. The EUT was tested with the GPS antenna.





6. Test Setup Photos of the EUT

Transmitter Radiated Spurious Emission:



Radiated Emission:





Conducted Emissions:






7. External and Internal Photos of the EUT



External photos of the EUT
















Internal photos of the EUT

























.....End of Report.....