# FCC 47 CFR PART 15 SUBPART C AND ANSI C63.10:2009 TEST REPORT

For

**MW GPS Watch** 

Model: MWW

**Data Applies To: MWS** 

Trade Name: Marathon's World

Issued for

iTravel-tech Co., Ltd.

1F.,No.129, Guangming 9th Rd., Zhubei City, Hsinchu County 30268, Taiwan

Issued by

Compliance Certification Services Inc. Hsinchu Lab.

No.989-1, Wenshan Rd., Shangshan Village, Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)

TEL: +886-3-5921698 FAX: +886-3-5921108

http://www.ccsrf.com E-Mail : service@ccsrf.com Issued Date: June 09, 2015



**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document. The client should not use it to claim product endorsement by TAF or any government agencies. The test results of this report relate only to the tested sample identified in this report.

Report No.: T150415S08-RP1

# **Revision History**

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	06/01/2015	Initial Issue	All Page 45	Dola Hsieh
01	06/09/2015	Revised Product Name	P.1, P.4-6, P.30-33, P.41-42	Dola Hsieh

#### TABLE OF CONTENTS

TITLE PAGE NO. 1. TEST REPORT CERTIFICATION ......4 3. DESCRIPTION OF TEST MODES ......6 4. TEST METHODOLOGY .......7 5. FACILITIES AND ACCREDITATION......7 6. SETUP OF EQUIPMENT UNDER TEST......9 7. FCC PART 15.247 REQUIREMENTS......10 7.5 CONDUCTED SPURIOUS EMISSION ......22 APPENDIX SETUP PHOTOS .......43

# 1. TEST REPORT CERTIFICATION

**Applicant**: iTravel-tech Co., Ltd.

Address: 1F.,No.129, Guangming 9th Rd., Zhubei City, Hsinchu County

30268, Taiwan

**Equipment Under Test:** MW GPS Watch

Model : MWW

Data Applies To : MWS

Trade Name : Marathon's World

**Tested Date** : April 15 ~ May 11, 2015

APPLICABLE STANDARD			
Standard	Test Result		
FCC Part 15 Subpart C AND ANSI C63.10:2009	PASS		

WE HEREBY CERTIFY THAT: The above equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved by:

Sb. Lu

Sr. Engineer

Reviewed by:

Gundam Lin Sr. Engineer

# 2. EUT DESCRIPTION

Product Name	MW GPS Watch	
Model Number	MWW	
Data Applies To	MWS	
Identify Number	T150415S08	
Received Date	April 15, 2015	
Frequency Range	2402MHz ~ 2480MHz	
Transmit Power	0.51 dBm (0.0011W)	
Channel Spacing	2MHz	
Channel Number	40 Channels	
Transmit Data Rate	1Mbps	
Type of Modulation	GFSK	
Antenna Type	Chip Antenna, Antenna Gain : 0 dBi	
B	3.7Vdc, 350mAh (For Battery)	
Power Rating	5.0Vdc (For Charging)	
Test Voltage	120Vac, 60Hz	
DC Power Cable Type	Shielded USB cable, 0.85m × 1(Detachable)	
I/O Port	Charge Port × 1	

# The difference of the series model

Model Number	Trade Name	Difference
MWW	Marathon's world	Scratch-resistant glass and Sirf IV     GPS high performance chipset
MWS	Marathon's world	<ul><li>2. Metronome support and help runners to adjust stride temple</li><li>3. ANT+ sensors support</li><li>4. Mulitlingual support</li></ul>

#### Remark:

- 1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
- 2. For more details, please refer to the User's manual of the EUT.
- 3. The model MWS was considered the main model for testing.
- 4 This submittal(s) (test report) is intended for FCC ID: 2AEKT-MWW filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.

# 3. DESCRIPTION OF TEST MODES

The EUT is an 802.11n transceiver in MW GPS Watch form factor.

# Conducted Emission / Radiated Emission Test (Below 1 GHz)

1. The following test modes were scanned during the preliminary test:

No.	Pre-Test Mode
1	TX Mode
2	Charge + Read/Write Mode

2. After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test Mode				
Emission	Radiated Emission	TX Mode		
LIIII33I0II	Conducted Emission	Charge + Read/Write Mode		

**Remark :** Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.

# Conducted / Radiated Emission Test (Above 1 GHz)

The EUT had been tested under operating condition.

There are three channels have been tested as following:

Channel	Frequency (MHz)		
Low	2402		
Middle	2440		
High	2480		

**Remark:** The field strength of spurious emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X, Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.

# 4. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2009 and FCC CFR 47, 15.207, 15.209 and 15.247.

# 5. FACILITIES AND ACCREDITATION

#### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.989-1, Wenshan Rd., Shangshan Village, Qionglin Township, Hsinchu County 30741, Taiwan (R.O.C.)

The sites are constructed in conformance with the requirements of ANSI C63.10:2009 and CISPR 22. All receiving equipment conforms to CISPR 16-1-1, CISPR 16-1-2, CISPR 16-1-3, CISPR 16-1-4, CISPR 16-1-5.

#### 5.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

Taiwan TAF

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada INDUSTRY CANADA

Japan VCCI

Taiwan BSMI

USA FCC MRA

Copies of granted accreditation certificates are available for downloading from our web site, http:///www.ccsrf.com

Remark: FCC Designation Number TW1027.

#### 5.3 MEASUREMENT UNCERTAINTY

The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4-2.

PARAMETER	UNCERTAINTY
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 30 to 1000 MHz	+/- 3.97
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 1 to 18GHz	+/- 3.58
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 18 to 26 GHz	+/- 3.59
Semi Anechoic Chamber (966 Chamber_B) / Radiated Emission, 26 to 40 GHz	+/- 3.81
Conducted Emission (Mains Terminals), 9kHz to 30MHz	+/- 2.48

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Consistent with industry standard (e.g. CISPR 22, clause 11, Measurement Uncertainty) determining compliance with the limits shall be base on the results of the compliance measurement. Consequently the measure emissions being less than the maximum allowed emission result in this be a compliant test or passing test.

The acceptable measurement uncertainty value without requiring revision of the compliance statement is base on conducted and radiated emissions being less than  $U_{CISPR}$  which is 3.6dB and 5.2dB respectively. CCS values (called  $U_{Lab}$  in CISPR 16-4-2) is less than  $U_{CISPR}$  as shown in the table above. Therefore, MU need not be considered for compliance.

# 6. SETUP OF EQUIPMENT UNDER TEST

# **SUPPORT EQUIPMENT**

No.	Product	Manufacturer	Model No.	Serial No.
1	Notebook PC	TOSHIBA	M840	9C104267C
2	Notebook PC	TOSHIBA	PORTEGE R30-A	4E087535H

No.	Signal Cable Description
1	Shielded micro USB cable, 1m × 1

# SETUP DIAGRAM FOR TESTS

EUT & peripherals setup diagram is shown in appendix setup photos.

# **EUT OPERATING CONDITION**

#### **RF Mode**

- 1. EUT & peripherals setup diagram is shown in appendix setup photos.
- 2. Run "nRFgo Studio" Software to test.
- 3. PACKET TRANSMIT (TX Mode)

Freq: 2402, 2440, 2480

Power Setting: Default

- 4. All of the functions are under run.
- 5. Start test

# Charge + Read/Write Mode

- 1. EUT & peripherals setup diagram is shown in appendix setup photos.
- 2. EUT link Notebook PC with USB cable (charge mode).
- 3. Notebook PC run software to read / write with EUT.
- 4. All of the functions are under run.
- 5. Start test.

# 7. FCC PART 15.247 REQUIREMENTS

# 7.1 6dB BANDWIDTH

#### **LIMITS**


§ 15.247(a) (2) For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

#### **TEST EQUIPMENT**

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

# **TEST SETUP**




# **TEST PROCEDURE**


- 1. The transmitter output was connected to a spectrum analyzer.
- 2. Set RBW = 100 kHz.
- 3. Set the video bandwidth (VBW)  $\geq$  3 x RBW.
- 4. Detector = Peak.
- 5. Trace mode = max hold.
- 6. Sweep = auto couple.
- 7. Allow the trace to stabilize.
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

# **TEST RESULTS**

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
Low	2402	707.5	500	PASS
Middle	2440	671.7	500	PASS
High	2480	670.5	500	PASS

# **6dB BANDWIDTH**





# 7.2 MAXIMUM PEAK OUTPUT POWER

#### **LIMITS**

§ 15.247(b) The maximum peak output power of the intentional radiator shall not exceed the following :

§ 15.247(b) (3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands : 1 watt.

§ 15.247(b) (4) Except as shown in paragraphs (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

§ KDB 662911 : For power measurements on IEEE 802.11 devices

Array Gain = 0 dB (i.e., no array gain) for  $N_{ANT} \le 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N<sub>ANT</sub>;


Array Gain =  $5 \log(N_{ANT}/N_{SS})$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $N_{ANT} \ge 5$ .

#### **TEST EQUIPMENT**

Name of Equipment	t Manufacturer Model		Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1149001	12/11/2015
Power Sensor	Anritsu	MA2411B	1126148	12/11/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

#### **TEST SETUP**



# **TEST PROCEDURE**

The transmitter output is connected to the power meter. The power meter is set to the peak power detection.

# **TEST RESULTS**

Channel	Channel Frequency	Peak Power Peak Power		wer Limit	Pass / Fail	
Onamici	(MHz)	(dBm)	(W)	(dBm)	(W)	1 433 / 1 411
Low	2402	0.42	0.0011	30	1	PASS
Middle	2440	0.51	0.0011	30	1	PASS
High	2480	0.42	0.0011	30	1	PASS

**Remark:** The cable assembly insertion loss of 11.5 dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

# 7.3 AVERAGE POWER

# **LIMITS**

None; for reporting purposes only.

# **TEST EQUIPMENT**

Name of Equipment	Manufacturer Model		Serial Number	Calibration Due
Power Meter	ANRITSU	ML2495A	1149001	12/11/2015
Power Sensor	ANRITSU	MA2411B	1126148	12/11/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

# **TEST SETUP**



# **TEST PROCEDURE**

The transmitter output is connected to the power meter. The power meter is set to the average power detection.

# **TEST RESULTS**

Channel	Channel Frequency (MHz)	Average Power (dBm)	
Low	2402	-0.24	
Middle	2440	-0.32	
High	2480	-0.54	

**Remark:** The cable assembly insertion loss of 11.5 dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the power meter to allow for direct reading of power.

# 7.4 POWER SPECTRAL DENSITY

# **LIMITS**

§ 15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

## **TEST EQUIPMENT**

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

## **TEST SETUP**



#### **TEST PROCEDURE**


- 1. The transmitter output was connected to the spectrum analyzer.
- 2. Set analyzer center frequency to DTS channel center frequency.
- 3. Set the span to 1.5 times the DTS channel bandwidth.
- 4. Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- 5. Set the VBW  $\geq$  3 x RBW.
- 6. Detector = peak.
- 7. Sweep time = auto couple.
- 8. Trace mode = max hold.
- 9. Allow trace to fully stabilize.
- 10. Use the peak marker function to determine the maximum amplitude level within the RBW.
- 11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


# **TEST RESULTS**

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Minimum Limit (dBm)	Pass / Fail
Low	2402	-7.31	8	PASS
Middle	2440	2440 -6.45		PASS
High	2480	-6.30	8	PASS

**Remark:** The cable assembly insertion loss of 11.5 dB (including 10 dB pad and 1.5 dB cable) was Entered as an offset in the spectrum analyzer to allow for direct reading of power.

# **POWER SPECTRAL DENSITY**





# 7.5 CONDUCTED SPURIOUS EMISSION

# **LIMITS**

§ 15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the and that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

#### **TEST EQUIPMENT**

Name of Equipment	ame of Equipment Manufacturer		Serial Number	Calibration Due
EXA Signal Analyzer	Agilent	N9010A	MY52220817	03/19/2016

Remark: Each piece of equipment is scheduled for calibration once a year.

# **TEST SETUP**




# **TEST PROCEDURE**


The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz.


The spectrum from 30 MHz to 26.5 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

# **TEST RESULTS**

# **OUT-OF-BAND SPURIOUS EMISSIONS-CONDUCTED MEASUREMENT**







#### 7.6 RADIATED EMISSION

# **LIMITS**

(1) According to § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 -1710	10.6 -12.7
6.26775 - 6.26825	108 -121.94	1718.8 - 1722.2	13.25 -13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 – 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 -16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3338	36.43 - 36.5
12.57675 - 12.57725	322 -335.4	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41			

#### Remark:

(2) According to § 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown is Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

<sup>1. 1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2. 2</sup> Above 38.6

FCC ID: 2AEKT-MWW

(3) According to § 15.209 (a) Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table :

Report No.: T150415S08-RP1

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 - 0.490	2400/F(KHz)	300
0.490 – 1.705	24000/F(KHz)	30
1.705 – 30.0	30	30
30 - 88	100 **	3
88 - 216	150 **	3
216 - 960	200 **	3
Above 960	500	3

**Remark:** \*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

(4) According to § 15.209 (b) In the emission table above, the tighter limit applies at the band edges.

# **TEST EQUIPMENT**

# Radiated Emission / 966Chamber\_B

Name of Equipment	Manufacture	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY46180323	04/14/2016
EMI Test Receiver	ROHDE & SCHWARZ	ESCS 30	835418/008	10/14/2015
Bi-log Antenna	SCHWARZBECK	VULB 9168	9168-250	08/21/2015
Double-Ridged Waveguide Horn	ETS-LINDGREN	3117	00078733	12/02/2015
Horn Antenna	COM-POWER	AH-840	03077	12/17/2015
Pre-Amplifier	Agilent	8447D	2944A10052	07/15/2015
Pre-Amplifier	Agilent	8449B	3008A01916	07/15/2015
LOOP Antenna	EMCO	6502	8905-2356	09/23/2015
Notch Filters Band Reject	Micro-Tronics	BRM05702-01	026	N.C.R


**Remark:** 1. Each piece of equipment is scheduled for calibration once a year.

2. N.C.R = No Calibration Request.


# **TEST SETUP**

The diagram below shows the test setup that is utilized to make the measurements for emission below 1GHz.


9kHz ~ 30MHz



#### 30MHz ~ 1GHz



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



# **TEST PROCEDURE**

- 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2. While measuring the radiated emission below 1GHz, the EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. While measuring the radiated emission above 1GHz, the EUT was set 3 meters away from the interference-receiving antenna.
- 3. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- 6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### Remark:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

# **TEST RESULTS**

# Below 1 GHz (9kHz ~ 30MHz)

No emission found between lowest internal used/generated frequency to 30MHz.

# Below 1 GHz (30MHz ~ 1GHz)

<b>Product Name</b>	MW GPS Watch	Test By	Rex Chiu
Test Model	MWS	Test Date	2015/04/29
Test Mode	TX Mode	Temp. & Humidity	25°C, 56%

	966 Chamber_B at 3Meter / Horizontal						
Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark	
95.96	59.70	-32.32	27.38	43.50	-16.12	Peak	
143.49	50.53	-25.38	25.15	43.50	-18.35	Peak	
239.52	54.79	-25.60	29.19	46.00	-16.81	Peak	
288.02	49.91	-22.02	27.89	46.00	-18.11	Peak	
335.55	48.68	-20.23	28.45	46.00	-17.55	Peak	
384.05	49.17	-19.88	29.29	46.00	-16.71	Peak	
480.08	44.25	-17.31	26.94	46.00	-19.06	Peak	
		966 Chamb	er_B at 3Met	er / Vertical			
Frequency (MHz)	Reading (dBµV)	Correction Factor (dB/m)	Result (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Remark	
42.61	59.38	-24.58	34.80	40.00	-5.20	Peak	
95.96	49.71	-22.46	27.25	43.50	-16.25	Peak	
152.22	43.55	-18.05	25.50	43.50	-18.00	Peak	
239.52	45.22	-18.59	26.63	46.00	-19.37	Peak	
383.08	46.54	-20.29	26.26	46.00	-19.74	Peak	
480.08	39.34	-16.54	22.79	46.00	-23.21	Peak	

#### Remark:

- 1. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit.
- 2. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 3. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) PreAmp.Gain (dB)
- 4. Result (dBuV/m) = Reading (dBuV) + Correction Factor (dB/m)
- 5. Margin (dB) = Remark result (dBuV/m) Quasi-peak limit (dBuV/m).

#### **Above 1 GHz**

Product Name	MW GPS Watch	Test By	Rex Chiu
Test Model	MWS	Test Date	2015/04/29
Test Mode	Bluetooth 4.0 / TX Mode / CH Low	Temp. & Humidity	25°C, 56%

	966 Chamber_B at 3Meter / Horizontal								
Frequency (MHz)	Reading- PK (dBuV)	Reading- AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2250.00	45.78		2.39	48.17		74.00	54.00	-5.83	Peak
2498.00	46.07		3.01	49.08		74.00	54.00	-4.92	Peak
2898.00	47.25		3.82	51.07		74.00	54.00	-2.93	Peak
3285.00	42.64		4.60	47.24		74.00	54.00	-6.76	Peak
4995.00	44.29		8.14	52.42		74.00	54.00	-1.58	Peak
7020.00	39.45		12.26	51.71		74.00	54.00	-2.29	Peak
		9	66 Chaml	ber_B at 3	3Meter / V	ertical			
Frequency (MHz)	Reading- PK (dBuV)	Reading- AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1492.00	49.59		-2.87	46.72		74.00	54.00	-7.28	Peak
2208.00	45.61		2.29	47.90		74.00	54.00	-6.10	Peak
2492.00	49.34		2.99	52.34		74.00	54.00	-1.66	Peak
3285.00	42.84		4.60	47.44		74.00	54.00	-6.56	Peak
4980.00	47.82	29.76	8.12	55.95	37.88	74.00	54.00	-16.12	AVG
6990.00	39.02		12.30	51.31		74.00	54.00	-2.69	Peak

#### Remark:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Average test would be performed if the peak result were greater than the average limit.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 5. Result = Reading + Correction Factor

Margin = Result - Limit

Remark Peak = Result(PK) - Limit(AV)

Remark AVG = Result(AV) - Limit(AV)

Product Name	MW GPS Watch	Test By	Rex Chiu
Test Model	MWS	Test Date	2015/04/29
Test Mode	Bluetooth 4.0 / TX Mode / CH Middle	Temp. & Humidity	25°C, 56%

	966 Chamber_B at 3Meter / Horizontal								
Frequency (MHz)	Reading- PK (dBuV)	Reading- AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
1788.00	45.62		-0.19	45.44		74.00	54.00	-8.56	Peak
2272.00	43.81		2.45	46.26		74.00	54.00	-7.74	Peak
2492.00	44.70		2.99	47.70		74.00	54.00	-6.30	Peak
3210.00	42.46		4.45	46.91		74.00	54.00	-7.09	Peak
4980.00	43.88		8.12	52.00		74.00	54.00	-2.00	Peak
6540.00	39.75		11.70	51.45		74.00	54.00	-2.55	Peak
		9	66 Chaml	ber_B at 3	3Meter / V	ertical			
Frequency (MHz)	Reading- PK (dBuV)	Reading- AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)	Limit-AV (dBuV/m)	Margin (dB)	Remark
2152.00	45.60		2.15	47.76		74.00	54.00	-6.24	Peak
2268.00	46.02		2.44	48.45		74.00	54.00	-5.55	Peak
2498.00	49.04		3.01	52.04		74.00	54.00	-1.96	Peak
3180.00	43.97		4.39	48.36		74.00	54.00	-5.64	Peak
4995.00	47.11	29.40	8.14	55.25	37.54	74.00	54.00	-16.46	AVG
7050.00	39.92		12.20	52.12		74.00	54.00	-1.88	Peak

#### Remark:

- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Average test would be performed if the peak result were greater than the average limit.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 5. Result = Reading + Correction Factor

Margin = Result - Limit

Remark Peak = Result(PK) - Limit(AV)

 $Remark\ AVG = Result(AV) - Limit(AV)$ 

Product Name	MW GPS Watch	Test By	Rex Chiu
Test Model	MWS	Test Date	2015/04/29
Test Mode	Bluetooth 4.0 / TX Mode / CH High	Temp. & Humidity	25°C, 56%

	966 Chamber_B at 3Meter / Horizontal								
Frequency (MHz)	Reading- PK (dBuV)	Reading- AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)	Result-AV (dBuV/m)	Limit-PK (dBuV/m)		Margin (dB)	Remark
1020.00	49.90		-3.37	46.53		74.00	54.00	-7.47	Peak
1984.00	44.32		1.63	45.96		74.00	54.00	-8.04	Peak
2318.00	45.96		2.56	48.52		74.00	54.00	-5.48	Peak
3255.00	42.15		4.54	46.69		74.00	54.00	-7.31	Peak
4980.00	43.21		8.12	51.34		74.00	54.00	-2.66	Peak
7005.00	39.35		12.30	51.65		74.00	54.00	-2.35	Peak
	966 Chamber_B at 3Meter / Vertical								
Frequency	Reading-	Reading-	Correction	Result-PK	Result-AV	Limit-PK	Limit-AV	Margin	

	966 Chamber_B at 3Meter / Vertical								
Frequency (MHz)	Reading- PK (dBuV)	Reading- AV (dBuV)	Correction Factor (dB/m)	Result-PK (dBuV/m)		Limit-PK (dBuV/m)		Margin (dB)	Remark
1724.00	52.61		-0.78	51.83		74.00	54.00	-2.17	Peak
2390.00	45.88		2.74	48.62		74.00	54.00	-5.38	Peak
2686.00	46.37		3.39	49.76		74.00	54.00	-4.24	Peak
3570.00	41.89		5.16	47.05		74.00	54.00	-6.95	Peak
4995.00	47.89	30.16	8.14	56.03	38.30	74.00	54.00	-15.70	AVG
7140.00	40.06		11.99	52.05		74.00	54.00	-1.95	Peak

#### Remark:


- 1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- 2. Average test would be performed if the peak result were greater than the average limit.
- 3. Data of measurement within this frequency range shown "---" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
- 5. Result = Reading + Correction Factor


Margin = Result - Limit


Remark Peak = Result(PK) - Limit(AV)


 $Remark\ AVG = Result(AV) - Limit(AV)$ 


# **Restricted Band Edges**




















# 7.7 CONDUCTED EMISSION

# **LIMITS**

§ 15.207 (a) Except as shown in paragraph (b) and (c) this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50  $\mu$ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range	Conducted Limit (dBµv)				
(MHz)	Quasi-peak	Average			
0.15 - 0.50	66 to 56	56 to 46			
0.50 - 5.00	56	46			
5.00 - 30.0	60	50			


#### **TEST EQUIPMENT**


Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
L.I.S.N	SCHWARZBECK	NSLK 8127	8127465	08/06/2015
L.I.S.N	SCHWARZBECK	NSLK 8127	8127473	03/09/2016
EMI Receiver	ROHDE & SCHWARZ	ESHS 30	838550/003	11/02/2015
Pulse Limiter	ROHDE & SCHWARZ	ESH3-Z2	100111	06/30/2015

Remark: Each piece of equipment is scheduled for calibration once a year.

Report No.: T150415S08-RP1

# **TEST SETUP**





# **TEST PROCEDURE**

The basic test procedure was in accordance with ANSI C63.10:2009.

The test procedure is performed in a 4m × 3m × 2.4m (L×W×H) shielded room.

The EUT along with its peripherals were placed on a 1.0 m (W)  $\times$  1.5 m (L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.


The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room.

The EUT was located so that the distance between the boundary of the EUT and the closest surface of the LISN is 0.8 m. Where a mains flexible cord was provided by the manufacturer shall be 1 m long, or if in excess of 1 m, the excess cable was folded back and forth as far as possible so as to form a bundle not exceeding 0.4 m in length.

# **TEST RESULTS**

Product Name	roduct Name MW GPS Watch Test By		Jey Li	
Test Model	Test Model MWS Test Date			
Test Mode	Test Mode Charge + Read/Write Mode Temp		23.9°C, 49%	

#### LINE




#### Remark:

- 1. Correction Factor = Insertion loss + Cable loss
- 2. Emission level = Reading Value + Correction factor
- 3. Margin value = Emission level Limit value

<b>Product Name</b>	MW GPS Watch	Test By	Jey Li	
Test Model	Test Model MWS Test Date			
Test Mode	Charge + Read/Write Mode	Temp. & Humidity	23.9°C, 49%	

#### **NEUTRAL**



#### Remark:

- 1. Correction Factor = Insertion loss + Cable loss
- 2. Emission level = Reading Value + Correction factor
- 3. Margin value = Emission level Limit value