

RF EXPOSURE REPORT



Report No.: 15070226-FCC-H1

Supersede Report No.: N/A

| | | |
|---|--|---|
| Applicant | KINGTA TECHNOLOGY CO.,LIMITED | |
| Product Name | Bluetooth Speaker | |
| Model No. | 8034423 | |
| Serial No. | SPBW1035 B18 20510 , 20511, 20512,Extreme Pump H2O ,Escape, UB-SPB15, BT- 018MW,KB102H,B1,B3D,B6H,B9H,B25,B26,B28 ,B30, B38,B39, B55,B52,B58,B68 ,YA3300,WS-4014,Blunote 2.0,NU-024, 3134 | |
| Test Standard | FCC 2.1093 | |
| Test Date | April 8 to April 14, 2015 | |
| Issue Date | April 15, 2015 | |
| Test Result | <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail | |
| Equipment complied with the specification | | <input checked="" type="checkbox"/> |
| Equipment did not comply with the specification | | <input type="checkbox"/> |
| Wiky.Jam | Chris You |  |
| Wiky Jam Test Engineer | Chris You Checked By | |
| This test report may be reproduced in full only | | |
| Test result presented in this test report is applicable to the tested sample only | | |

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

| Country/Region | Scope |
|----------------|------------------------------------|
| USA | EMC, RF/Wireless, SAR, Telecom |
| Canada | EMC, RF/Wireless, SAR, Telecom |
| Taiwan | EMC, RF, Telecom, SAR, Safety |
| Hong Kong | RF/Wireless, SAR, Telecom |
| Australia | EMC, RF, Telecom, SAR, Safety |
| Korea | EMI, EMS, RF, SAR, Telecom, Safety |
| Japan | EMI, RF/Wireless, SAR, Telecom |
| Singapore | EMC, RF, SAR, Telecom |
| Europe | EMC, RF, SAR, Telecom, Safety |

| | |
|-------------|-----------------|
| Test Report | 15070226-FCC-H1 |
| Page | 3 of 8 |

This page has been left blank intentionally.

CONTENTS

| | |
|--|---|
| 1. REPORT REVISION HISTORY | 5 |
| 2. CUSTOMER INFORMATION | 5 |
| 3. TEST SITE INFORMATION..... | 5 |
| 4. EQUIPMENT UNDER TEST (EUT) INFORMATION | 6 |
| 5. FCC §2.1093 - MAXIMUM PERMISSIBLE EXPOSURE..... | 7 |
| 5.1 RF EXPOSURE..... | 7 |
| 5.2 TEST RESULT | 8 |

1. Report Revision History

| Report No. | Report Version | Description | Issue Date |
|-----------------|----------------|-------------|----------------|
| 15070226-FCC-H1 | NONE | Original | April 15, 2015 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

2. Customer information

| | |
|------------------|---|
| Applicant Name | KINGTA TECHNOLOGY CO.,LIMITED |
| Applicant Add | FLOOR 4,BUILDING 9,FUTING INDUSTRIAL ZONE,ZHUCUN,GUANLAN,BAO' AN ,SHENZHEN |
| Manufacturer | KINGTA TECHNOLOGY CO.,LIMITED |
| Manufacturer Add | FLOOR 4,BUILDING 9,FUTING INDUSTRIAL ZONE,ZHUCUN,GUANLAN,BAO' AN ,SHENZHEN |

3. Test site information

| | |
|----------------------|--|
| Lab performing tests | SIEMIC (Shenzhen-China) LABORATORIES |
| Lab Address | Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108 |
| FCC Test Site No. | 718246 |
| IC Test Site No. | 4842E-1 |
| Test Software | Radiated Emission Program-To Shenzhen v2.0 |

4. Equipment under Test (EUT) Information

Description of EUT: Bluetooth Speaker

 Main Model: 8034423

 Serial Model: SPBW1035 B18 20510 , 20511, 20512,Extreme Pump H2O ,Escape, UB-SPB15, BT-018MW,KB102H,B1,B3D,B6H,B9H,B25,B26,B28 ,B30, B38,B39, B55,B52,B58,B68 ,YA3300,WS-4014,Blunote 2.0,NU-024, 3134

 Date EUT received: April 7, 2015

 Test Date(s): April 8 to April 14, 2015

 Antenna Gain: Bluetooth: 0 dBi

 Type of Modulation: Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK

 RF Operating Frequency (ies): Bluetooth: 2402-2480 MHz

 Number of Channels: Bluetooth: 79CH

 Port: Power Port, Earphone Port, USB Port

 Input Power: Battery:
 Model: ZKH523450AR
 Spec: 3.7V 1000mAh
 Limited charger voltage: 4.2V

 Trade Name : NA

 GPRS/EGPRS Multi-slot class N/A

 FCC ID: 2AEKUB29

5. FCC §2.1093 - Maximum Permissible exposure

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16} \text{ where}$$

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

5.2 Test Result

Bluetooth Mode:

| Modulation | CH | Freq (MHz) | Conducted Power (dBm) | Tune Up Power (dBm) | Max Tune Up Power (dBm) | Max Tune Up Power (mW) | Result | Limit |
|---------------|------|------------|-----------------------|---------------------|-------------------------|------------------------|--------|-------|
| GFSK | Low | 2402 | -7.976 | -8±1 | -7 | 0.20 | 0.06 | 3 |
| | Mid | 2441 | -10.0 | -10±1 | -9 | 0.126 | 0.04 | 3 |
| | High | 2480 | -9.793 | -10±1 | -9 | 0.126 | 0.04 | 3 |
| $\pi/4$ DQPSK | Low | 2402 | -8.249 | -8±1 | -7 | 0.20 | 0.06 | 3 |
| | Mid | 2441 | -10.11 | -10±1 | -9 | 0.126 | 0.04 | 3 |
| | High | 2480 | -10.08 | -10±1 | -9 | 0.126 | 0.04 | 3 |
| 8-DPSK | Low | 2402 | -8.23 | -8±1 | -7 | 0.20 | 0.06 | 3 |
| | Mid | 2441 | -10.16 | -10±1 | -9 | 0.126 | 0.04 | 3 |
| | High | 2480 | -10.04 | -10±1 | -9 | 0.126 | 0.04 | 3 |

Result: Compliance

No SAR measurement is required.