

K103EN-RF Keyboard User Manual

This keyboard has been shipped with 3 AAA batteries installed and is already paired to its respective dongle. Simply plug the dongle into a PC and wait for USB to discover device and install drivers.

Highest operating temperature: 50°C

Pairing Instructions

User can manually pair the dongle and keyboard by pressing ctrl + alt + p to enter pairing mode. The keyboard will start searching for dongles for pairing; this will take approximately 10 seconds.

If a replaceable component or module provides a safeguard function, identification of a suitable replacement component or module shall be provided in the ordinary person instructions or instructed person instructions, or skilled person instructions as applicable.

FCC label for Keyboard

Purekeys BV

Model No.:K103EN-RF

FCC ID: 2AELMPKKRF02

MADE IN CHINA

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

Appendix

Changes or Modifications not expressly approved by the party responsible could void the user's authority to operate this device.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.