

FCC PART 15 B TEST REPORT

For

MAXWEST INTERNATIONAL LIMITED

No.1, Longgang Road, Buji, Longgang, Shenzhen City, Guangdong Province, P.R. China

FCC ID: 2AEN3NITRO4

Report Type: Product Type: Original Report Mobile Phone Dean Lau Test Engineer: Dean Liu Report Number: RDG160727004-00C **Report Date: 2016-08-18** Jerry Zhang Jerry Zhang Reviewed By: EMC Manager Bay Area Compliance Laboratories Corp. (Dongguan) **Test Laboratory:** No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	
TEST FACILITY	3
SYSTEM TEST CONFIGURATION	
DESCRIPTION OF TEST CONFIGURATION	4
EUT Exercise Software	4
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	
SUPPORT CABLE LIST AND DETAILS	4
CONFIGURATION OF TEST SETUP	5
SUMMARY OF TEST RESULTS	
FCC§15.107 - CONDUCTED EMISSIONS	7
MEASUREMENT UNCERTAINTY	
EUT SETUP	
EMI TEST RECEIVER SETUP.	
TEST EQUIPMENT LIST AND DETAILS	8
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	9
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	12
MEASUREMENT UNCERTAINTY	12
EUT SETUP	
EMI TEST RECEIVER SETUP	13
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	14

GENERAL INFORMATION

Product Description for Equipment Under Test (EUT)

The MAXWEST INTERNATIONAL LIMITED's product, model number: Nitro 4(FCC ID: 2AEN3NITRO4) (the "EUT") in this report was a Mobile Phone, which was measured approximately: 12.7 cm (L) x 6.5 cm (W) x 0.9 cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Report No.: RDG160727004-00C

Adapter Information: AC/DC ADAPTOR

INPUT: AC100-240V 50/60Hz OUTPUT: DC5V±5% 500mA

All measurement and test data in this report was gathered from production sample serial number: 160727004 (Assigned by BACL, Dongguan). The EUT was received on 2016-07-26.

Objective

This test report is prepared on behalf of *MAXWEST INTERNATIONAL LIMITED*. in accordance with Part 2, Subpart J, and Part 15-Subparts A and B of the Federal Communications Commission's rules.

The objective of the manufacturer is to determine the compliance of EUT with FCC Part 15 B Class B.

Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: 2AEN3NITRO4. FCC Part 15C DTS submissions with FCC ID: 2AEN3NITRO4. FCC Part 22H, 24E PCE submissions with FCC ID: 2AEN3NITRO4.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15 B Page 3 of 18

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a typical fashion (as normally used by a typical user).

Report No.: RDG160727004-00C

EUT Exercise Software

The software "winthrax.exe" was used during test.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	Laptop	PP11L	QDS-BRCM1017
НР	Printer	C3941A	JPTVOB2337
DELL	Keyboard	L100	CNORH656658907BL05DC
SAST	Modem	AEM-2100	0293
Kingston	Micro SD Card	8GB	/

Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
Serial Cable	Yes	No	1.2	Serial Port of Laptop	Modem
Parallel Cable	Yes	No	1.2	Parallel Port of Laptop	Printer
Keyboard Cable	Yes	No	1.8	USB Port of Laptop	Keyboard
USB Cable	No	No	1.0	USB Port of Laptop	EUT
Earphone Cable	No	No	1.2	Audio Port of EUT	Earphone

FCC Part 15 B Page 4 of 18

Configuration of Test Setup



FCC Part 15 B Page 5 of 18

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	Conducted Emissions	Compliance
§15.109	Radiated Emissions	Compliance

Report No.: RDG160727004-00C

FCC Part 15 B Page 6 of 18

FCC§15.107 - CONDUCTED EMISSIONS

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are Receiver, cable loss, and LISN.

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

Report No.: RDG160727004-00C

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- -compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- -compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.12 dB (150 kHz to 30 MHz).

Table 1 – Values of
$$U_{\text{cispr}}$$

Measurement	$U_{ m cispr}$
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

Note: The $U_{\text{lab}} > U_{\text{cispr}}$, so the U_{lab} is add in the calculation.

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

FCC Part 15 B Page 7 of 18

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15 B Class B limits.

Report No.: RDG160727004-00C

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter of laptop was connected to a 120V/60Hz AC power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W		
150 kHz – 30 MHz	9 kHz		

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date			
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-10-20	2016-10-20			
R&S	L.I.S.N	ESH2-Z5	892107/021	2016-07-16	2017-07-15			
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25			
N/A	Coaxial Cable	1.8m	N/A	2016-05-06	2017-05-06			
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A			

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

During the conducted emission test, the adapter of laptop was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

FCC Part 15 B Page 8 of 18

Herein,

V_C: corrected voltage amplitude

V_R: reading voltage amplitude

A_c: attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "Margin" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Report No.: RDG160727004-00C

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15 B Class B

Test Data

Environmental Conditions


Temperature:	29.1 °C
Relative Humidity:	60 %
ATM Pressure:	100.2 kPa

The testing was performed by Dean Liu on 2016-08-03

FCC Part 15 B

Test Mode: Downloading

AC120V, 60Hz, Line:




Report No.: RDG160727004-00C

Frequency (MHz)	Quasi Peak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.167702	43.0	9.000	L1	10.1	22.1	65.1	Compliance
0.335433	35.5	9.000	L1	10.3	23.8	59.3	Compliance
0.387164	35.7	9.000	L1	10.2	22.4	58.1	Compliance
0.436318	36.4	9.000	L1	10.2	20.7	57.1	Compliance
1.385415	32.2	9.000	L1	10.4	23.8	56.0	Compliance
1.624765	32.6	9.000	L1	10.4	23.4	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.157346	40.6	9.000	L1	10.2	15.0	55.6	Compliance
0.330129	32.4	9.000	L1	10.3	17.0	49.4	Compliance
0.381043	32.2	9.000	L1	10.2	16.1	48.3	Compliance
0.432855	34.4	9.000	L1	10.2	12.8	47.2	Compliance
1.331304	26.5	9.000	L1	10.4	19.5	46.0	Compliance
1.385415	25.3	9.000	L1	10.4	20.7	46.0	Compliance

FCC Part 15 B Page 10 of 18

AC120V, 60Hz, Neutral:



Report No.: RDG160727004-00C

Frequency (MHz)	Quasi Peak (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.159873	43.7	9.000	N	10.1	21.8	65.5	Compliance
0.381043	37.1	9.000	N	10.2	21.2	58.3	Compliance
0.429420	37.5	9.000	N	10.2	19.8	57.3	Compliance
0.436318	32.9	9.000	N	10.1	24.2	57.1	Compliance
1.190776	32.7	9.000	N	10.4	23.3	56.0	Compliance
1.289541	30.8	9.000	N	10.4	25.2	56.0	Compliance

Frequency (MHz)	Average (dBµV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)	Comment
0.152410	36.0	9.000	N	10.2	19.9	55.9	Compliance
0.335433	34.8	9.000	N	10.3	14.5	49.3	Compliance
0.381043	36.3	9.000	N	10.2	12.0	48.3	Compliance
0.426011	36.4	9.000	N	10.2	10.9	47.3	Compliance
0.432855	29.3	9.000	N	10.1	17.9	47.2	Compliance
1.144267	27.6	9.000	N	10.4	18.4	46.0	Compliance

FCC Part 15 B Page 11 of 18

FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- -compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If $U_{\rm lab}$ is greater than $U_{\rm cispr}$ of Table 1, then:
- -compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;

Report No.: RDG160727004-00C

-non - compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.


Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is: 30M~200MHz: 4.58 dB for Horizontal, 4.59 dB for Vertical; 200M~1GHz: 4.83 dB for Horizontal, 5.85 dB for Vertical; 1G~6GHz: 4.45 dB, 6G~18GHz: 5.23 dB

Table 1 – Values of U_{cispr}

Measurement					
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB				
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB				
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB				


EUT Setup

Below 1GHz:



FCC Part 15 B Page 12 of 18

Above 1GHz:



Report No.: RDG160727004-00C

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 13 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	Peak
Above I GHZ	1 MHz	10 Hz	/	AVG

Test Procedure

During the radiated emissions, the adapter of laptop was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The data was recorded in the Quasi-peak detection mode for below 1 GHz, peak and average detection mode above 1 GHz.

FCC Part 15 B Page 13 of 18

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2015-11-23	2016-11-22
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2016-02-19	2017-02-19
Farad	Test Software	EZ-EMC	V1.1.4.2	N/A	N/A
N/A	Coaxial Cable	14m	N/A	2016-05-06	2017-05-06
N/A	Coaxial Cable	8m	N/A	2016-05-06	2017-05-06

Report No.: RDG160727004-00C

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15 B Class B.

Test Data

Environmental Conditions

Temperature:	28.9 °C
Relative Humidity:	47 %
ATM Pressure:	100.3 kPa

The testing was performed by Dean Liu on 2016-07-29

Test Result: Compliance

FCC Part 15 B Page 14 of 18


^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Report No.: RDG160727004-00C

Test Mode: Downloading

1) Below 1GHz:


Horizontal



Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
45.5200	46.31	QP	-10.11	36.20	40.00	3.80
163.8600	43.57	QP	-7.47	36.10	43.50	7.40
281.2300	43.73	QP	-5.93	37.80	46.00	8.20
480.0800	40.63	QP	-1.73	38.90	46.00	7.10
683.7800	32.40	QP	1.00	33.40	46.00	12.60
723.5500	29.52	QP	1.58	31.10	46.00	14.90

FCC Part 15 B Page 15 of 18

Vertical




Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
54.2500	51.30	QP	-12.80	38.50	40.00	1.50
166.7700	46.76	QP	-7.66	39.10	43.50	4.40
253.1000	38.82	QP	-7.72	31.10	46.00	14.90
276.3800	38.30	QP	-6.00	32.30	46.00	13.70
341.3700	36.44	QP	-5.04	31.40	46.00	14.60
480.0800	40.43	QP	-1.73	38.70	46.00	7.30

FCC Part 15 B Page 16 of 18

2) Above 1GHz:

Horizontal




Report No.: RDG160727004-00C

Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Amp. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
1768.000	39.21	peak	-0.62	38.59	74.00	35.41
1768.000	26.96	AVG	-0.62	26.34	54.00	27.66
2128.000	40.29	peak	0.68	40.97	74.00	33.03
2128.000	27.61	AVG	0.68	28.29	54.00	25.71
3064.000	31.66	peak	6.74	38.40	74.00	35.60
3064.000	19.57	AVG	6.74	26.31	54.00	27.69

FCC Part 15 B Page 17 of 18

Vertical



Report No.: RDG160727004-00C

Frequency (MHz)	Receiver Reading (dBµV)	Detector	Correction Factor (dB/m)	Cord. Атр. (dBµV/m)	Limit (dBμV/m)	Margin (dB)
1768.000	43.84	peak	-0.62	43.22	74.00	30.78
1768.000	31.65	AVG	-0.62	31.03	54.00	22.97
2128.000	44.67	peak	0.68	45.35	74.00	28.65
2128.000	32.47	AVG	0.68	33.15	54.00	20.85
3070.000	33.01	peak	6.78	39.79	74.00	34.21
3070.000	20.86	AVG	6.78	27.64	54.00	26.36

*****END OF REPORT****

FCC Part 15 B Page 18 of 18