

# RF EXPOSURE REPORT



Report No.: 15050006-FCC-H

Applicant	Fenghua Tiancheng Plastic Electronics Co.,Ltd	
Product Name	INTELLIGENT CONTROLLER	
Model No.	CRZ-8X8	
Serial No.	N/A	
Test Standard	FCC 2.1091	
Test Date	May 07 to June 02, 2015	
Issue Date	June 03, 2015	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification		<input checked="" type="checkbox"/>
Equipment did not comply with the specification		<input type="checkbox"/>
Winnie Zhang Test Engineer	Chris You Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15050006-FCC-H
Page	3 of 10

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY .....	5
2. CUSTOMER INFORMATION .....	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. FCC §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....	8
6.1 APPLICABLE STANDARD .....	8
6.2 TEST RESULT .....	9

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
15050006-FCC-H	NONE	Original	June 03, 2015

## 2. Customer information

Applicant Name	Fenghua Tiancheng Plastic Electronics Co.,Ltd
Applicant Add	No.66 Dongfeng Road Fenghua Zhejiang China
Manufacturer	Fenghua Tiancheng Plastic Electronics Co.,Ltd
Manufacturer Add	No.66 Dongfeng Road Fenghua Zhejiang China

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Labview of SIEMIC version 2.0

#### 4. Equipment under Test (EUT) Information

Description of EUT: INTELLIGENT CONTROLLER

Main Model: CRZ-8X8

Serial Model: N/A

Date EUT received: April 09, 2015

Test Date(s): May 07 to June 02, 2015

Equipment Category : DXT

Antenna Gain:  
WIFI: -0.5 dBi  
15.249: 4.5 dBi

Input Power: AC 120V 60Hz

Trade Name : CRZ

FCC ID: 2AENLCRZ

Test Report	15050006-FCC-H
Page	7 of 10

Type of Modulation: 802.11b/g/n: DSSS, OFDM  
15.249: DSSS

RF Operating Frequency (ies): WIFI:802.11b/g/n(20M): 2412-2462 MHz  
WIFI:802.11n(40M): 2422-2452 MHz  
15.249: 2470 MHz

Number of Channels: WIFI :802.11b/g/n(20M): 11CH  
WIFI :802.11n(40M): 7CH  
15.249: 1 Channel

Port: Power Port,

## 5. FCC §2.1091 - Maximum Permissible exposure (MPE)

### 6.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

#### Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

## 6.2 Test Result

Type	Test mode	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)
Output power	802.11b	Low	2412	14.85	14.0±1
		Mid	2437	15.79	15.0±1
		High	2462	<b>16.72</b>	16.0±1
	802.11g	Low	2412	11.03	11.0±1
		Mid	2437	11.04	11.0±1
		High	2462	<b>11.67</b>	11.0±1
	802.11n (20M)	Low	2412	10.54	10.0±1
		Mid	2437	10.98	11.0±1
		High	2462	<b>11.87</b>	11.0±1
	802.11n (40M)	Low	2422	9.45	9.0±1
		Mid	2437	8.96	9.0±1
		High	2452	<b>10.18</b>	10.0±1

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

Where: S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power **Tune Up** to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For the antenna manufacturer provide only used limited to ERP/EIRP or radiated spurious emission test. The MPE evaluation as below:

Maximum Tune Up power at antenna input terminal: 17 dBm

Maximum output power at antenna input terminal: 50.119 (mW)

Prediction distance: >20 (cm)

Test Report	15050006-FCC-H
Page	10 of 10

Predication frequency: 2462 (MHz) High frequency

Antenna Gain (typical): -0.5 (dBi)

Antenna Gain (typical): 0.891 (numeric)

The worst case is power density at predication frequency at 20 cm: 0.009(mW/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1.0 (mW/cm<sup>2</sup>)

$0.009(\text{mW/cm}^2) < 1.0 (\text{mW/cm}^2)$

**Result:** Pass