





Report No.: FA990601

# **RF Exposure Evaluation Report**

FCC ID : 2AENP-MB01

Equipment : Wireless Headphones

Brand Name : Montblanc

Model Name : MB 01

Applicant/ : Montblanc-Simplo GmbH

Manufacturer Hellgrundweg 100, 22525 Hamburg, Germany

Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Sep. 06, 2019, and testing was started from Sep. 25, 2019 and completed on Oct. 15, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Allen Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

TEL: 886-3-327-3456 Page Number : 1 of 5

FAX: 886-3-327-0973 Issued Date : Oct. 16, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01



# RF Exposure Evaluation Report

### **Table of Contents**

HISTO	RY OF THIS TEST REPORT	3
1.	GENERAL DESCRIPTION	4
1.1.	EUT General Information	4
1.2.	Table for Multiple Listing	4
1.3.	Testing Location Information	4
2	RF EXPOSURE EVALUATION	_
	Applicable Standard	
2.2.	SAR evaluation	5

Photographs of EUT V01

TEL: 886-3-327-3456 FAX: 886-3-327-0973

Report Template No.: HE1-A3 Ver2.1

FCC ID: 2AENP-MB01

Page Number : 2 of 5

Issued Date : Oct. 16, 2019

Report No. : FA990601

Report Version : 01

### **HISTORY OF THIS TEST REPORT**

Report No. : FA990601

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA990601	01	Initial issue of report	Oct. 16, 2019

Reviewed by: Sam Tsai

Report Producer: Kate Lo

TEL: 886-3-327-3456 Page Number : 3 of 5
FAX: 886-3-327-0973 Issued Date : Oct. 16, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01

# 1. GENERAL DESCRIPTION

#### 1.1. EUT General Information

RF General Information						
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type			
Bluetooth	BILIQTOOTO   /4111=/4835   /411/=/4811		BR / EDR: FHSS (GFSK / π/4-DQPSK / 8DPSK) LE: DSSS (GFSK)			

Report No.: FA990601

### 1.2. Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description				
MB 01(EUT)					
MB 01(USB Cable)	There are three appearance colors.				
MB 01(Audio Cable)					

### 1.3. Testing Location Information

Testing Location									
$\boxtimes$	HWA YA	ADD	:	No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)					
		TEL	:	886-3-327-3456	FAX	:	886-3-327-0973		
	Test site Designation No. TW1190 with FCC.								
	JHUBEI ADD : No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County, Taiwan (R.O.C.)								
		TEL	:	886-3-656-9065	FAX	:	886-3-656-9085		
	Test site Designation No. TW0006 with FCC.								

TEL: 886-3-327-3456 Page Number : 4 of 5
FAX: 886-3-327-0973 Issued Date : Oct. 16, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01



#### 2. RF EXPOSURE EVALUATION

#### 2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Report No.: FA990601

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

#### 2.2. SAR evaluation

1. Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]•

 $[\sqrt{f}_{(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Max. Power	Gain	Tolerance	Tune-up Max. Power		<b>Test Distance</b>	Frequency	Exclusion	
(dBm)	(dBi)	(dB)	(dBm) (mW)		(mm)	(GHz)	Thresholds	
3.06	1.82	0.5	5.38	3.45	5	2.402	1.07	

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is 1.07 < 3, RF exposure evaluation is not required.

——THE END——

TEL: 886-3-327-3456 Page Number : 5 of 5
FAX: 886-3-327-0973 Issued Date : Oct. 16, 2019

Report Template No.: HE1-A3 Ver2.1 Report Version : 01