

## TEST REPORT

**Product** : SMARTCHIME DOOR CHIME RECEIVER  
**Trade mark** : N/A  
**Model/Type reference** : 2602-RX, S-2601, S-2602, 216596  
**Serial Number** : N/A  
**Report Number** : EED32H000296-3  
**FCC ID** : 2AEOF-SCDB2602RX  
**Date of Issue:** : Jun. 16, 2015  
**Test Standards** : 47 CFR Part 15 Subpart C (2014)  
**Test result** : PASS

Prepared for:

**DONGGUAN SMART HERO ELECTRONIC PRODUCTS CO LTD**  
**118 LI XIANG ROAD WEST, SHUI PING VILLAGE, DALANG, DONGGUAN,**  
**GUANGDONG, CHINA**

Prepared by:

**Centre Testing International (Shenzhen) Corporation**  
**Hongwei Industrial Zone, 70 Area, Bao'an District,**  
**Shenzhen, Guangdong, China**  
**TEL: +86-755-3368 3668**  
**FAX: +86-755-3368 3385**

Tested by:

Wang Xin

Reviewed by:

Kevin Lan

Approved by:

Sheek, Luo

Date:

Jun. 08, 2015

Sheek Luo

Lab supervisor

Check No.: 1996277469



## 2 Version

Version No.	Date	Description
00	2015-04-01	Original



### 3 Test Summary

Test Item	Test Requirement	Test method	Result
<b>Antenna Requirement</b>	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2009	PASS
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10-2009	PASS
<b>Conducted Peak Output Power</b>	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10-2009	PASS
<b>6dB Occupied Bandwidth</b>	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10-2009	PASS
<b>Power Spectral Density</b>	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10-2009	PASS
<b>Band-edge for RF Conducted Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10-2009	PASS
<b>RF Conducted Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10-2009	PASS
<b>Radiated Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10-2009	PASS
<b>Restricted bands around fundamental frequency (Radiated Emission)</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10-2009	PASS

## Remark:

1. Model No.: 2602-RX, S-2601, S-2602, 216596

Only the Model 2602-RX was tested, since the electrical circuit design, layout, components used and internal wiring were identical for all above models. Only different on outer colors and model names.

2. Test according to ANSI C63.4-2009 &amp; ANSI C63.10-2009.


## 4 Content

1	<b>COVER PAGE</b>	1
2	<b>VERSION</b>	2
3	<b>TEST SUMMARY</b>	3
4	<b>CONTENT</b>	4
5	<b>TEST REQUIREMENT</b>	5
5.1	<b>TEST SETUP</b>	5
5.1.1	<i>For Conducted test setup</i>	5
5.1.2	<i>For Radiated Emissions test setup</i>	5
5.1.3	<i>For Conducted Emissions test setup</i>	6
5.2	<b>TEST ENVIRONMENT</b>	6
5.3	<b>TEST CONDITION</b>	6
6	<b>GENERAL INFORMATION</b>	8
6.1	<b>CLIENT INFORMATION</b>	8
6.2	<b>GENERAL DESCRIPTION OF EUT</b>	8
6.3	<b>PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD</b>	8
6.4	<b>DESCRIPTION OF SUPPORT UNITS</b>	9
6.5	<b>TEST LOCATION</b>	9
6.6	<b>TEST FACILITY</b>	9
6.7	<b>DEVIATION FROM STANDARDS</b>	10
6.8	<b>ABNORMALITIES FROM STANDARD CONDITIONS</b>	10
6.9	<b>OTHER INFORMATION REQUESTED BY THE CUSTOMER</b>	10
7	<b>EQUIPMENT LIST</b>	11
8	<b>RADIO TECHNICAL REQUIREMENTS SPECIFICATION</b>	12
	Appendix A): <i>Conducted Peak Output Power</i>	13
	Appendix B): <i>6dB Occupied Bandwidth</i>	18
	Appendix C): <i>Band-edge for RF Conducted Emissions</i>	23
	Appendix D): <i>RF Conducted Spurious Emissions</i>	26
	Appendix E): <i>Power Spectral Density</i>	38
	Appendix F) <i>Antenna Requirement</i>	43
	Appendix G) <i>AC Power Line Conducted Emission</i>	44
	Appendix H) <i>Restricted bands around fundamental frequency (Radiated) / Radiated Spurious Emissions</i>	47
	<b>PHOTOGRAPHS OF TEST SETUP</b>	55
	<b>PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS</b>	57

## 5 Test Requirement

### 5.1 Test setup

#### 5.1.1 For Conducted test setup



#### 5.1.2 For Radiated Emissions test setup

##### Radiated Emissions setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1GHz

### 5.1.3 For Conducted Emissions test setup

#### Conducted Emissions setup



## 5.2 Test Environment

### Operating Environment:

Temperature:	25.0 °C
Humidity:	53 % RH
Atmospheric Pressure:	995mbar

## 5.3 Test Condition

Test channel:

Test Mode	Tx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11b/g/n(HT20)	2412MHz ~2462 MHz	Channel 1	Channel 6	Channel 11
		2412MHz	2437MHz	2462MHz
802.11n(HT40)	2422MHz ~2452 MHz	Channel 1	Channel 4	Channel 7
		2422MHz	2437MHz	2452MHz
Transmitting mode:	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.			

Test mode:

**Pre-scan under all rate at lowest channel 1**

Mode	802.11b							
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
EIRP(dBm)	15.87	15.98	16.53	16.73				
Mode	802.11g							
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
EIRP(dBm)	16.68	16.67	16.45	16.34	16.33	16.08	16.23	16.32
Mode	802.11n (HT20)							
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
EIRP(dBm)	16.73	16.72	16.38	16.33	16.32	16.23	16.22	16.23
Mode	802.11n (HT40)							
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps
EIRP(dBm)	16.32	16.23	16.20	16.19	16.12	16.23	16.20	16.21

Through Pre-scan, 11Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n (HT20); 13.5Mbps of rate is the worst case of 802.11n (HT40).



## 6 General Information

### 6.1 Client Information

Applicant:	DONGGUAN SMART HERO ELECTRONIC PRODUCTS CO LTD
Address of Applicant:	118 LI XIANG ROAD WEST, SHUI PING VILLAGE, DALANG, DONGGUAN, GUANGDONG, CHINA
Manufacturer:	UNIVERSAL CONSUMER PRODUCTS
Address of Manufacturer:	UNIVERSAL CONSUMER PRODUCTS 2801 EAST BELTLINE NE, GRAND RAPIDS, MI 49525, USA

### 6.2 General Description of EUT

Product Name:	SMARTCHIME DOOR CHIME RECEIVER	
Model No.(EUT):	2602-RX	
Add Mode No.:	S-2601, S-2602, 216596	
Trade Mark:	N/A	
EUT Supports Radios application	Wlan 2.4GHz 802.11b/g/n(HT20&HT40)	
Power Supply:	Adapter:	Input: AC 100V-240V 50-60Hz 300mA Output: DC 5.0V 500mA
Sample Received Date:	Mar. 13, 2015	
Sample tested Date:	Mar. 20, 2015 to Jun. 16, 2015	

### 6.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels IEEE 802.11n HT40: 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20 and HT40) : OFDM (64QAM, 16QAM, QPSK,BPSK)
Sample Type:	fixed production
Antenna Type and Gain:	Type: Integral antenna Gain:0dBi
Test Voltage:	AC 120V, 60Hz

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel(802.11n HT40)					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2422MHz	4	2437MHz	7	2452MHz
2	2427MHz	5	2442MHz		
3	2432MHz	6	2447MHz		

## 6.4 Description of Support Units

The EUT has been tested independently.

## 6.5 Test Location

All tests were performed at:

Centre Testing International (Shenzhen) Corporation Hongwei Industrial Zone, Bao'an 70 District, Shenzhen, Guangdong, China 518101

Telephone: +86 (0) 755 3368 3668 Fax:+86 (0) 755 3368 3385

No tests were sub-contracted.

## 6.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### CNAS-Lab Code: L1910

Centre Testing International (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. .

### A2LA-Lab Cert. No. 3061.01

Centre Testing International (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

**FCC-Registration No.: 756231**

Centre Testing International (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 756231.

**IC-Registration No.: 7408A**

The 3m Alternate Test Site of Centre Testing International (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408A .

**IC-Registration No.: 7408B**

The 10m Alternate Test Site of Centre Testing International (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 7408B.

**NEMKO-Aut. No.: ELA503**

Centre Testing International (Shenzhen) Co., Ltd. has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10.

**VCCI**

The Radiation 3 & 10 meters site of Centre Testing International (Shenzhen) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-4096.

Main Ports Conducted Interference Measurement of Centre Testing International (Shenzhen) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-4563.

Telecommunication Ports Conducted Disturbance Measurement of Centre Testing International (Shenzhen) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-2146.

The Radiation 3 meters site of Centre Testing International (Shenzhen) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-758

## **6.7 Deviation from Standards**

None.

## **6.8 Abnormalities from Standard Conditions**

None.

## **6.9 Other Information Requested by the Customer**

None.

## 7 Equipment List

Equipment	Manufacturer	Model	Serial No.	Due Date
3M Chamber & Accessory Equipment	TDK	SAC-3	---	06/01/2016
Receiver	R&S	ESCI	100435	07/08/2015
Spectrum Analyzer	R&S	FSP40	100416	07/06/2015
Signal Generator	R&S	SMB 100A	3008A02145	01/15/2016
Vector Signal Generator	R&S	SMBV 100A	3636A01004	01/15/2016
Signal Analyzer	R&S	FSV	100263	01/15/2016
Communication test set test set	Agilent	N4010A	MY47230124	01/15/2016
Spectrum Analyzer	Keysight	N9010A	5522H-HY5KC-VL	01/15/2016
Signal Generator	Keysight	N5182B	MMAPJ-I6AC3	01/15/2016
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	618	06/17/2015
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	617	07/13/2015
Multi device Controller	maturo	NCD/070/107 11112	---	N/A
Horn Antenna	ETS-LINGREN	3117	00057407	07/07/2015
Horn Antenna	ETS-LINGREN	3117	00057362	07/07/2015
Microwave Preamplifier	Agilent	8449B	3008A02425	03/19/2016
ESG Vector signal generators	Agilent	E4438C	MY45095744	01/15/2016
Temperature & Humidity Chamber	ESPEC	EL-04KA	N/A	08/03/2015
Receiver	R&S	ESCI	100009	07/19/2015
LISN	R&S	ENV216	100098	07/19/2015

## 8 Radio Technical Requirements Specification

### Reference documents for testing:

No.	Identity	Document Title
1	FCC Part15C (2014)	Subpart C-Intentional Radiators
2	ANSI C63.10-2009	American National Standard for Testing Unlicensed Wireless Devices

### Test Results List:


Test Requirement	Test method	Test item	Verdict	Note
Part15C Section 15.247 (b)(3)	ANSI C63.10	Conducted Peak Output Power	PASS	Appendix A)
Part15C Section 15.247 (a)(2)	ANSI C63.10	6dB Occupied Bandwidth	PASS	Appendix B)
Part15C Section 15.247(d)	ANSI C63.10	Band-edge for RF Conducted Emissions	PASS	Appendix C)
Part15C Section 15.247(d)	ANSI C63.10	RF Conducted Spurious Emissions	PASS	Appendix D)
Part15C Section 15.247 (e)	ANSI C63.10	Power Spectral Density	PASS	Appendix E)
Part15C Section 15.203/15.247 (c)	ANSI C63.10	Antenna Requirement	PASS	Appendix F)
Part15C Section 15.207	ANSI C63.10	AC Power Line Conducted Emission	PASS	Appendix G)
Part15C Section 15.205/15.209	ANSI C63.10	Restricted bands around fundamental frequency (Radiated Emission)	PASS	Appendix H)
Part15C Section 15.205/15.209	ANSI C63.10	Radiated Spurious Emissions	PASS	Appendix I)

## Appendix A): Conducted Peak Output Power


**Result Table**

Mode	Channel	Meas.Level [dBm]	Verdict
11B	LCH	16.73	PASS
11B	MCH	16.49	PASS
11B	HCH	15.67	PASS
11G	LCH	16.15	PASS
11G	MCH	16.51	PASS
11G	HCH	16.68	PASS
11N20SISO	LCH	16.20	PASS
11N20SISO	MCH	16.41	PASS
11N20SISO	HCH	16.73	PASS
11N40SISO	LCH	16.08	PASS
11N40SISO	MCH	16.07	PASS
11N40SISO	HCH	16.32	PASS


**Test Graph**












## Appendix B): 6dB Occupied Bandwidth


### Result Table

Mode	Channel	6dB Bandwidth [MHz]	99% OBW [MHz]	Verdict
11B	LCH	10.04	15.317	PASS
11B	MCH	10.06	15.475	PASS
11B	HCH	10.02	15.318	PASS
11G	LCH	16.37	16.539	PASS
11G	MCH	16.35	16.533	PASS
11G	HCH	16.35	16.552	PASS
11N20SISO	LCH	17.62	17.759	PASS
11N20SISO	MCH	17.58	17.744	PASS
11N20SISO	HCH	17.60	17.766	PASS
11N40SISO	LCH	35.44	36.092	PASS
11N40SISO	MCH	35.37	36.016	PASS
11N40SISO	HCH	35.34	36.025	PASS


### Test Graph












## Appendix C): Band-edge for RF Conducted Emissions

### Test Graph











## Appendix D): RF Conducted Spurious Emissions


### Test Graph

































## Appendix E): Power Spectral Density

### Result Table

Mode	Channel	Meas.Level [dBm]	Verdict
11B	LCH	-1.157	PASS
11B	MCH	-0.344	PASS
11B	HCH	-1.614	PASS
11G	LCH	-12.278	PASS
11G	MCH	-12.653	PASS
11G	HCH	-12.341	PASS
11N20SISO	LCH	-13.399	PASS
11N20SISO	MCH	-12.412	PASS
11N20SISO	HCH	-12.327	PASS
11N40SISO	LCH	-28.191	PASS
11N40SISO	MCH	-25.625	PASS
11N40SISO	HCH	-27.946	PASS

### Test Graph











## Appendix F) Antenna Requirement

### 15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:	
--------------	--

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0dBi.

## Appendix G) AC Power Line Conducted Emission

Test Procedure:	<p>Test frequency range :150KHz-30MHz</p> <ol style="list-style-type: none"> <li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.</li> </ol>																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr> <tr> <th>Quasi-peak</th><th>Average</th></tr> </thead> <tbody> <tr> <td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr> <tr> <td>0.5-5</td><td>56</td><td>46</td></tr> <tr> <td>5-30</td><td>60</td><td>50</td></tr> </tbody> </table> <p>* The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.</p> <p>NOTE : The lower limit is applicable at the transition frequency</p>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															


**Measurement Data**

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


<b>Product</b>	:	SMARTCHIME DOOR CHIME RECEIVER	<b>Model/Type reference</b>	:	2602-RX
<b>Power</b>	:	AC 120V/60Hz	<b>Temperature</b>	:	22°C
<b>Mode</b>	:	Keeping TX	<b>Humidity</b>	:	52%

Live line:



No.	Freq.	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		MHz	Peak	QP	Avg	dB	peak	QP	Avg	QP	Avg	QP	Avg	
1	0.2980	25.70	25.43	16.20	9.90	35.60	35.33	26.10	60.30	50.30	-24.97	-24.20	P	
2	0.4620	20.49	17.30	8.34	9.90	30.39	27.20	18.24	56.66	46.66	-29.46	-28.42	P	
3	0.6740	23.75	17.10	7.60	9.90	33.65	27.00	17.50	56.00	46.00	-29.00	-28.50	P	
4	1.9500	22.95	16.51	6.15	9.90	32.85	26.41	16.05	56.00	46.00	-29.59	-29.95	P	
5	3.2019	21.02	15.40	5.94	9.90	30.92	25.30	15.84	56.00	46.00	-30.70	-30.16	P	
6	17.7780	28.95	22.10	10.65	10.18	39.13	32.28	20.83	60.00	50.00	-27.72	-29.17	P	

Neutral line:



No.	Freq.	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		
		MHz	Peak	QP	Avg	peak	QP	Avg	QP	Avg	QP	Avg	P/F
1	0.2540	24.11	22.00	6.53	9.90	34.01	31.90	16.43	61.62	51.62	-29.72	-35.19	P
2	0.3020	24.58	22.41	9.80	9.90	34.48	32.31	19.70	60.19	50.19	-27.88	-30.49	P
3	0.8500	19.71	16.37	4.85	9.90	29.61	26.27	14.75	56.00	46.00	-29.73	-31.25	P
4	1.6860	20.49	12.42	0.62	9.90	30.39	22.32	10.52	56.00	46.00	-33.68	-35.48	P
5	2.4780	18.48	11.25	2.67	9.90	28.38	21.15	12.57	56.00	46.00	-34.85	-33.43	P
6	17.7700	30.66	23.45	9.58	10.18	40.84	33.63	19.76	60.00	50.00	-26.37	-30.24	P

## Appendix H) Restricted bands around fundamental frequency (Radiated) / Radiated Spurious Emissions

Receiver Setup:	Frequency	Detector	RBW	VBW	Remark					
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak					
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average					
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak					
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak					
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average					
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak					
	30MHz-1GHz	Quasi-peak	120 kHz	300kHz	Quasi-peak					
	Above 1GHz	Peak	1MHz	3MHz	Peak					
		Peak	1MHz	10Hz	Average					
Test Procedure:										
<b>Below 1GHz test procedure as below:</b>										
<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>										
<b>Above 1GHz test procedure as below:</b>										
<ol style="list-style-type: none"> <li>Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber.</li> <li>Test the EUT in the lowest channel ,the middle channel ,the Highest channel</li> <li>The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case.</li> <li>Repeat above procedures until all frequencies measured was complete.</li> </ol>										

Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	-	30
1.705MHz-30MHz	30	-	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3	
88MHz-216MHz	150	43.5	Quasi-peak	3	
216MHz-960MHz	200	46.0	Quasi-peak	3	
960MHz-1GHz	500	54.0	Quasi-peak	3	
Above 1GHz	500	54.0	Average	3	

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

## Radiated Spurious Emissions test Data:

All the modes of operation (X, Y, Z) were investigated and the worst-case emissions are reported.


### A. Below 30MHz:

No emissions were found higher than the background below 30MHz and background is lower than the limit, so it deems to compliance with the limit without recorded.

### B. 30MHz ~ 1GHz:

The test data of low channel, middle channel and high channel in IEEE 802.11b/g/n are almost same in frequency bands 30MHz to 1GHz and the data of low channel in IEEE 802.11b of 11Mbps are chosen as representative in below:

H:




### MEASUREMENT RESULT: "CTI150605011\_red"

05/06/2015 15:18

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
49.400000	22.50	16.0	40.0	17.5	---	200.0	71.00	HORIZONTAL
55.220000	21.20	15.4	40.0	18.8	---	200.0	172.00	HORIZONTAL
99.840000	18.80	13.4	43.5	24.7	---	100.0	174.00	HORIZONTAL
198.780000	19.80	14.2	43.5	23.7	---	100.0	10.00	HORIZONTAL
544.100000	26.90	21.6	46.0	19.1	---	200.0	132.00	HORIZONTAL
939.860000	33.90	27.2	46.0	12.1	---	200.0	303.00	HORIZONTAL

V:



**MEASUREMENT RESULT: "CTI150605010\_red"**

05/06/2015 15:15

Frequency MHz	Level dB $\mu$ V/m	Transd dB	Limit dB $\mu$ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
49.400000	28.70	16.0	40.0	11.3	---	100.0	54.00	VERTICAL
55.220000	22.50	15.4	40.0	17.5	---	200.0	320.00	VERTICAL
136.700000	19.80	10.9	43.5	23.7	---	100.0	66.00	VERTICAL
214.300000	20.10	14.6	43.5	23.4	---	100.0	135.00	VERTICAL
546.040000	28.00	21.7	46.0	18.0	---	100.0	146.00	VERTICAL
939.860000	32.90	27.2	46.0	13.1	---	200.0	41.00	VERTICAL

**C. Above 1GHz:**

The test data of worst case are below:

IEEE 802.11b:

Frequency (MHz)	Measurement (dBuV/m)	Limit (dBuV/m)	Detector Type	Antenna (H/V)	Result (P/F)
Low channel (2412MHz)					
2390.0	34.78	74	PK	H	P
2400.0	49.09	74	PK	H	P
4824.0	43.84	74	PK	H	P
2390.0	35.08	74	PK	V	P
2400.0	48.56	74	PK	V	P
4824.0	44.81	74	PK	V	P
Middle channel (2437MHz)					
4874.0	43.74	74	PK	H	P
4874.0	44.42	74	PK	V	P
High channel (2462MHz)					
2483.5	42.36	74	PK	H	P
4924.0	43.73	74	PK	H	P
2483.5	44.41	74	PK	V	P
4924.0	44.33	74	PK	V	P

## IEEE 802.11g:

Frequency (MHz)	Measurement (dBuV/m)	Limit (dBuV/m)	Detector Type	Antenna (H/V)	Result (P/F)
Low channel (2412MHz)					
2390.0	34.23	74	PK	H	P
2400.0	48.23	74	PK	H	P
4824.0	43.37	74	PK	H	P
2390.0	35.13	74	PK	V	P
2400.0	48.82	74	PK	V	P
4824.0	44.36	74	PK	V	P
Middle channel (2437MHz)					
4874.0	44.37	74	PK	H	P
4874.0	43.41	74	PK	V	P
High channel (2462MHz)					
2483.5	43.43	74	PK	H	P
4924.0	44.18	74	PK	H	P
2483.5	44.02	74	PK	V	P
4924.0	44.01	74	PK	V	P

IEEE 802.11n HT20:

Frequency (MHz)	Measurement (dBuV/m)	Limit (dBuV/m)	Detector Type	Antenna (H/V)	Result (P/F)
Low channel (2412MHz)					
2390.0	34.28	74	PK	H	P
2400.0	48.25	74	PK	H	P
4824.0	43.31	74	PK	H	P
2390.0	35.28	74	PK	V	P
2400.0	48.23	74	PK	V	P
4824.0	45.47	74	PK	V	P
Middle channel (2437MHz)					
4874.0	44.36	74	PK	H	P
4874.0	44.67	74	PK	V	P
High channel (2462MHz)					
2483.5	43.81	74	PK	H	P
4924.0	45.36	74	PK	H	P
2483.5	44.23	74	PK	V	P
4924.0	45.02	74	PK	V	P

## IEEE 802.11n HT40:

Frequency (MHz)	Measurement (dBuV/m)	Limit (dBuV/m)	Detector Type	Antenna (H/V)	Result (P/F)
Low channel (2422MHz)					
2390.0	34.36	74	PK	H	P
2400.0	49.15	74	PK	H	P
4844.0	44.83	74	PK	H	P
2390.0	36.07	74	PK	V	P
2400.0	49.11	74	PK	V	P
4844.0	46.47	74	PK	V	P
Middle channel (2437MHz)					
4874.0	46.37	74	PK	H	P
4874.0	45.30	74	PK	V	P
High channel (2462MHz)					
2483.5	44.54	74	PK	H	P
4904.0	47.12	74	PK	H	P
2483.5	43.34	74	PK	V	P
4904.0	45.32	74	PK	V	P

## Remark:


1. The above tables show that the frequencies peak data are all below the average limit, so the average data of these frequencies are deemed to fulfill the average limits and not reported.
2. No emission found from 18GHz to 25GHz.
3. All outside of operating frequency band and restricted band specified are below 15.209.

## PHOTOGRAPHS OF TEST SETUP

Test mode No: 2602-RX.



Radiated spurious emission Test Setup-1 (Below 1GHz)



Radiated spurious emission Test Setup-2(Above 1GHz)



**Conducted emission Test Setup**

### PHOTOGRAPHS OF EUT Constructional Details



View of EUT-1



View of EUT-2



View of EUT-3



View of EUT-4




View of EUT-5




View of EUT-6




View of EUT-7




View of EUT-8




View of EUT-9



View of EUT-10



View of EUT-11



View of EUT-12

\*\*\* End of Report \*\*\*

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.