

TEST REPORT

Product : WIRELESS DOOR CHIME PUSH BUTTON
Trade mark : N/A
Model/Type reference : 2324-TX, 2325-TX, 2326-TX, 2327-TX
Serial number : N/A
Ratings : DC 3V
FCC ID : 2AEOF-WLDB2324TX
Report number : EED32H000300-1
Date : Apr. 28, 2015
Regulations : See below

Test Standards	Results
<input checked="" type="checkbox"/> 47 CFR FCC Part 15 Subpart C 15.231: 2014	PASS

Prepared for:

DONGGUAN SMART HERO ELECTRONIC PRODUCTS CO LTD
118 LI XIANG ROAD WEST, SHUI PING VILLAGE, DALANG, DONGGUAN,
GUANGDONG, CHINA

Prepared by:

Centre Testing International (Shenzhen) Corporation
Hongwei Industrial Zone, 70 Area, Bao'an District,
Shenzhen, Guangdong, China
TEL: +86-755-3368 3668
FAX: +86-755-3368 3385

Tested by: Wang Xin

Reviewed by: Sheek, Luo

Approved by: Jimmy Li
Jimmy Li
Lab manager

Date: Apr. 28, 2015

Check No.: 1996277469



TABLE OF CONTENTS

1. CERTIFICATION INFORMATION	3
2. TEST SUMMARY	3
3. MEASUREMENT UNCERTAINTY	4
4. PRODUCT INFORMATION	4
5. TEST EQUIPMENT LIST	4
6. SUPPORT EQUIPMENT LIST	4
7. OPERATION CHARACTERISTICS	5
7.1. LIMITS	5
7.2. BLOCK DIAGRAM OF TEST SETUP	5
7.3. TEST PROCEDURE	5
7.4. TEST RESULT	5
8. 20DB/ 99% BANDWIDTH MEASUREMENT	6
8.1. LIMITS	6
8.2. BLOCK DIAGRAM OF TEST SETUP	6
8.3. TEST PROCEDURE	6
8.4. TEST RESULT	6
9. RADIATED EMISSION MEASUREMENT	8
9.1. LIMITS	8
9.2. BLOCK DIAGRAM OF TEST SETUP	8
9.3. TEST PROCEDURE	9
9.4. TEST RESULT	10
APPENDIX 1 PHOTOGRAPHS OF TEST SETUP	15
APPENDIX 2 EXTERNAL PHOTOGRAPHS OF PRODUCT	16
APPENDIX 3 INTERNAL PHOTOGRAPHS OF PRODUCT	17

N/A means not applicable.

1. CERTIFICATION INFORMATION

Applicant: DONGGUAN SMART HERO ELECTRONIC PRODUCTS CO LTD
 118 LI XIANG ROAD WEST, SHUI PING VILLAGE, DALANG,
 DONGGUAN, GUANGDONG, CHINA

Manufacturer: UNIVERSAL CONSUMER PRODUCTS
 2801 EAST BELTLINE NE, GRAND RAPIDS, MI 49525, USA

FCC ID: 2AE0F-WLDB2324TX

Product: WIRELESS DOOR CHIME PUSH BUTTON

Model/Type reference: 2324-TX, 2325-TX, 2326-TX, 2327-TX

Trade Name: N/A

Serial Number: N/A

Report Number: EED32H000300-1

Sample Received Date: Mar. 20, 2015

Sample tested Date: Mar. 20, 2015 to Apr. 28, 2015

The above equipment was tested by Centre Testing International (Shenzhen) Corporation for compliance with the requirements set forth in the FCC Rules and Regulations Part 15, Subpart C and the measurement procedure according to ANSI C63.4:2014 and ANSI C63.10:2013.

2. TEST SUMMARY

No.	Test Item	Rule	Result
1	Operation characteristics	FCC Part15.231(a) & A1.1.1	PASS
2	Radiated Emission	FCC Part15.231(b) & A1.1	PASS
3	20dB bandwidth & 99% bandwidth	FCC Part15.231 & A1.1.3	PASS
4	AC Conducted Emission	FCC PART15.207 & RSS-Gen 7.2.4	N/A
5	Antenna requirements	FCC PART15.203 & RSS-Gen 7.1.2 (See Note 1)	PASS

Note:

1. According to Section 15.203 and RSS-Gen 7.1.2, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The EUT has a built in antenna which is a short wire solder on the PCB, this is permanently attached antenna and meets the requirements of this section.
2. New battery is used during all the test.

3. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Value (dB)
Conducted Emission Test	3.2 dB
Radiated Emissions / Bandedge Emission	4.5 dB

4. PRODUCT INFORMATION

Items	Description
Rating	DC 3V
Type of Modulation	ASK
Antenna Type	Integral antenna
Frequency	315 MHz
Gain	0dBi

All models are same except model name and brand name. Model 2324-TX was selected for test.

5. TEST EQUIPMENT LIST

Equipment	Manufacturer	Model	Serial No.	Due Date
3M Chamber & Accessory Equipment	ETS-LINDGREN	FACT-3	3510	07/12/2016
Spectrum Analyzer	Agilent	E4443A	MY45300910	01/12/2016
Receiver	R&S	ESCI	100435	07/08/2015
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	617	07/13/2015
Multi device Controller	ETS-LINGREN	2090	00057230	N/A
Horn Antenna	ETS-LINGREN	3117	00057407	07/07/2015
Microwave Preamplifier	Agilent	8449B	3008A02425	01/28/2016
Spectrum Analyzer	R&S	FSP40	100416	07/06/2015

6. SUPPORT EQUIPMENT LIST

Device Type	Brand	Model	Data Cable	Remark
---	---	---	---	---
---	---	---	---	---


7. Operation characteristics

7.1. LIMITS

FCC PART15.231 a(1):

A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

7.2. BLOCK DIAGRAM OF TEST SETUP




7.3. TEST PROCEDURE

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set the center frequency is 315MHz and set the Span is 0Hz.
3. Set spectrum analyzer's RBW and VBW to applicable value with Peak.
4. Read the transmission time and silent time from the spectrum analyzer directly.

7.4. TEST RESULT

The test data of worst case are below:

Channel	Frequency (MHz)	Test (s)	Limit (s)	Result (Pass / Fail)
1	315	0.48	5	Pass



Date: 28.APR.2015 20:03:31


8. 20dB/ 99% Bandwidth Measurement

8.1. LIMITS

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

As the center frequency for the device operating is 315MHz, thus, the 20dB bandwidth limit is 787.5kHz.

8.2. BLOCK DIAGRAM OF TEST SETUP



8.3. TEST PROCEDURE


1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Set spectrum analyzer's RBW and VBW to applicable value with Peak in Max Hold.
3. A PEAK output reading and 20B/99% BW function in spectrum analyzer were taken.

8.4. TEST RESULT


The test data of worst case are below:

Channel	Frequency (MHz)	20dB BW (kHz)	99% BW (kHz)	Limit (kHz)	Result (Pass / Fail)
1	315	470.0	580.0	787.5	Pass

Please see the following plots:
20dB BW:



99% BW:



Date: 28.APR.2015 20:19:18

9. RADIATED EMISSION MEASUREMENT

9.1. LIMITS

FCC part 15.231(b):


Fundamental Frequency (MHz)	Field Strength of Fundamental microvolts/m at 3 metres	Field Strength of Unwanted Emissions microvolts/m at 3 metres
260-470	3750 to 12500*	375 to 1250*

* Linear interpolation with frequency F in MHz


The limits on the field strength of the spurious emissions in the above table are based on the fundamental frequency of the intentional radiator. Spurious emissions shall be attenuated to the average (or, alternatively, CISPR quasi-peak) limits shown in this table or to the general limits shown in § 15.209, whichever limit permits a higher field strength.

9.2. BLOCK DIAGRAM OF TEST SETUP


For radiated emissions from 9kHz to 30MHz



For radiated emissions from 30 - 1000MHz



For radiated emissions from 1GHz to 25GHz



9.3. TEST PROCEDURE

Below 30MHz

- The Product is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The maximum values of the field strength are recorded by adjusting the polarizations of the test antenna and rotating the turntable.
- For each suspected emission, the Product was arranged to its worst case and then turn table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

30MHz ~ 1GHz:

- The Product was placed on the non-conductive turntable 0.8m above the ground at a chamber.
- Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 100 kHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the antenna is varied between 1~4 m in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.
- For each frequency whose maximum record was higher or close to limit, measure its QP value (120 kHz RBW): vary the antenna's height and rotate the turntable from 0 to 360 degrees to find the height and degree where Product radiated the maximum emission, then set the test frequency analyzer/receiver to QP Detector and specified bandwidth with Maximum Hold Mode, and record the maximum value.

Above 1GHz:

- The EUT was placed on the non-conductive turntable 1.5m above the ground at a chamber.
- Set the spectrum analyzer/receiver in Peak detector, Max Hold mode, and 1MHz RBW. Record the maximum field strength of all the pre-scan process in the full band when the

antenna is varied in both horizontal and vertical, and the turntable is rotated from 0 to 360 degrees.

9.4. TEST RESULT


All the modes of operation (X, Y, Z) were investigated and the worst-case emissions are reported.

Below 30MHz:


No emissions were found higher than the background below 30MHz and background is lower than the limit, so it deems to compliance with the limit without recorded.

H:


30MHz ~ 1GHz:




Above 1GHz:



V:
30MHz ~ 1GHz:



Above 1GHz:



Test data:

Frequency (MHZ)	Polarization (H/V)	Emission _PK (dB μ V/m)	Duty Cycle Correction Factor (dB)	Emission _AV (dB μ V/m)	Limit (dB μ V/m)		Result (P/F)
					PK	AV	
315.0*	H	67.64	-11.75	55.89	95.62	75.62	P
315.0*	V	73.97	-11.75	62.22	95.62	75.62	P
630.0	H	59.89	-11.75	48.14	75.62	55.62	P
945.0	H	53.97	-11.75	42.22	75.62	55.62	P
1260.0	H	57.39	-11.75	45.64	75.62	55.62	P
1575.0**	H	46.12	-11.75	34.37	74.00	54.00	P
1890.0	H	37.69	-11.75	25.94	75.62	55.62	P
2205.0**	H	43.46	-11.75	31.71	74.00	54.00	P
2835.0**	H	32.54	-11.75	20.79	74.00	54.00	P
630.0	V	62.87	-11.75	51.12	75.62	55.62	P
945.0	V	55.98	-11.75	44.23	75.62	55.62	P
1260.0	V	59.83	-11.75	48.08	75.62	55.62	P
1575.0**	V	53.11	-11.75	41.36	74.00	54.00	P
1890.0	V	52.31	-11.75	40.56	75.62	55.62	P
2205.0**	V	52.92	-11.75	41.17	74.00	54.00	P
2835.0**	V	32.73	-11.75	20.98	74.00	54.00	P


*: Fundamental Frequency

**: Restriction bands.


Duty Cycle Correction Factor is calculated by averaging the sum of the pulse train. Correction factor is measured as follows:

Keep the EUT in continuous transmission mode (modulated), and set the spectrum to the fundamental frequency and set the span width to 0 Hz. Then connect a storage oscilloscope to the video output of the spectrum that is used to detect the pulse train. Adjust the oscilloscope settings to observe the pulse train and determine the number and width of the pulses, as well as the period of the train. Duty Cycle Correction Factor at its minimum value (Worst case): -11.75dB


Duty Cycle= $20\log[(1.48\text{ms}^*10+0.48\text{ms}^*23)/100] = -11.75\text{dB}$




Date: 28.APR.2015 20:00:04



Date: 28.APR.2015 20:00:44




Date: 28.APR.2015 19:59:35



Date: 28.APR.2015 20:01:00

APPENDIX 1 PHOTOGRAPHS OF TEST SETUP



TEST SETUP OF RADIATED EMISSION (30MHz-1GHz)



TEST SETUP OF RADIATED EMISSION (above 1GHz)

APPENDIX 2 EXTERNAL PHOTOGRAPHS OF PRODUCT





External View of product-1



External View of product-2

APPENDIX 3 INTERNAL PHOTOGRAPHS OF PRODUCT





Internal View of product-3



Internal View of product-4

*** End of Report ***

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.