

## RF exposure test exclusion evaluation report

Product:	Laser Distance Meter
Model no.:	S50, S50 Pro, S50 C, S50 Lite, S50R, S70, S90, S10, S30, S23G
FCC ID:	2AEOGS50
Rating:	5VDC, 1A supplied by USB-C port or 2.4VDC supplied by 2pcs "AA" size rechargeable Ni-MH batteries or 3.0VDC supplied by 2pcs "AA" alkaline batteries
RF Transmission Frequency:	2402MHz-2480MHz
Modulation:	GFSK
Antenna Type:	PCB Antenna
Max Antenna Gain:	0.2dBi
Description of the EUT:	The Equipment Under Test (EUT) is a Laser Distance Meter which supports BLE-1Mbps function.
Reference Report	6895025131801

### 1. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance v06, Mobile Portable RF Exposure, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f(\text{GHz})$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $<$  5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### 2. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Max Tune-up power = -2.0dBm = 0.631mW

Distance = 5 mm

$f = 2.402 \text{ GHz}$

$$[0.631/5] * \text{SQRT}(2.402) = 0.196$$

$$0.196 \leq 3.0$$



Therefore, excluded from SAR testing.

TUV SUD China, Shenzhen Branch

Reviewed by:

A handwritten signature of "John Zhi" in black ink.



John Zhi/Project Manager  
Date: 2025-08-21

Prepared By:

A handwritten signature of "Sanvin Zheng" in black ink.

Sanvin Zheng/Project Engineer  
Date: 2025-08-21