

MPE TEST REPORT

FCC Per 47 CFR 2.1091(b)

Report Reference No.....: A150A166267-MPE

FCC ID.....: 2AEP9-DXS-W014S

Compiled by
(position+printed name+signature)....: File administrators Tony Li

Supervised by
(position+printed name+signature)....: Technique principal Robin Fang

Approved by
(position+printed name+signature)....: Manager James Wu

Date of issue.....: May 04, 2015

Tony Li
Robin Fang
James Wu

Representative Laboratory Name: Shenzhen CTL Electron Technology Co., Ltd.

Address.....: A0402, Block 1, Kefa Industrial District, Huanguan Nan Rd, Xintian community, Guanlan, Baoan, Shenzhen, China

Testing Laboratory Name: Dongguan Dongdian Testing Service Co.,Ltd

Address.....: No.17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China

Applicant's name.....: SHENZHEN YUANLI ELECTRONICS CO., LTD.

Address.....: 5F West, Building F, Licheng Industrial Park, Xinhe road, Shajing town, Baoan District, Shenzhen, Guangdong, P.R.C.

Test specification:

Standard: **FCC Per 47 CFR 2.1091(b)**

KDB447498 v05r02

TRF Originator: Shenzhen CTL Electron Technology Co., Ltd.

Master TRF.....: Dated 2012-06

Shenzhen CTL Electron Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Electron Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Electron Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: Wireless WIFI Module

Trade Mark: YUANLI

Model/Type reference.....: DXS-W014S

Listed Models: /

Manufacturer: **SHENZHEN YUANLI ELECTRONICS CO., LTD.**

Operation Frequency.....: From 2402MHz to 2480MHz

Rating: DC 3.30V

Device Type.....: Mobile Device

Exposure category.....: General population/uncontrolled environment

EUT Type.....: Production Unit

Result.....: **PASS**

MPE T E S T R E P O R T

Test Report No. :	A150A166267-MPE	May 04, 2015
		Date of issue

Equipment under Test : Wireless WIFI Module

Model /Type : DXS-W014S

Listed Models : /

Applicant : **SHENZHEN YUANLI ELECTRONICS CO., LTD.**

Address : 5F West, Building F, Licheng Industrial Park, Xinhe road, Shajing town, Baoan District, Shenzhen, Guangdong, P.R.C.

Manufacturer : **SHENZHEN YUANLI ELECTRONICS CO., LTD.**

Address : 5F West, Building F, Licheng Industrial Park, Xinhe road, Shajing town, Baoan District, Shenzhen, Guangdong, P.R.C.

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>SUMMARY</u>	4
1.1.	EUT configuration	4
1.2.	NOTE	4
<u>2.</u>	<u>TEST ENVIRONMENT</u>	5
2.1.	Address of the test laboratory	5
2.2.	Test Facility	5
2.3.	Environmental conditions	5
2.4.	Statement of the measurement uncertainty	5
<u>3.</u>	<u>METHOD OF MEASUREMENT</u>	6
3.1.	Applicable Standard	6
3.2.	Limit	6
3.3.	Conducted Power Results	6
3.4.	MPE Calculation Method	7
3.4.1	Standalone MPE	7
3.4.2	Simultaneous transmission MPE Considerations	8
<u>4.</u>	<u>CONCLUSION</u>	8

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- - supplied by the manufacturer
- - supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

1.2. NOTE

1. The EUT is a Wireless WIFI Module, The functions of the EUT listed as below:

	Test Standards	Reference Report
WLAN	FCC Part 15 Subpart C	A150A166267-RW
MPE	FCC Per 47 CFR 2.1091(d)	A150A166267-MPE

2. The frequency bands used in this EUT are listed as follows:

Frequency Band(MHz)	2400-2483.5	5150-5350	5470-5725	5725-5850
802.11b	√	—	—	—
802.11g	√	—	—	—
802.11n(20MHz)	√	—	—	—
802.11n(40MHz)	√	—	—	—

3. The EUT incorporates a SISO function, Physically, the EUT provides one completed transmitter and one completed receiver.

Modulation Mode	TX Function
802.11b	1TX
802.11g	1TX
802.11n (20MHz)	1TX
802.11n (40MHz)	1TX

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Dongguan Dongdian Testing Service Co.,Ltd.

No.17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 10288A-1

The 3m alternate test site of Dongguan Dongdian Testing Service Co.,Ltd EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 10288A-1 on May, 2012.

FCC-Registration No.: 270092

Dongguan Dongdian Testing Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 270092, Mar, 2015.

2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Dongguan Dongdian Testing Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Dongguan Dongdian Testing Service Co.,Ltd laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.16 dB	(1)
Radiated Emission	1~18GHz	2.56 dB	(1)
Radiated Emission	18-40GHz	2.56 dB	(1)
Conducted Disturbance	0.15~30MHz	2.44 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 v05r02: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100)*	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.3. Conducted Power Results

WLAN

Mode	Channel	Frequency (MHz)	Worst case Data rate of worst case	Conducted Output Power (dBm)	
				Peak	Average
802.11b	1	2412	1Mbps	15.13	12.09
	6	2437	1Mbps	14.68	11.70
	11	2462	1Mbps	14.55	11.60
802.11g	1	2412	6Mbps	20.74	13.13
	6	2437	6Mbps	20.40	12.80
	11	2462	6Mbps	20.27	12.65
802.11n(20MHz)	1	2412	6.5 Mbps	20.90	13.02
	6	2437	6.5 Mbps	20.45	12.63
	11	2462	6.5 Mbps	20.33	12.52
802.11n(40MHz)	3	2422	13.5 Mbps	20.72	13.45
	6	2437	13.5 Mbps	20.47	13.19
	9	2452	13.5 Mbps	20.32	13.04

Manufacturing tolerance

WLAN			
802.11b (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	12.0	12.0	12.0
Tolerance \pm (dB)	1.0	1.0	1.0
802.11g (Average)			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	13.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0
802.11n(20MHz) (Average)			
Channel	Channel 1	Channel 6	Channel 11
Target (dBm)	13.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0
802.11n(40MHz) (Average)			
Channel	Channel 3	Channel 6	Channel 9
Target (dBm)	13.0	13.0	13.0
Tolerance \pm (dB)	1.0	1.0	1.0

3.4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum source-based Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is 3.0dBi for WLAN, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained..

TEST RESULTS**3.4.1 Standalone MPE****For 802.11b**

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (Turn-up Procedure)		Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit (mW/cm ²)	Test Results
		dBm	mW				
2412	20.00	13.00	19.9526	1.9953	0.0079	1.0000	PASS
2437	20.00	13.00	19.9526	1.9953	0.0079	1.0000	PASS
2462	20.00	13.00	19.9526	1.9953	0.0079	1.0000	PASS

For 802.11g

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (Turn-up Procedure)		Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit (mW/cm ²)	Test Results
		dBm	mW				
2412	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS
2437	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS
2462	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS

For 802.11n HT20

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (Turn-up Procedure)		Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit (mW/cm ²)	Test Results
		dBm	mW				
2412	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS
2437	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS
2462	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS

For 802.11n HT40

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (Turn-up Procedure)		Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit (mW/cm ²)	Test Results
		dBm	mW				
2422	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS
2437	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS
2452	20.00	14.00	25.1189	1.9953	0.0100	1.0000	PASS

3.4.2 Simultaneous transmission MPE Considerations

According to KDB447498 :For mobile exposure host platform to qualify for simultaneous transmission MPE test exclusion, all transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 .

This means that:

$$\sum \text{ of MPE ratios} \leq 1.0$$

The WiFi modular only with WiFi modular, without any simultaneous transmission with other transmitter in this modular, so not need consider simultaneous transmission for this WiFi modular.

4. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091(b) for the uncontrolled RF Exposure.

.....End of Report.....