

TEST REPORT

Reference No. : WTD25D06165706W005
FCC ID..... : 2AEPIBLACKZ2
Applicant..... : COLOMBIANA DE COMERCIO S.A.
Address : Car. 43E No 8-71, Medellin, Colombia
Manufacturer : Sichuan Koobee Communication Equipment Co., Ltd.
Address : 3 Floor, Building 2, 69 Gangyuan Road West Section, Lingang
Development Zone, Yibin City, Sichuan Province, China
Product..... : Smart Phone
Model(s)..... : Black Z2
Brand Name..... : Kalley
Standards..... : FCC 47CFR Part 15 Section 15.407
Date of Receipt sample..... : 2025-06-25
Date of Test..... : 2025-06-26 to 2025-07-17
Date of Issue : 2025-08-13
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company.

The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

Frank Yin

Frank Yin/ Project Engineer

Approved by:

Deval Qin

Deval Qin / Designated Reviewer

2 Contents

	Page
1 COVER PAGE.....	1
2 CONTENTS.....	2
3 REVISION HISTORY.....	4
4 GENERAL INFORMATION.....	5
4.1 GENERAL DESCRIPTION OF E.U.T.	5
4.2 DETAILS OF E.U.T.....	5
4.3 CHANNEL LIST.....	6
4.4 TEST MODE DESCRIPTION	9
4.5 TEST FACILITY	9
5 EQUIPMENT USED DURING TEST.....	10
5.1 EQUIPMENTS LIST	10
5.2 DESCRIPTION OF SUPPORT UNITS.....	11
5.3 MEASUREMENT UNCERTAINTY	11
6 TEST SUMMARY.....	12
7 DUTY CYCLE.....	13
7.1 SUMMARY OF TEST RESULTS.....	13
8 CONDUCTED EMISSION.....	27
8.1 E.U.T. OPERATION.....	27
8.2 EUT SETUP	27
8.3 MEASUREMENT DESCRIPTION	27
8.4 CONDUCTED EMISSION TEST RESULT	28
9 RADIATED EMISSIONS.....	30
9.1 EUT OPERATION.....	30
9.2 TEST SETUP	31
9.3 SPECTRUM ANALYZER SETUP	32
9.4 TEST PROCEDURE.....	33
9.5 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	33
9.6 SUMMARY OF TEST RESULTS.....	34
10 BAND EDGE.....	62
10.1 TEST PRODUCE	62
10.2 TEST RESULT	63
11 6 DB BANDWIDTH.....	87
11.1 TEST PROCEDURE	87
11.2 TEST RESULT	87
12 26 DB BANDWIDTH AND 99% OCCUPIED BANDWIDTH.....	95
12.1 TEST PROCEDURE	95
12.2 TEST RESULT	96
13 CONDUCTED OUTPUT POWER.....	151
13.1 TEST PROCEDURE	151
13.2 TEST RESULT	152
14 POWER SPECTRAL DENSITY.....	186
14.1 TEST PROCEDURE	186
14.2 TEST RESULT	187

15 FREQUENCY STABILITY221
15.1 TEST PROCEDURE221
15.2 TEST RESULT222

16 ANTENNA REQUIREMENT224

17 RF EXPOSURE224

18 PHOTOGRAPHS OF TEST SETUP AND EUT.....224

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD25D06165706W005	2025-06-25	2025-06-26 to 2025-07-17	2025-08-13	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	Smart Phone
Model(s):	Black Z2
Model Description:	N/A
Test Sample No.:	1-1/1
Wi-Fi Specification:	5G-802.11a/ n(HT20/40)/ac(VHT20/40/80)
Hardware Version:	KE34NM_01
Software Version:	Kalley_BLACK_Z2_V02_20250705

4.2 Details of E.U.T.

Operation Frequency:	802.11a/n(HT20)/ac (VHT20): U-NII-1: 5180-5240MHz, U-NII-2A: 5260-5320MHz(DFS), U-NII-2C: 5500-5700MHz(DFS), U-NII-3: 5745-5825MHz 802.11n(HT40)/ac (VHT40): U-NII-1: 5190-5230MHz, U-NII-2A: 5270-5310MHz(DFS), U-NII-2C: 5510-5670MHz(DFS), U-NII-3: 5755-5795MHz 802.11ac (VHT80): U-NII-1: 5210MHz, U-NII-2A: 5290MHz(DFS), U-NII-2C: 5530-5610MHz(DFS), U-NII-3: 5775MHz
Max. RF output power:	U-NII-1: 10.73dBm U-NII-2A: 12.21dBm U-NII-2C: 13.22dBm U-NII-3: 14.26dBm
Type of Modulation:	OFDM
Antenna installation:	Internal antenna
Antenna Gain:	3.08dBi
Note:	#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTERK lab has not verified the authenticity of its information.
Ratings:	Battery: DC 3.89V, 5900mAh, 22.951Wh DC 5.0V=== 3.0A charging from adapter
Adapter:	Model No.: ES166A-US-1200167 Input: 100-240V~, 50/60Hz, 0.6A Output: 5.0V===3.0A, 15.0W; 9.0V===2.22A, 20.0W; 12.0V===1.67A, 20.0W (PPS): 5.0-11.0V===1.8A (20.0W MAX) Manufacturer: Shenzhen East Sun Electronics Co., Ltd.

4.3 Channel List

U-NII-1 (5.15-5.25GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
36	5180	38	5190
40	5200	42	5210
44	5220	46	5230
48	5240		

U-NII-2A (5.25-5.35GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
52	5260	54	5270
56	5280	58	5290
60	5300	62	5310
64	5320		

U-NII-2C (5.47-5.725GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
100	5500	102	5510
104	5520	106	5530
108	5540	110	5550
112	5560	116	5580
118	5590	120	5580
122	5610	124	5620
126	5630	128	5640
132	5660	134	5670
136	5680	140	5700

U-NII-3 (5.725-5.85GHz)			
channel	Frequency(MHz)	channel	Frequency(MHz)
149	5745	151	5755
153	5765	155	5775
157	5785	159	5795
161	5805	165	5825

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11a/n/ac(VHT20):

channel	Frequency(MHz)	channel	Frequency(MHz)
36	5180	40	5200
48	5240		

channel	Frequency(MHz)	channel	Frequency(MHz)
52	5260	56	5280
64	5320		

channel	Frequency(MHz)	channel	Frequency(MHz)
100	5500	120	5580
140	5700		

channel	Frequency(MHz)	channel	Frequency(MHz)
149	5745	157	5785
165	5825		

For 802.11n/ac(VHT40):

channel	Frequency(MHz)	channel	Frequency(MHz)
38	5190	46	5230

channel	Frequency(MHz)	channel	Frequency(MHz)
54	5270	62	5310

channel	Frequency(MHz)	channel	Frequency(MHz)
102	5510	110	5550
134	5670		

channel	Frequency(MHz)	channel	Frequency(MHz)
151	5755	159	5795

For 802.11ac(VHT80):

channel	Frequency(MHz)	channel	Frequency(MHz)
42	5210		

channel	Frequency(MHz)	channel	Frequency(MHz)
58	5290		

channel	Frequency(MHz)	channel	Frequency(MHz)
106	5530	122	5610

channel	Frequency(MHz)	channel	Frequency(MHz)
155	5775		

4.4 Test Mode Description

During testing, Channel and Power Controlling Software provided by the applicant was used to control the operating channel as well as the maximum output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Transmitting duty cycle is no less 98%.

The software is TermAssist and SecureCRT tool Use together.

Test Items	Mode	Data Rate	TX/RX
Radiated Emissions	802.11a (HT20)	6 Mbps	TX
	802.11n/ac(HT20/40/80)	MCS0	TX
Duty Cycle	802.11a (HT20)	6 Mbps	TX
	802.11n/ac(HT20/40/80)	MCS0	TX
Band Edge	802.11a (HT20)	6 Mbps	TX
	802.11n/ac(HT20/40/80)	MCS0	TX
6dB Bandwidth	802.11a (HT20)	6 Mbps	TX
	802.11n/ac(HT20/40/80)	MCS0	TX
26dB Bandwidth and 99% Occupied Bandwidth	802.11a (HT20)	6 Mbps	TX
	802.11n/ac(HT20/40/80)	MCS0	TX
Conducted Output Power	802.11a (HT20)	6 Mbps	TX
	802.11n/ac(HT20/40/80)	MCS0	TX
Power Spectral Density	802.11a (HT20)	6 Mbps	TX
	802.11n/ac(HT20/40/80)	MCS0	TX
Frequency Stability	Un-modulation	/	TX

4.5 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions Test Site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	EMI Test Receiver	R&S	ESCI	100947	2024-07-18	2025-07-17
2.	LISN	R&S	ENV216	100115	2024-07-18	2025-07-17
3.	Cable	Top	TYPE16(3.5M)	-	2024-07-18	2025-07-17
3m Semi-anechoic Chamber for Radiation Emissions Test site 1#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP30	100091	2025-04-19	2026-04-18
2	Amplifier	Agilent	8447D	2944A10178	2024-07-18	2025-07-17
3	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2024-07-21	2025-07-20
4	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2025-04-19	2026-04-18
5	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2025-01-17	2026-01-16
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9170	335	2024-07-18	2025-07-17
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2024-07-18	2025-07-17
8	Coaxial Cable (above 1GHz)	ZT26-NJ-NJ-8M/FA	1GHz-18GHz	NA	2025-04-19	2026-04-18
3m Semi-anechoic Chamber for Radiation Emissions Test site 2#						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2025-04-19	2026-04-18
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2024-11-04	2025-11-03
3	Active Loop Antenna	Com-Power Corp.	AL-130R	10160007	2025-04-21	2026-04-20
4	Amplifier	ANRITSU	MH648A	M43381	2025-04-19	2026-04-18
5	Cable	HUBER+SUHNER	CBL2	525178	2025-04-19	2026-04-18
RF Conducted Testing						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1.	Spectrum Analyzer	R&S	FSP40	100501	2024-07-18	2025-07-17
2.	EXA Signal Analyzer	Malaysia Keysight	N9010A	MY50520207	2025-04-19	2026-04-18

Test Software:

Test Item	Software name	Software version
Conduction disturbance Radiated Emission(3m)	EZ-EMC	EZ-EMC(RA-03A1-1)

5.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

5.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (30M~1000MHz)
	± 5.47 dB (1000M~25000MHz)
Conducted Spurious Emissions test	± 3.64 dB (AC mains 150KHz~30MHz)

6 Test Summary

Test Items	Test Requirement	Result
Conducted Emissions	15.207(a)	PASS
Radiated Emissions	15.407(a) 15.205(a) 15.209(a)	PASS
Duty Cycle	KDB 789033	PASS
6dB Bandwidth	15.407(a)	PASS
26 dB Emission Bandwidth & 99% Occupied Bandwidth	15.407(a)	PASS
Maximum Conducted Output Power	15.407(a)	PASS
Power Spectral Density	15.407(a)	PASS
Restricted bands around fundamental frequency	15.407(a)	PASS
Antenna Requirement	15.203	PASS
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	1.1307(b)(1)	PASS

7 Duty cycle

Test Requirement:	FCC 47CFR Part 15 Section 15.407 KDB789033 D02 General U-NII Test Procedures New Rules v02r01, Section (B)
Test Method:	ANSI C63.10: 2013
Test Limit:	N/A
Test Result:	PASS
Remark:	Through Pre-scan, and found 802.11a at lowest channel is the worst case. Only the worst case is recorded in the report.


7.1 Summary of Test Results

Type of Modulation	On time ms	Period ms	Duty Cycle linear	Duty Cycle %	Duty Cycle Factor(dB)	Average Factor(dB)
U-NII-1 802.11a	1.385	1.435	0.97	96.52	0.15	-0.31
U-NII-1 802.11n(HT20)	1.295	1.345	0.96	96.28	0.16	-0.33
U-NII-1 802.11n(HT40)	0.645	0.691	0.93	93.34	0.30	-0.60
U-NII-1 802.11ac(VHT20)	1.305	1.355	0.96	96.31	0.16	-0.33
U-NII-1 802.11ac(VHT40)	0.651	0.695	0.94	93.67	0.28	-0.57
U-NII-1 802.11ac(VHT80)	0.323	0.368	0.88	87.77	0.57	-1.13
U-NII-2A 802.11a	1.383	1.434	0.96	96.44	0.16	-0.31
U-NII-2A 802.11n(HT20)	1.298	1.344	0.97	96.58	0.15	-0.30
U-NII-2A 802.11n(HT40)	0.648	0.693	0.94	93.51	0.29	-0.58
U-NII-2A 802.11ac(VHT20)	1.310	1.361	0.96	96.25	0.17	-0.33
U-NII-2A 802.11ac(VHT40)	0.652	0.697	0.94	93.54	0.29	-0.58
U-NII-2A 802.11ac(VHT80)	0.324	0.368	0.88	88.04	0.55	-1.11
U-NII-2C 802.11a	1.393	1.437	0.97	96.94	0.14	-0.27
U-NII-2C 802.11n(HT20)	1.303	1.352	0.96	96.38	0.16	-0.32
U-NII-2C 802.11n(HT40)	0.648	0.691	0.94	93.78	0.28	-0.56
U-NII-2C 802.11ac(VHT20)	1.308	1.357	0.96	96.39	0.16	-0.32
U-NII-2C 802.11ac(VHT40)	0.650	0.695	0.94	93.53	0.29	-0.58
U-NII-2C 802.11ac(VHT80)	0.323	0.368	0.88	87.77	0.57	-1.13


U-NII-3 802.11a	1.393	1.438	0.97	96.87	0.14	-0.28
U-NII-3 802.11n(HT20)	1.303	1.348	0.97	96.66	0.15	-0.29
U-NII-3 802.11n(HT40)	0.649	0.693	0.94	93.65	0.28	-0.57
U-NII-3 802.11ac(VHT20)	1.313	1.363	0.96	96.33	0.16	-0.32
U-NII-3 802.11ac(VHT40)	0.653	0.697	0.94	93.69	0.28	-0.57
U-NII-3 802.11ac(VHT80)	0.324	0.368	0.88	88.04	0.55	-1.11

Test result plots shown as follows:


802.11a U-NII-1 Low channel




802.11n(HT20) U-NII-1 Low channel




802.11n(HT40) U-NII-1 Low channel




802.11ac(VHT20) U-NII-1 Low channel




802.11ac(VHT40) U-NII-1 Low channel




802.11ac(VHT80) U-NII-1 Low channel




802.11a U-NII-2A Low channel




802.11n(HT20) U-NII-2A Low channel




802.11n(HT40) U-NII-2A Low channel




802.11ac(VHT20) U-NII-2A Low channel




802.11ac(VHT40) U-NII-2A Low channel




802.11ac(VHT80) U-NII-2A Low channel




802.11a U-NII-2C Low channel




802.11n(HT20) U-NII-2C Low channel




802.11n(HT40) U-NII-2C Low channel




802.11ac(VHT20) U-NII-2C Low channel




802.11ac(VHT40) U-NII-2C Low channel




802.11ac(VHT80) U-NII-2C Low channel




802.11a U-NII-3 Low channel




802.11n(HT20) U-NII-3 Low channel




802.11n(HT40) U-NII-3 Low channel




802.11ac(VHT20) U-NII-3 Low channel



802.11ac(VHT40) U-NII-3 Low channel



802.11ac(VHT80) U-NII-3 Low channel



8 Conducted Emission

Test Requirement: FCC 47CFR Part 15 Section 15.207

Test Method: ANSI C63.10:2013

Test Result: PASS

Frequency Range: 150kHz to 30MHz

Limit:

Frequency (MHz)	Limit (dB μ V)	
	Quasi-peak	Average
0.15 to 0.5	66 to 56	56 to 46
0.5 to 5	56	46
5 to 30	60	50

8.1 E.U.T. Operation

Operating Environment :

Temperature: 26.1°C

Humidity: 64.3%RH


Atmospheric Pressure: 101.1kPa

EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.

8.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.




8.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


8.4 Conducted Emission Test Result

Remark: only the worst data (U-NII-1 802.11a High channel mode) were reported

Live line:



Neutral line:



9 Radiated Emissions

Test Requirement: FCC 47CFR Part 15 Section 15.209 & 15.407

Test Method: ANSI C63.10:2013

Test Result: PASS

Measurement Distance: 3m

Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Distance	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	$2400/F(\text{kHz})$	300	$10000 * 2400/F(\text{kHz})$	$20\log^{(2400/F(\text{kHz}))} + 80$
0.490 ~ 1.705	$24000/F(\text{kHz})$	30	$100 * 24000/F(\text{kHz})$	$20\log^{(24000/F(\text{kHz}))} + 40$
1.705 ~ 30	30	30	$100 * 30$	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

9.1 EUT Operation

Operating Environment :

Temperature: 27.1 °C

Humidity: 41.5 % RH

Atmospheric Pressure: 101.1kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


9.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.10: 2013.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



9.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed Auto
IF Bandwidth.....10kHz
Video Bandwidth.....10kHz
Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....100kHz
Video Bandwidth.....300kHz

Above 1GHz

Sweep Speed Auto
DetectorPK
Resolution Bandwidth.....1MHz
Video Bandwidth.....3MHz
DetectorAve.
Resolution Bandwidth.....1MHz
Video Bandwidth.....10Hz

9.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane for below 1GHz and 1.5m for above 1GHz.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are performed in X,Y and Z axis positioning(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand),the worst condition was tested putting the eut in X axis,so the worst data were shown as follow.
8. A 2.4GHz high –pass filter is used during radiated emissions above 1GHz measurement.

9.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

9.6 Summary of Test Results

Test Frequency: 9KHz~30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 18GHz

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-1 Low Channel 5180MHz									
436.59	40.37	QP	267	1.9	H	-11.62	28.75	46.00	-17.25
436.59	47.01	QP	97	1.6	V	-11.62	35.39	46.00	-10.61
4519.69	53.48	PK	352	1.9	H	-2.03	51.45	74.00	-22.55
4519.69	43.87	Ave	352	1.9	H	-2.03	41.84	54.00	-12.16
5145.70	52.78	PK	173	1.7	H	-1.02	51.76	74.00	-22.24
5145.70	44.60	Ave	173	1.7	H	-1.02	43.58	54.00	-10.42
10360.00	41.56	PK	65	1.3	H	5.33	46.89	74.00	-27.11
10360.00	37.69	Ave	65	1.3	H	5.33	43.02	54.00	-10.98
802.11a U-NII-1 Middle channel 5200MHz									
436.59	39.38	QP	35	1.2	H	-11.62	27.76	46.00	-18.24
436.59	45.67	QP	99	1.2	V	-11.62	34.05	46.00	-11.95
4522.17	52.56	PK	43	1.9	H	-1.94	50.62	74.00	-23.38
4522.17	42.93	Ave	43	1.9	H	-1.94	40.99	54.00	-13.01
5140.77	52.38	PK	96	1.7	H	-1.06	51.32	74.00	-22.68
5140.77	44.16	Ave	96	1.7	H	-1.06	43.10	54.00	-10.90
10400.00	40.23	PK	282	1.2	H	5.21	45.44	74.00	-28.56
10400.00	36.42	Ave	282	1.2	H	5.21	41.63	54.00	-12.37

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-1 High channel 5240MHz									
436.59	39.15	QP	252	1.1	H	-11.62	27.53	46.00	-18.47
436.59	45.41	QP	333	2.0	V	-11.62	33.79	46.00	-12.21
4534.71	51.94	PK	109	1.3	H	-2.24	49.70	74.00	-24.30
4534.71	41.63	Ave	109	1.3	H	-2.24	39.39	54.00	-14.61
5128.30	51.71	PK	148	1.5	H	-1.09	50.62	74.00	-23.38
5128.30	43.35	Ave	148	1.5	H	-1.09	42.26	54.00	-11.74
10480.00	41.43	PK	149	1.5	H	5.14	46.57	74.00	-27.43
10480.00	36.86	Ave	149	1.5	H	5.14	42.00	54.00	-12.00
802.11a U-NII-2A Low Channel 5260MHz									
436.59	38.13	QP	87	1.2	H	-11.62	26.51	46.00	-19.49
436.59	45.89	QP	204	1.1	V	-11.62	34.27	46.00	-11.73
4515.58	54.48	PK	138	1.4	H	-2.03	52.45	74.00	-21.55
4515.58	40.87	Ave	138	1.4	H	-2.03	38.84	54.00	-15.16
5123.28	52.75	PK	60	1.5	H	-1.02	51.73	74.00	-22.27
5123.28	39.06	Ave	60	1.5	H	-1.02	38.04	54.00	-15.96
10520.00	41.63	PK	330	1.5	H	5.33	46.96	74.00	-27.04
10520.00	33.17	Ave	330	1.5	H	5.33	38.50	54.00	-15.50

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-2A middle channel 5280MHz									
436.59	37.91	QP	27	1.0	H	-11.62	26.29	46.00	-19.71
436.59	45.82	QP	25	1.3	V	-11.62	34.20	46.00	-11.80
4514.58	54.21	PK	307	1.2	H	-1.94	52.27	74.00	-21.73
4514.58	39.46	Ave	307	1.2	H	-1.94	37.52	54.00	-16.48
5127.33	52.28	PK	228	1.2	H	-1.06	51.22	74.00	-22.78
5127.33	39.02	Ave	228	1.2	H	-1.06	37.96	54.00	-16.04
10560.00	40.86	PK	132	1.0	H	5.21	46.07	74.00	-27.93
10560.00	32.99	Ave	132	1.0	H	5.21	38.20	54.00	-15.80
802.11a U-NII-2A High channel 5320MHz									
436.59	36.92	QP	31	1.8	H	-11.62	25.30	46.00	-20.70
436.59	45.00	QP	285	1.9	V	-11.62	33.38	46.00	-12.62
4524.18	53.27	PK	259	1.2	H	-2.24	51.03	74.00	-22.97
4524.18	38.22	Ave	259	1.2	H	-2.24	35.98	54.00	-18.02
5146.58	52.41	PK	348	2.0	H	-1.09	51.32	74.00	-22.68
5146.58	39.15	Ave	348	2.0	H	-1.09	38.06	54.00	-15.94
10640.00	40.36	PK	63	1.5	H	5.14	45.50	74.00	-28.50
10640.00	31.80	Ave	63	1.5	H	5.14	36.94	54.00	-17.06

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-2C Low Channel 5500MHz									
436.59	41.35	QP	229	1.7	H	-11.62	29.73	46.00	-16.27
436.59	45.27	QP	146	1.8	V	-11.62	33.65	46.00	-12.35
4537.18	53.12	PK	0	1.4	H	-2.03	51.09	74.00	-22.91
4537.18	40.45	Ave	0	1.4	H	-2.03	38.42	54.00	-15.58
5147.93	53.38	PK	210	1.6	H	-1.02	52.36	74.00	-21.64
5147.93	38.23	Ave	210	1.6	H	-1.02	37.21	54.00	-16.79
11000.00	41.17	PK	154	1.5	H	5.33	46.50	74.00	-27.50
11000.00	37.04	Ave	154	1.5	H	5.33	42.37	54.00	-11.63
802.11a U-NII-2C Middle channel 5580MHz									
436.59	39.96	QP	330	1.6	H	-11.62	28.34	46.00	-17.66
436.59	43.90	QP	109	1.6	V	-11.62	32.28	46.00	-13.72
4504.12	52.50	PK	272	1.4	H	-1.94	50.56	74.00	-23.44
4504.12	39.44	Ave	272	1.4	H	-1.94	37.50	54.00	-16.50
5114.96	52.96	PK	114	1.2	H	-1.06	51.90	74.00	-22.10
5114.96	37.40	Ave	114	1.2	H	-1.06	36.34	54.00	-17.66
11160.00	40.47	PK	30	1.2	H	5.21	45.68	74.00	-28.32
11160.00	36.79	Ave	30	1.2	H	5.21	42.00	54.00	-12.00

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-2C High channel 5700MHz									
436.59	39.20	QP	283	1.2	H	-11.62	27.58	46.00	-18.42
436.59	42.76	QP	202	1.6	V	-11.62	31.14	46.00	-14.86
4510.00	51.46	PK	190	1.7	H	-2.24	49.22	74.00	-24.78
4510.00	38.69	Ave	190	1.7	H	-2.24	36.45	54.00	-17.55
5110.93	52.41	PK	22	1.2	H	-1.09	51.32	74.00	-22.68
5110.93	37.33	Ave	22	1.2	H	-1.09	36.24	54.00	-17.76
11400.00	41.02	PK	232	1.3	H	5.14	46.16	74.00	-27.84
11400.00	36.22	Ave	232	1.3	H	5.14	41.36	54.00	-12.64
802.11a U-NII-3 Low Channel 5745MHz									
436.59	37.73	QP	27	1.0	H	-11.62	26.11	46.00	-19.89
436.59	44.52	QP	11	1.5	V	-11.62	32.90	46.00	-13.10
4505.05	50.50	PK	346	1.2	H	-2.06	48.44	74.00	-25.56
4505.05	41.44	Ave	346	1.2	H	-2.06	39.38	54.00	-14.62
5389.94	40.57	PK	251	1.3	H	5.93	46.50	74.00	-27.50
5389.94	36.59	Ave	251	1.3	H	5.93	42.52	54.00	-11.48
11490.00	46.32	PK	40	1.2	H	-1.25	45.07	74.00	-28.93
11490.00	37.84	Ave	40	1.2	H	-1.25	36.59	54.00	-17.41

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11a U-NII-3 middle channel 5785MHz									
436.59	37.22	QP	330	1.7	H	-11.62	25.60	46.00	-20.40
436.59	44.03	QP	62	1.6	V	-11.62	32.41	46.00	-13.59
4517.66	49.91	PK	56	1.9	H	-2.03	47.88	74.00	-26.12
4517.66	40.95	Ave	56	1.9	H	-2.03	38.92	54.00	-15.08
5364.80	40.77	PK	283	1.5	H	5.81	46.58	74.00	-27.42
5364.80	36.89	Ave	283	1.5	H	5.81	42.70	54.00	-11.30
11570.00	46.28	PK	345	1.3	H	-1.22	45.06	74.00	-28.94
11570.00	38.14	Ave	345	1.3	H	-1.22	36.92	54.00	-17.08
802.11a U-NII-3 High channel 5825MHz									
436.59	36.88	QP	118	1.2	H	-11.62	25.26	46.00	-20.74
436.59	43.87	QP	244	1.5	V	-11.62	32.25	46.00	-13.75
4519.16	49.38	PK	23	1.2	H	-1.84	47.54	74.00	-26.46
4519.16	40.03	Ave	23	1.2	H	-1.84	38.19	54.00	-15.81
5387.44	40.38	PK	171	1.0	H	5.84	46.22	74.00	-27.78
5387.44	37.06	Ave	171	1.0	H	5.84	42.90	54.00	-11.10
11650.00	46.72	PK	281	1.1	H	-1.30	45.42	74.00	-28.58
11650.00	37.01	Ave	281	1.1	H	-1.30	35.71	54.00	-18.29

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-1 Low Channel 5180MHz									
436.59	35.53	QP	174	1.3	H	-11.62	23.91	46.00	-22.09
436.59	42.98	QP	350	1.8	V	-11.62	31.36	46.00	-14.64
4504.37	48.88	PK	48	1.2	H	-2.14	46.74	74.00	-27.26
4504.37	38.91	Ave	48	1.2	H	-2.14	36.77	54.00	-17.23
5128.74	45.90	PK	305	1.5	H	-1.06	44.84	74.00	-29.16
5128.74	39.77	Ave	305	1.5	H	-1.06	38.71	54.00	-15.29
10360.00	40.73	PK	80	1.2	H	5.33	46.06	74.00	-27.94
10360.00	37.65	Ave	80	1.2	H	5.33	42.98	54.00	-11.02
802.11n(HT20) U-NII-1 Middle channel 5200MHz									
436.59	35.11	QP	193	2.0	H	-11.62	23.49	46.00	-22.51
436.59	42.27	QP	152	1.3	V	-11.62	30.65	46.00	-15.35
4516.28	47.63	PK	323	1.9	H	-2.12	45.51	74.00	-28.49
4516.28	38.76	Ave	323	1.9	H	-2.12	36.64	54.00	-17.36
5148.47	45.21	PK	80	1.4	H	-1.06	44.15	74.00	-29.85
5148.47	41.65	Ave	80	1.4	H	-1.06	40.59	54.00	-13.41
10400.00	42.82	PK	202	1.9	H	5.21	48.03	74.00	-25.97
10400.00	36.40	Ave	202	1.9	H	5.21	41.61	54.00	-12.39

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-1 High channel 5240MHz									
436.59	33.86	QP	107	1.5	H	-11.62	22.24	46.00	-23.76
436.59	43.46	QP	75	1.8	V	-11.62	31.84	46.00	-14.16
4501.33	47.66	PK	238	1.8	H	-1.96	45.70	74.00	-28.30
4501.33	40.22	Ave	238	1.8	H	-1.96	38.26	54.00	-15.74
5144.32	46.70	PK	7	1.2	H	-1.06	45.64	74.00	-28.36
5144.32	42.44	Ave	7	1.2	H	-1.06	41.38	54.00	-12.62
10480.00	40.45	PK	234	1.7	H	5.14	45.59	74.00	-28.41
10480.00	38.47	Ave	234	1.7	H	5.14	43.61	54.00	-10.39
802.11n(HT20) U-NII-2A Low Channel 5260MHz									
436.59	34.74	QP	156	1.2	H	-11.62	23.12	46.00	-22.88
436.59	40.61	QP	51	1.3	V	-11.62	28.99	46.00	-17.01
4511.54	39.69	PK	211	1.1	H	-2.03	37.66	74.00	-36.34
4511.54	43.65	Ave	211	1.1	H	-2.03	41.62	54.00	-12.38
5115.01	41.25	PK	53	2.0	H	-1.02	40.23	74.00	-33.77
5115.01	40.79	Ave	53	2.0	H	-1.02	39.77	54.00	-14.23
10520.00	37.99	PK	85	1.1	H	5.33	43.32	74.00	-30.68
10520.00	36.78	Ave	85	1.1	H	5.33	42.11	54.00	-11.89

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-2A middle channel 5280MHz									
436.59	34.48	QP	179	1.3	H	-11.62	22.86	46.00	-23.14
436.59	40.20	QP	140	1.6	V	-11.62	28.58	46.00	-17.42
4500.27	40.97	PK	209	1.8	H	-1.94	39.03	74.00	-34.97
4500.27	44.40	Ave	209	1.8	H	-1.94	42.46	54.00	-11.54
5117.05	42.66	PK	268	1.3	H	-1.06	41.60	74.00	-32.40
5117.05	41.71	Ave	268	1.3	H	-1.06	40.65	54.00	-13.35
10560.00	38.20	PK	256	1.6	H	5.21	43.41	74.00	-30.59
10560.00	36.79	Ave	256	1.6	H	5.21	42.00	54.00	-12.00
802.11n(HT20) U-NII-2A High channel 5320MHz									
436.59	33.30	QP	341	1.4	H	-11.62	21.68	46.00	-24.32
436.59	41.62	QP	137	1.7	V	-11.62	30.00	46.00	-16.00
4527.13	41.48	PK	250	1.8	H	-2.24	39.24	74.00	-34.76
4527.13	44.42	Ave	250	1.8	H	-2.24	42.18	54.00	-11.82
5148.44	41.97	PK	57	1.9	H	-1.09	40.88	74.00	-33.12
5148.44	40.95	Ave	57	1.9	H	-1.09	39.86	54.00	-14.14
10640.00	38.22	PK	254	1.5	H	5.14	43.36	74.00	-30.64
10640.00	37.08	Ave	254	1.5	H	5.14	42.22	54.00	-11.78

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-2C Low Channel 5500MHz									
436.59	31.98	QP	265	1.1	H	-11.62	20.36	46.00	-25.64
436.59	43.95	QP	315	1.8	V	-11.62	32.33	46.00	-13.67
4500.90	37.44	PK	220	1.3	H	-2.03	35.41	74.00	-38.59
4500.90	38.45	Ave	220	1.3	H	-2.03	36.42	54.00	-17.58
5146.72	46.59	PK	348	1.6	H	-1.02	45.57	74.00	-28.43
5146.72	37.03	Ave	348	1.6	H	-1.02	36.01	54.00	-17.99
11000.00	35.69	PK	190	1.2	H	5.33	41.02	74.00	-32.98
11000.00	28.74	Ave	190	1.2	H	5.33	34.07	54.00	-19.93
802.11n(HT20) U-NII-2C Middle channel 5580MHz									
436.59	32.24	QP	92	1.6	H	-11.62	20.62	46.00	-25.38
436.59	44.42	QP	348	1.3	V	-11.62	32.80	46.00	-13.20
4532.22	38.35	PK	156	1.7	H	-1.94	36.41	74.00	-37.59
4532.22	37.33	Ave	156	1.7	H	-1.94	35.39	54.00	-18.61
5127.45	48.17	PK	169	1.5	H	-1.06	47.11	74.00	-26.89
5127.45	36.52	Ave	169	1.5	H	-1.06	35.46	54.00	-18.54
11160.00	36.39	PK	216	1.2	H	5.21	41.60	74.00	-32.40
11160.00	29.07	Ave	216	1.2	H	5.21	34.28	54.00	-19.72

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-2C High channel 5700MHz									
436.59	31.75	QP	102	1.0	H	-11.62	20.13	46.00	-25.87
436.59	45.80	QP	269	1.4	V	-11.62	34.18	46.00	-11.82
4508.83	38.39	PK	338	1.2	H	-2.24	36.15	74.00	-37.85
4508.83	36.96	Ave	338	1.2	H	-2.24	34.72	54.00	-19.28
5146.67	49.86	PK	122	1.8	H	-1.09	48.77	74.00	-25.23
5146.67	36.05	Ave	122	1.8	H	-1.09	34.96	54.00	-19.04
11400.00	34.71	PK	359	1.7	H	5.14	39.85	74.00	-34.15
11400.00	28.20	Ave	359	1.7	H	5.14	33.34	54.00	-20.66
802.11n(HT20) U-NII-3 Low Channel 5745MHz									
436.59	26.55	QP	325	1.3	H	-11.62	14.93	46.00	-31.07
436.59	41.89	QP	115	1.8	V	-11.62	30.27	46.00	-15.73
4531.75	39.07	PK	53	1.2	H	-2.06	37.01	74.00	-36.99
4531.75	46.72	Ave	53	1.2	H	-2.06	44.66	54.00	-9.34
5363.95	36.95	PK	53	1.0	H	5.93	42.88	74.00	-31.12
5363.95	39.16	Ave	53	1.0	H	5.93	45.09	54.00	-8.91
11490.00	46.45	PK	280	1.3	H	-1.25	45.20	74.00	-28.80
11490.00	37.58	Ave	280	1.3	H	-1.25	36.33	54.00	-17.67

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT20) U-NII-3 middle channel 5785MHz									
436.59	26.15	QP	154	1.5	H	-11.62	14.53	46.00	-31.47
436.59	44.88	QP	226	1.1	V	-11.62	33.26	46.00	-12.74
4503.52	37.67	PK	97	2.0	H	-2.03	35.64	74.00	-38.36
4503.52	47.75	Ave	97	2.0	H	-2.03	45.72	54.00	-8.28
5388.18	38.80	PK	250	1.3	H	5.81	44.61	74.00	-29.39
5388.18	40.92	Ave	250	1.3	H	5.81	46.73	54.00	-7.27
11570.00	46.50	PK	142	1.4	H	-1.22	45.28	74.00	-28.72
11570.00	39.00	Ave	142	1.4	H	-1.22	37.78	54.00	-16.22
802.11n(HT20) U-NII-3 High channel 5825MHz									
436.59	26.68	QP	304	1.1	H	-11.62	15.06	46.00	-30.94
436.59	44.22	QP	247	1.1	V	-11.62	32.60	46.00	-13.40
4535.78	38.02	PK	209	1.1	H	-1.84	36.18	74.00	-37.82
4535.78	48.81	Ave	209	1.1	H	-1.84	46.97	54.00	-7.03
5366.78	37.18	PK	329	1.8	H	5.84	43.02	74.00	-30.98
5366.78	41.28	Ave	329	1.8	H	5.84	47.12	54.00	-6.88
11650.00	45.62	PK	330	1.3	H	-1.30	44.32	74.00	-29.68
11650.00	39.52	Ave	330	1.3	H	-1.30	38.22	54.00	-15.78

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT20) U-NII-1 Low Channel 5180MHz									
436.59	26.46	QP	101	1.6	H	-11.62	14.84	46.00	-31.16
436.59	45.54	QP	211	1.2	V	-11.62	33.92	46.00	-12.08
4515.71	45.72	PK	240	1.4	H	-1.86	43.86	74.00	-30.14
4515.71	40.13	Ave	240	1.4	H	-1.86	38.27	54.00	-15.73
5113.65	33.55	PK	53	1.8	H	-1.06	32.49	74.00	-41.51
5113.65	42.76	Ave	53	1.8	H	-1.06	41.70	54.00	-12.30
10360.00	45.48	PK	355	1.6	H	5.33	50.81	74.00	-23.19
10360.00	38.66	Ave	355	1.6	H	5.33	43.99	54.00	-10.01
802.11ac(VHT20) U-NII-1 Middle channel 5200MHz									
436.59	27.13	QP	70	2.0	H	-11.62	15.51	46.00	-30.49
436.59	46.23	QP	336	1.9	V	-11.62	34.61	46.00	-11.39
4514.49	46.38	PK	217	1.5	H	-1.82	44.56	74.00	-29.44
4514.49	39.34	Ave	217	1.5	H	-1.82	37.52	54.00	-16.48
5129.25	33.18	PK	236	1.9	H	-1.06	32.12	74.00	-41.88
5129.25	42.21	Ave	236	1.9	H	-1.06	41.15	54.00	-12.85
10400.00	41.42	PK	157	2.0	H	5.21	46.63	74.00	-27.37
10400.00	38.68	Ave	157	2.0	H	5.21	43.89	54.00	-10.11

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT20) U-NII-1 High channel 5240MHz									
436.59	27.96	QP	298	1.2	H	-11.62	16.34	46.00	-29.66
436.59	45.88	QP	204	1.7	V	-11.62	34.26	46.00	-11.74
4506.83	46.86	PK	334	1.5	H	-1.81	45.05	74.00	-28.95
4506.83	40.30	Ave	334	1.5	H	-1.81	38.49	54.00	-15.51
5121.00	32.21	PK	260	1.6	H	-1.06	31.15	74.00	-42.85
5121.00	43.48	Ave	260	1.6	H	-1.06	42.42	54.00	-11.58
10480.00	42.06	PK	222	1.9	H	5.14	47.20	74.00	-26.80
10480.00	38.53	Ave	222	1.9	H	5.14	43.67	54.00	-10.33
802.11ac(VHT20) U-NII-2A Low Channel 5260MHz									
436.59	33.60	QP	36	1.4	H	-11.62	21.98	46.00	-24.02
436.59	43.96	QP	262	1.9	V	-11.62	32.34	46.00	-13.66
4504.06	42.61	PK	90	1.7	H	-2.03	40.58	74.00	-33.42
4504.06	38.12	Ave	90	1.7	H	-2.03	36.09	54.00	-17.91
5133.07	47.08	PK	331	1.6	H	-1.02	46.06	74.00	-27.94
5133.07	39.13	Ave	331	1.6	H	-1.02	38.11	54.00	-15.89
10520.00	34.66	PK	342	1.8	H	5.33	39.99	74.00	-34.01
10520.00	42.55	Ave	342	1.8	H	5.33	47.88	54.00	-6.12

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT20) U-NII-2A middle channel 5280MHz									
436.59	34.18	QP	36	1.5	H	-11.62	22.56	46.00	-23.44
436.59	43.64	QP	222	1.3	V	-11.62	32.02	46.00	-13.98
4526.39	43.55	PK	142	1.1	H	-1.94	41.61	74.00	-32.39
4526.39	37.58	Ave	142	1.1	H	-1.94	35.64	54.00	-18.36
5148.16	48.87	PK	176	2.0	H	-1.06	47.81	74.00	-26.19
5148.16	40.08	Ave	176	2.0	H	-1.06	39.02	54.00	-14.98
10560.00	33.30	PK	307	1.5	H	5.21	38.51	74.00	-35.49
10560.00	42.43	Ave	307	1.5	H	5.21	47.64	54.00	-6.36
802.11ac(VHT20) U-NII-2A High channel 5320MHz									
436.59	35.43	QP	127	1.6	H	-11.62	23.81	46.00	-22.19
436.59	42.29	QP	206	1.2	V	-11.62	30.67	46.00	-15.33
4525.02	42.45	PK	121	1.1	H	-2.24	40.21	74.00	-33.79
4525.02	37.92	Ave	121	1.1	H	-2.24	35.68	54.00	-18.32
5144.33	49.72	PK	204	1.2	H	-1.09	48.63	74.00	-25.37
5144.33	39.52	Ave	204	1.2	H	-1.09	38.43	54.00	-15.57
10640.00	34.68	PK	30	1.8	H	5.14	39.82	74.00	-34.18
10640.00	41.33	Ave	30	1.8	H	5.14	46.47	54.00	-7.53

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT20) U-NII-2C Low Channel 5500MHz									
436.59	35.45	QP	220	1.8	H	-11.62	23.83	46.00	-22.17
436.59	42.08	QP	158	1.7	V	-11.62	30.46	46.00	-15.54
4534.32	34.89	PK	39	1.6	H	-2.03	32.86	74.00	-41.14
4534.32	41.75	Ave	39	1.6	H	-2.03	39.72	54.00	-14.28
5148.38	46.05	PK	6	1.1	H	-1.02	45.03	74.00	-28.97
5148.38	41.50	Ave	6	1.1	H	-1.02	40.48	54.00	-13.52
11000.00	36.62	PK	134	1.6	H	5.33	41.95	74.00	-32.05
11000.00	35.49	Ave	134	1.6	H	5.33	40.82	54.00	-13.18
802.11ac(VHT20) U-NII-2C Middle channel 5580MHz									
436.59	35.10	QP	288	1.2	H	-11.62	23.48	46.00	-22.52
436.59	40.83	QP	60	1.3	V	-11.62	29.21	46.00	-16.79
4516.43	33.88	PK	256	1.9	H	-1.94	31.94	74.00	-42.06
4516.43	41.06	Ave	256	1.9	H	-1.94	39.12	54.00	-14.88
5144.84	46.94	PK	334	1.1	H	-1.06	45.88	74.00	-28.12
5144.84	40.71	Ave	334	1.1	H	-1.06	39.65	54.00	-14.35
11160.00	36.55	PK	292	1.7	H	5.21	41.76	74.00	-32.24
11160.00	36.72	Ave	292	1.7	H	5.21	41.93	54.00	-12.07

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT20) U-NII-2C High channel 5700MHz									
436.59	35.81	QP	49	1.6	H	-11.62	24.19	46.00	-21.81
436.59	40.37	QP	58	1.0	V	-11.62	28.75	46.00	-17.25
4505.57	34.55	PK	0	1.5	H	-2.24	32.31	74.00	-41.69
4505.57	39.92	Ave	0	1.5	H	-2.24	37.68	54.00	-16.32
5145.74	48.47	PK	180	1.8	H	-1.09	47.38	74.00	-26.62
5145.74	40.89	Ave	180	1.8	H	-1.09	39.80	54.00	-14.20
11400.00	36.21	PK	44	1.9	H	5.14	41.35	74.00	-32.65
11400.00	36.66	Ave	44	1.9	H	5.14	41.80	54.00	-12.20
802.11ac(VHT20) U-NII-3 Low Channel 5745MHz									
436.59	27.37	QP	216	1.7	H	-11.62	15.75	46.00	-30.25
436.59	46.91	QP	31	1.2	V	-11.62	35.29	46.00	-10.71
4523.96	44.83	PK	157	1.0	H	-1.92	42.91	74.00	-31.09
4523.96	37.39	Ave	157	1.0	H	-1.92	35.47	54.00	-18.53
5351.16	40.19	PK	212	1.9	H	5.93	46.12	74.00	-27.88
5351.16	35.15	Ave	212	1.9	H	5.93	41.08	54.00	-12.92
11490.00	46.07	PK	147	1.8	H	-1.03	45.04	74.00	-28.96
11490.00	39.68	Ave	147	1.8	H	-1.03	38.65	54.00	-15.35

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT20) U-NII-3 middle channel 5785MHz									
436.59	26.88	QP	129	1.4	H	-11.62	15.26	46.00	-30.74
436.59	46.12	QP	181	1.6	V	-11.62	34.50	46.00	-11.50
4531.67	43.96	PK	308	1.0	H	-1.97	41.99	74.00	-32.01
4531.67	36.40	Ave	308	1.0	H	-1.97	34.43	54.00	-19.57
5358.19	41.32	PK	106	1.4	H	5.81	47.13	74.00	-26.87
5358.19	38.66	Ave	106	1.4	H	5.81	44.47	54.00	-9.53
11570.00	45.21	PK	34	1.8	H	-1.05	44.16	74.00	-29.84
11570.00	37.77	Ave	34	1.8	H	-1.05	36.72	54.00	-17.28
802.11ac(VHT20) U-NII-3 High channel 5825MHz									
436.59	27.01	QP	239	1.8	H	-11.62	15.39	46.00	-30.61
436.59	46.62	QP	48	1.7	V	-11.62	35.00	46.00	-11.00
4539.69	44.41	PK	70	1.1	H	-1.88	42.53	74.00	-31.47
4539.69	36.40	Ave	70	1.1	H	-1.88	34.52	54.00	-19.48
5362.99	42.46	PK	98	1.5	H	5.84	48.30	74.00	-25.70
5362.99	36.95	Ave	98	1.5	H	5.84	42.79	54.00	-11.21
11650.00	45.76	PK	85	1.7	H	-1.06	44.70	74.00	-29.30
11650.00	39.78	Ave	85	1.7	H	-1.06	38.72	54.00	-15.28

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) U-NII-1 Low Channel 5190MHz									
436.59	28.02	QP	146	1.1	H	-11.62	16.40	46.00	-29.60
436.59	46.54	QP	109	1.0	V	-11.62	34.92	46.00	-11.08
4537.12	43.35	PK	79	1.8	H	-1.89	41.46	74.00	-32.54
4537.12	34.67	Ave	79	1.8	H	-1.89	32.78	54.00	-21.22
5148.09	47.95	PK	212	1.9	H	-1.06	46.89	74.00	-27.11
5148.09	38.02	Ave	212	1.9	H	-1.06	36.96	54.00	-17.04
10380.00	39.04	PK	167	1.9	H	5.26	44.30	74.00	-29.70
10380.00	35.66	Ave	167	1.9	H	5.26	40.92	54.00	-13.08
802.11n(HT40) U-NII-1 High channel 5230MHz									
436.59	28.21	QP	145	1.6	H	-11.62	16.59	46.00	-29.41
436.59	45.63	QP	225	1.9	V	-11.62	34.01	46.00	-11.99
4539.56	43.59	PK	45	1.1	H	-1.94	41.65	74.00	-32.35
4539.56	35.25	Ave	45	1.1	H	-1.94	33.31	54.00	-20.69
5134.22	47.68	PK	211	1.8	H	-1.06	46.62	74.00	-27.38
5134.22	38.29	Ave	211	1.8	H	-1.06	37.23	54.00	-16.77
10460.00	41.67	PK	138	1.7	H	5.28	46.95	74.00	-27.05
10460.00	38.00	Ave	138	1.7	H	5.28	43.28	54.00	-10.72

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) U-NII-2A Low Channel 5270MHz									
436.59	27.43	QP	299	1.9	H	-11.62	15.81	46.00	-30.19
436.59	46.46	QP	345	1.1	V	-11.62	34.84	46.00	-11.16
4515.70	40.92	PK	291	1.0	H	-1.89	39.03	74.00	-34.97
4515.70	38.02	Ave	291	1.0	H	-1.89	36.13	54.00	-17.87
5121.86	48.22	PK	127	1.5	H	-1.06	47.16	74.00	-26.84
5121.86	40.06	Ave	127	1.5	H	-1.06	39.00	54.00	-15.00
10540.00	46.37	PK	49	1.6	H	5.26	51.63	74.00	-22.37
10540.00	37.36	Ave	49	1.6	H	5.26	42.62	54.00	-11.38
802.11n(HT40) U-NII-2A High channel 5310MHz									
436.59	27.11	QP	222	1.3	H	-11.62	15.49	46.00	-30.51
436.59	45.93	QP	38	1.2	V	-11.62	34.31	46.00	-11.69
4516.75	41.26	PK	36	1.5	H	-1.94	39.32	74.00	-34.68
4516.75	37.35	Ave	36	1.5	H	-1.94	35.41	54.00	-18.59
5132.87	47.86	PK	115	1.4	H	-1.06	46.80	74.00	-27.20
5132.87	40.67	Ave	115	1.4	H	-1.06	39.61	54.00	-14.39
10620.00	41.57	PK	116	1.4	H	5.28	46.85	74.00	-27.15
10620.00	37.85	Ave	116	1.4	H	5.28	43.13	54.00	-10.87

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) U-NII-2C Low Channel 5510MHz									
436.59	26.46	QP	164	1.6	H	-11.62	14.84	46.00	-31.16
436.59	46.61	QP	194	1.8	V	-11.62	34.99	46.00	-11.01
4513.60	41.17	PK	233	1.1	H	-1.89	39.28	74.00	-34.72
4513.60	37.04	Ave	233	1.1	H	-1.89	35.15	54.00	-18.85
5119.92	47.52	PK	60	1.9	H	-1.06	46.46	74.00	-27.54
5119.92	39.12	Ave	60	1.9	H	-1.06	38.06	54.00	-15.94
11020.00	42.41	PK	51	1.3	H	5.26	47.67	74.00	-26.33
11020.00	36.22	Ave	51	1.3	H	5.26	41.48	54.00	-12.52
802.11n(HT40) U-NII-2C Middle channel 5550MHz									
436.59	26.82	QP	175	1.4	H	-11.62	15.20	46.00	-30.80
436.59	45.92	QP	89	1.8	V	-11.62	34.30	46.00	-11.70
4529.75	41.11	PK	27	2.0	H	-1.94	39.17	74.00	-34.83
4529.75	37.29	Ave	27	2.0	H	-1.94	35.35	54.00	-18.65
5139.45	48.08	PK	163	1.6	H	-1.06	47.02	74.00	-26.98
5139.45	40.47	Ave	163	1.6	H	-1.06	39.41	54.00	-14.59
11100.00	44.36	PK	251	1.6	H	5.28	49.64	74.00	-24.36
11100.00	37.41	Ave	251	1.6	H	5.28	42.69	54.00	-11.31
802.11n(HT40) U-NII-2C High channel 5670MHz									
436.59	27.70	QP	286	1.4	H	-11.62	16.08	46.00	-29.92
436.59	45.44	QP	145	1.2	V	-11.62	33.82	46.00	-12.18
4508.99	41.66	PK	291	1.8	H	-1.94	39.72	74.00	-34.28
4508.99	37.78	Ave	291	1.8	H	-1.94	35.84	54.00	-18.16
5137.82	49.11	PK	114	1.9	H	-1.06	48.05	74.00	-25.95
5137.82	40.32	Ave	114	1.9	H	-1.06	39.26	54.00	-14.74
11340.00	41.05	PK	347	1.0	H	5.28	46.33	74.00	-27.67
11340.00	33.28	Ave	347	1.0	H	5.28	38.56	54.00	-15.44

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11n(HT40) U-NII-3 Low Channel 5755MHz									
436.59	29.05	QP	315	1.9	H	-11.62	17.43	46.00	-28.57
436.59	46.07	QP	237	1.1	V	-11.62	34.45	46.00	-11.55
4539.36	41.59	PK	48	1.2	H	-1.96	39.63	74.00	-34.37
4539.36	33.55	Ave	48	1.2	H	-1.96	31.59	54.00	-22.41
5354.24	40.17	PK	311	1.8	H	5.88	46.05	74.00	-27.95
5354.24	35.65	Ave	311	1.8	H	5.88	41.53	54.00	-12.47
11510.00	46.28	PK	226	1.5	H	-1.01	45.27	74.00	-28.73
11510.00	38.51	Ave	226	1.5	H	-1.01	37.50	54.00	-16.50
802.11n(HT40) U-NII-3 High Channel 5795MHz									
436.59	28.33	QP	209	1.3	H	-11.62	16.71	46.00	-29.29
436.59	45.48	QP	165	1.9	V	-11.62	33.86	46.00	-12.14
4534.50	41.78	PK	223	1.2	H	-1.92	39.86	74.00	-34.14
4534.50	32.83	Ave	223	1.2	H	-1.92	30.91	54.00	-23.09
5363.64	42.00	PK	200	1.7	H	5.63	47.63	74.00	-26.37
5363.64	37.43	Ave	200	1.7	H	5.63	43.06	54.00	-10.94
11590.00	46.94	PK	86	1.5	H	-1.04	45.90	74.00	-28.10
11590.00	37.40	Ave	86	1.5	H	-1.04	36.36	54.00	-17.64

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT40) U-NII-1 Low Channel 5190MHz									
436.59	28.62	QP	52	1.0	H	-11.62	17.00	46.00	-29.00
436.59	45.90	QP	229	1.7	V	-11.62	34.28	46.00	-11.72
4515.11	38.86	PK	186	1.3	H	-1.91	36.95	74.00	-37.05
4515.11	31.33	Ave	186	1.3	H	-1.91	29.42	54.00	-24.58
5143.68	45.21	PK	258	1.8	H	-1.06	44.15	74.00	-29.85
5143.68	40.94	Ave	258	1.8	H	-1.06	39.88	54.00	-14.12
10380.00	38.78	PK	353	1.5	H	5.26	44.04	74.00	-29.96
10380.00	36.53	Ave	353	1.5	H	5.26	41.79	54.00	-12.21
802.11ac(VHT40) U-NII-1 High channel 5230MHz									
436.59	28.40	QP	196	1.1	H	-11.62	16.78	46.00	-29.22
436.59	45.35	QP	218	1.0	V	-11.62	33.73	46.00	-12.27
4511.84	39.57	PK	354	1.6	H	-1.93	37.64	74.00	-36.36
4511.84	30.66	Ave	354	1.6	H	-1.93	28.73	54.00	-25.27
5131.97	44.75	PK	20	1.7	H	-1.06	43.69	74.00	-30.31
5131.97	42.18	Ave	20	1.7	H	-1.06	41.12	54.00	-12.88
10460.00	41.28	PK	51	1.5	H	5.28	46.56	74.00	-27.44
10460.00	37.50	Ave	51	1.5	H	5.28	42.78	54.00	-11.22

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT40) U-NII-2A Low Channel 5270MHz									
436.59	27.65	QP	353	1.3	H	-11.62	16.03	46.00	-29.97
436.59	41.34	QP	308	1.1	V	-11.62	29.72	46.00	-16.28
4528.81	41.27	PK	225	1.9	H	-1.89	39.38	74.00	-34.62
4528.81	36.68	Ave	225	1.9	H	-1.89	34.79	54.00	-19.21
5115.67	47.67	PK	151	1.2	H	-1.06	46.61	74.00	-27.39
5115.67	37.89	Ave	151	1.2	H	-1.06	36.83	54.00	-17.17
10540.00	42.88	PK	248	1.6	H	5.26	48.14	74.00	-25.86
10540.00	33.15	Ave	248	1.6	H	5.26	38.41	54.00	-15.59
802.11ac(VHT40) U-NII-2A High channel 5310MHz									
436.59	26.71	QP	304	1.3	H	-11.62	15.09	46.00	-30.91
436.59	40.72	QP	195	1.7	V	-11.62	29.10	46.00	-16.90
4506.57	40.45	PK	45	1.1	H	-1.94	38.51	74.00	-35.49
4506.57	36.94	Ave	45	1.1	H	-1.94	35.00	54.00	-19.00
5111.99	49.39	PK	309	1.0	H	-1.06	48.33	74.00	-25.67
5111.99	38.31	Ave	309	1.0	H	-1.06	37.25	54.00	-16.75
10620.00	42.74	PK	4	1.5	H	5.28	48.02	74.00	-25.98
10620.00	37.67	Ave	4	1.5	H	5.28	42.95	54.00	-11.05

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT40) U-NII-2C Low Channel 5510MHz									
436.59	26.89	QP	189	1.3	H	-11.62	15.27	46.00	-30.73
436.59	39.26	QP	116	1.2	V	-11.62	27.64	46.00	-18.36
4538.69	42.56	PK	61	1.1	H	-1.89	40.67	74.00	-33.33
4538.69	36.98	Ave	61	1.1	H	-1.89	35.09	54.00	-18.91
5149.33	48.42	PK	83	1.3	H	-1.06	47.36	74.00	-26.64
5149.33	38.52	Ave	83	1.3	H	-1.06	37.46	54.00	-16.54
11020.00	41.28	PK	333	2.0	H	5.26	46.54	74.00	-27.46
11020.00	38.44	Ave	333	2.0	H	5.26	43.70	54.00	-10.30
802.11ac(VHT40) U-NII-2C Middle channel 5550MHz									
436.59	26.28	QP	307	1.7	H	-11.62	14.66	46.00	-31.34
436.59	40.22	QP	304	1.4	V	-11.62	28.60	46.00	-17.40
4519.54	43.26	PK	267	1.6	H	-1.94	41.32	74.00	-32.68
4519.54	36.70	Ave	267	1.6	H	-1.94	34.76	54.00	-19.24
5132.46	48.37	PK	246	1.0	H	-1.06	47.31	74.00	-26.69
5132.46	39.74	Ave	246	1.0	H	-1.06	38.68	54.00	-15.32
11100.00	43.25	PK	10	1.8	H	5.28	48.53	74.00	-25.47
11100.00	38.03	Ave	10	1.8	H	5.28	43.31	54.00	-10.69
802.11ac(VHT40) U-NII-2C High channel 5670MHz									
436.59	25.54	QP	209	1.6	H	-11.62	13.92	46.00	-32.08
436.59	40.20	QP	254	1.6	V	-11.62	28.58	46.00	-17.42
4524.63	43.62	PK	202	1.1	H	-1.94	41.68	74.00	-32.32
4524.63	35.73	Ave	202	1.1	H	-1.94	33.79	54.00	-20.21
5111.92	48.11	PK	227	1.4	H	-1.06	47.05	74.00	-26.95
5111.92	40.53	Ave	227	1.4	H	-1.06	39.47	54.00	-14.53
11340.00	42.63	PK	35	1.6	H	5.28	47.91	74.00	-26.09
11340.00	35.66	Ave	35	1.6	H	5.28	40.94	54.00	-13.06

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT40) U-NII-3 Low Channel 5755MHz									
436.59	29.35	QP	21	1.0	H	-11.62	17.73	46.00	-28.27
436.59	44.09	QP	156	1.0	V	-11.62	32.47	46.00	-13.53
4520.34	37.75	PK	58	1.2	H	-1.92	35.83	74.00	-38.17
4520.34	28.85	Ave	58	1.2	H	-1.92	26.93	54.00	-27.07
5385.61	39.91	PK	224	1.0	H	5.88	45.79	74.00	-28.21
5385.61	35.31	Ave	224	1.0	H	5.88	41.19	54.00	-12.81
11510.00	45.14	PK	122	1.6	H	-1.07	44.07	74.00	-29.93
11510.00	37.51	Ave	122	1.6	H	-1.07	36.44	54.00	-17.56
802.11ac(VHT40) U-NII-3 High Channel 5795MHz									
436.59	29.10	QP	338	1.9	H	-11.62	17.48	46.00	-28.52
436.59	43.59	QP	237	1.0	V	-11.62	31.97	46.00	-14.03
4528.21	36.86	PK	255	1.2	H	-1.86	35.00	74.00	-39.00
4528.21	29.57	Ave	255	1.2	H	-1.86	27.71	54.00	-26.29
5377.55	41.64	PK	288	1.0	H	5.63	47.27	74.00	-26.73
5377.55	38.19	Ave	288	1.0	H	5.63	43.82	54.00	-10.18
11590.00	46.54	PK	318	1.6	H	-1.03	45.51	74.00	-28.49
11590.00	38.96	Ave	318	1.6	H	-1.03	37.93	54.00	-16.07

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT80) U-NII-1 Low Channel 5210MHz									
436.59	29.09	QP	183	1.4	H	-11.62	17.47	46.00	-28.53
436.59	42.94	QP	355	1.4	V	-11.62	31.32	46.00	-14.68
4506.64	30.16	PK	138	1.9	H	-1.88	28.28	74.00	-45.72
4506.64	42.53	Ave	138	1.9	H	-1.88	40.65	54.00	-13.35
5125.26	39.25	PK	180	1.0	H	-1.06	38.19	74.00	-35.81
5125.26	47.74	Ave	180	1.0	H	-1.06	46.68	54.00	-7.32
10420.00	42.00	PK	3	1.5	H	4.65	46.65	74.00	-27.35
10420.00	37.25	Ave	3	1.5	H	4.65	41.90	54.00	-12.10
802.11ac(VHT80) U-NII-2A Low Channel 5290MHz									
436.59	28.17	QP	187	1.3	H	-11.62	16.55	46.00	-29.45
436.59	36.00	QP	340	1.9	V	-11.62	24.38	46.00	-21.62
4532.08	42.24	PK	342	1.6	H	-1.88	40.36	74.00	-33.64
4532.08	39.71	Ave	342	1.6	H	-1.88	37.83	54.00	-16.17
5125.17	46.82	PK	152	1.1	H	-1.06	45.76	74.00	-28.24
5125.17	41.21	Ave	152	1.1	H	-1.06	40.15	54.00	-13.85
10580.00	35.96	PK	176	2.0	H	4.65	40.61	74.00	-33.39
10580.00	37.09	Ave	176	2.0	H	4.65	41.74	54.00	-12.26

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.407/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP/Ave)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
802.11ac(VHT80) U-NII-2C Low Channel 5530MHz									
436.59	35.71	QP	323	1.0	H	-11.62	24.09	46.00	-21.91
436.59	41.28	QP	29	1.4	V	-11.62	29.66	46.00	-16.34
4502.73	39.33	PK	212	1.8	H	-1.88	37.45	74.00	-36.55
4502.73	47.68	Ave	212	1.8	H	-1.88	45.80	54.00	-8.20
5117.33	42.19	PK	294	1.7	H	-1.06	41.13	74.00	-32.87
5117.33	36.61	Ave	294	1.7	H	-1.06	35.55	54.00	-18.45
11060.00	45.06	PK	0	1.2	H	4.65	49.71	74.00	-24.29
11060.00	36.95	Ave	0	1.2	H	4.65	41.60	54.00	-12.40
802.11ac(VHT80) U-NII-3 Low channel 5775MHz									
436.59	35.52	QP	57	1.4	H	-11.62	23.90	46.00	-22.10
436.59	40.88	QP	333	1.5	V	-11.62	29.26	46.00	-16.74
4515.67	41.64	PK	261	1.3	H	-1.85	39.79	74.00	-34.21
4515.67	42.92	Ave	261	1.3	H	-1.85	41.07	54.00	-12.93
5370.80	40.90	PK	341	1.7	H	4.83	45.73	74.00	-28.27
5370.80	37.46	Ave	341	1.7	H	4.83	42.29	54.00	-11.71
11550.00	46.16	PK	330	1.0	H	-1.14	45.02	74.00	-28.98
11550.00	38.61	Ave	330	1.0	H	-1.14	37.47	54.00	-16.53

Test Frequency: 12GHz~40GHz

The measurements were more than 20 dB below the limit and not reported.

10 Band Edge

Test Requirement:	FCC 47CFR Part 15 Section 15.407
Test Method:	ANSI C63.10 2013
Test Limit:	For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27dBm/MHz. For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. (ii) Devices certified before March 2, 2017 with antenna gain greater than 10 dBi may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease by March 2, 2018. Devices certified before March 2, 2018 with antenna gain of 10 dBi or less may demonstrate compliance with the emission limits in §15.247(d), but manufacturing, marketing and importing of devices certified under this alternative must cease before March 2, 2020.
Test Result:	PASS


10.1 Test Produce

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.


10.2 Test Result

Test result plots shown as follows:


802.11a U-NII-1 Band edge-left side




802.11a U-NII-1 Band edge-right side




802.11a U-NII-2A Band edge-left side




802.11a U-NII-2A Band edge-right side




802.11a U-NII-2C Band edge-left side




802.11a U-NII-2C Band edge-right side




802.11a U-NII-3 Band edge-left side




802.11a U-NII-3 Band edge-right side




802.11n(HT20) U-NII-1 Band edge-left side




802.11n(HT20) U-NII-1 Band edge-right side




802.11n(HT20) U-NII-2A Band edge-left side




802.11n(HT20) U-NII-2A Band edge-right side




802.11n(HT20) U-NII-2C Band edge-left side




802.11n(HT20) U-NII-2C Band edge-right side




802.11n(HT20) U-NII-3 Band edge-left side




802.11n(HT20) U-NII-3 Band edge-right side




802.11n(HT40) U-NII-1 Band edge-left side



802.11n(HT40) U-NII-1 Band edge-right side




802.11n(HT40) U-NII-2A Band edge-left side




802.11n(HT40) U-NII-2A Band edge-right side




802.11n(HT40) U-NII-2C Band edge-left side




802.11n(HT40) U-NII-2C Band edge-right side




802.11n(HT40) U-NII-3 Band edge-left side




802.11n(HT40) U-NII-3 Band edge-right side




802.11ac(VHT20) U-NII-1 Band edge-left side




802.11ac(VHT20) U-NII-1 Band edge-right side




802.11ac(VHT20) U-NII-2A Band edge-left side




802.11ac(VHT20) U-NII-2A Band edge-right side




802.11ac(VHT20) U-NII-2C Band edge-left side




802.11ac(VHT20) U-NII-2C Band edge-right side




802.11ac(VHT20) U-NII-3 Band edge-left side




802.11ac(VHT20) U-NII-3 Band edge-right side




802.11ac(VHT40) U-NII-1 Band edge-left side




802.11ac(VHT40) U-NII-1 Band edge-right side




802.11ac(VHT40) U-NII-2A Band edge-left side




802.11ac(VHT40) U-NII-2A Band edge-right side




802.11ac(VHT40) U-NII-2C Band edge-left side




802.11ac(VHT40) U-NII-2C Band edge-right side




802.11ac(VHT40) U-NII-3 Band edge-left side




802.11ac(VHT40) U-NII-3 Band edge-right side




802.11ac(VHT80) U-NII-1 Band edge-left side




802.11ac(VHT80) U-NII-1 Band edge-right side




802.11ac(VHT80) U-NII-2A Band edge-left side




802.11ac(VHT80) U-NII-2A Band edge-right side




802.11ac(VHT80) U-NII-2C Band edge-left side




802.11ac(VHT80) U-NII-2C Band edge-right side



802.11ac(VHT80) U-NII-3 Band edge-left side



802.11ac(VHT80) U-NII-3 Band edge-right side



11 6 dB Bandwidth

Test Requirement:	FCC 47CFR Part 15 Section 15.407(e) KDB662911 D01 Multiple Transmitter Output v02r01
Test Method:	KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Section C
Test Limit:	≥ 500 kHz
Test Result:	PASS

11.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

11.2 Test Result


Band	Operation mode	6 dB Bandwidth (MHz)		
		Low	Middle	High
U-NII-3	802.11a	15.35	15.11	15.10
	802.11n(HT20)	15.07	15.12	15.08
	802.11n(HT40)	35.10	/	35.10
	802.11ac(VHT20)	15.02	15.13	15.07
	802.11ac(VHT40)	35.09	/	35.10
	802.11ac(VHT80)	/	75.11	/

Test result plots shown as follows:


802.11a U-NII-3 Low channel




802.11a U-NII-3 Middle channel




802.11a U-NII-3 High channel




802.11n(HT20) U-NII-3 Low channel




802.11n(HT20) U-NII-3 Middle channel




802.11n(HT20) U-NII-3 High channel





802.11n(HT40) U-NII-3 Low channel




802.11n(HT40) U-NII-3 High channel







802.11ac(VHT20) U-NII-3 High channel




802.11ac(VHT40) U-NII-3 Low channel



802.11ac(VHT40) U-NII-3 High channel



802.11ac(VHT80) U-NII-3 Middle channel



12 26 dB Bandwidth and 99% Occupied Bandwidth

Test Requirement:	FCC 47CFR Part 15 Section 15.407 (a) KDB662911 D01 Multiple Transmitter Output v02r01
Test Method:	KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Section D
Test Limit:	No restriction limits
Test Result:	PASS

12.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 1% to 5% of the OBW, VBW = 3x RBW

12.2 Test Result

Band	Operation mode	26 dB Bandwidth (MHz)			99% Bandwidth (MHz)		
		Low	Middle	High	Low	Middle	High
U-NII-1	802.11a	20.08	20.05	19.71	16.500	16.500	16.500
	802.11n(HT20)	20.03	19.95	20.22	17.580	17.700	17.640
	802.11n(HT40)	40.65	/	40.69	36.240	/	36.360
	802.11ac(VHT20)	20.06	20.14	20.38	17.580	17.640	17.640
	802.11ac(VHT40)	40.13	/	40.20	36.240	/	36.240
	802.11ac(VHT80)	81.20	/	/	/	75.840	/

Band	Operation mode	26 dB Bandwidth (MHz)			99% Bandwidth (MHz)		
		Low	Middle	High	Low	Middle	High
U-NII-2A	802.11a	19.86	19.84	19.75	16.500	16.440	16.500
	802.11n(HT20)	19.96	20.23	20.20	17.640	17.640	17.640
	802.11n(HT40)	40.27	/	40.18	36.240	/	36.240
	802.11ac(VHT20)	20.15	19.99	20.36	17.640	17.640	17.640
	802.11ac(VHT40)	39.69	/	39.97	36.360	/	36.240
	802.11ac(VHT80)	80.54	/	/	/	75.360	/


Band	Operation mode	26 dB Bandwidth (MHz)			99% Bandwidth (MHz)		
		Low	Middle	High	Low	Middle	High
U-NII-2C	802.11a	19.74	19.70	19.74	16.500	16.500	16.500
	802.11n(HT20)	20.19	20.27	20.02	17.700	17.580	17.640
	802.11n(HT40)	40.62	40.31	40.17	36.240	36.240	36.240
	802.11ac(VHT20)	20.06	20.45	20.12	17.640	17.580	17.640
	802.11ac(VHT40)	40.28	39.77	39.75	36.240	36.240	36.240
	802.11ac(VHT80)	80.14	/	80.14	75.600	75.600	/

Band	Operation mode	99% Bandwidth (MHz)		
		Low	Middle	High
U-NII-3	802.11a	16.500	16.500	16.500
	802.11n(HT20)	17.700	17.700	17.640
	802.11n(HT40)	36.240	/	36.240
	802.11ac(VHT20)	17.580	17.640	17.640
	802.11ac(VHT40)	36.240	/	36.240
	802.11ac(VHT80)	/	75.360	/


Test result plots shown as follows:

26 dB Bandwidth


802.11a U-NII-1 Low channel




802.11a U-NII-1 Middle channel




802.11a U-NII-1 High channel




802.11n(HT20) U-NII-1 Low channel




802.11n(HT20) U-NII-1 Middle channel




802.11n(HT20) U-NII-1 High channel





802.11n(HT40) U-NII-1 Low channel




802.11n(HT40) U-NII-1 High channel







802.11ac(VHT20) U-NII-1 High channel




802.11ac(VHT40) U-NII-1 Low channel




802.11ac(VHT40) U-NII-1 High channel




802.11ac(VHT80) U-NII-1 Low channel




802.11a U-NII-2A Low channel




802.11a U-NII-2A Middle channel




802.11a U-NII-2A High channel




802.11n(HT20) U-NII-2A Low channel




802.11n(HT20) U-NII-2A Middle channel




802.11n(HT20) U-NII-2A High channel




802.11n(HT40) U-NII-2A Low channel




802.11n(HT40) U-NII-2A High channel




802.11ac(VHT20) U-NII-2A Low channel




802.11ac(VHT20) U-NII-2A Middle channel




802.11ac(VHT20) U-NII-2A High channel




802.11ac(VHT40) U-NII-2A Low channel




802.11ac(VHT40) U-NII-2A High channel




802.11ac(VHT80) U-NII-2A Low channel




802.11a U-NII-2C Low channel




802.11a U-NII-2C Middle channel




802.11a U-NII-2C High channel




802.11n(HT20) U-NII-2C Low channel




802.11n(HT20) U-NII-2C Middle channel



802.11n(HT20) U-NII-2C High channel



802.11n(HT40) U-NII-2C Low channel



802.11n(HT40) U-NII-2C Middle channel

