



# A Test Lab Techno Corp.

Changan Lab : No. 140-1, Changan Street, Bade District, Taoyuan City 33465, Taiwan (R.O.C)  
Tel : 886-3-271-0188 / Fax : 886-3-271-0190



## MPE Report

Test Report No.	: 1709FS14
Applicant	: WeatherFlow, Inc.
Product Type	: SWS RF Module
Trade Name	: WeatherFlow
Model Number	: WF-RF915
Date of Received	: Aug. 18, 2017
Test Period	: Aug. 29, 2017
Date of Issued	: Oct. 12, 2017
Test Specification	: ANSI / IEEE Std.C95.1-1992 / IEEE Std. 1528-2013 47 CFR § 2.1091 47 CFR § 1.1310
Location of Test Lab.	: Chang-an Lab.

1. The test operations have to be performed with cautious behavior, the test results are as attached.
2. The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp.
4. This document may be altered or revised by A Test Lab Techno. Corp. personnel only, and shall be noted in the revision section of the document.

Approved By

:

(Mark Duan)

Tested By

(Sky Chou)



## Contents

1.	<i>Description of Equipment under Test (EUT)</i> .....	3
2.	<i>Human Exposure Assessment</i> .....	4
3.	<i>RF Output Power</i> .....	5
4.	<i>Test Results</i> .....	5



## 1. Description of Equipment under Test (EUT)

Applicant	WeatherFlow, Inc. 108 Whispering Pines Suite 245 Scotts Valley California 95066 United States	
Manufacturer	WeatherFlow, Inc. 108 Whispering Pines Suite 245 Scotts Valley California 95066 United States	
Product Type	SWS RF Module	
Trade Name	WeatherFlow	
Model Number	WF-RF915	
FCC ID	2AEQB-WXFLW001	
Frequency Range	Operate Band	Frequency Range (MHz)
	RFID	915
Antenna information	Type	Max. Gain (dBi)
	Internal antenna	2.15
RF Evaluation	0.002 mW/cm <sup>2</sup>	
Temperature Range	0 ~ +40°C	

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1091 / 47 CFR § 1.1310. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties



## 2. Human Exposure Assessment

Due to the design and installation of this product, it is not possible to conduct SAR evaluation. This is because client either manufactures or supplies the antenna(s) that will be used in the installation of this product. Therefore, this product will be evaluated as a mobile device per 47 CFR § 1.1310 titled "Radiofrequency radiation exposure limits", generally referred to as MPE limits.

In 47 CFR § 2.1091, paragraph (b) defines a mobile device as "a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons." This product is intended to be installed into a vehicle such that the unit is physically secured at one location. In the installation guide supplied with the product,

Client has made the following statement: "IMPORTANT: To meet the FCC's RF Exposure Guidelines, the antenna should be installed so there is at least 20 cm of separation between the body of the user and nearby persons and the antenna". Based on the installation of the transceiver and the antenna, the transmitters radiating structure is more than 20 cm from the user. Thus, this product is a "mobile device" as defined in section § 2.1091 paragraph (b).

Exposure evaluation
$S = \frac{PG}{4\pi R^2}$ <p>Where</p> <p>S: power density</p> <p>P: power input to the antenna</p> <p>G: power gain of the antenna in the direction of interest relative to an isotropic radiator.</p> <p>R: distance to the center of radiation of the antenna.</p>



### 3. RF Output Power

The conducted power turn-up tolerance reference manufacturer specification.

Band	Frequency (MHz)	Average Conducted power (dBm)
RFID	915	7.31

Note: The relevant measured result has the offset with cable loss already.

### 4. Test Results

Band	Frequency (MHz)	Limit (mw)	Distance [R] (cm)	Max tune-up Power (upper limit) [P] (dBm)	ANT Gain (dBi)	Numeric Gain [G]	Duty Cycle	[P] x [G] with Duty cycle [TP] (mW)	Power Density [S] (mw/cm <sup>2</sup> )
RFID	915	0.61	20	7.40	2.15	1.64	1	9.01	0.002

Note:

1. Mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.
2. The Numeric Gain calculated by  $10^{(ant. Gain(dBi) / 10)}$ .
3. Each band max power which perform MPE of any configurations.
4. The device not support simultaneous transmission.