

FCC PART 15.249 TEST REPORT

For

HHC Changzhou Corp.

No. 61 Xinggang Road, Zhonglou District, Changzhou, Jiangsu, China, 213023

FCC ID: 2AEQWCH10HHC005

Report Type:		Product T	Type:		
Original Report		Remote Con	trol		
Test Engineer:	Matt Yao		Ment	tto Jas	
Report Number:	RKS16011100	1-00A			
Report Date:	2016-01-19				
Reviewed By:	Jesse Huang EMC Manager	<	fesse. H	uonf	
Test Laboratory:	Bay Area Comp Chenghu Road, No.248,Kunsha Tel: +86-0512- Fax: +86-0512- www.baclcorp.	Kunshan Dev an, Jiangsu, C 86175000 -88934268	velopment	rp. (Kunshan) Zone	CH.
				SMITTENDO .	SHITH

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Kunshan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

Report No.: RKS160111001-00A

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
Objective	
RELATED SUBMITTAL(S)/GRANT(S)	
TEST METHODOLOGY	
TEST FACILITY	3
SYSTEM TEST CONFIGURATION	4
JUSTIFICATION	4
EUT Exercise Software	
BLOCK DIAGRAM OF TEST SETUP	
SUMMARY OF TEST RESULTS	5
FCC§15.203 - ANTENNA REQUIREMENT	6
APPLICABLE STANDARD	
ANTENNA CONNECTOR CONSTRUCTION	
FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS	7
APPLICABLE STANDARD	7
MEASUREMENT UNCERTAINTY	7
EUT Setup	8
TEST EQUIPMENT SETUP	
TEST PROCEDURE	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST RESULTS SUMMARY	
TEST DATA	10
FCC§15.249(D) - OUT OF BAND EMISSION (50 DB ATTENUATION)	
APPLICABLE STANDARD	15
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	15
FCC §15.215(C) – 20 DB BANDWIDTH TESTING	17
APPLICABLE STANDARD	17
TEST PROCEDURE	17
TEST EQUIPMENT LIST AND DETAILS.	
Test Data	17
DECLADATION	20

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The HHC Changzhou Corp.'s product, model number: CH10 (FCC ID: 2AEQWCH10HHC005) (the "EUT") in this report was a Remote Control, was measured approximately: 170 mm (L) x65mm (W) x 28mm (H), Weight:150g, rated input voltage: 3*battery AAA 1.5V.

Report No.: RKS160111001-00A

Note: The series product model CH04, CH10, They have same RF module. The different is the quantity of button. CH10 has 10 buttons. CH04 has 4 buttons, so the PCB layout have some changes, but not affect RF performance, we clarify that both CH10 and CH04, the duty cycle of RF signal is the same, when press any button, the transmitted spectrum is the same, they do not affect RF spectrum.

All measurement and test data in this report was gathered from production sample serial number: 20160107002. (Assigned by BACL, Kunshan). The EUT was received on 2016-01-07.

Objective

This type approval report is prepared on behalf of HHC Changzhou Corp. in accordance with Part 2-Subpart J, and Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Related Submittal(s)/Grant(s)

N/A.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz.and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the Chenghu Road, Kunshan Development Zone No.248, Kunshan, Jiangsu, China.

Test site at Bay Area Compliance Laboratories Corp. (Kunshan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2014. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 815570. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15.249 Page 3 of 20

SYSTEM TEST CONFIGURATION

Justification


The system was configured in testing mode which was provided by manufacturer.

EUT was tested with Channel 2403MHz, 2412MHz and 2425MHz.

EUT Exercise Software

No software was used during the test.

Block Diagram of Test Setup



Report No.: RKS160111001-00A

FCC Part 15.249 Page 4 of 20

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.207(a)	Conduction Emissions	Not Applicable*
15.205, §15.209, §15.249	Radiated Emissions	Compliance
§15.249(d)	OUT OF BAND EMISSION (50 dB ATTENUATION)	Compliance
§15.215 (c)	20 dB Bandwidth	Compliance

Report No.: RKS160111001-00A

FCC Part 15.249 Page 5 of 20

^{*}Not Applicable: The EUT is battery operated equipment.

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

For intentional device, according to §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used.

Report No.: RKS160111001-00A

Antenna Connector Construction

The EUT has one integral antenna arrangement and antenna gain is 2dBi, which was permanently attached ,fulfill the requirement of this section, please refer to the EUT photos.

Result: Compliant.

FCC Part 15.249 Page 6 of 20

FCC§15.205, §15.209&§15.249- RADIATED EMISSIONS

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

Report No.: RKS160111001-00A

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit. If U_{lab} is greater than U_{cispr} of Table 1, then:
- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} U_{cispr})$, exceeds the disturbance limit;
- non compliance is deemed to occur if any measured disturbance level, increased by $(U_{\text{lab}} U_{\text{cispr}})$, exceeds the disturbance limit.

Based on CISPR 16-4-2: 2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Kunshan) is:

30M~200MHz: 5.0 dB 200M~1GHz: 6.2 dB 1G~6GHz: 4.45 dB 6G~18GHz: 5.23 dB


FCC Part 15.249 Page 7 of 20

Table 1 – Values of U_{cispr}


Measurement	$U_{ m cispr}$
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1 GHz:



Above 1 GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

FCC Part 15.249 Page 8 of 20

Test Equipment Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 CHz	1MHz	3 MHz	/	PK
Above 1 GHz	1MHz	10 Hz	/	Ave.

Report No.: RKS160111001-00A

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detection mode from 30MHz to 1GHz, Peak and average detection mode above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit –Corrected Amplitude

FCC Part 15.249 Page 9 of 20

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sonoma Instrunent	Amplifier	330	171377	2015-9-16	2016-9-16
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2015-5-20	2016-5-19
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2015-11-7	2016-11-6
ETS	Horn Antenna	3115	6229	2015-11-7	2016-11-6
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2015-11-4	2016-11-3
Mini	Pre-amplifier	ZVA-183-S+	857001418	2015-9-16	2016-9-16
R&S	Auto test Software	EMC32	V 09.10.0	-	-
BACL	RF cable	KS-LAB-012	KS-LAB-012	2015-12-16	2016-6-15

Report No.: RKS160111001-00A

Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209 &15.205 & 15.249, with the worst margin reading of:

4.44 dB at 4806 MHz in the Horizontal polarization for Low Channel

Test Data

Environmental Conditions

Temperature:	25.6°C
Relative Humidity:	52%
ATM Pressure:	101.2 kPa


The testing was performed by Matt Yao on 2016-1-19.

FCC Part 15.249 Page 10 of 20

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

30MHz-1GHz:

For CH10




Report No.: RKS160111001-00A

Frequency	R	eceiver	Turntable	Rx Antenna		Corrected	Factor Amplitude =		Part 05/209
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (cm)	Polar (H/V)	Factor (dB)	Amplitude (dBμV/m)	Limit (dB \mu V/m)	Margin (dB)
40.063750	22.22	QP	1.0	100.0	V	-10.3	11.92	40.00	28.08
54.954150	26.42	QP	300.0	100.0	V	-16.6	9.82	40.00	30.18
75.070800	27.17	QP	291.0	100.0	V	-17.1	10.07	40.00	29.93
84.666700	19.27	QP	30.0	100.0	V	-17.1	2.17	40.00	37.83
138.258850	23.02	QP	1.0	100.0	Н	-12.1	10.92	43.50	32.58
291.556250	18.45	QP	324.0	100.0	V	-10.4	8.05	46.00	37.95

FCC Part 15.249 Page 11 of 20

For CH04



Report No.: RKS160111001-00A

Frequency	R	eceiver	Turntable	Rx An	Rx Antenna Corrected Corrected Factor Amplitude FCC Part 15.249/205/209		ed Corrected 15.249 Amplitude		
(MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Degree	Height (cm)	Polar (H/V)	(uD)	Amplitude (dBμV/m)	Limit (dB \mu V/m)	Margin (dB)
31.778050	25.44	QP	164.0	100.0	V	-10.4	15.04	40.00	24.96
57.414750	26.05	QP	269.0	100.0	V	-16.6	9.45	40.00	30.55
70.032800	28.21	QP	255.0	100.0	V	-17.0	11.21	40.00	28.79
139.137200	22.06	QP	0.0	100.0	Н	-12.0	10.06	43.50	33.44
202.404350	22.94	QP	110.0	100.0	Н	-12.3	10.64	43.50	32.86
498.054000	18.39	QP	245.0	100.0	Н	-5.4	12.99	46.00	33.01

FCC Part 15.249 Page 12 of 20

1GHz-25GHz

Test Mode: Transmitting (Scan with X, Y, Z axis, the worst case is X axis)

	R	eceiver		Rx An	itenna	Correcte	Corrected		C Part /205/209
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Turntable Degree	Height (cm)	Polar (H/V)	d Factor (dB)	Amplitude (dBµV/m)	Limit (dB µ V/m)	Margin (dB)
			Low Cha	annel (2403	3 MHz)				
2403	91.45	PK	160	150	V	3.0	94.45	114	19.55
2403	84.13	Ave	160	150	V	3.0	87.13	94	6.87
2403	91.13	PK	220	200	Н	3.0	94.13	114	19.87
2403	83.42	Ave	220	200	Н	3.0	86.42	94	7.58
1289	50.62	PK	289	200	Н	-2.1	48.52	74	25.48
1289	38.34	Ave	289	200	Н	-2.1	36.24	54	17.76
2395	32.53	PK	42	200	Н	4.1	36.63	74	37.37
2395	20.81	Ave	42	200	Н	4.1	24.91	54	29.09
2400	49.36	PK	107	200	V	3.0	52.36	74	21.64
2400	35.55	Ave	107	200	V	3.0	38.55	54	15.45
4806	35.86	Ave	194	200	Н	13.7	49.56	54	4.44
4806	40.61	PK	194	200	Н	13.7	54.31	74	19.69
7209	20.84	Ave	358	200	Н	20.5	41.34	54	12.66
7209	34.85	PK	358	200	Н	20.5	55.35	74	18.65

Report No.: RKS160111001-00A

FCC Part 15.249 Page 13 of 20

_	R	eceiver		Rx Ar	ntenna	Correcte	Corrected		C Part 0/205/209
Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Turntable Degree	Height (cm)	Polar (H/V)	d Factor (dB)	Amplitude (dBμV/m)	Limit (dB µ V/m)	Margin (dB)
			Middle C	hannel (24	12MHz)				
2412	91.31	PK	210	150	V	3.0	94.31	114	19.69
2412	84.33	Ave	210	150	V	3.0	87.33	94	6.67
2412	90.24	PK	130	200	Н	3.0	93.24	114	20.76
2412	83.65	Ave	130	200	Н	3.0	86.65	94	7.35
1280	40.83	Ave	291	200	Н	-1.9	38.93	54	15.07
1280	52.46	PK	291	200	Н	-1.9	50.56	74	23.44
4824	36.11	PK	184	200	Н	13.9	50.01	74	23.99
4824	25.55	Ave	184	200	Н	13.9	39.45	54	14.55
6980	33.80	PK	57	200	V	19.8	53.60	74	20.40
6980	20.45	Ave	57	200	V	19.8	40.25	54	13.75
7236	36.20	PK	3	200	Н	20.8	57.00	74	17.00
7236	20.65	Ave	3	200	Н	20.8	41.45	54	12.55
7890	29.18	PK	227	200	Н	22.5	51.68	74	22.32
7890	15.31	Ave	227	200	Н	22.5	37.81	54	16.19
		11,0	Rx Anter		11	22.3	37.01	JT	10.17
	Re	ceiver	221					FCC	C Part 0/205/209
Frequency (MHz)	Reading (dBµV)		Turntable Degree			Correcte d Factor (dB)	Corrected Amplitude (dBµV/m)	FCC	C Part
	Reading	ceiver Detector	Turntable Degree	Rx An	Polar (H/V)	Correcte d Factor	Corrected Amplitude	FC0 15.249 Limit (dB µ	C Part 0/205/209 Margin
	Reading	ceiver Detector	Turntable Degree	Rx An	Polar (H/V)	Correcte d Factor	Corrected Amplitude	FC0 15.249 Limit (dB µ	C Part 0/205/209 Margin
(MHz)	Reading (dBμV)	Detector (PK/QP/Ave.)	Turntable Degree High Ch	Rx Ar Height (cm) annel (242	Polar (H/V)	Correcte d Factor (dB)	Corrected Amplitude (dBµV/m)	FCC 15.249 Limit (dB µ V/m)	C Part //205/209 Margin (dB)
(MHz)	Reading (dBμV)	Detector (PK/QP/Ave.)	Turntable Degree High Ch	Rx An Height (cm) annel (242	Polar (H/V) 5MHz)	Correcte d Factor (dB)	Corrected Amplitude (dBµV/m)	FCC 15.249 Limit (dB µ V/m)	C Part (/205/209 Margin (dB)
(MHz) 2425 2425	Reading (dBμV) 91.54 84.12	Detector (PK/QP/Ave.) PK Ave	Turntable Degree High Ch 62 62	Rx Ar Height (cm) annel (242 150 150	Polar (H/V) 5MHz) V	Correcte d Factor (dB) 3.0 3.0	Corrected Amplitude (dBµV/m) 94.54 87.12	FCC 15.249 Limit (dB µ V/m)	Margin (dB) 19.46 6.88
2425 2425 2425 2425	Reading (dBμV) 91.54 84.12 91.31	Detector (PK/QP/Ave.) PK Ave PK	Turntable Degree High Ch 62 62 230	Rx An Height (cm) annel (242 150 150 200	Polar (H/V) 5MHz) V V H	3.0 3.0 3.0	Corrected Amplitude (dBµV/m) 94.54 87.12 94.31	FCC 15.249 Limit (dB µ V/m)	Margin (dB) 19.46 6.88 19.69
2425 2425 2425 2425 2425	Reading (dBμV) 91.54 84.12 91.31 83.55	Detector (PK/QP/Ave.) PK Ave PK Ave	Turntable Degree High Ch 62 62 230 230	Rx Ar Height (cm) annel (242 150 150 200 200	Polar (H/V) 5MHz) V V H H	3.0 3.0 3.0 3.0 3.0	Corrected Amplitude (dBμV/m) 94.54 87.12 94.31 86.55	FCC 15.249 Limit (dB µ V/m) 114 94 114 94	Margin (dB) 19.46 6.88 19.69 7.45
2425 2425 2425 2425 2425 2483.5	Reading (dBμV) 91.54 84.12 91.31 83.55 44.01	PK Ave PK Ave PK Ave PK	Turntable Degree High Ch 62 62 230 230 67	Rx Ar Height (cm) annel (242 150 150 200 200 249	Polar (H/V) 5MHz) V V H H	3.0 3.0 3.0 3.0 4.2	Corrected Amplitude (dBμV/m) 94.54 87.12 94.31 86.55 48.21	FCC 15.249 Limit (dB µ V/m) 114 94 114 94 74	Margin (dB) 19.46 6.88 19.69 7.45 25.79
2425 2425 2425 2425 2425 2483.5 2483.5	Reading (dBμV) 91.54 84.12 91.31 83.55 44.01 31.47	PK Ave PK Ave PK Ave PK Ave	High Ch 62 62 230 230 67 67	Rx Ar Height (cm) annel (242 150 150 200 200 249 249	Polar (H/V) 5MHz) V H H H	3.0 3.0 3.0 3.0 4.2 4.2	Corrected Amplitude (dBμV/m) 94.54 87.12 94.31 86.55 48.21 35.67	FCC 15.249 Limit (dB µ V/m) 114 94 114 94 74 54	Margin (dB) 19.46 6.88 19.69 7.45 25.79 18.33
2425 2425 2425 2425 2425 2483.5 2483.5 4850	Reading (dBμV) 91.54 84.12 91.31 83.55 44.01 31.47 26.93	PK Ave PK Ave PK Ave Ave Ave Ave Ave Ave	Turntable Degree High Ch 62 62 230 230 67 67 183	Rx Ar Height (cm) annel (242 150 150 200 200 249 249 249 200	Polar (H/V) 5MHz) V V H H H H	3.0 3.0 3.0 3.0 4.2 4.2 14.1	Corrected Amplitude (dBμV/m) 94.54 87.12 94.31 86.55 48.21 35.67 41.03	FCC 15.249 Limit (dB µ V/m) 114 94 114 94 74 54	Margin (dB) 19.46 6.88 19.69 7.45 25.79 18.33 12.97
2425 2425 2425 2425 2425 2483.5 2483.5 4850 4850	Reading (dBμV) 91.54 84.12 91.31 83.55 44.01 31.47 26.93 40.29	PK Ave PK Ave PK Ave PK Ave PK Ave PK Ave	High Ch 62 62 230 230 67 67 183 183	Rx Ar Height (cm) annel (242 150 150 200 249 249 200 249 200 200	Polar (H/V) 5MHz) V H H H H	3.0 3.0 3.0 3.0 4.2 4.2 14.1 14.1	Corrected Amplitude (dBμV/m) 94.54 87.12 94.31 86.55 48.21 35.67 41.03 54.39	FCC 15.249 Limit (dB µ V/m) 114 94 114 94 74 54 54	19.46 6.88 19.69 7.45 25.79 18.33 12.97 19.61
2425 2425 2425 2425 2425 2483.5 2483.5 4850 4850 6965	Reading (dBμV) 91.54 84.12 91.31 83.55 44.01 31.47 26.93 40.29 33.80	PK Ave	Turntable Degree High Ch 62 62 230 230 67 67 183 183 57	Rx Ar Height (cm) annel (242 150 150 200 249 249 249 200 200 200	Polar (H/V) 5MHz) V H H H H H V	3.0 3.0 3.0 3.0 4.2 4.2 14.1 19.8	Corrected Amplitude (dBμV/m) 94.54 87.12 94.31 86.55 48.21 35.67 41.03 54.39 53.60	FCC 15.249 Limit (dB µ V/m) 114 94 114 94 74 54 74 74	Margin (dB) 19.46 6.88 19.69 7.45 25.79 18.33 12.97 19.61 20.40
2425 2425 2425 2425 2425 2483.5 2483.5 4850 4850 6965 6965	Reading (dBμV) 91.54 84.12 91.31 83.55 44.01 31.47 26.93 40.29 33.80 20.45	PK Ave PK Ave PK Ave PK Ave Ave Ave Ave Ave Ave Ave Ave Ave	Turntable Degree High Ch 62 62 230 230 67 67 183 183 57	Rx Ar Height (cm) annel (242 150 150 200 249 249 200 200 200 200 20	Polar (H/V) 5MHz) V H H H H V V	3.0 3.0 3.0 3.0 4.2 4.2 14.1 19.8 19.8	Corrected Amplitude (dBμV/m) 94.54 87.12 94.31 86.55 48.21 35.67 41.03 54.39 53.60 40.25	FCC 15.249 Limit (dB µ V/m) 114 94 114 94 74 54 54 74 54	Margin (dB) 19.46 6.88 19.69 7.45 25.79 18.33 12.97 19.61 20.40 13.75
2425 2425 2425 2425 2425 2483.5 2483.5 4850 4850 6965 6965 7275	Reading (dBμV) 91.54 84.12 91.31 83.55 44.01 31.47 26.93 40.29 33.80 20.45 20.22	PK Ave PK Ave PK Ave PK Ave	Turntable Degree High Ch 62 62 230 230 67 67 183 183 57 57 0.0	Rx Ar Height (cm) annel (242 150 150 200 249 249 249 200 200 200 20	Polar (H/V) 5MHz) V H H H H V V V	3.0 3.0 3.0 3.0 4.2 4.2 14.1 19.8 19.8 20.8	Corrected Amplitude (dBμV/m) 94.54 87.12 94.31 86.55 48.21 35.67 41.03 54.39 53.60 40.25 41.02	FCC 15.249 Limit (dB µ V/m) 114 94 114 94 54 54 74 54 54 54	19.46 6.88 19.69 7.45 25.79 18.33 12.97 19.61 20.40 13.75 12.98

Report No.: RKS160111001-00A

FCC Part 15.249 Page 14 of 20

FCC § 15.249(d) - OUT OF BAND EMISSION (50 dB ATTENUATION)

Applicable Standard

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation

Report No.: RKS160111001-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2015-11-4	2016-11-3
Dressler	Attenuator	ATT 6/75	510020010004	2015-11-12	2016-11-12

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.6°C
Relative Humidity:	51 %
ATM Pressure:	101.2kPa

^{*} The testing was performed by Matt Yao on 2016-1-18.


Test Result: Compliant.

Please refer to following plots


FCC Part 15.249 Page 15 of 20

Band Edge, Left Side

Report No.: RKS160111001-00A



Band Edge, Right Side



Note: The band emission compliant with the general radiated emission limits in § 15.209. Please refer to radiated emissions test section.

FCC Part 15.249 Page 16 of 20

FCC §15.215(c) – 20 dB BANDWIDTH TESTING

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Report No.: RKS160111001-00A

Test Procedure

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT on the test table without connection to measurement instrument. Turn on the EUT. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- 3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- 4. Repeat above procedures until all frequencies measured were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	100048	2015-11-4	2016-11-3
Dressler	Attenuator	ATT 6/75	510020010004	2015-11-12	2016-11-12

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25.6°C
Relative Humidity:	51 %
ATM Pressure:	101.2kPa

^{*} The testing was performed by Matt Yao on 2016-1-18.

Test Result: Compliant.

Please refer to following tables and plots


FCC Part 15.249 Page 17 of 20

Test Mode: Transmitting

Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
Low	2403	2.2004
Middle	2412	2.3086
High	2425	2.2545

Report No.: RKS160111001-00A


Low Channel




FCC Part 15.249 Page 18 of 20

Middle Channel

Report No.: RKS160111001-00A



High Channel



FCC Part 15.249 Page 19 of 20

DECLARATION

DECLARATION

Date:2016-1-14

Report No.: RKS160111001-00A

To:

Bay Area Compliance Laboratories Corp. (Kunshan)
No.248 Chenghu Road Kunshan, Jiangsu, China
http://www.baclcorp.com

Dear Sir or Madam:

We, (company name: HHC Changzhou Corp.) hereby declare that product: Remote Control, model: CH10, serial model: CH04, which has been tested by BACL.

CH10 and CH04 have same RF module. The different is the quantity of button. CH10 has 10 buttons. CH04 has 4 buttons ,so the PCB layout have some changes ,but not affect RF performance ,we clarify that both CH10 and CH04 ,the duty cycle of RF signal is the same ,when press any button ,the transmitted spectrum is the same ,they do not affect RF spectrum.

Please contact me if there is need for any additional clarification or information.

Best Regards

Signature:

Printed name: Jack Chen Jack Chen

Title: Project Manager

***** END OF REPORT *****

FCC Part 15.249 Page 20 of 20