

# FCC PART 15.247 TEST REPORT

For

# ShenZhen HongFa Technology Co., Ltd.

319# Building, King Design Industrial Park, NanShan Avenue, NanShan District, Shenzhen China

FCC ID: 2AEUUMBH530 Trade Name: MAGNAVOX

Report Type: **Product Name:** Original Report Bluetooth Earphone Lorin Dian **Test Engineer:** Lorin Bian Report Number: RDG170328003B **Report Date:** 2017-04-18 **Henry Ding** Henry Ding **EMC Leader** Reviewed By: Bay Area Compliance Laboratories Corp. (Chengdu) **Test Laboratory:** No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

# **TABLE OF CONTENTS**

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
OBJECTIVE	
RELATED SUBMITTAL(S)/GRANT(S)	
MEASUREMENT UNCERTAINTY	
TEST FACILITY	
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	
EUT EXERCISE SOFTWARE	
SUPPORT EQUIPMENT LIST AND DETAILSEXTERNAL CABLE	
BLOCK DIAGRAM OF TEST SETUP	 8
SUMMARY OF TEST RESULTS	
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	
APPLICABLE STANDARD	
FCC §15.203 - ANTENNA REQUIREMENT	
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	
EMI Test Receiver Setup	
Test Procedure	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST RESULTS SUMMARYTEST DATA	
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	
APPLICABLE STANDARD	
EUT SETUP	
EMI Test Receiver & Spectrum Analyzer Setup	19
Test Procedure	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	22
APPLICABLE STANDARD	
TEST PROCEDURE	22
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	
Report No.: RDG170328003B	Page 2 of 32

# Bay Area Compliance Laboratories Corp. (Chengdu)

APPLICABLE STANDARD	25
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	25
TEST DATA	
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	28
APPLICABLE STANDARD	28
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	
FCC §15.247(e) - POWER SPECTRAL DENSITY	30
APPLICABLE STANDARD	30
Test Procedure	
TEST EQUIPMENT LIST AND DETAILS	
TEST DATA	30

#### **GENERAL INFORMATION**

#### **Product Description for Equipment under Test (EUT)**

The **ShenZhen HongFa Technology Co., Ltd.**'s product, model number: **MBH530** (**FCC ID: 2AEUUMBH530**) or (the "EUT") in this report was a **Bluetooth Earphone**, which was measured approximately: 2.6 cm (L) x 1.7 cm (W) x 2.4 cxm (H), rated input voltage: DC3.7V from battery or DC 5V charged from USB Port.

Note: The series product, model MBH530 and BH41 are electrically identical, the difference between them is the model name, we selected MBH530 for fully testing, the details was explained in the declaration letter.

\*All measurement and test data in this report was gathered from final production sample, serial number: 170328003 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-03-28, and EUT conformed to test requirement.

### **Objective**

This report is prepared on behalf of **ShenZhen HongFa Technology Co., Ltd.** in accordance with Part 2, Subpart J, Part 15, Subparts A and C of the Federal Communications Commission's rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.209 and 15.247 rules.

#### Related Submittal(s)/Grant(s)

FCC Part 15C DSS submissions with FCC ID: 2AEUUMBH530. Part of system submissions with FCC ID: 2AEUUMBH530R.

#### **Test Methodology**

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Chengdu). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Report No.: RDG170328003B Page 4 of 32

#### **Measurement Uncertainty**

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.62dB
Unwanted Emissions, radiated	30M~200MHz: 4.7 dB for Horizontal, 4.7 dB for Vertical 200M~1GHz:6.0 dB for Horizontal, 6.0 for Vertical 1G~6GHz: 5.13 dB, 6G~18GHz: 5.47 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.17 dB (150 kHz to 30 MHz)

## **Test Facility**

The test site used by BACL to collect test data is located in the No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Report No.: RDG170328003B Page 5 of 32

# **SYSTEM TEST CONFIGURATION**

# **Description of Test Configuration**

The system was configured for testing in testing mode, which was provided by manufacturer.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404		
		38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

# **Equipment Modifications**

No modification was made to the EUT tested.

## **EUT Exercise Software**


The software "ACTsBTAPP" was used during testing, the system configured maxmum output power as default setting.

The duty cycle as below:

Test mode	T <sub>on</sub>	T <sub>on+off</sub>	Duty Cycle
	(ms)	(ms)	(%)
BLE	100	100	100

Report No.: RDG170328003B Page 6 of 32

# Bay Area Compliance Laboratories Corp. (Chengdu)



Date: 15.APR.2017 01:45:34

# **Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
Huntkey	Adapter	HKA01105021	0D1603003303

# **External Cable**

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	То
USB Cable	NO	NO	0.8	Adapter	Base

Report No.: RDG170328003B Page 7 of 32

# **Block Diagram of Test Setup**



Report No.: RDG170328003B Page 8 of 32

# SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum conducted output power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Report No.: RDG170328003B Page 9 of 32

# FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

# **Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

- mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where
  - f(GHz) is the RF channel transmit frequency in GHz
  - Power and distance are rounded to the nearest mW and mm before calculation
  - The result is rounded to one decimal place for comparison
  - 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

#### **Measurement Result**

The max conducted power including tune-up tolerance is -3.0 dBm (0.5 mW). [(max. power of channel, mW)/(min. test separation distance, mm)][ $\sqrt{f(GHz)}$ ] = 0.5/5\*( $\sqrt{2.480}$ ) = 0.2< 3.0

So the stand-alone SAR evaluation is not necessary.

Report No.: RDG170328003B Page 10 of 32

# FCC §15.203 - ANTENNA REQUIREMENT

# **Applicable Standard**

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

#### **Antenna Connector Construction**

The EUT has one internal antenna arrangement for BT, and the antenna gain is 0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

Report No.: RDG170328003B Page 11 of 32

# FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

## **Applicable Standard**

FCC§15.207(a)

## **Measurement Uncertainty**

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 1, then:

- -compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

- If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 1, then:


  -compliance is deemed to occur if no measured disturbance level, increased by ( $U_{lab} U_{cispr}$ ), exceeds the disturbance limit:
- -non compliance is deemed to occur if any measured disturbance level, increased by ( $U_{lab}$  - $U_{\text{cispr}}$ ), exceeds the disturbance limit.

Based on CISPR 16-4-2:2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Chengdu) is ±3.17 dB (150 kHz to 30 MHz).

Table 1 – Values of  $U_{cispr}$ 

Measurement		$U_{cispr}$
Conducted disturbance at mains port using AMN	(150 kHz to 30 MHz)	3.4 dB

## **EUT Setup**



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

Report No.: RDG170328003B Page 12 of 32 The setup of EUT was according to ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The power cables and external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to an AC120V/60Hz power source.

#### **EMI Test Receiver Setup**

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

#### **Test Procedure**

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

### **Corrected Amplitude & Margin Calculation**

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

Herein,s

V<sub>C</sub>: corrected voltage amplitude V<sub>R</sub>: reading voltage amplitude A<sub>c</sub>: attenuation caused by cable loss

VDF: voltage division factor of AMN or ISN

The "**Margin**" column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

# **Test Equipment List and Details**

Manufacturer	Description	Model Number	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	100018	2016-12-02	2017-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	DE14781	2016-10-31	2017-10-30
N/A	Conducted Cable	NO.5	N/A	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

<sup>\*</sup> **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

# **Test Results Summary**

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

#### **Test Data**

#### **Environmental Conditions**


Temperature:	20.8 °C
Relative Humidity:	56 %
ATM Pressure:	96.2 kPa

The testing was performed by Lorin Bian on 2017-04-11.

Report No.: RDG170328003B Page 14 of 32

Test Mode: Transmitting

# AC120V/60Hz, Line




Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.163741	41.4	9.000	L1	19.7	23.9	65.3	Compliance
0.238124	40.2	9.000	L1	19.7	22.0	62.2	Compliance
0.558572	37.5	9.000	L1	19.7	18.5	56.0	Compliance
0.681699	31.8	9.000	L1	19.7	24.2	56.0	Compliance
1.171949	31.4	9.000	L1	19.7	24.6	56.0	Compliance
1.548915	30.6	9.000	L1	19.7	25.4	56.0	Compliance

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.236234	26.1	9.000	L1	19.7	26.1	52.2	Compliance
0.563041	26.8	9.000	L1	19.7	19.2	46.0	Compliance
0.703777	22.0	9.000	L1	19.7	24.0	46.0	Compliance
1.239175	26.5	9.000	L1	19.7	19.5	46.0	Compliance
1.289541	26.9	9.000	L1	19.7	19.1	46.0	Compliance
9.604822	21.2	9.000	L1	19.9	28.8	50.0	Compliance

Report No.: RDG170328003B Page 15 of 32

# AC120V/60Hz, Neutral



Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.154858	43.2	9.000	N	19.7	22.5	65.7	Compliance
0.240029	42.4	9.000	N	19.6	19.7	62.1	Compliance
0.563041	40.1	9.000	N	19.6	15.9	56.0	Compliance
0.676289	32.7	9.000	N	19.6	23.3	56.0	Compliance
1.289541	34.9	9.000	N	19.6	21.1	56.0	Compliance
1.586387	29.8	9.000	N	19.7	26.2	56.0	Compliance

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)	Comment
0.238124	28.3	9.000	N	19.6	23.9	52.2	Compliance
0.399703	24.2	9.000	N	19.6	23.7	47.9	Compliance
0.558572	31.6	9.000	N	19.6	14.4	46.0	Compliance
0.660314	24.0	9.000	N	19.6	22.0	46.0	Compliance
1.239175	28.8	9.000	N	19.6	17.2	46.0	Compliance
1.289541	28.3	9.000	N	19.6	17.7	46.0	Compliance

Report No.: RDG170328003B Page 16 of 32

# FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

#### **Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

## **Measurement Uncertainty**

Compliance or non- compliance with a disturbance limit shall be determined in the following manner:

If  $U_{lab}$  is less than or equal to  $U_{cispr}$  of Table 2, then:

- -compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.
- If  $U_{lab}$  is greater than  $U_{cispr}$  of Table 2, then:
- –compliance is deemed to occur if no measured disturbance level, increased by  $(U_{lab} U_{cispr})$ , exceeds the disturbance limit;
- -non compliance is deemed to occur if any measured disturbance level, increased by ( $U_{lab} U_{cisor}$ ), exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Chengdu) is:

30M~200MHz: ±4.7 dB; 200M~1GHz: ±6.0 dB; 1G~6GHz: ±5.13 dB; 6G~25GHz: ±5.47 dB;


Table 2 – Values of  $U_{cisor}$ 

Measurement					
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB				
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB				
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB				


Report No.: RDG170328003B Page 17 of 32

## **EUT Setup**

#### **Below 1GHz:**



#### **Above 1GHz:**



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

Report No.: RDG170328003B Page 18 of 32

#### **EMI Test Receiver & Spectrum Analyzer Setup**

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Detector	RBW	Video B/W	IF B/W	
QP	120 kHz	300 kHz	120kHz	

#### 1GHz-25GHz:

Detector	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Avo	>98%	1MHz	10 Hz
Ave.	<98%	1MHz	1/T

Note: T is minimum transmission duration

#### **Test Procedure**

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

#### **Corrected Amplitude & Margin Calculation**

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Loss + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit –Corrected Amplitude

Report No.: RDG170328003B Page 19 of 32

## **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726- 0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	N/A	2015-04-24	2018-04-23
N/A	RF Cable (below 1GHz)	NO.1	N/A	2016-11-10	2017-11-09
N/A	RF Cable (below 1GHz)	NO.4	N/A	2016-11-10	2017-11-09
N/A	RF Cable (above 1GHz)	NO.2	N/A	2016-11-10	2017-11-09

<sup>\*</sup> **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

# **Test Results Summary**

According to the recorded data in following table, the EUT complied with the <u>FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247</u>.

#### **Test Data**

#### **Environmental Conditions**

Temperature:	20.1 °C
Relative Humidity:	58 %
ATM Pressure:	96.3 kPa

<sup>\*</sup> The testing was performed by Lorin Bian on 2017-04-13.

Test Mode: Transmitting

Report No.: RDG170328003B Page 20 of 32

# 30MHz-25GHz:

_	Rec	eiver	Rx A	ntenna	Cable	Amplifier	Corrected		
Frequency (MHz)	Reading (dBµV)	Detector	Polar (H/V)	Factor (dB)	loss (dB)	Gain (dB)	Amplitude (dBµV/m)	Limit (dBµV/m)	Margin (dB)
				ow Chann					
2402	63.5	PK	Н	23.53	3.00	0.00	90.03	N/A	N/A
2402	62.69	AV	Н	23.53	3.00	0.00	89.22	N/A	N/A
2402	54.08	PK	V	23.53	3.00	0.00	80.61	N/A	N/A
2402	52.96	AV	V	23.53	3.00	0.00	79.49	N/A	N/A
2390	30.81	PK	Н	23.57	3.00	0.00	57.38	74.00	16.62
2390	16.09	AV	Н	23.57	3.00	0.00	42.66	54.00	11.34
4804	37.07	PK	Н	30.77	5.12	26.87	46.09	74.00	27.91
4804	24.89	AV	Н	30.77	5.12	26.87	33.91	54.00	20.09
7206	34.59	PK	Н	34.71	6.16	26.35	49.11	74.00	24.89
7206	20.97	AV	Н	34.71	6.16	26.35	35.49	54.00	18.51
9608	35.14	PK	Н	37.06	7.82	26.18	53.84	74.00	20.16
9608	22.19	AV	Н	37.06	7.82	26.18	40.89	54.00	13.11
2949	38.92	PK	Н	24.10	3.39	26.46	39.95	74.00	34.05
2949	25.55	AV	Н	24.10	3.39	26.46	26.58	54.00	27.42
79.47	41.2	QP	Н	8.05	0.45	28.40	21.30	40.00	18.70
99.84	40.5	QP	Н	10.71	0.51	28.31	23.41	43.50	20.09
				ddle Chan					
2440	60.87	PK	Н	23.40	3.00	0.00	87.27	N/A	N/A
2440	60.13	AV	Н	23.40	3.00	0.00	86.53	N/A	N/A
2440	49.18	PK	V	23.40	3.00	0.00	75.58	N/A	N/A
2440	47.67	AV	V	23.40	3.00	0.00	74.07	N/A	N/A
4880	36.65	PK	Н	31.02	5.09	26.87	45.89	74.00	28.11
4880	24.25	AV	Н	31.02	5.09	26.87	33.49	54.00	20.51
7320	34.01	PK	Н	34.94	6.22	26.40	48.77	74.00	25.23
7320	20.73	AV	Н	34.94	6.22	26.40	35.49	54.00	18.51
9760	35.92	PK	Н	37.16	7.71	26.27	54.52	74.00	19.48
9760	24.17	AV	Н	37.16	7.71	26.27	42.77	54.00	11.23
3254	39.84	PK	Н	25.62	3.81	26.50	42.77	74.00	31.23
3254	27.36	AV	Н	25.62	3.81	26.50	30.29	54.00	23.71
2795	37.2	PK	Н	23.79	3.25	26.61	37.63	74.00	36.37
2795	24.16	AV	Н	23.79	3.25	26.61	24.59	54.00	29.41
79.47	41.2	QP	Н	8.05	0.45	28.40	21.30	40.00	18.70
99.84	40.6	QP	Н	10.71	0.51	28.31	23.51	43.50	19.99
			Hi	gh Chanr	el: 2480	MHz			
2480	59.34	PK	Н	23.27	2.99	0.00	85.60	N/A	N/A
2480	58.18	AV	Н	23.27	2.99	0.00	84.44	N/A	N/A
2480	48.92	PK	V	23.27	2.99	0.00	75.18	N/A	N/A
2480	48.43	AV	V	23.27	2.99	0.00	74.69	N/A	N/A
2483.5	31.62	PK	Н	23.26	2.99	0.00	57.87	74.00	16.13
2483.5	16.88	AV	Н	23.26	2.99	0.00	43.13	54.00	10.87
4960	36.36	PK	Н	31.27	5.05	26.88	45.80	74.00	28.20
4960	24.8	AV	Н	31.27	5.05	26.88	34.24	54.00	19.76
7440	34.13	PK	Н	35.18	6.27	26.45	49.13	74.00	24.87
7440	21.62	AV	Н	35.18	6.27	26.45	36.62	54.00	17.38
9920	35.97	PK	Н	37.25	7.60	26.37	54.45	74.00	19.55
9920	23.15	AV	Н	37.25	7.60	26.37	41.63	54.00	12.37
2972	37.73	PK	Н	24.14	3.41	26.44	38.84	74.00	35.16
2972	25.12	AV	Н	24.14	3.41	26.44	26.23	54.00	27.77
79.47	41.3	QP	Н	8.05	0.45	28.40	21.40	40.00	18.60
99.84	40.5	QP	Н	10.71	0.51	28.31	23.41	43.50	20.09

Report No.: RDG170328003B Page 21 of 32


# FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH

#### **Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

#### **Test Procedure**

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) ≥ 3×RBW
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



## **Test Equipment List and Details**

Manufacturer	Description Model		Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	1

<sup>\*</sup> Statement of Traceability: BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

Temperature:	20.3 °C
Relative Humidity:	48 %
ATM Pressure:	95.8 kPa

<sup>\*</sup> The testing was performed by Lorin Bian on 2017-04-15.

Report No.: RDG170328003B Page 22 of 32


# Bay Area Compliance Laboratories Corp. (Chengdu)

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
Low	2402	0.52	≥0.5
Middle	2440	0.52	≥0.5
High	2480	0.51	≥0.5

# **Low Channel**




Date: 15.APR.2017 01:36:18

#### **Middle Channel**



Date: 15.APR.2017 01:42:31

## **High Channel**



Date: 15.APR.2017 01:43:28


# FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

# **Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

#### **Test Procedure**

- a) Set the RBW ≥ DTS bandwidth.
- b) Set VBW ≥ 3 RBW.
- c) Set span ≥ 3 x RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.



#### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	1

<sup>\*</sup> Statement of Traceability: BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Report No.: RDG170328003B Page 25 of 32

#### **Test Data**

#### **Environmental Conditions**

Temperature:	20.3 °C	
Relative Humidity:	48 %	
ATM Pressure:	95.8 kPa	


<sup>\*</sup> The testing was performed by Lorin Bian on 2017-04-15.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Limit (dBm)
Low	2402	-3.83	30
Middle	2440	-4.65	30
High	2480	-5.66	30


## **Low Channel**



Date: 15.APR.2017 01:36:40

# Bay Area Compliance Laboratories Corp. (Chengdu)

#### **Middle Channel**



Date: 15.APR.2017 01:42:52

## **High Channel**



Date: 15.APR.2017 01:43:48

# FCC §15.247(d) - 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

#### **Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- 5. Repeat above procedures until all measured frequencies were complete.

#### **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	/

<sup>\*</sup> Statement of Traceability: BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

Temperature:	20.3 °C	
Relative Humidity:	48 %	
ATM Pressure:	95.8 kPa	


<sup>\*</sup> The testing was performed by Lorin Bian on 2017-04-15.

Report No.: RDG170328003B Page 28 of 32

Test mode: Transmitting


Test Result: Compliant. Please refer to following plots.

# **BLE Band Edge, Left Side**



Date: 15.APR.2017 01:37:02

# **BLE Band Edge, Right Side**



Date: 15.APR.2017 01:44:22

Report No.: RDG170328003B Page 29 of 32

# FCC §15.247(e) - POWER SPECTRAL DENSITY

# **Applicable Standard**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

#### **Test Procedure**

- 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- 2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- 3. set the RBW = 3 kHz, VBW = 10 kHz, Set the span to 1.5 times the DTS channel bandwidth.
- 4. Use the peak marker function to determine the maximum power level in any 3 kHz band segment within the fundamental EBW.

## **Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
N/A	RF Cable	N/A	N/A	Each Time	1

<sup>\*</sup> **Statement of Traceability:** BACL (Chengdu) attested that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

#### **Test Data**

#### **Environmental Conditions**

Temperature:	20.3 °C	
Relative Humidity:	48 %	
ATM Pressure:	95.8 kPa	

<sup>\*</sup> The testing was performed by Lorin Bian on 2017-04-15.

Report No.: RDG170328003B Page 30 of 32


# Bay Area Compliance Laboratories Corp. (Chengdu)

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
Low	2402	-14.18	≤8
Middle	2440	-15.07	≤8
High	2480	-16	≤8


#### **Low Channel**



Date: 15.APR.2017 01:36:46


# Bay Area Compliance Laboratories Corp. (Chengdu)

#### **Middle Channel**



Date: 15.APR.2017 01:42:58

## **High Channel**



Date: 15.APR.2017 01:43:55

\*\*\*\*\* END OF REPORT \*\*\*\*\*

Report No.: RDG170328003B Page 32 of 32