

Evaluation Report: 2016-MODC-CDTLE:20150708_1_MPE_0001_V1.0					
Evaluation report for:	CDTLE:20150708_1				
	MOD.01				
FCC ID:	2AEV4-01				
Client Name:	ModCam AB				
Client address	Bredgatan 4				
	211 30 Malmö, Sweden				
According to:	FCC 47 CFR §2.1091				
Report Issued By:	Niall Forrester / Technical Manager				
Issue Date:	2016-04-13				
On Behalf of:	CDTL Europe, Tech Mahindra Ltd.				
Lab Address	4th Floor, Mobilvägen 10				
	SE-22362 Lund, Sweden				
	Tel: 46 46 272 5746				
	Org. Nr. 516405-4115				
Authorised By:	Håkan Sjöberg (Lab Manager)				
Review Date:	2016-04-13				

No part of this report may be quoted out of context, reproduced or transmitted partially, in any form or by any means, except in full, without the previous written permission of Tech Mahindra (CDTL Europe).

This test report includes no annexes. The total number of pages is 7



Public

RF Exposure Information - MPE Calculations

CDTLE:20150708_1_MPE_0001_V1.0

CONTENTS

1.	GENERAL CONDITIONS	.3
2.	APPLICANT DETAILS	.3
3.	DETAILS OF DEVICE	.4
4.	EVALUATION	.5
5.	DETAILED MPE CALCULATIONS	.6
6.	AMENDMENT HISTORY	.7



CDTLE:20150708_1_MPE_0001_V1.0

1. GENERAL CONDITIONS

- 1. This report refers only to the item or items that have undergone the evaluation (see section 3. "Details of Device").
- 2. This document supersedes all previous versions of the report. For details, please refer to "Amendment History"
- 3. This report does not constitute or imply on its own an approval of the device by the Certification Bodies or competent Authorities.
- 4. This document is only valid if complete; no partial reproduction can be made without previous written permission of Lab.
- 5. This report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of the Lab, and the relevant Accreditation Bodies.
- 6. The evaluation summarised in this report was <u>not</u> performed as part of the accredited scope of the CDTL Europe lab.

2. APPLICANT DETAILS

Table 1 Applicant Details						
Company Name	ModCam AB					
Address:	Bredgatan 4					
	211 30 Malmö					
	Sweden					
e-mail	contact@modcam.com					
Telephone:	-					
Contact Name	Bogdan Tudosoiu					
e-mail	bogdan@modcam.com					
Telephone:	-					



CDTLE:20150708_1_MPE_0001_V1.0

3. DETAILS OF DEVICE

The device is an IP Camera supporting Bluetooth and Wireless LAN technologies. Since the device only carries a single antenna for both WiFi and Bluetooth, simultaneous transmission is not possible.

Table 3.1 Details of device					
Description of device: IP Camera					
Manufacturer:	ModCam AB				
Model Name:	MOD.01				
FCC ID	2AEV4-01				
Hardware Version	2.0				

Table 3.2 Wireless Technologies and Frequency Bands supported by the DUT								
Technology	Band	Frequency Range (Tx)	Power Class	Modulations	Evaluation Performed			
Bluetooth BDR/EDR/BLE	2.4 GHz	2402 MHz – 2480 MHz	1	GFSK	YES			
WLAN 802.11 b/g/n	2.4 GHz	2412 MHz – 2462 MHz	N/A	OFDM, DSS	YES			
WLAN 802.11 a/n	5 GHz	5150 MHz – 5725 MHz	N/A	BPSK, QPSK, 16QAM, 64QAM	YES			
GPS/GLONASS	N/A	N/A (Receive Only)	N/A	N/A	NO (Receive Only)			

Table 3.3 DUT Transmitter Characteristics							
Technology Band Max. Avg. Output Power* Antenna Gain							
Bluetooth BDR/EDR/BLE	2.4 GHz	9.0 dBm	0.1 dBi				
WLAN 802.11 b/g/n	2.4 GHz	17.5 dBm	0.1 dBi				
WLAN 802.11 a/n	5 GHz	14.5 dBm	1.3 dBi				

^{*}These figures represent the maximum average conducted output power attainable by the device type, including manufacturing tolerances. They are based on the manufacturer's own data.



CDTLE:20150708_1_MPE_0001_V1.0

4. EVALUATION

4.1 SUMMARY

At 20cm, the device is compliant with the "General Population / Uncontrolled" requirements set out in FCC 47 CFR §1.1310 Table 1 (B) for all wireless technologies supported by the device.

See chapter 5 for further details of the tests.

4.2 APPLICABLE STANDARDS

- FCC 47 CFR §2.1091
- FCC 47 CFR §1.1307
- FCC 47 CFR §1.1310
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- IEEE C95.1-2005



CDTLE:20150708_1_MPE_0001_V1.0

5. DETAILED MPE CALCULATIONS

The Power Density at 20cm separation distance has been calculated for each of the transmitter technologies supported by the device according to a re-arrangement of the Friis formula, as below:

 $S = \frac{P * G}{4\pi * r^2}$

Where:

"S" is power density in mW/cm²

"P" is maximum avg. conducted power (incl. tolerances) in mW according to data from the manufacturer

"G" is the peak antenna gain (numerical) according to data from the manufacturer

"r" is the separation distance (20 cm)

Since the device is not capable of simultaneous transmissions for any of these technologies, each technology has been evaluated individually.

MPE Calculations for Mobile Equipment General population/ Uncontrolled use								
Technology	Frequency Range (MHz)	[P] (dBm)	P (mW)	[G] (dBi)	G (Numerical)	r (cm)	S (mW/cm²)	Limit* (mW/cm²)
Bluetooth BDR/EDR/BLE	2402 - 2480	9.0	7.94	0.1	1.02	20	0.0016	1.0
WLAN 802.11b/g/n	2412 - 2472	17.5	56.23	0.1	1.02	20	0.0114	1.0
WLAN 802.11a/n	5150 - 5725	14.5	28.18	1.3	1.35	20	0.0076	1.0

^{*}The limits listed are from FCC 47 CFR §1.1310 Table 1 (B): "Limits for General Population/Uncontrolled"



CDTLE:20150708_1_MPE_0001_V1.0

6. AMENDMENT HISTORY

Version	Date	Author(s)/ Function	Reviewed by	Approved by	Nature of Changes
Initial Draft	2016-04-13	Niall Forrester			
1.0	2016-04-13	Niall Forrester	Kaushlendra Tripathi	Håkan Sjöberg	First release

