

TEST REPORT

Test Report No.: UL-RPT-RP10874323JD05C V2.0

Manufacturer : ModCam AB

Model No. : MOD.01

FCC ID : 2AEV4-01

Technology : Bluetooth – Low Energy

Test Standard(s) : FCC Parts 15.207, 15.209(a) & 15.247

1. This test report shall not be reproduced in full or partial, without the written approval of UL VS LTD.

- 2. The results in this report apply only to the sample(s) tested.
- 3. The sample tested is in compliance with the above standard(s).
- 4. The test results in this report are traceable to the national or international standards.

5. Version 2.0 supersedes all previous versions.

Date of Issue: 30 September 2015

Checked by:

Sarah Williams Engineer, Radio Laboratory

- Welkers

Issued by:

pp

John Newell Quality Manager, UL VS LTD

Per Old

IBC MRA

UKAS
TESTING
0644

This laboratory is accredited by UKAS. The tests reported herein have been performed in accordance with its terms of accreditation.

The *Bluetooth*[®] word mark and logos are owned by the *Bluetooth* SIG, Inc. and any use of such marks by UL VS LTD is under licence. Other trademarks and trade names are those of their respective owners.

Telephone: +44 (0)1256 312000 Facsimile: +44 (0)1256 312001

VERSION 2.0 ISSUE DATE: 30 SEPTEMBER 2015

This page has been left intentionally blank.

Page 2 of 32 UL VS LTD

Table of Contents

1. Customer Information	4
2. Summary of Testing	5 5 5 5 5
3. Equipment Under Test (EUT) 3.1. Identification of Equipment Under Test (EUT) 3.2. Description of EUT 3.3. Modifications Incorporated in the EUT 3.4. Additional Information Related to Testing 3.5. Support Equipment	6 6 6 6 7 7
4. Operation and Monitoring of the EUT during Testing	8 8 8
5. Measurements, Examinations and Derived Results 5.1. General Comments 5.2. Test Results 5.2.1. Transmitter AC Conducted Spurious Emissions 5.2.2. Transmitter Minimum 6 dB Bandwidth 5.2.3. Transmitter Maximum Peak Output Power 5.2.4. Transmitter Radiated Emissions 5.2.5. Transmitter Band Edge Radiated Emissions	9 10 10 14 17 21 29
6. Measurement Uncertainty	31
7. Report Revision History	32

UL VS LTD Page 3 of 32

VERSION 2.0 ISSUE DATE: 30 SEPTEMBER 2015

1. Customer Information

Company Name:	ModCam AB
Address:	Bredgatan 4, 211 30 Malmő, Sweden

Page 4 of 32 UL VS LTD

2. Summary of Testing

2.1. General Information

Specification Reference:	47CFR15.247
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) - Section 15.247
Specification Reference:	47CFR15.207 and 47CFR15.209
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) - Sections 15.207 and 15.209
Site Registration:	209735
Location of Testing:	UL VS LTD, Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, RG24 8AH, United Kingdom
Test Dates:	29 August 2015 to 18 September 2015

2.2. Summary of Test Results

FCC Reference (47CFR)	Measurement	Result
Part 15.207	Transmitter AC Conducted Emissions	②
Part 15.247(a)(2)	Transmitter Minimum 6 dB Bandwidth	②
Part 15.247(e)	Transmitter Power Spectral Density	Note 1
Part 15.247(b)(3)	Transmitter Maximum Peak Output Power	②
Part 15.247(d)/15.209(a)	Transmitter Radiated Emissions	②
Part 15.247(d)/15.209(a)	Transmitter Band Edge Radiated Emissions	②
Key to Results		
= Complied = Did no	ot comply	

Note(s):

1. In accordance with FCC KDB 558074 Section 10.1, PSD is not required if the maximum conducted output power is less than the PSD limit of 8 dBm / 3 kHz. The PSD level is therefore deemed to be equal to the measured total output power.

2.3. Methods and Procedures

Reference:	ANSI C63.10-2013
Title:	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Reference:	KDB 558074 D01 v03r03 June 9, 2015
Title:	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247

2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

UL VS LTD Page 5 of 32

3. Equipment Under Test (EUT)

3.1. Identification of Equipment Under Test (EUT)

Brand Name:	ModCam
Model Name or Number:	MOD.01
Test Sample Serial Number:	MC000170 (Radiated sample)
Hardware Version:	2.0
Software Version:	114
FCC ID:	2AEV4-01

Brand Name:	ModCam
Model Name or Number:	MOD.01
Test Sample Serial Number:	MC000058 (Conducted sample with RF port)
Hardware Version:	2.0
Software Version:	114
FCC ID:	2AEV4-01

3.2. Description of EUT

The equipment under test was an IP camera which incorporated the following wireless technologies; *Bluetooth*, *Bluetooth*

3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

Page 6 of 32

3.4. Additional Information Related to Testing

Technology Tested:	Bluetooth Low Energy (Digital Transmission System)		
Type of Unit:	Transceiver		
Channel Spacing:	2 MHz		
Modulation:	GFSK		
Data Rate:	1 Mbps		
Power Supply Requirement(s):	Nominal 3.8 VDC via 120 VAC 60 Hz		
Maximum Conducted Output Power:	6.9 dBm		
Antenna Gain:	0.1 dBi		
Transmit Frequency Range:	2402 MHz to 2480 MH	Z	
Transmit Channels Tested:	Channel ID	RF Channel	Channel Frequency (MHz)
	Bottom	0	2402
	Middle	19	2440
	Тор	39	2480

3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

Description:	Test laptop
Brand Name:	Hewlett Packard
Model Name or Number:	Compaq 6910p
Serial Number:	HUB7451SGN

Description:	USB Cable
Brand Name:	SONY
Model Name or Number:	EC450
Serial Number:	132112D80289990

Description:	AC Charger
Brand Name:	SONY
Model Name or Number:	EP880
Serial Number:	8512W32 101946 SEM0600

UL VS LTD Page 7 of 32

4. Operation and Monitoring of the EUT during Testing

4.1. Operating Modes

The EUT was tested in the following operating mode(s):

 Transmitting at maximum power in Bluetooth LE mode with a modulated carrier, maximum data length available and Pseudorandom Bit Sequence 9.

4.2. Configuration and Peripherals

The EUT was tested in the following configuration(s):

- Controlled using a terminal application on the laptop PC supplied by the customer. The application
 was used to enable continuous transmission and to select the test channels as required.
- The EUT was connected to a DC power supply for all conducted tests. A USB diagnostic cable was connected to the EUT to change channels as required.
- Transmitter radiated spurious emissions tests were performed with the AC Charger and USB cable connected to the EUT. The AC charger was power by 120 VAC 60 Hz.
- The EUT conducted sample was used for 6 dB bandwidth and maximum peak output power.
- The EUT radiated sample was used for AC conducted emissions and radiated spurious emissions tests.

Page 8 of 32 UL VS LTD

5. Measurements, Examinations and Derived Results

5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to Section 6. Measurement Uncertainty for details.

In accordance with UKAS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

UL VS LTD Page 9 of 32

5.2. Test Results

5.2.1. Transmitter AC Conducted Spurious Emissions

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	18 September 2015
Test Sample Serial Number:	MC000170		

FCC Reference:	Part 15.207
Test Method Used:	ANSI C63.10 Section 6.2


Environmental Conditions:

Temperature (°C):	22
Relative Humidity (%):	46

Note(s):

- 1. The EUT was plugged into a USB cable which is connected to an AC charger. The AC charger was connected to 120 VAC 60 Hz single phase supply via a LISN.
- 2. Pre-scans were performed and markers placed on the highest live and neutral measured levels. Final measurements were performed on the marker frequencies and the results entered into the tables below.
- 3. A pulse limiter was fitted between the LISN and the test receiver.

Test setup:



Page 10 of 32 UL VS LTD

VERSION 2.0

Transmitter AC Conducted Spurious Emissions (continued)

Results: Live / Quasi Peak

Frequency (MHz)	Line	Level (dB _µ V)	Limit (dBµV)	Margin (dB)	Result
0.159	Live	56.1	65.5	9.4	Complied
0.191	Live	53.2	64.0	10.8	Complied
0.263	Live	47.6	61.4	13.8	Complied
0.411	Live	38.3	57.6	19.3	Complied
0.605	Live	28.4	56.0	27.6	Complied
1.280	Live	14.0	56.0	42.0	Complied

Results: Live / Average

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result
0.150	Live	28.2	55.8	27.6	Complied
0.479	Live	22.5	46.4	23.9	Complied
1.077	Live	17.7	46.0	28.3	Complied
1.460	Live	6.7	46.0	39.3	Complied

UL VS LTD Page 11 of 32

Transmitter AC Conducted Spurious Emissions (continued)

Results: Neutral / Quasi Peak


Frequency (MHz)	Line	Level (dB _µ V)	Limit (dBµV)	Margin (dB)	Result
0.150	Neutral	56.4	66.0	9.6	Complied
0.186	Neutral	53.4	64.2	10.8	Complied
0.267	Neutral	47.1	61.2	14.1	Complied
0.438	Neutral	36.8	57.1	20.3	Complied
0.604	Neutral	28.5	56.0	27.5	Complied
1.302	Neutral	9.0	56.0	47.0	Complied

Results: Neutral / Average

Frequency (MHz)	Line	Level (dB _µ V)	Limit (dBµV)	Margin (dB)	Result
0.155	Neutral	27.2	55.8	28.6	Complied
0.263	Neutral	23.3	51.4	28.1	Complied
0.456	Neutral	18.0	46.8	28.8	Complied
0.996	Neutral	11.2	46.0	34.8	Complied

Page 12 of 32 UL VS LTD

Transmitter AC Conducted Spurious Emissions (continued)



Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1625	Thermohygrometer	JM Handelspunkt	30.5015.06	Not stated	07 Jan 2016	12
M1263	Test Receiver	Rohde & Schwarz	ESIB7	100265	14 Oct 2015	12
A649	LISN	Rohde & Schwarz	ESH3-Z5	825562/008	14 Jul 2016	12
A1830	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100668	02 Mar 2016	12

UL VS LTD Page 13 of 32

ISSUE DATE: 30 SEPTEMBER 2015

5.2.2. Transmitter Minimum 6 dB Bandwidth

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	29 August 2015
Test Sample Serial Number:	MC000058		

FCC Reference:	Part 15.247(a)(2)
Test Method Used:	FCC KDB 558074 Section 8.1 Option 1


Environmental Conditions:

Temperature (°C):	25
Relative Humidity (%):	37

Note(s):

- 6 dB DTS bandwidth tests were performed using a signal analyser in accordance with FCC KDB 558074
 Section 8.1 Option 1 measurement procedure. The signal analyser resolution bandwidth was set to 100
 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and the trace
 mode was Max Hold. The DTS bandwidth was measured at 6 dB down from the peak of the signal.
- 2. The signal analyser was connected to the RF port on the EUT using suitable attenuation and RF cable.

Test setup:





Page 14 of 32 UL VS LTD

Transmitter Minimum 6 dB Bandwidth (continued)

Results:


Channel	6 dB Bandwidth (kHz)	Limit (kHz)	Margin (kHz)	Result
Bottom	713.130	≥500	213.130	Complied
Middle	715.200	≥500	215.200	Complied
Тор	716.000	≥500	216.000	Complied





Bottom Channel

Middle Channel



Top Channel

UL VS LTD Page 15 of 32

Transmitter Minimum 6 dB Bandwidth (continued)

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1783	Thermohygrometer	JM Handelspunkt	30.5015.13	Not stated	23 Apr 2016	12
M1883	Signal Analyser	Rohde & Schwarz	FSV30	103084	23 Jul 2016	12
A2521	Attenuator	AtlanTechRF	AN18-20	832797#2	Calibrated before use	-
M122	Multimeter	Fluke	77	64910017	22 Apr 2016	12
S021	Power Supply Unit	TTI	CPX200	061034	Calibrated before use	-

Page 16 of 32 UL VS LTD

5.2.3. Transmitter Maximum Peak Output Power

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	29 August 2015
Test Sample Serial Number:	MC000058		

FCC Reference:	Part 15.247(b)(3)
Test Method Used:	FCC KDB 558074 Section 9.1.1


Environmental Conditions:

Temperature (°C):	25
Relative Humidity (%):	37

Note(s):

- 1. Conducted power tests were performed using a signal analyser in accordance with FCC KDB 558074 Section 9.1.1 with the RBW > *DTS bandwidth* procedure. A resolution bandwidth of 1 MHz was used and the video bandwidth was set to 3 MHz.
- 2. The signal analyser was connected to the RF port on the EUT using suitable attenuation and RF cable. An RF level offset was entered on the signal analyser to compensate for the loss of the attenuator and RF cable.
- 3. The conducted power was added to the declared antenna gain to obtain the EIRP.

Test setup:



UL VS LTD Page 17 of 32

ISSUE DATE: 30 SEPTEMBER 2015


<u>Transmitter Maximum Peak Output Power (continued)</u> <u>Results:</u>


Channel	Conducted Peak Power (dBm)	Conducted Peak Power Limit (dBm)	Margin (dB)	Result
Bottom	6.9	30.0	23.1	Complied
Middle	6.8	30.0	23.2	Complied
Тор	6.8	30.0	23.2	Complied

Channel	Conducted Peak Power (dBm)	Declared Antenna Gain (dBi)	EIRP (dBm)	De Facto EIRP Limit (dBm)	Margin (dB)	Result
Bottom	6.9	0.1	7.0	36.0	29.0	Complied
Middle	6.8	0.1	6.9	36.0	29.1	Complied
Тор	6.8	0.1	6.9	36.0	29.1	Complied

Page 18 of 32 UL VS LTD


Transmitter Maximum Peak Output Power (continued)





Bottom Channel

Middle Channel



Top Channel

UL VS LTD Page 19 of 32

<u>Transmitter Maximum Peak Output Power (continued)</u> <u>Test Equipment Used:</u>

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1783	Thermohygrometer	JM Handelspunkt	30.5015.13	Not stated	23 Apr 2016	12
M1883	Signal Analyser	Rohde & Schwarz	FSV30	103084	23 Jul 2015	12
A2521	Attenuator	AtlanTechRF	AN18-20	832797#2	Calibrated before use	-
A2072	Directional Coupler	Narda	4242B	03549	Calibrated before use	-
G0614	Signal Generator	Rohde & Schwarz	SMB100A	177687	01 May 2017	36
M199	Power Meter	Rohde & Schwarz	NRVS	827023/075	08 Apr 2016	24
M1267	Power Sensor	Rohde & Schwarz	NRV-Z52	100155	23 Apr 2016	24
M122	Multimeter	Fluke	77	64910017	22 Apr 2016	12
S021	Power Supply Unit	TTI	CPX200	061034	Calibrated before use	-

Page 20 of 32 UL VS LTD

ISSUE DATE: 30 SEPTEMBER 2015

5.2.4. Transmitter Radiated Emissions

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	30 August 2015
Test Sample Serial Number:	MC000170		

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	ANSI C63.10 Sections 6.3 and 6.5
Frequency Range	30 MHz to 1000 MHz

Environmental Conditions:


Temperature (°C):	24
Relative Humidity (%):	43


Note(s):

- 1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
- 2. The preliminary scans showed similar emission levels below 1 GHz, for each channel of operation. Therefore final radiated emissions measurements were performed with the EUT set to the middle channel only.
- 3. All other emissions shown on the pre-scans were investigated and found to be ambient, or > 20 dB below the appropriate limit or below the noise floor of the measurement system.
- 4. Measurements below 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.

UL VS LTD Page 21 of 32

Test setup for radiated measurements:






Page 22 of 32 UL VS LTD

Results: Middle Channel

Frequency	Antenna	Level	Limit	Margin	Result
(MHz)	Polarity	(dBμV/m)	(dBμV/m)	(dB)	
325.437	Horizontal	35.3	46.0	10.7	Complied



Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1945	Thermohygrometer	JM Handelspunkt	30.5015.01	0112	23 Apr 2016	12
K0001	5 m RSE Chamber	Rainford EMC	N/A	N/A	19 Mar 2016	12
M1273	Test Receiver	Rohde & Schwarz	ESIB26	100275	19 Mar 2016	12
A490	Antenna	Chase	CBL6111A	1590	30 Apr 2016	12
G0543	Amplifier	Sonoma	310N	230801	06 Nov 2015	3
A1834	Attenuator	Hewlett Packard	8491B	10444	05 Mar 2016	12

UL VS LTD Page 23 of 32

VERSION 2.0

ISSUE DATE: 30 SEPTEMBER 2015

Transmitter Radiated Emissions (continued)

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	01 September 2015
Test Sample Serial Number:	MC000170		

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	FCC KDB 558074 Sections 11 & 12 referencing ANSI C63.10 Sections 6.3 & 6.6
Frequency Range	1 GHz to 25 GHz

Environmental Conditions:

Temperature (°C):	24
Relative Humidity (%):	40

Note(s):

- 1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
- 2. All other emissions shown on the pre-scan plot were investigated and found to be ambient or >20 dB below the applicable limit or below the measurement system noise floor.
- 3. The emission shown on the 1 GHz to 4 GHz plot is the EUT fundamental.
- 4. Pre-scans above 1 GHz were performed in a fully anechoic chamber (Asset Number K0002) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT. Final measurements above 1 GHz were performed in a semi-anechoic chamber (Asset Number K0001) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
- 5. Pre-scans were performed and a marker placed on the highest measured level of the appropriate plot. The test receiver resolution bandwidth was set to 1 MHz and video bandwidth 3 MHz. The sweep time was set to auto.
- 6. In accordance with ANSI C63.10 Section 6.6.4.3, Note 1, if the peak measured value complies with the average limit, it is unnecessary to perform an average measurement.

Page 24 of 32 UL VS LTD

ISSUE DATE: 30 SEPTEMBER 2015

Transmitter Radiated Emissions (continued)

Results: Peak / Bottom Channel

Frequenc (MHz)	у	Antenna Polarity	Peak Level (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
4803.48	7	Vertical	45.2	54.0	8.8	Complied


Results: Peak / Middle Channel


Frequency (MHz)	Antenna Polarity	Peak Level (dBμV/m)	Average Limit (dBμV/m)	Margin (dB)	Result
4880.337	Vertical	44.1	54.0	9.9	Complied

Results: Peak / Top Channel


Frequency	Antenna	Peak Level	Average Limit	Margin	Result
(MHz)	Polarity	(dBμV/m)	(dBμV/m)	(dB)	
4959.535	Vertical	44.1	54.0	9.9	Complied

UL VS LTD Page 25 of 32







Peak Detector





Average Detector



Page 26 of 32 UL VS LTD







Note: The above plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

UL VS LTD Page 27 of 32

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1656	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	23 Apr 2016	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	01 May 2016	12
M1874	Test Receiver	Rohde & Schwarz	ESU26	100553	12 Jun 2016	12
A1534	Pre Amplifier	Hewlett Packard	8449B	3008A00405	21 Dec 2015	12
A1818	Antenna	EMCO	3118	00075692	20 Dec 2015	12
A253	Antenna	Flann Microwave	12240-20	128	20 Dec 2015	12
A254	Antenna	Flann Microwave	14240-20	139	20 Dec 2015	12
A255	Antenna	Flann Microwave	16240-20	519	20 Dec 2015	12
A256	Antenna	Flann Microwave	18240-20	400	20 Dec 2015	12
A436	Antenna	Flann Microwave	20240-20	330	20 Dec 2015	12
A1396	Attenuator	Huber & Suhner	6810.17.B	757987	05 May 2016	12
A1975	High Pass Filter	AtlanTecRF	AFH-03000	090424010	17 Apr 2016	12

Page 28 of 32 UL VS LTD

5.2.5. Transmitter Band Edge Radiated Emissions

Test Summary:

Test Engineer:	Andrew Edwards	Test Date:	01 September 2015
Test Sample Serial Number:	MC000170		

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	ANSI C63.10 Section 6.10.4, 6.10.5 & KDB 558074 Section 11

Environmental Conditions:

Temperature (°C):	24
Relative Humidity (%):	42

Note(s):

- 1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
- 2. The maximum peak conducted output power was previously measured. In accordance with FCC KDB 558074 Section 11.1(a), the lower band edge measurement was performed with a peak detector and the -20 dBc limit applied.
- 3. There is a restricted band 10 MHz below the lower band edge. The test receiver was set up as follows: the RBW set to 1 MHz, the VBW set to 3 MHz, with the sweep time set to auto couple. Peak and average measurements were performed with their respective detectors. Markers were placed on the highest point on each trace.
- 4. * -20 dBc limit.
- 5. The reference level was set to 115 dBµV in order to achieve sufficient headroom.

Results: Peak


Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Result
2354.487	52.3	74.0	21.7	Complied
2400.0	41.3	79.4*	38.1	Complied
2483.5	49.2	74.0	24.8	Complied


Results: Average

Frequency (MHz)	Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Result
2340.256	42.3	54.0	11.7	Complied
2483.5	42.3	54.0	11.7	Complied


UL VS LTD Page 29 of 32

Transmitter Band Edge Radiated Emissions (continued)






Lower Band Edge Peak Measurement



Upper Band Edge Peak Measurement



2310 MHz to 2390 MHz Restricted Band Plot

Upper Band Edge Average Measurement

Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M1656	Thermohygrometer	JM Handelspunkt	30.5015.13	None stated	23 Apr 2016	12
K0002	3m RSE Chamber	Rainford EMC	N/A	N/A	01 May 2016	12
M1874	Test Receiver	Rohde & Schwarz	ESU26	100553	12 Jun 2016	12
A1534	Pre Amplifier	Hewlett Packard	8449B	3008A00405	21 Dec 2015	12
A1818	Antenna	EMCO	3118	00075692	20 Dec 2015	12
A1396	Attenuator	Huber & Suhner	6810.17.B	757987	05 May 2016	12

Page 30 of 32

6. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value measured (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±4.69 dB
Conducted Maximum Peak Output Power	2.4 GHz to 2.4835 GHz	95%	±1.13 dB
Minimum 6 dB Bandwidth	2.4 GHz to 2.4835 GHz	95%	±3.92 %
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±5.65 dB
Radiated Spurious Emissions	1 GHz to 26.5 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

UL VS LTD Page 31 of 32

VERSION 2.0

ISSUE DATE: 30 SEPTEMBER 2015

7. Report Revision History

Version	Revision Details		
Number	Page No(s)	Clause	Details
1.0	-	-	Initial Version
2.0	-	-	Customer Information & FCC ID updated

⁻⁻⁻ END OF REPORT ---

Page 32 of 32 UL VS LTD