

Produkte  
Products

**Prüfbericht - Nr.:** 14039853 001

Test Report No.:

Seite 1 von 9  
Page 1 of 9

**Auftraggeber:** ALDI Sourcing Asia Limited  
**Client:**  
 Suite 2506, 25/F., Tower 1  
 The Gateway, Harbour City  
 Kowloon, Hong Kong

**Gegenstand der Prüfung:** Short Range Device - 434MHz Receiver  
**Test Item:**

**Bezeichnung:** 92596 **Serien-Nr.:** Engineering sample  
**Identification:** Serial No.:

**Wareneingangs-Nr.:** A000213733-004 **Eingangsdatum:** 15.06.2015  
**Receipt No.:** A000220196-012 **Date of Receipt:** 29.06.2015

**Zustand des Prüfgegenstandes bei Anlieferung:** Test sample(s) is/are not damaged and suitable for testing.  
**Condition of test item at delivery:**

**Prüfort:** TÜV Rheinland Hong Kong Ltd.  
**Testing Location:**  
 8/F, First Group Centre, 14 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong  
**Hong Kong Productivity Council**  
 HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

**Prüfgrundlage:** FCC Part 15 Subpart B  
**Test Specification:** ANSI C63.4-2003

**Prüfergebnis:** Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage.  
**Test Results:**  
 The above mentioned product was tested and **passed**.

**Prüflaboratorium:** TÜV Rheinland Hong Kong Ltd.  
**Testing Laboratory:**  
 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong

geprüft/ tested by:

07.08.2015 Benny Lau  
 Datum Name/Stellung  
 Senior Project Manager



kontrolliert/ reviewed by:

07.08.2015 Sharon Li  
 Datum Name/Stellung  
 Department Manager



**Sonstiges:** FCC ID: 2AEWF00092596H  
 Other Aspects

**Abkürzungen:** P(ass) = entspricht Prüfgrundlage  
 Fail) = entspricht nicht Prüfgrundlage  
 N/A = nicht anwendbar  
 N/T = nicht getestet

**Abbreviations:** P(ass) = passed  
 Fail) = failed  
 N/A = not applicable  
 N/T = not tested

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

## Table of Content

	Page
<b>Cover Page .....</b>	<b>1</b>
<b>Table of Content .....</b>	<b>2</b>
<b>Test Summary .....</b>	<b>3</b>
<b>Product information.....</b>	<b>4</b>
Manufacturers declarations .....	4
Product function and intended use.....	4
Submitted documents.....	4
Independent Operation Modes .....	4
Related Submittal(s) Grants .....	4
Remark .....	4
<b>Test Set-up and Operation Mode.....</b>	<b>5</b>
Principle of Configuration Selection .....	5
Test Operation and Test Software.....	5
Special Accessories and Auxiliary Equipment.....	5
Countermeasures to achieve EMC Compliance.....	5
<b>Test Methodology .....</b>	<b>6</b>
Radiated Emission .....	6
Field Strength Calculation.....	6
<b>List of Test and Measurement Instruments.....</b>	<b>7</b>
<b>Results FCC Part 15 – Subpart B .....</b>	<b>8</b>
Subclause 15.107 – Conducted Emission on AC Mains.....	Pass.....
Subclause 15.109 – Radiated Emission .....	Pass.....
Appendix 1 – Test Results.....	4 pages
Appendix 2 – Test Setup Photos.....	2 pages
Appendix 3 – EUT External Photos.....	5 pages
Appendix 4 – EUT Internal Photos .....	3 pages
Appendix 5 – Label, Operational Description, Block, Schematics and User Manual.....	32 pages

## Test Summary

### Conducted Emissions

*Result: Pass*

### Radiated Emissions

*Result: Pass*

## Product information

### Manufacturers declarations

Receiver	
Operating frequency range	434 MHz
Number of channels	1
Type of antenna	Integral Antenna
Connection to public utility power line	Yes
Nominal voltage	V <sub>nor</sub> : 3.0Vdc (2 x 1.5V "AA" battery) and/ or 100-240Vac

### Product function and intended use

The equipment under test (EUT) is a receiver operating at 434MHz. And it is powered by 3.0Vdc (2 x 1.5V "AA" battery) and/ or 100-240Vac.

### FCC ID: 2AEWF00092596V

Models	Product description
92596	Weather Station

### Submitted documents

Circuit Diagram  
 Block Diagram  
 Bill of material  
 User manual  
 Rating Label

### Independent Operation Modes

The basic operation modes are:

- Receiving mode .

For further information refer to User Manual

### Related Submittal(s) Grants

This is a single application for certification of the receiver. The FCC ID of the corresponding transmitter is 2AEWF00092596S.

### Remark

- None.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- No testing software is provided by the applicant.

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- AC-DC adaptor, Model: 6301-US-A, Input: 100-240VAC 50/60Hz, Output 5.0VDC 1000mA.
- 5ohm resistive load.

### Countermeasures to achieve EMC Compliance

- none

## Test Methodology

### Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.4-2003.

The equipment under test (EUT) was placed at the middle of the 80 cm height turntable, and the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 °, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

### Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

$$FS = R + AF + CF + FA - PA$$

Where FS= Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

## List of Test and Measurement Instruments

Hong Kong Productivity Council (Registration number: 90656)

### Radiated Emission

Equipment	Manufacturer	Type	Cal. date	Cal. Due date
Semi-anechoic Chamber	Frankonia	Nil	14-Apr-15	14-Apr-16
New Fully Ancheonic Chamber	TDK	N/A	15-Apr-15	15-Apr-16
Cable	Hubersuhner	SUCOFLEX 104	31-Mar-14	31-Mar-16
Test Receiver	R & S	ESU26	12-Feb-15	12-Feb-16
Bi-conical Antenna	R & S	HK116	22-Aug-13	22-Aug-15
Log Periodic Antenna	R & S	HL223	16-Aug-13	16-Aug-15
Coaxial cable	Harbour	LL335	10-Jun-14	10-Jun-16
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	17-Jul-14	17-Jul-16
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	28-Oct-13	28-Oct-15
Horn Antenna	EMCO	3115	7-Aug-13	7-Aug-15
FSP 30 Spectrum Analyzer	Frankonia	FSP 30	12-Jan-16	12-Jan-17

TÜV Rheinland Hong Kong Ltd.

### AC Mains Conducted Emission

Equipment	Manufacturer	Type	Cal. date	Cal. Due date
Test Receiver	R & S	ESR3	11-Sep-14	12-Sep-15
LISN	R & S	ENV216	04-Feb-15	05-Feb-16
EMC32	R & S	v9.12	N/A	N/A

## Results FCC Part 15 – Subpart B

Subclause 15.107 – Conducted Emission on AC Mains						Pass
Test Specification : ANSI C63.4 – 2003						
Mode of operation : Receiving mode						
Port of testing : AC Mains input port of power supply						
Detector : Quasi-peak and Average						
RBW : 9 kHz						
Supply voltage : 120Vac 60Hz						
Temperature : 23°C						
Humidity : 50%						
Requirement: The emissions from the unintentional radiators comply with the following limit.						
<b>Results:</b> Pass						
<b>Live measurement</b>						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dB $\mu$ V	Average dB $\mu$ V	Limit QP (dB $\mu$ V)	Limit AV (dB $\mu$ V)	Verdict
0,15 – 0,5	0.150	47.6	31.1	66 - 56	56 - 46	Pass
> 0,5 - 5	No peak found	---	---	56	46	Pass
> 5 - 30	No peak found	---	---	60	50	Pass
<b>Neutral measurement</b>						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dB $\mu$ V	Average dB $\mu$ V	Limit QP (dB $\mu$ V)	Limit AV (dB $\mu$ V)	Verdict
0,15 – 0,5	0.150	45.3	28.4	66 - 56	56 - 46	Pass
> 0,5 - 5	No peak found	---	---	56	46	Pass
> 5 - 30	No peak found	---	---	60	50	Pass
<b>Results:</b> Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.						
The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz does not exceed the limits. For test Results plots refer to Appendix 1, page 2.						

<b>Subclause 15.109 – Radiated Emission</b>		<b>Pass</b>
Test Specification	: ANSI C63.4 – 2003	
Mode of operation	: Receiving mode	
Port of testing	: Enclosure	
RBW/VBW	: 120 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz	
Supply voltage	: 3.0VDC	
Frequency range	: 30MHz to 2GHz	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	The field strength of emissions from the unintentional radiators comply with the following limit.	
<b>Results:</b>	Pass	
Vertical Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
31.800	22.4	40.0 / QP
47.970	26.9	40.0 / QP
136.290	28.0	43.5 / QP
Horizontal Polarization		
<b>Freq MHz</b>	<b>Level dBuV/m</b>	<b>Limit/ Detector dBuV/m</b>
125.670	23.2	43.5 / QP