

Produkte  
Products

**Prüfbericht - Nr.:** 14045184 001

Test Report No.:

Seite 1 von 10

Page 1 of 10

<b>Auftraggeber:</b> Client:	ALDI Sourcing Asia Limited Suite 2501, Tower 1 The Gateway, Harbour City Kowloon, Hong Kong				
<b>Gegenstand der Prüfung:</b> Test Item:	Short Range Device - 434MHz Receiver				
<b>Bezeichnung:</b> Identification:	93716	<b>Serien-Nr.:</b> Serial No.:	Engineering sample		
<b>Wareneingangs-Nr.:</b> Receipt No.:	A000357609-005	<b>Eingangsdatum:</b> Date of Receipt:	10.05.2016		
<b>Zustand des Prüfgegenstandes bei Anlieferung:</b> Condition of test item at delivery:	Test sample(s) is/are not damaged and suitable for testing.				
<b>Prüfort:</b> Testing Location:	Hong Kong Productivity Council HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong				
<b>Prüfgrundlage:</b> Test Specification:	FCC Part 15 Subpart B ANSI C63.4-2014				
<b>Prüfergebnis:</b> Test Results:	Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben genannter Prüfgrundlage. The above mentioned product was tested and <b>passed</b> .				
<b>Prüflaboratorium:</b> Testing Laboratory:	TÜV Rheinland Hong Kong Ltd. 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay, Kowloon, Hong Kong				
<b>geprüft/ tested by:</b>	<b>kontrolliert/ reviewed by:</b>				
25.07.2016	Hugo Wan Senior Project Manager		25.07.2016	Sharon Li Department Manager	
Datum Date	Name/Stellung Name/Position	Unterschrift Signature	Datum Date	Name/Stellung Name/Position	Unterschrift Signature
<b>Sonstiges:</b> Other Aspects	<b>FCC ID: 2AEWF00093716V</b>				
<b>Abkürzungen:</b>	P(pass) = entspricht Prüfgrundlage F(all) = entspricht nicht Prüfgrundlage N/A = nicht anwendbar N/T = nicht getestet			<b>Abbreviations:</b>	P(pass) = passed F(all) = failed N/A = not applicable N/T = not tested
<p>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</p> <p>This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.</p>					

## Table of Content

	Page
<b>Cover Page .....</b>	<b>1</b>
<b>Table of Content .....</b>	<b>2</b>
<b>Test Summary .....</b>	<b>3</b>
<b>Product information.....</b>	<b>4</b>
Manufacturers declarations .....	4
Product function and intended use.....	4
Submitted documents.....	4
Independent Operation Modes .....	4
Related Submittal(s) Grants .....	4
Remark .....	4
<b>Test Set-up and Operation Mode.....</b>	<b>5</b>
Principle of Configuration Selection .....	5
Test Operation and Test Software.....	5
Special Accessories and Auxiliary Equipment.....	5
Countermeasures to achieve EMC Compliance.....	5
<b>Test Setup Diagram .....</b>	<b>6</b>
<b>List of Test and Measurement Instruments.....</b>	<b>8</b>
<b>Results FCC Part 15 – Subpart B .....</b>	<b>9</b>
Subclause 15.107 – Conducted Emission on AC Mains.....	Pass.....
Subclause 15.109 – Radiated Emission .....	Pass.....
Appendix 1 – Test Results.....	9 pages
Appendix 2 – Test Setup Photos.....	2 pages
Appendix 3 – EUT External Photos .....	6 pages
Appendix 4 – EUT Internal Photos .....	8 pages
Appendix 5 – Label, Operational Description, Block, Schematics and User Manual.....	19 pages

## Test Summary

### Conducted Emissions

*Result: Pass*

### Radiated Emissions

*Result: Pass*

## Product information

### Manufacturers declarations

Receiver	
Operating frequency range	434 MHz
Number of channels	1
Type of antenna	Integral Antenna
Connection to public utility power line	Yes
Nominal voltage	V <sub>nor</sub> : 3.0VDC (2 x 1.5V "AAA" battery) and/ or 100-240VAC

### Product function and intended use

The equipment under test (EUT) is a receiver operating at 434MHz. And it is powered by 3.0VDC (2 x 1.5V "AAA" battery) and/ or 100-240VAC.

The EUT receiver has two housing colors: black and white. The EUT of two colors are totally identical including schematics, PCB layouts and components used except the housing color only.

### FCC ID: 2AEWF00093716V

Models	Product description
93716	Weather Station

### Submitted documents

Circuit Diagram  
 Block Diagram  
 Bill of material  
 User manual  
 Rating Label

### Independent Operation Modes

The basic operation modes are:

- Receiving mode .

For further information refer to User Manual

### Related Submittal(s) Grants

This is a single application for certification of the receiver. The FCC ID of the corresponding transmitter is 2AEWF00093716S.

### Remark

- None.

## Test Set-up and Operation Mode

### Principle of Configuration Selection

**Emission:** The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

### Test Operation and Test Software

Test operation should refer to test methodology.

- No testing software is provided by the applicant.

### Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:


- AC/DC adaptor, Model: 6301-US-A, Input: 100-240VAC 50/60Hz, Output 5.0VDC 1000mA.
- 5ohm resistive load.

### Countermeasures to achieve EMC Compliance

- none


## Test Setup Diagram


**Diagram of Measurement Configuration for Radiated Emission Test**



Note: For measurements above 1 GHz, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

**Diagram of Measurement Configuration for Conducted RF Test**



**Diagram of Measurement Equipment Configuration for AC Mains Conducted Emission Test (if applicable)**

## List of Test and Measurement Instruments

**Hong Kong Productivity Council (Registration number: 90656)**

### Radiated Emission

Equipment	Manufacturer	Type	Cal. date	Cal. Due date
Semi-anechoic Chamber	Frankonia	Nil	25 Apr 2016	25 Apr 2017
Cable	Hubersuhner	SUCOFLEX 104	31 Mar 2016	31 Mar 2018
Test Receiver	R & S	ESU40	07 Dec 2015	07 Dec 2016
Bi-conical Antenna	R & S	HK116	01 Sep 2015	01 Sep 2017
Log Periodic Antenna	R & S	HL223	01 Sep 2015	01 Sep 2017
Coaxial cable	Harbour	LL335	10 Jun 2014	10 Aug 2016
Microwave amplifier 0.5-26.5GHz, 25dB gain	HP	83017A	17 Jul 2014	17 Aug 2016
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	28 Oct 2015	28 Oct 2017
Horn Antenna	EMCO	3115	26 Aug 2015	26 Aug 2017
Active Loop Antenna	EMCO	6502	15 Aug 2015	15 Aug 2016

### AC Mains Conducted Emission

Equipment	Manufacturer	Type	Cal. date	Cal. Due date
Test Receiver	R & S	ESU40	08 Dec 2015	07 Dec 2016
LISN	R & S	ESH3-Z5	16 Aug 2016	15 Aug 2016
EMC32	R & S	v9.20	N/A	N/A

## Results FCC Part 15 – Subpart B

Subclause 15.107 – Conducted Emission on AC Mains						Pass
Test Specification : ANSI C63.4 – 2014						
Mode of operation : Receiving mode						
Port of testing : AC Mains input port of power supply						
Detector : Quasi-peak and Average						
RBW : 9 kHz						
Supply voltage : 120VAC 60Hz						
Temperature : 23°C						
Humidity : 50%						
Requirement: The emissions from the unintentional radiators comply with the following limit.						
<b>Results:</b> Pass						
<b>Live measurement</b>						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dB $\mu$ V	Average dB $\mu$ V	Limit QP (dB $\mu$ V)	Limit AV (dB $\mu$ V)	Verdict
0,15 – 0,5	No peak found	---	---	66 - 56	56 - 46	Pass
> 0,5 - 5	No peak found	---	---	56	46	Pass
> 5 - 30	No peak found	---	---	60	50	Pass
<b>Neutral measurement</b>						
Frequency range (MHz)	Frequency (MHz)	Quasi-peak dB $\mu$ V	Average dB $\mu$ V	Limit QP (dB $\mu$ V)	Limit AV (dB $\mu$ V)	Verdict
0,15 – 0,5	No peak found	---	---	66 - 56	56 - 46	Pass
> 0,5 - 5	No peak found	---	---	56	46	Pass
> 5 - 30	No peak found	---	---	60	50	Pass
<b>Results:</b> Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate.						
The radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz does not exceed the limits. For test Results plots refer to Appendix 1, page 2.						

<b>Subclause 15.109 – Radiated Emission</b>		<b>Pass</b>
Test Specification	: ANSI C63.4 – 2014	
Mode of operation	: Receiving mode	
Port of testing	: Enclosure	
RBW/VBW	: 120 kHz for f < 1 GHz 1 MHz / 3 MHz for f > 1 GHz	
Supply voltage	: 120VAC 60Hz	
Frequency range	: 9kHz to 2GHz	
Temperature	: 23°C	
Humidity	: 50%	
Requirement:	The field strength of emissions from the unintentional radiators comply with the following limit.	
<b>Results:</b>	Pass	
Vertical Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
30.090	28.3	40.0 / QP
125.100	30.2	43.5 / QP
Horizontal Polarization		
Freq MHz	Level dBuV/m	Limit/ Detector dBuV/m
113.430	20.8	43.5 / QP