



Shenzhen Asia Test Technology Co., Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China
Tel: +86-0755-23284990 Email: att@att-lab.com Http: // www.att-lab.cn

FCC RADIO TEST REPORT

FCC ID: 2AEWXBLUE1

Product : Budiu Blue Button

Trade Name : budiu

Model Name : blue button

Serial Model : blue button 1.0

Prepared for

Beijing ANDL Technology co.,ltd
Room 202 BIFTPARK, No.2 East Yinghua Road, Chaoyang District,
Beijing, China

Prepared by

Shenzhen Asia Test Technology Co.,Ltd.
7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District,
Shenzhen, China
Tel: +(86)-0755-23284990 Fax: +(86)-0755-23284990
Http: www.att-lab.cn

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 2 of 41 -

TEST RESULT CERTIFICATION

Applicant's name Beijing ANDL Technology co.,ltd

Address Room 202 BIFTPARK, No.2 East Yinghua Road, Chaoyang District, Beijing, China

Manufacture's Name Beijing ANDL Technology co.,ltd

Address Room 202 BIFTPARK, No.2 East Yinghua Road, Chaoyang District, Beijing, China

Product description

Product name Budiu Blue Button

Model and/or type blue button
reference

Serial Model blue button 1.0

Standards FCC Part15.247

Test procedure ANSI C63.4-2003

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.

Date of Test

Date (s) of performance of tests Sep. 06, 2015 ~ Sep. 17, 2015

Date of Issue Sep. 17, 2015

Test Result **Pass**

Tested by: Eric Wang
Eric Wang
Project Leader

Reviewed by: Jerry You
Jerry You
Laboratory Supervisor

Approved by: Jack Yu
Jack Yu
Technical Director



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 3 of 41 -

| Table of Contents | Page |
|---|-----------|
| 1 . SUMMARY OF TEST RESULTS | 5 |
| 1.1 TEST FACILITY | 6 |
| 1.2 MEASUREMENT UNCERTAINTY | 6 |
| 2 . GENERAL INFORMATION | 7 |
| 2.1 GENERAL DESCRIPTION OF EUT | 7 |
| 2.2 DESCRIPTION OF TEST MODES | 8 |
| 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 9 |
| 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) | 10 |
| 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS | 11 |
| 3 . EMC EMISSION TEST | 12 |
| 3.1 CONDUCTED EMISSION MEASUREMENT | 12 |
| 3.1.1 POWER LINE CONDUCTED EMISSION LIMITS | 12 |
| 3.1.2 TEST PROCEDURE | 13 |
| 3.1.3 DEVIATION FROM TEST STANDARD | 13 |
| 3.1.4 TEST SETUP | 13 |
| 3.1.5 EUT OPERATING CONDITIONS | 13 |
| 3.1.6 TEST RESULTS | 14 |
| 3.2 RADIATED EMISSION MEASUREMENT | 15 |
| 3.2.1 RADIATED EMISSION LIMITS | 15 |
| 3.2.2 TEST PROCEDURE | 16 |
| 3.2.3 DEVIATION FROM TEST STANDARD | 16 |
| 3.2.4 TEST SETUP | 17 |
| 3.2.5 EUT OPERATING CONDITIONS | 18 |
| 3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ) | 19 |
| 3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ) | 20 |
| 3.2.8 TEST RESULTS (ABOVE 1000 MHZ) | 21 |
| 4 . POWER SPECTRAL DENSITY TEST | 27 |
| 4.1 APPLIED PROCEDURES / LIMIT | 27 |
| 4.1.1 TEST PROCEDURE | 27 |
| 4.1.2 DEVIATION FROM STANDARD | 27 |
| 4.1.3 TEST SETUP | 27 |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 4 of 41 -

| Table of Contents | Page |
|---|-----------|
| 4.1.4 EUT OPERATION CONDITIONS | 27 |
| 4.1.5 TEST RESULTS | 28 |
| 5 . BANDWIDTH TEST | 30 |
| 5.1 APPLIED PROCEDURES / LIMIT | 30 |
| 5.1.1 TEST PROCEDURE | 30 |
| 5.1.2 EUT OPERATION CONDITIONS | 30 |
| 5.1.3 TEST RESULTS | 31 |
| 6 . PEAK OUTPUT POWER TEST | 33 |
| 6.1 APPLIED PROCEDURES / LIMIT | 33 |
| 6.1.1 TEST PROCEDURE | 33 |
| 6.1.2 DEVIATION FROM STANDARD | 33 |
| 6.1.3 TEST SETUP | 33 |
| 6.1.4 EUT OPERATION CONDITIONS | 33 |
| 6.1.5 TEST RESULTS | 34 |
| 7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE | 35 |
| 7.1 DEVIATION FROM STANDARD | 35 |
| 7.2 TEST SETUP | 36 |
| 7.3 EUT OPERATION CONDITIONS | 36 |
| 7.4 TEST RESULTS | 37 |
| 8 . ANTENNA REQUIREMENT | 40 |
| 8.1 STANDARD REQUIREMENT | 40 |
| 8.2 EUT ANTENNA | 40 |
| 9 . EUT TEST PHOTO | 41 |
| APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS | |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 5 of 41 -

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

| FCC Part15 (15.247) , Subpart C | | | |
|---------------------------------|----------------------------|----------|--------|
| Standard Section | Test Item | Judgment | Remark |
| 15.207 | Conducted Emission | N/A | |
| 15.247 (a)(2) | 6dB Bandwidth | PASS | |
| 15.247 (b) | Peak Output Power | PASS | |
| 15.247 (c) | Radiated Spurious Emission | PASS | |
| 15.247 (d) | Power Spectral Density | PASS | |
| 15.205 | Band Edge Emission | PASS | |
| 15.203 | Antenna Requirement | PASS | |

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 6 of 41 -

1.1 TEST FACILITY

DONGGUAN UTL ELECTRONIC TECHNOLOGY CO., LTD.

1F, Hengzheng Bldg, North Road of Station, Nancheng District, Dongguan, Guangdong, China.

FCC Registration No.: 713614

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

| No. | Item | Uncertainty |
|-----|-------------------------------|-------------------------|
| 1 | Conducted Emission Test | $\pm 1.38\text{dB}$ |
| 2 | RF power, conducted | $\pm 0.16\text{dB}$ |
| 3 | Spurious emissions, conducted | $\pm 0.21\text{dB}$ |
| 4 | All emissions, radiated(<1G) | $\pm 4.68\text{dB}$ |
| 5 | All emissions, radiated(>1G) | $\pm 4.89\text{dB}$ |
| 6 | Temperature | $\pm 0.5^\circ\text{C}$ |
| 7 | Humidity | $\pm 2\%$ |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 7 of 41 -

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

| | | |
|---------------------|---|--------------------|
| Equipment | Budiu Blue Button | |
| Model Name | blue button | |
| Serial Model | blue button 1.0 | |
| Model Difference | All models are identical except model name. | |
| Product Description | The EUT is a Budiu Bluetooth Button | |
| | Operation Frequency: | 2402~2480MHz |
| | Modulation Type: | GFSK |
| | Bluetooth version: | 4.1 BLE |
| | Bit Rate of Transmitter | 1 Mbps |
| | Number Of Channel | 40CH |
| | Antenna Designation: | Please see Note 3. |
| | Output Power(Conducted): | 0dBm(PK) |
| | Antenna Gain (dBi) | 0dbi |
| | | |
| Channel List | Please refer to the Note 2. | |
| Ratings | DC 3.0V | |
| Adapter | N/A | |
| Battery | DC 3.0V | |
| HW | B_CC2640_V1.0 | |
| SW | V1.1 | |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

| Channel | Frequency (MHz) |
|---------|-----------------|
| 00 | 2402 |
| 01 | 2404 |
| | |
| 38 | 2478 |
| 39 | 2480 |

3.

Table for Filed Antenna

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) | NOTE |
|------|-------|------------|--------------|-----------|------------|------|
| | | | | | | |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 8 of 41 -

| | | | | | | |
|---|-----|-----|-------------|-----|---|------------|
| A | N/A | N/A | PCB Antenna | N/A | 0 | BT Antenna |
|---|-----|-----|-------------|-----|---|------------|

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| Pretest Mode | Description |
|--------------|-------------|
| Mode 1 | CH00 |
| Mode 2 | CH19 |
| Mode 3 | CH39 |

| For Conducted Emission | |
|------------------------|-------------|
| Final Test Mode | Description |
| / | / |

| For Radiated Emission | |
|-----------------------|-------------|
| Final Test Mode | Description |
| Mode 1 | CH00 |
| Mode 2 | CH19 |
| Mode 3 | CH39 |

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%. measurements are performed according to the KDB 558074 D01 DTS Meas Guidance v03r03




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 9 of 41 -

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 10 of 41 -

2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

| Item | Equipment | Brand | Model/Type No. | Series No. | Note |
|------|-------------------|-------|----------------|------------|------|
| E-1 | Budiu Blue Button | budiu | blue button | N/A | EUT |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

| Item | Shielded Type | Ferrite Core | Length | Note |
|------|---------------|--------------|--------|------|
| | | | | |
| | | | | |
| | | | | |
| | | | | |
| | | | | |

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 11 of 41 -

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

| No | Test Equipment | Manufacturer | Model No | Serial No | Cal. Date | Cal. Due Date |
|----|-------------------------------------|--------------|------------------|--------------|------------|---------------|
| 1 | Spectrum Analyzer | ADVANTEST | R3182 | 150900201 | 2015.06.29 | 2016.06.28 |
| 2 | EMI Measuring Receiver | R&S | ESR | 101660 | 2014.12.12 | 2015.12.11 |
| 3 | Low Noise Pre Amplifier | Tsj | MLA-10K01-B01-27 | 1205323 | 2015.06.29 | 2016.06.28 |
| 4 | Low Noise Pre Amplifier | Tsj | MLA-0120-A02-34 | 2648A04738 | 2014.12.02 | 2015.12.01 |
| 5 | TRILOG Super Broadband test Antenna | SCHWARZBECK | VULB9160 | 9160-3206 | 2014.12.03 | 2015.12.02 |
| 6 | Broadband Horn Antenna | SCHWARZBECK | BBHA9120D | 452 | 2014.12.03 | 2015.12.02 |
| 7 | SHF-EHF Horn | SCHWARZBECK | BBHA9170 | BBHA9170367 | 2014.12.03 | 2015.12.02 |
| 8 | Loop Antenna | ARA | PLA-1030/B | 1029 | 2015.03.20 | 2016.03.19 |
| 9 | Radiated Cable 1# (30MHz-1GHz) | FUJIKURA | 5D-2W | 01 | 2015.01.04 | 2016.01.03 |
| 10 | Radiated Cable 2# (1GHz -25GHz) | FUJIKURA | 10D2W | 02 | 2014.12.25 | 2015.12.24 |
| 11 | Radiated Cable 1#(9KHz-30MHz) | FUJIKURA | 1D-2W | 01 | 2015.01.04 | 2016.01.03 |
| 12 | SMA Antenna connector | Dosin | Dosin-SMA | N/A | N/A | N/A |
| 13 | Power Meter | R&S | NRVS | 100696 | 2015.07.06 | 2016.07.05 |
| 14 | Power Sensor | R&S | URV5-Z4 | 0395.1619.05 | 2015.07.06 | 2016.07.05 |

Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 12 of 41 -

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

| FREQUENCY (MHz) | Class A (dBuV) | | Class B (dBuV) | | Standard |
|-----------------|----------------|---------|----------------|-----------|----------|
| | Quasi-peak | Average | Quasi-peak | Average | |
| 0.15 -0.5 | 79.00 | 66.00 | 66 - 56 * | 56 - 46 * | CISPR |
| 0.50 -5.0 | 73.00 | 60.00 | 56.00 | 46.00 | CISPR |
| 5.0 -30.0 | 73.00 | 60.00 | 60.00 | 50.00 | CISPR |

| | | | | | |
|-----------|-------|-------|-----------|-----------|-----|
| 0.15 -0.5 | 79.00 | 66.00 | 66 - 56 * | 56 - 46 * | FCC |
| 0.50 -5.0 | 73.00 | 60.00 | 56.00 | 46.00 | FCC |
| 5.0 -30.0 | 73.00 | 60.00 | 60.00 | 50.00 | FCC |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 kHz |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 13 of 41 -


3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 14 of 41 -

3.1.6 TEST RESULTS

Note : Due to this EUT is powered by batteries only, this test item is not applicable.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 15 of 41 -

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a)&A8.5, then the 15.209(a) limit in the table below has to be followed.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section A8.4 (4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

| Frequencies (MHz) | Field Strength (micorvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| FREQUENCY (MHz) | Class A (dBuV/m) (at 3M) | | Class B (dBuV/m) (at 3M) | |
|-----------------|--------------------------|---------|--------------------------|---------|
| | PEAK | AVERAGE | PEAK | AVERAGE |
| Above 1000 | 80 | 60 | 74 | 54 |

Notes:

(1) Emission level (dBuV/m)=20log Emission level (uV/m).

| Spectrum Parameter | Setting |
|---------------------------------------|--|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10th carrier harmonic |
| RB / VB (emission in restricted band) | 1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 16 of 41 -

| Receiver Parameter | Setting |
|------------------------|----------------------------------|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB 200Hz for QP |
| Start ~ Stop Frequency | 150kHz~30MHz / RB 9kHz for QP |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB 120kHz for QP |

3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


3.2.3 DEVIATION FROM TEST STANDARD

No deviation




3.2.4 TEST SETUP

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 18 of 41 -

(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 19 of 41 -

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

| | | | |
|--------------|------------------|--------------------|--------------------|
| EUT: | Budu Blue Button | Model Name. : | blue button |
| Temperature: | 20 °C | Relative Humidity: | 48% |
| Pressure: | 1010 hPa | Test Voltage : | DC 3.0V by battery |
| Test Mode : | TX | Polarization : | -- |

| Freq. | Reading | Limit | Margin | State |
|-------|----------|----------|--------|-------|
| (MHz) | (dBuV/m) | (dBuV/m) | (dB) | P/F |
| -- | -- | -- | -- | P |
| -- | -- | -- | -- | P |

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);
Limit line = specific limits(dBuV) + distance extrapolation factor.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 20 of 41 -

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

| | | | |
|---------------|---------------------|---------------------|--------------------|
| EUT : | Budiu Blue Button | Model Name : | blue button |
| Temperature : | 20 °C | Relative Humidity : | 48% |
| Pressure: | 1010 hPa | Test Voltage : | DC 3.0V by battery |
| Test Mode : | TX 2402(worse-case) | | |

| Polar (H/V) | Frequency | Meter Reading | Factor | Emission Level | Limits | Margin | Detector Type |
|----------------|-----------|------------------|--------|-------------------|----------|--------|------------------|
| | (MHz) | (dBuV) | (dB) | (dBuV/m) | (dBuV/m) | (dB) | |
| V | 43.62 | 20.36 | 7.85 | 28.21 | 40 | -11.79 | QP |
| V | 148.65 | 19.65 | 9.57 | 29.22 | 43.5 | -14.28 | QP |
| V | 213.54 | 18.64 | 11.78 | 30.42 | 46 | -15.58 | QP |
| V | 277.16 | 19.87 | 12.28 | 32.15 | 46 | -13.85 | QP |
| V | 357.65 | 16.51 | 13.65 | 30.16 | 46 | -15.84 | QP |
| V | 418.62 | 17.36 | 16.66 | 34.02 | 46 | -11.98 | QP |
| H | 61.57 | 16.58 | 7.86 | 24.44 | 40 | -15.56 | QP |
| H | 176.35 | 20.54 | 10.58 | 31.12 | 43.5 | -12.38 | QP |
| H | 254.17 | 21.15 | 11.38 | 32.53 | 46 | -13.47 | QP |
| H | 368.47 | 20.33 | 14.25 | 34.58 | 46 | -11.42 | QP |
| H | 442.66 | 21.54 | 15.47 | 37.01 | 46 | -8.99 | QP |
| H | 518.54 | 20.75 | 18.94 | 39.69 | 46 | -6.31 | QP |

Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Absolute Level - Limit



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 21 of 41 -

3.2.8 TEST RESULTS (1000 MHz-10th)

| Frequency (MHz) | Reading (dB μ V) | Factor (dB) | Corrected Amplitude (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) | Detector (PK/QP/AV) | Polar (H/V) |
|----------------------------------|----------------------|-------------|------------------------------------|----------------------|-------------|---------------------|-------------|
| Low Channel (2402 MHz)-Above 1G | | | | | | | |
| 4804.12 | 57.61 | 1.58 | 59.19 | 74 | -14.81 | Pk | Vertical |
| 4804.12 | 45.16 | 1.58 | 46.74 | 54 | -7.26 | AV | Vertical |
| 7206.22 | 51.45 | 1.02 | 52.47 | 74 | -21.53 | Pk | Vertical |
| 7206.22 | 42.32 | 1.02 | 43.34 | 54 | -10.66 | AV | Vertical |
| 4804.05 | 50.38 | 0.57 | 50.95 | 74 | -23.05 | Pk | Horizontal |
| 4804.05 | 41.05 | 0.57 | 41.62 | 54 | -12.38 | AV | Horizontal |
| 7206.17 | 46.76 | 0.14 | 46.9 | 74 | -27.1 | Pk | Horizontal |
| 7206.17 | 30.22 | 0.14 | 30.36 | 54 | -23.64 | AV | Horizontal |
| Mid Channel (2440 MHz)-Above 1G | | | | | | | |
| 4880.12 | 55.16 | 1.76 | 56.92 | 74 | -17.08 | Pk | Vertical |
| 4880.12 | 43.61 | 1.76 | 45.37 | 54 | -8.63 | AV | Vertical |
| 7320.37 | 52.72 | 1.15 | 53.87 | 74 | -20.13 | Pk | Vertical |
| 7320.37 | 40.38 | 1.15 | 41.53 | 54 | -12.47 | AV | Vertical |
| 4880.19 | 48.38 | 0.68 | 49.06 | 74 | -24.94 | Pk | Horizontal |
| 4880.19 | 29.38 | 0.68 | 30.06 | 54 | -23.94 | AV | Horizontal |
| 7320.68 | 39.58 | 0.27 | 39.85 | 74 | -34.15 | Pk | Horizontal |
| 7320.68 | 27.65 | 0.27 | 27.92 | 54 | -26.08 | AV | Horizontal |
| High Channel (2480MHz)- Above 1G | | | | | | | |
| 4960.18 | 54.68 | 1.82 | 56.5 | 74 | -17.5 | Pk | Vertical |
| 4960.18 | 42.66 | 1.82 | 44.48 | 54 | -9.52 | AV | Vertical |
| 7440.43 | 51.04 | 1.37 | 52.41 | 74 | -21.59 | Pk | Vertical |
| 7440.43 | 40.57 | 1.37 | 41.94 | 54 | -12.06 | AV | Vertical |
| 4960.08 | 49.37 | 0.74 | 50.11 | 74 | -23.89 | Pk | Horizontal |
| 4960.08 | 30.75 | 0.74 | 31.49 | 54 | -22.51 | AV | Horizontal |
| 7440.21 | 41.72 | 0.46 | 42.18 | 74 | -31.82 | Pk | Horizontal |
| 7440.21 | 33.25 | 0.46 | 33.71 | 54 | -20.29 | AV | Horizontal |





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0908111F
- Page 22 of 41 -

Conducted Spurious Emissions at Antenna Port:


Low Channel






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0908111F
- Page 23 of 41 -





Middle Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0908111F
- Page 24 of 41 -







Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 25 of 41 -


High Channel





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0908111F
- Page 26 of 41 -





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 27 of 41 -

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C&A8.2 | | | | |
|--------------------------------------|------------------------|------------------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247&A8.2 | Power Spectral Density | 8 dBm (in any 3KHz) | 2400-2483.5 | PASS |


4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the RBW \geq 3 kHz.
4. Set the VBW \geq 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.



Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT- 2015SZ0908111F
- Page 28 of 41 -

4.1.5 TEST RESULTS

| | | | |
|---------------|---------------------------|---------------------|-------------|
| EUT : | Budu Blue Button | Model Name : | blue button |
| Temperature : | 25 °C | Relative Humidity : | 56% |
| Pressure : | 1015 hPa | Test Voltage : | DC 3.0V |
| Test Mode : | TX Mode /CH00, CH19, CH39 | | |

Note: The relevant measured result has the offset with cable loss already.

| Frequency | Power Density (dBm/3kHz) | Limit (dBm/3kHz) | Result |
|-----------|-----------------------------|---------------------|--------|
| 2402 MHz | -13.37 | 8 | PASS |
| 2440 MHz | -11.46 | 8 | PASS |
| 2480 MHz | -12.15 | 8 | PASS |





TX CH19



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0908111F
- Page 29 of 41 -





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 30 of 41 -

5. BANDWIDTH TEST


5.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C&A8.2 | | | | |
|--------------------------------------|-----------|------------------------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(a)(2) &A8.2 | Bandwidth | >= 500KHz (6dB bandwidth) | 2400-2483.5 | PASS |

5.1.1 TEST PROCEDURE

According to KDB 558074 D01 DTS Meas Guidance v03r03

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



5.1.2 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 31 of 41 -

5.1.3 TEST RESULTS

| | | | |
|---------------|---------------------------|---------------------|-------------|
| EUT : | Budiu Blue Button | Model Name : | blue button |
| Temperature : | 25 °C | Relative Humidity : | 56% |
| Pressure : | 1012 hPa | Test Voltage : | DC 3.0V |
| Test Mode : | TX Mode /CH00, CH19, CH39 | | |

| Channel | Frequency (MHz) | 6dB bandwidth (kHz) | 99% bandwidth (MHz) | Limit (kHz) | Result |
|---------|-----------------|---------------------|---------------------|-------------|--------|
| Low | 2402 | 717.00 | / | >500 | Pass |
| Middle | 2440 | 721.00 | / | >500 | Pass |
| High | 2480 | 726.00 | / | >500 | Pass |




TX CH 19



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0908111F
- Page 32 of 41 -





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 33 of 41 -

6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES / LIMIT

| FCC Part15 (15.247) , Subpart C &A8.4 | | | | |
|---------------------------------------|-------------------|-----------------|-----------------------|--------|
| Section | Test Item | Limit | Frequency Range (MHz) | Result |
| 15.247(b)(3) &A8.4 | Peak Output Power | 1 watt or 30dBm | 2400-2483.5 | PASS |

6.1.1 TEST PROCEDURE

- The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 34 of 41 -

6.1.5 TEST RESULTS

| | | | |
|---------------|-------------------|---------------------|-------------|
| EUT : | Budiu Blue Button | Model Name : | blue button |
| Temperature : | 25 °C | Relative Humidity : | 60% |
| Pressure : | 1012 hPa | Test Voltage : | DC 3.0V |
| Test Mode : | TX Mode | | |

| TX Mode | | | | |
|--------------|--------------------|---------|--------------------------------|-------|
| Test Channel | Frequency (MHz) | Maximum | Conducted Output Power (PK) | LIMIT |
| | | | (dBm) | dBm |
| CH00 | 2402 | | 0 | 30 |
| CH19 | 2440 | | -0.02 | 30 |
| CH39 | 2480 | | -0.08 | 30 |



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 35 of 41 -

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a)&A1.1 is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a)&A8.5, must also comply with the radiated emission limits specified in §15.209(a) &A1.1 (see §15.205(c)) &A8.5.

TEST PROCEDURE

- a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
- c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
- d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
- e) Repeat above procedures until all measured frequencies were complete.

7.1 DEVIATION FROM STANDARD


No deviation.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 36 of 41 -

7.2 TEST SETUP



7.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 37 of 41 -

7.4 TEST RESULTS

| | | | |
|---------------|-------------------|---------------------|-------------|
| EUT : | Budiu Blue Button | Model Name : | blue button |
| Temperature : | 25 °C | Relative Humidity : | 56% |
| Pressure : | 1012 hPa | Test Voltage : | DC 3.0V |

| Frequency Band | Delta Peak to band emission (dBc) | > Limit (dBc) | Result |
|----------------|-----------------------------------|---------------|--------|
| Left-band | 44.08 | 20 | Pass |
| Right-band | 45.30 | 20 | Pass |

| Frequency (MHz) | Meter Reading (dB μ V) | Factor (dB) | Emission Level (dB μ V/m) | Limits (dB μ V/m) | Margin (dB) | Detector Type | Comment |
|-----------------|----------------------------|-------------|-------------------------------|-----------------------|-------------|---------------|------------|
| 2390 | 49.68 | 1.05 | 50.73 | 74 | -23.27 | peak | Vertical |
| 2390 | 47.35 | 1.05 | 48.4 | 74 | -25.6 | peak | Horizontal |
| 2483.5 | 45.16 | 1.29 | 46.45 | 74 | -27.55 | peak | Vertical |
| 2483.5 | 44.98 | 1.29 | 46.27 | 74 | -27.73 | peak | Horizontal |


Note: Test method to see chapter 3.2 . When PK value is lower than the Average value limit, average not record.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0908111F
- Page 38 of 41 -

Band Edge, Left Side






Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT-2015SZ0908111F
- Page 39 of 41 -

Band Edge, Right Side





Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 40 of 41 -

8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA

The EUT antenna is PCB antenna. It comply with the standard requirement.



Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT- 2015SZ0908111F
- Page 41 of 41 -

9. EUT TEST PHOTO

Radiated Measurement Photos

