

RF exposure evaluation

The RF exposure evaluation was calculated as below:

- 1) The maximum conducted output power is 9.57dBm (9.06mW) at 2462MHz of 802.11g. (2dBi antenna gain, with 2 ceramic antenna gain.)
- 2) For WIFI device or fixed location transmitters, no SAR consideration applied.
- 3) Per KDB 447498 D01v05r02, the 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
-
- The result is rounded to one decimal place for comparison

Channel	Frequency (GHz)	Power (dBm)	Max. Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 11	2.462	9.57	9.06	5	2.84	3.0

- Base on the calculation value, SAR evaluation is not required.
- The public is not exposed to radio frequency energy level in excess of the Commission's guideline.