



198 Kezhu Road, Scientech Park, Guangzhou Economic & Technological
Development District, Guangzhou, China 510663

Telephone: +86 (0) 20 82155555
Fax: +86 (0) 20 82075059
Email: ee.guangzhou@sgs.com

Report No.: GZEM180700437205
Page: 1 of 10

RF Exposure Evaluation Report

Application No.:	GZEM1807004372CR
Applicant:	GUANGZHOU BOSMA TECHNOLOGY CO.,LTD
Address of Applicant:	FL.2&3, Building A5, NO.11 Kai-Yuan AVE., Guangzhou, China
Manufacturer:	The same as Applicant
Address of Manufacturer:	The same as Applicant
Factory:	The same as Applicant
Address of Factory:	The same as Applicant
Equipment Under Test (EUT):	
FCC ID: 2AEZA-DI2018	
EUT Name:	SMART HUB CAMERA
Model No.:	BOSMA X1
Trade Mark:	BOSMA
Date of Receipt:	2018-07-31
Date of Test:	2018-08-08 to 2018-08-22
Date of Issue:	2018-08-24
Test Result:	Pass*

* In the configuration tested, the EUT complied with the standards specified above.



Kobe Jian
EMC Laboratory Manager
The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2018-08-24		Original

Authorized for issue by:			
Tested By	 Curry_Wu /Project Engineer	2018-08-08 to 2018-08-22	Date
Checked By	 Ricky_Liu /Reviewer	2018-08-24	Date

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 GENERAL DESCRIPTION OF EUT	4
4.2 TEST LOCATION	5
4.3 TEST FACILITY	6
4.4 DEVIATION FROM STANDARDS	7
4.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER	7
5 RF EXPOSURE EVALUATION	8
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	8
5.1.1 <i>Limits</i>	8
5.1.2 <i>Test Procedure</i>	8
4.1.3 EUT RF EXPOSURE EVALUATION.....	9

4 General Information

4.1 General Description of EUT

Power Supply:	Model:LX050200U001 INPUT:AC 100-240V 50/60Hz OUTPUT:DC 5V 2A												
Test Voltage:	AC 120V												
Cable:	About 0.8m unscreened USB cable												
WIFI:	<table><tr><td>Antenna Gain</td><td>3dBi</td></tr><tr><td>Antenna Type</td><td>Integral Antenna</td></tr><tr><td>Channel Spacing</td><td>5MHz</td></tr><tr><td>Modulation Type</td><td>802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)</td></tr><tr><td>Number of Channels</td><td>802.11b/g/n(HT20):11 802.11n(HT40):7</td></tr><tr><td>Operation Frequency</td><td>802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz</td></tr></table>	Antenna Gain	3dBi	Antenna Type	Integral Antenna	Channel Spacing	5MHz	Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)	Number of Channels	802.11b/g/n(HT20):11 802.11n(HT40):7	Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Antenna Gain	3dBi												
Antenna Type	Integral Antenna												
Channel Spacing	5MHz												
Modulation Type	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)												
Number of Channels	802.11b/g/n(HT20):11 802.11n(HT40):7												
Operation Frequency	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz												
BT:	<table><tr><td>Antenna Gain</td><td>1.72dBi</td></tr><tr><td>Antenna Type</td><td>Ceramic Antenna</td></tr><tr><td>Channel Spacing</td><td>2MHz</td></tr><tr><td>Modulation Type</td><td>GFSK</td></tr><tr><td>Number of Channels</td><td>40</td></tr><tr><td>Operation Frequency</td><td>2402MHz to 2480MHz</td></tr></table>	Antenna Gain	1.72dBi	Antenna Type	Ceramic Antenna	Channel Spacing	2MHz	Modulation Type	GFSK	Number of Channels	40	Operation Frequency	2402MHz to 2480MHz
Antenna Gain	1.72dBi												
Antenna Type	Ceramic Antenna												
Channel Spacing	2MHz												
Modulation Type	GFSK												
Number of Channels	40												
Operation Frequency	2402MHz to 2480MHz												
915MHz	<table><tr><td>Antenna Type</td><td>Integral</td></tr><tr><td>Antenna Gain</td><td>0dBi</td></tr><tr><td>Number of Channels</td><td>1</td></tr><tr><td>Operation Frequency</td><td>915MHz</td></tr></table>	Antenna Type	Integral	Antenna Gain	0dBi	Number of Channels	1	Operation Frequency	915MHz				
Antenna Type	Integral												
Antenna Gain	0dBi												
Number of Channels	1												
Operation Frequency	915MHz												



SGS-CSTC Standards Technical Services Co., Ltd Guangzhou Branch.

Report No.: GZEM180700437205
Page: 5 of 10

4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,
198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District,
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our NVLAP accreditation.

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2006 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized 2.948 Listed Test Firm(Registration No.: 282399)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399, May 31, 2002.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818, Jul 13, 2017.

- **Industry Canada (Registration No.: 4620B-1)**

The 3m/10m Alternate Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Certification and Engineering of Industry Canada for radio equipment testing with Registration No. 4620B-1.

- **VCCI (Registration No.: R-2460, C-2584, G-449 and T-1179)**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2460, C-2584, G-449 and T-1179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2005, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation

For WIFI

Antenna Gain: 3dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.995 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Lowest	2412	19.30	85.114	0.03378	1.0	PASS

For Bluetooth

Antenna Gain: 1.72dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.49 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
Highest	2480	0.12	1.028	0.00031	1.0	PASS

For 915MHz

Antenna Gain: 2.5dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.78 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency (MHz)	Output Power to Antenna (dBuV/m)	Output Power to Antenna (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
915	87.38	0.6	0.00012	1.0	PASS

BLE and 2.4GHz WIFI and 915MHz modules can simultaneous transmitting, so the maximum rate of MPE is $0.03378/1+0.00031/1+0.00012/1 = 0.03421 \leq 1.0$

According to the KDB447498 section 7.2 determine the device is exclusion from SAR test.

Note: Refer to report No. GZEM180700437201, GZEM180700437202, GZEM180700437203 for EUT test Max Peak Output Power value.



**SGS-CSTC Standards Technical Services Co., Ltd
Guangzhou Branch.**

Report No.: GZEM180700437205
Page: 10 of 10

The distance r calculated from the Fries transmission formula is far greater than 20 cm separation requirement.