

Standalone SAR test exclusion considerations

October 5, 2015

- Device category = Portable device Mobile device
- Transmitting mode = Single Transmitting Simultaneous Transmitting
- Max. transmitting frequency = **2480** MHz
- Min. test separation distance = **200** mm
- Max. Antenna Gain = **4.38** dBi
- Max. power with turn-up tolerance = **10.00** dBm = **10.0** mW (Typical Power = **Max. 10.00** dBm)

Note.

KDB 447498 D01 clause 4.3.1 Step 2-2) SAR test exclusion thresholds for 1500MHz to 6GHz at test separation distances > 50 mm

[Threshold at 50 mm + (test separation distance - 50 mm) X 10] mW

$$= [0.08 + (200\text{mm} - 50\text{mm} \times 10)] = 1500.1$$

Note. The calculation result was rounded to one decimal place for comparison.

→ ***SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.***

Maximum Permissible Exposure(MPE) evaluation for mobile device

$$S = P G / (4 R^2 \pi), \text{ mW/cm}^2$$
$$= 0.005454 \text{ mW/cm}^2$$

S = Maximum power density

P = Maximum power with turn-up tolerance

G = Numeric power gain of the antenna

R = Distance from transmitting antenna

Conclusion: The exposure condition of this device is compliant with FCC rules.

The limit for maximum permissible exposure = **1.000000** mW/cm²