

Brio Sonud Inc.
Floor C, 2 Chung-Yang 1st St, Xindian, New Taipei City, Taiwan

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product
Product description: PartyPro- Karaoke PA System
Model No: BRIO 320
FCC ID: 2AF2HBRIO320

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the Product : Slim Multi-Link Bluetooth Keyboard with Stand will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: HA150667-RA and the accompanying calculations:

According to KDB 447498 D01 General RF Exposure Guidance v05r02, the 1-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances of 50mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] * [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, where}$$

min. test separation distance: 5 mm

Frequency: 2.480 GHz

$(0.3177 \text{ mW}/5\text{mm}) \times \sqrt{2.480\text{GHz}} = 0.100063 < 3$

Result of Calculation:

The result of calculation is far below 3 . Therefore, SAR test is not required.

Company: Brio Sonud Inc.

Address: Floor C, 2 Chung-Yang 1stSt, Xindian, New Taipei City, Taiwan

Date: DEC 08, 2015

By:


Signature