

# TEST REPORT

**FCC ID: 2AF34HD1000**

**Product: Wired Aluminum Selfie Stick**

**Model No.: 99-HD1000-0078**

**Additional Model: ACM15BSS**

**Trade Mark: LONTION**

**Report No.: TCT150918E014**

**Issued Date: Oct. 14, 2015**

Issued for:

**Hongkong Lontion Electronic Limited  
Room 1103, Hangsengmongkok Building, 677 Nathan Road, Mongkok,  
Kowloon, HK**

Issued By:

**Shenzhen Tongce Testing Lab.  
1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China  
TEL: +86-755-27673339  
FAX: +86-755-27673332**

**Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.**

**This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.**

**TABLE OF CONTENTS**

<b>1. Test Certification.....</b>	<b>3</b>
<b>2. Test Result Summary .....</b>	<b>4</b>
<b>3. EUT Description .....</b>	<b>5</b>
<b>4. Genera Information.....</b>	<b>6</b>
4.1. Test environment and mode.....	6
4.2. Description of Support Units.....	6
<b>5. Facilities and Accreditations .....</b>	<b>7</b>
5.1. Facilities .....	7
5.2. Location .....	7
5.3. Measurement Uncertainty.....	7
<b>6. Test Results and Measurement Data .....</b>	<b>8</b>
6.1. Antenna requirement .....	8
6.2. Conducted Emission.....	9
6.3. Conducted Output Power .....	13
6.4. 20dB Occupy Bandwidth .....	16
6.5. Carrier Frequencies Separation .....	19
6.6. Hopping Channel Number .....	22
6.7. Dwell Time.....	24
6.8. Pseudorandom Frequency Hopping Sequence .....	26
6.9. Conducted Band Edge Measurement .....	27
6.10. Conducted Spurious Emission Measurement.....	29
6.11. Radiated Spurious Emission Measurement .....	31

**Appendix A: Photographs of Test Setup****Appendix B: Photographs of EUT**

## 1. Test Certification

<b>Product:</b>	Wired Aluminum Selfie Stick
<b>Model No.:</b>	99-HD1000-0078
<b>Additional Model:</b>	ACM15BSS
<b>Applicant:</b>	Hongkong Lotion Electronic Limited
<b>Address:</b>	Room 1103, Hengsengmongkok Building, 677 Nathan Road, Mongkok, Kowloon, HK
<b>Manufacturer:</b>	Dongguan Lotion Industrial Co.,Ltd
<b>Address:</b>	Block B, Guangcheng Industrial Area, Jianan Road 689#, Shatou Village, Changan Town, Dongguan City, Guangdong, China 523863
<b>Date of Test:</b>	Sep. 18 –Oct. 13, 2015
<b>Applicable Standards:</b>	FCC CFR Title 47 Part 15 Subpart C Section 15.247

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

**Tested By:****Date:** Oct. 13, 2015

Beryl Zhao

**Reviewed By:****Date:** Oct. 14, 2015

Joe Zhou

**Approved By:****Date:** Oct. 14, 2015

Tomsin

## 2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna Requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(1)	PASS
20dB Occupied Bandwidth	§15.247 (a)(1)	PASS
Carrier Frequencies Separation	§15.247 (a)(1)	PASS
Hopping Channel Number	§15.247 (a)(1)	PASS
Dwell Time	§15.247 (a)(1)	PASS
Radiated Emission	§15.205/§15.209	PASS
Band Edge	§15.247(d)	PASS

**Note:**

1. PASS: *Test item meets the requirement.*
2. Fail: *Test item does not meet the requirement.*
3. N/A: *Test case does not apply to the test object.*
4. *The test result judgment is decided by the limit of test standard.*

### 3. EUT Description

<b>Product Name:</b>	Wired Aluminum Selfie Stick
<b>Model :</b>	99-HD1000-0078
<b>Additional Model:</b>	ACM15BSS
<b>Trade Mark:</b>	<b>LONTION</b>
<b>Operation Frequency:</b>	2402MHz~2480MHz
<b>Transfer Rate:</b>	1 Mbits/s
<b>Number of Channel:</b>	79
<b>Modulation Type:</b>	GFSK
<b>Modulation Technology:</b>	FHSS
<b>Antenna Type:</b>	Internal Antenna
<b>Antenna Gain:</b>	2.3dBi
<b>Power Supply:</b>	Rechargeable Li-ion Battery DC3.7V

#### Operation Frequency each of channel for GFSK

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
...	...	...	...	...	...	...	...
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
...	...	...	...	...	...	...	...
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz		-

Remark: Channel 0, 39 & 78 have been tested for GFSK modulation mode.

## 4. General Information

### 4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations
<p>The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y &amp; Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.</p>	

### 4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
Notebook	G485	/	/	Lenovo

#### Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

## 5. Facilities and Accreditations

### 5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 572331

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

- CNAS - Registration No.: CNAS L6165

Shenzhen TCT Testing Technology Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6165.

### 5.2. Location

Shenzhen Tongce Testing Lab

Address: 1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

Tel: 86-755-36638142


### 5.3. Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^\circ\text{C}$
7	Humidity	$\pm 1.0\%$


## 6. Test Results and Measurement Data

### 6.1. Antenna requirement

<b>Standard requirement:</b>	FCC Part15 C Section 15.203 /247(c)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
<p>15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.</p>	
<b>E.U.T Antenna:</b>	
<p>The Bluetooth antenna is an internal antenna which permanently attached, and the best case gain of the antenna is 2.3dBi.</p>	
	

## 6.2. Conducted Emission

### 6.2.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.207														
<b>Test Method:</b>	ANSI C63.4:2014														
<b>Frequency Range:</b>	150 kHz to 30 MHz														
<b>Receiver setup:</b>	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
<b>Limits:</b>	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
<b>Test Setup:</b>	 <p><i>Remark:</i>  <i>E.U.T: Equipment Under Test</i>  <i>LISN: Line Impedance Stabilization Network</i>  <i>Test table height=0.8m</i></p>														
<b>Test Mode:</b>	Reference to item 4.1														
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.</li> </ol>														
<b>Test Result:</b>	PASS														


### 6.2.2. Test Instruments

Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	100139	Nov. 16, 2015
LISN	Schwarzbeck	NSLK 8126	8126453	Nov. 29, 2015
Coax cable	TCT	CE-05	N/A	Nov.15 , 2015
EMI Test Software	Shurples Technology	EZ-EMC	N/A	N/A

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.2.3. Test data

**Please refer to following diagram for individual  
Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)**



Site Chamber #2				Phase:	<b>L1</b>	Temperature:	25 (C)	
Limit: FCC Part 15B Class B Conduction(QP)				Power:	AC 120V/60Hz	Humidity:	56 %	
No.	Mk.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dB	Detector	
1	*	0.1852	41.92	11.48	53.40	64.24	-10.84	QP
2		0.1852	27.15	11.48	38.63	54.24	-15.61	AVG
3		0.2477	35.15	11.44	46.59	61.83	-15.24	QP
4		0.2477	18.99	11.44	30.43	51.83	-21.40	AVG
5		0.3180	32.82	11.40	44.22	59.76	-15.54	QP
6		0.3180	17.81	11.40	29.21	49.76	-20.55	AVG
7		0.4508	26.97	11.32	38.29	56.86	-18.57	QP
8		0.4508	13.47	11.32	24.79	46.86	-22.07	AVG
9		4.8788	24.56	10.65	35.21	56.00	-20.79	QP
10		4.8788	13.26	10.65	23.91	46.00	-22.09	AVG
11		13.9258	18.79	11.52	30.31	60.00	-29.69	QP
12		13.9258	9.94	11.52	21.46	50.00	-28.54	AVG

**Note:**

Freq. = Emission frequency in MHz

Reading level (dB $\mu$ V) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dB $\mu$ V) = Reading level (dB $\mu$ V) + Corr. Factor (dB)

Limit (dB $\mu$ V) = Limit stated in standard


Margin (dB) = Measurement (dB $\mu$ V) – Limits (dB $\mu$ V)

Q.P. = Quasi-Peak

AVG = average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz

**Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)**



Site Chamber #2				Phase:	<b>N</b>	Temperature:	25 (C)	
Limit: FCC Part 15B Class B Conduction(QP)				Power:	AC 120V/60Hz	Humidity:	56 %	
No.	Mk.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dB	Detector	
1	*	0.1812	42.74	11.50	54.24	64.43	-10.19	QP
2		0.1812	24.21	11.50	35.71	54.43	-18.72	AVG
3		0.2398	34.27	11.46	45.73	62.10	-16.37	QP
4		0.2398	13.98	11.46	25.44	52.10	-26.66	AVG
5		0.4742	28.24	11.32	39.56	56.44	-16.88	QP
6		0.4742	8.41	11.32	19.73	46.44	-26.71	AVG
7		4.4375	25.82	10.83	36.65	56.00	-19.35	QP
8		4.4375	14.54	10.83	25.37	46.00	-20.63	AVG
9		8.1406	21.87	11.10	32.97	60.00	-27.03	QP
10		8.1406	12.81	11.10	23.91	50.00	-26.09	AVG
11		12.9022	22.44	11.49	33.93	60.00	-26.07	QP
12		12.9022	14.65	11.49	26.14	50.00	-23.86	AVG

**Note1:**

Freq. = Emission frequency in MHz

Reading level (dB $\mu$ V) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dB $\mu$ V) = Reading level (dB $\mu$ V) + Corr. Factor (dB)

Limit (dB $\mu$ V) = Limit stated in standard

Margin (dB) = Measurement (dB $\mu$ V) – Limits (dB $\mu$ V)

Q.P. =Quasi-Peak AVG =average

\* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

**Note2:**

Measurements were conducted in all three channels (high, middle, low) and modulation (GFSK), and the worst case Mode (Highest channel) was submitted only.

### 6.3. Conducted Output Power

### 6.3.1. Test Specification

### 6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Nov. 15, 2015
RF Cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015


**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

**6.3.3. Test Data**

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	-3.25	21.00	PASS
Middle	-3.91	21.00	PASS
Highest	-3.51	21.00	PASS


**Test plots as follows:**

### Lowest channel




Date: 28.SEP.2015 17:27:39

### Middle channel



Date: 28.SEP.2015 17:27:57


### Highest channel



Date: 28.SEP.2015 17:28:13

## 6.4. 20dB Occupy Bandwidth

### 6.4.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (a)(1)
<b>Test Method:</b>	ANSI C63.10:2013 and DA00-705
<b>Limit:</b>	N/A
<b>Test Setup:</b>	 <p><b>Spectrum Analyzer</b>      <b>EUT</b></p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel; RBW<math>\geq</math>1% of the 20 dB bandwidth; VBW<math>\geq</math>RBW; Sweep = auto; Detector function = peak; Trace = max hold.</li> <li>5. Measure and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS

### 6.4.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Nov. 15, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015


**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

**6.4.3. Test data**

Test channel	20dB Occupy Bandwidth (kHz)	
	GFSK	Conclusion
Lowest	868.59	PASS
Middle	862.18	PASS
Highest	865.38	PASS


**Test plots as follows:**

Lowest channel




Date: 28.SEP.2015 17:34:46

Middle channel



Date: 28.SEP.2015 17:33:44

Highest channel



Date: 28.SEP.2015 17:32:11

## 6.5. Carrier Frequencies Separation

### 6.5.1. Test Specification

### 6.5.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Nov. 15, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

**6.5.3. Test data**


GFSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1001.60	579.06	PASS
Middle	1005.61	579.06	PASS
Highest	1001.60	579.06	PASS

**Note: According to section 6.4**

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	868.59	579.06


**Test plots as follows:**

### Lowest channel



Date: 28.SEP.2015 17:42:12

### Middle channel



Date: 28.SEP.2015 17:48:08


### Highest channel



Date: 28.SEP.2015 17:55:11

## 6.6. Hopping Channel Number

### 6.6.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (a)(1)
<b>Test Method:</b>	ANSI C63.10:2013 and DA00-705
<b>Limit:</b>	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.
<b>Test Setup:</b>	 <p>The diagram illustrates the test setup. A green 'Spectrum Analyzer' is connected via an RF cable to a yellow 'EUT' (Equipment Under Test). A small white box, representing an attenuator, is placed between the two devices. The spectrum analyzer has a central frequency dial and two side knobs. The EUT is a simple rectangular box with a circular port for connection.</p>
<b>Test Mode:</b>	Hopping mode
<b>Test Procedure:</b>	<ol style="list-style-type: none"><li>1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.</li><li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li><li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li><li>4. Enable the EUT hopping function.</li><li>5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW <math>\geq</math> 1% of the span; VBW <math>\geq</math> RBW; Sweep = auto; Detector function = peak; Trace = max hold.</li><li>6. The number of hopping frequency used is defined as the number of total channel.</li><li>7. Record the measurement data derived from spectrum analyzer.</li></ol>
<b>Test Result:</b>	PASS

## 6.6.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Nov. 15, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.6.3. Test data

Mode	Hopping channel numbers	Limit	Result
GFSK	79	15	PASS


Test plots as follows:



Date: 28.SEP.2015 18:01:06

## 6.7. Dwell Time

### 6.7.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (a)(1)
<b>Test Method:</b>	ANSI C63.10:2013 and DA00-705
<b>Limit:</b>	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
<b>Test Setup:</b>	 <p><b>Spectrum Analyzer</b>      <b>EUT</b></p>
<b>Test Mode:</b>	Hopping mode
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Enable the EUT hopping function.</li> <li>5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW<math>\geq</math>RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.</li> <li>6. Measure and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS

### 6.7.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Nov. 15, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.7.3. Test Data


Mode	Packet	Hops Over Occupancy Time (hops)	Package Transfer Time (ms)	Dwell time (second)	Limit (second)	Result
GFSK	DH5	106.67	2.928	0.312	0.4	PASS

**Note:** 1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.

With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to  $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67$  hops

2. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

Test plots as follows:



## 6.8. Pseudorandom Frequency Hopping Sequence

<b>Test Requirement:</b>	<b>FCC Part15 C Section 15.247 (a)(1) requirement:</b>
--------------------------	--


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

<b>EUT Pseudorandom Frequency Hopping Sequence</b>
--


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of Pseudorandom Frequency Hopping Sequence as follow:




Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

## 6.9. Conducted Band Edge Measurement

### 6.9.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (d)
<b>Test Method:</b>	ANSI C63.10:2013 and DA00-705
<b>Limit:</b>	In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.
<b>Test Setup:</b>	 <p style="text-align: center;"><b>Spectrum Analyzer</b>    <b>EUT</b></p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Set RBW = 100 kHz (<math>\geq 1\%</math> span=10MHz), VBW = 300 kHz (<math>\geq</math>RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.</li> <li>4. Enable hopping function of the EUT and then repeat step 2 and 3.</li> <li>5. Measure and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS





## 6.9.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSU	200054	Nov. 15, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.9.3. Test Data

#### GFSK Modulation

Test channel:		Lowest channel	
 <p>RBW 100 kHz Marker 1 (T1) -3.63 dBm VRW 300 kHz Marker 2 (T1) -31.65 dBm SWT 10 ms 2.402041667 GHz</p> <p>Ref 10 dBm Att 10 dB</p> <p>10 Offset 1 dB 0 -10 -20 -30 -40 -50 -60 -70 -80 -90</p> <p>1 PP MAX 0 -10 -20 -30 -40 -50 -60 -70 -80 -90</p> <p>D1 -23.83 dBm</p> <p>Center 2.357 GHz Span 94 MHz</p>		 <p>RBW 100 kHz Marker 1 (T1) -3.70 dBm VRW 300 kHz Marker 2 (T2) -38.16 dBm SWT 10 ms 2.403096154 GHz</p> <p>Ref 10 dBm Att 10 dB</p> <p>10 Offset 1 dB 0 -10 -20 -30 -40 -50 -60 -70 -80 -90</p> <p>1 PP MAX 0 -10 -20 -30 -40 -50 -60 -70 -80 -90</p> <p>D1 -23.7 dBm</p> <p>Start 2.31 GHz Stop 2.404 GHz</p>	
Date: 28.SEP.2015 18:07:07		Date: 28.SEP.2015 18:12:57	
No-hopping mode		Hopping mode	
Test channel:		Highest channel	
 <p>RBW 100 kHz Marker 1 (T1) -4.06 dBm VRW 300 kHz Marker 2 (T1) -58.12 dBm SWT 10 ms 2.479974359 GHz</p> <p>Ref 10 dBm Att 10 dB</p> <p>10 Offset 1 dB 0 -10 -20 -30 -40 -50 -60 -70 -80 -90</p> <p>1 PP MAX 0 -10 -20 -30 -40 -50 -60 -70 -80 -90</p> <p>D1 -24.86 dBm</p> <p>Start 2.478 GHz Stop 2.5 GHz</p>		 <p>RBW 100 kHz Marker 1 (T1) -4.10 dBm VRW 300 kHz Marker 2 (T2) -58.43 dBm SWT 10 ms 2.479987179 GHz</p> <p>Ref 10 dBm Att 10 dB</p> <p>10 Offset 1 dB 0 -10 -20 -30 -40 -50 -60 -70 -80 -90</p> <p>1 PP MAX 0 -10 -20 -30 -40 -50 -60 -70 -80 -90</p> <p>D1 -24.1 dBm</p> <p>Start 2.478 GHz Stop 2.5 GHz</p>	
Date: 28.SEP.2015 18:08:16		Date: 28.SEP.2015 18:10:10	
No-hopping mode		Hopping mode	

## 6.10. Conducted Spurious Emission Measurement

### 6.10.1. Test Specification

### 6.10.2. Test Instruments


RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Dec. 21, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).


### 6.10.3. Test Data

GFSK mode


Lowest Channel



Middle Channel






Highest Channel



## 6.11. Radiated Spurious Emission Measurement

### 6.11.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.209																																							
<b>Test Method:</b>	ANSI C63.4: 2014 and ANSI C63.10: 2013																																							
<b>Frequency Range:</b>	9 kHz to 25 GHz																																							
<b>Measurement Distance:</b>	3 m																																							
<b>Antenna Polarization:</b>	Horizontal & Vertical																																							
<b>Receiver Setup:</b>	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>9kHz- 150kHz</td> <td>Quasi-peak</td> <td>200Hz</td> <td>1kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>150kHz- 30MHz</td> <td>Quasi-peak</td> <td>9kHz</td> <td>30kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>100KHz</td> <td>300KHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td rowspan="2">Above 1GHz</td><td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Remark	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value	Peak	1MHz	10Hz	Average Value						
Frequency	Detector	RBW	VBW	Remark																																				
9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value																																				
150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value																																				
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value																																				
Above 1GHz	Peak	1MHz	3MHz	Peak Value																																				
	Peak	1MHz	10Hz	Average Value																																				
<b>Limit:</b>	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> </tr> </thead> <tbody> <tr> <td>0.009-0.490</td> <td>2400/F(KHz)</td> <td>300</td> </tr> <tr> <td>0.490-1.705</td> <td>24000/F(KHz)</td> <td>30</td> </tr> <tr> <td>1.705-30</td> <td>30</td> <td>30</td> </tr> <tr> <td>30-88</td> <td>100</td> <td>3</td> </tr> <tr> <td>88-216</td> <td>150</td> <td>3</td> </tr> <tr> <td>216-960</td> <td>200</td> <td>3</td> </tr> <tr> <td>Above 960</td> <td>500</td> <td>3</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th>Frequency</th> <th>Field Strength (microvolts/meter)</th> <th>Measurement Distance (meters)</th> <th>Detector</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Above 1GHz</td><td>500</td> <td>3</td> <td>Average</td> </tr> <tr> <td>5000</td> <td>3</td> <td>Peak</td> </tr> </tbody> </table>					Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	0.009-0.490	2400/F(KHz)	300	0.490-1.705	24000/F(KHz)	30	1.705-30	30	30	30-88	100	3	88-216	150	3	216-960	200	3	Above 960	500	3	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector	Above 1GHz	500	3	Average	5000	3	Peak
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)																																						
0.009-0.490	2400/F(KHz)	300																																						
0.490-1.705	24000/F(KHz)	30																																						
1.705-30	30	30																																						
30-88	100	3																																						
88-216	150	3																																						
216-960	200	3																																						
Above 960	500	3																																						
Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector																																					
Above 1GHz	500	3	Average																																					
	5000	3	Peak																																					
<b>Test setup:</b>	<p>For radiated emissions below 30MHz</p>  <p>Distance = 3m</p> <p>Turn table</p> <p>EUT</p> <p>Computer</p> <p>Pre -Amplifier</p> <p>Receiver</p> <p>Ground Plane</p> <p>30MHz to 1GHz</p>																																							



<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<p>1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p>2. For the radiated emission test below 1GHz:          The EUT was placed on a turntable with 1.5 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.</p> <p>For the radiated emission test above 1GHz:          Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT,</p>

	<p>depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.</p> <p>3. Set to the maximum power setting and enable the EUT transmit continuously.</p> <p>4. Use the following spectrum analyzer settings:</p> <ol style="list-style-type: none"> <li>(1) Span shall wide enough to fully capture the emission being measured;</li> <li>(2) Set RBW=100 kHz for <math>f &lt; 1</math> GHz, RBW=1MHz for <math>f &gt; 1</math> GHz ; <math>VBW \geq RBW</math>; Sweep = auto; Detector function = peak; Trace = max hold for peak</li> <li>(3) For average measurement: use duty cycle correction factor method per 15.35(c). Duty cycle = On time/100 milliseconds On time = <math>N1 \cdot L1 + N2 \cdot L2 + \dots + Nn-1 \cdot L_{Nn-1} + Nn \cdot L_n</math> Where <math>N1</math> is number of type 1 pulses, <math>L1</math> is length of type 1 pulses, etc. Average Emission Level = Peak Emission Level + <math>20 \cdot \log(\text{Duty cycle})</math> Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level</li> </ol>
<b>Test results:</b>	PASS

### 6.11.2. Test Instruments


Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
ESPI Test Receiver	ROHDE&SCHW ARZ	ESVD	100008	Nov.16 , 2015
Spectrum Analyzer	ROHDE&SCHW ARZ	FSEM	848597/001	Nov.16 , 2015
Spectrum Analyzer	Agilent	N9020A	MY49100060	Dec. 21, 2015
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Nov.16 , 2015
Pre-amplifier	HP	8447D	2727A05017	Nov.16 , 2015
Loop antenna	ZHINAN	ZN30900A	12024	Dec.14 , 2015
Broadband Antenna	Schwarzbeck	VULB9163	340	Nov.16 , 2015
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Nov.16 , 2015
Horn Antenna	Schwarzbeck	BBHA 9170	373	Nov.16 , 2015
Antenna Mast	CCS	CC-A-4M	N/A	N/A
Coax cable	TCT	RE-low-01	N/A	Nov.15 , 2015
Coax cable	TCT	RE-high-02	N/A	Nov.15 , 2015
Coax cable	TCT	RE-low-03	N/A	Nov.15 , 2015
Coax cable	TCT	RE-high-04	N/A	Nov.15 , 2015
EMI Test Software	Shurples Technology	EZ-EMC	N/A	N/A

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.11.3. Test Data


#### Duty cycle correction factor for average measurement

##### DH5 on time (One Pulse) Plot on Channel 39



Date: 28.SEP.2015 18:03:25

##### DH5 on time (Count Pulses) Plot on Channel 39



Date: 28.SEP.2015 18:04:11


#### Note:

1. Worst case Duty cycle = on time/100 milliseconds =  $(2.920*26+2.282)/100=0.78202$
2. Worst case Duty cycle correction factor =  $20*\log(\text{Duty cycle}) = -2.14\text{dB}$
3. DH5 has the highest duty cycle worst case and is reported.
4. The average levels were calculated from the peak level corrected with duty cycle correction factor (-2.14dB) derived from  $20\log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

Please refer to following diagram for individual

### Below 1GHz

Horizontal:



Site

Polarization: **Horizontal**

Temperature: 23


Limit: FCC Part 15B Class B RE\_3 m

Power: DC 5V

Humidity: 54 %

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table		
			Level	Factor	ment						
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		233.4881	44.20	-10.53	33.67	46.00	-12.33	QP		0	
2	*	266.8394	48.40	-9.38	39.02	46.00	-6.98	QP		0	
3		300.6988	45.93	-8.25	37.68	46.00	-8.32	QP		0	
4		468.1650	36.98	-3.99	32.99	46.00	-13.01	QP		0	
5		665.2610	36.00	-0.59	35.41	46.00	-10.59	QP		0	
6		899.9577	34.53	2.67	37.20	46.00	-8.80	QP		0	

Vertical:



Site

 Polarization: **Vertical**

Temperature: 23

Limit: FCC Part 15B Class B RE\_3 m

Power: DC 5V

Humidity: 54 %

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Antenna	Table	
			Level	Factor	ment					Comment
		MHz	dBuV	dB	dBuV/m	dB	Detector	cm	degree	
1		233.4881	39.69	-10.53	29.16	46.00	-16.84	QP	0	
2		266.8394	41.80	-9.38	32.42	46.00	-13.58	QP	0	
3		300.6988	40.76	-8.25	32.51	46.00	-13.49	QP	0	
4		665.2610	34.54	-0.59	33.95	46.00	-12.05	QP	0	
5	*	827.1794	34.41	1.79	36.20	46.00	-9.80	QP	0	
6		912.6952	32.55	3.10	35.65	46.00	-10.35	QP	0	

**Note:** 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported

2. Measurements were conducted in all three channels (high, middle, low) and modulation (GFSK), and the worst case Mode (Highest channel and GFSK) was submitted only.

**Above 1GHz**

Modulation Type: GFSK									
Low channel: 2402 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
2390	H	46.08	---	-8.23	37.85	---	74	54	-16.15
4804	H	40.55	---	6.59	47.14	---	74	54	-6.86
7206	H	36.64	---	12.87	49.51	---	74	54	-4.49
---	H	---	---	---	---	---	---	---	---
2390	V	41.83	---	-8.23	33.6	---	74	54	-20.40
4804	V	40.13	---	6.59	46.72	---	74	54	-7.28
7206	V	36.82	---	12.87	49.69	---	74	54	-4.31
---	V	---	---	---	---	---	---	---	---

Middle channel: 2441 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
4882	H	38.99	---	7.01	46	---	74	54	-8.00
7323	H	37.21	---	13.21	50.42	---	74	54	-3.58
---	H	---	---	---	---	---	---	---	---
4882	V	39.58	---	7.01	46.59	---	74	54	-7.41
7323	V	37.24	---	13.21	50.45	---	74	54	-3.55
---	V	---	---	---	---	---	---	---	---

High channel: 2480 MHz									
Frequency (MHz)	Ant. Pol. H/V	Peak reading (dB $\mu$ V)	AV reading (dB $\mu$ V)	Correction Factor (dB/m)	Emission Level		Peak limit (dB $\mu$ V/m)	AV limit (dB $\mu$ V/m)	Margin (dB)
					Peak (dB $\mu$ V/m)	AV (dB $\mu$ V/m)			
2483.5	H	42.77	---	-7.52	35.25	---	74	54	-18.75
4960	H	40.24	---	7.44	47.68	---	74	54	-6.32
7440	H	36.4	---	13.54	49.94	---	74	54	-4.06
---	H	---	---	---	---	---	---	---	---
2483.5	V	41.59	---	-7.52	34.07	---	74	54	-19.93
4960	V	40.32	---	7.44	47.76	---	74	54	-6.24
7440	V	35.85	---	13.54	49.39	---	74	54	-4.61
---	V	---	---	---	---	---	---	---	---

**Note:**

1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dB $\mu$ V/m)-Average limit (dB $\mu$ V/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.
5. Data of measurement shown “---” in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.

\*\*\*\*\*END OF REPORT\*\*\*\*\*