

MPE REPORT

Product Name CDMA alarm device w/GPS receiver

Model **DS600**

FCC ID 2AF36-DS600

Mobilelock LLC **Applicant**

Asiatelco Technologies Co Manufacturer

October 21, 2015 Date of issue

Approved by

Director

Revised by

Jiangpeng Lan **SAR Manager**

Performed by

Liang Ye SAR Engineer

Test By

Company: TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China Address:

Contact: Xu Kai

Telephone: +86-021-50791141/2/3

Fax: +86-021-50791141/2/3-8000 Website: http://www.ta-shanghai.com

E-mail: xukai@ta-shanghai.com

Report No.: RXA1507-0128MPE01R1 Page 2 of 5

Maximum Permissible Exposure

Type of EUT: CDMA alarm device w/GPS receiver

FCC ID: 2AF36-DS600

Manufacturer: Asiatelco Technologies Co

Model: DS600

Maximum conducted output power (measured) and antenna Gain:

Band	maximum tune up procedure	
Dana	(dBm)	
CDMA Cellular	24	
CDMA PCS	24.5	
Bluetooth 4.0	2.5	

Band	maximum tune up procedure	Antenna Gain
	(dBm)	(dBi)
CDMA Cellular	24	2
CDMA PCS	24.5	2
Bluetooth 4.0	2.5	2

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

Report No.: RXA1507-0128MPE01R1 Page 3 of 5

TABLE 1 – LIMITS FOR MAXIMUN PERMISSIBLE EXPOSURE (MPE)

Frequency Range	Electric Field	Magnetic Field	Power Density	Averaging Time
(MHz)	Strength	Strength		
2000	(V/m)	(AVm)	(mVV/cm2)	(minutes)
	(A) Limits for Occu	upational/Controlle	d Exposures	
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f2)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f2)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f,__= frequency in MHz

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

⁼ Plane-wave equivalent power density

Report No.: RXA1507-0128MPE01R1 Page 4 of 5

The maximum permissible exposure for 300~1500MHz is f/1500, 1500~100,000MHz is 1.So

Band	The maximum permissible exposure	
CDMA Cellular	0.56 mW/cm ²	
CDMA PCS	1.00 mW/cm ²	
Bluetooth 4.0	1.00 mW/cm ²	

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

Report No.: RXA1507-0128MPE01R1 Page 5 of 5

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided.

This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 865664 D01 is used in the calculation.

Equation from KDB 865664 D01, Edition 97-01 is:

$$S = PG / 4 \square R^2$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

So, the numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G) =10^(antenna gain/10)=10^(2/10)=1.58 dB

CDMA Cellular: PG = 24dBm+ (1.58dB) =25.58dBm=361.41mW

CDMA PCS: PG = 24.5dBm + (1.58dB) = 26.08dBm = 405.51mW

Bluetooth 4.0 PG = 2.5dBm + (1.58dB) = 4.08dBm = 2.56mW

R = 20 cm

 Π = 3.1416

Solving for S, the power density at 20 cm is

Band	Test Result (mW/cm ²)	Limit Value (mW/cm ²)
CDMA Cellular	0.072	0.56 mW/cm ²
CDMA PCS	0.081	1 mW/cm ²
Bluetooth 4.0	0.0005	1 mW/cm ²

Note: For mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.