



## RF exposure Estimation for WPTT

### 1. Introduction

Product:	Kid Power Band
Model no.:	KPB03
FCC ID:	2AF4QKPB03-1727
Options and accessories:	USB Cable
Rating:	DC 3.7V, 70mAh Supplied by Li-ion rechargeable battery DC 5.0V Charged by USB Port
RF Transmission Frequency:	2402MHz-2480MHz
No. of Operated Channel:	40
Modulation:	GFSK
Antenna Type:	Integrated antenna
Antenna Gain:	0dBi
Description of the EUT:	The Equipment Under Test (EUT) is a smart watch which support Bluetooth function operated at 2.4GHz

### 2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

•  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

• Power and distance are rounded to the nearest mW and mm before calculation



- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

### 3. Calculation method

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Conducted Power + tune up tolerance = 0.57mW

Distance = 5 mm

f = 2.440 GHz

$$[0.57/5] * \text{SQRT}(2.440) = 0.18$$

$$0.18 \leq 3.0$$

Therefore, excluded from SAR testing.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Reviewed by:

John Zhi/ Project Manager

Date: 2018-03-05

Prepared By:

Alan Xiong/ Project Engineer

Date: 2018-03-05