# **FCC Test Report**

Report No.: AGC08918170301FE03

**FCC ID** : 2AF6A-Q10

**APPLICATION PURPOSE** : Original Equipment

**PRODUCT DESIGNATION**: mini projector

**BRAND NAME** : N/A

MODEL NAME : Q10, PA01, PA03, H3000, H5000, H6000, AN100, I100,

A1, BPHW01J

**CLIENT** : Guangxi Jiaway Technology Corporation Limited

**DATE OF ISSUE** : June. 1, 2017

STANDARD(S)

TEST PROCEDURE(S)

: FCC Part 15 Rules

**REPORT VERSION**: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

#### **CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



Report No.: AGC08918170301FE03 Page 2 of 31

# **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	June. 1, 2017	Valid	Original Report

# **TABLE OF CONTENTS**

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
2.2. TABLE OF CARRIER FREQUENCY	5
3. MEASUREMENT UNCERTAINTY	6
4. DESCRIPTION OF TEST MODES	6
5. SYSTEM TEST CONFIGURATION	7
5.1. CONFIGURATION OF EUT SYSTEM	7
5.2. EQUIPMENT USED IN EUT SYSTEM	7
5.3. SUMMARY OF TEST RESULTS	7
6. TEST FACILITY	8
7. RADIATED EMISSION	9
7.1TEST LIMIT	9
7.2. MEASUREMENT PROCEDURE	10
7.3. TEST SETUP	12
7.4. TEST RESULT	13
8. BAND EDGE EMISSION	18
8.1. MEASUREMENT PROCEDURE	18
8.2 TEST SETUP	18
8.3 RADIATED TEST RESULT	18
9. 20DB BANDWIDTH	23
9.1. MEASUREMENT PROCEDURE	23
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	23
9.3. MEASUREMENT RESULTS	24
10. FCC LINE CONDUCTED EMISSION TEST	26
10.1. LIMITS OF LINE CONDUCTED EMISSION TEST	26
10.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	26
10.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	27
10.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	27
10.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	28
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	30

Page 4 of 31

### 1. VERIFICATION OF CONFORMITY

Applicant	Guangxi Jiaway Technology Corporation Limited		
Address	Building 5, China-Asean Enterprise headquarters base(Phase 2), No.3 of Headquarters road, Nanning, China		
Manufacturer	Guangxi Jiaway Technology Corporation Limited		
Address	Building 5, China-Asean Enterprise headquarters base(Phase 2), No.3 of Headquarters road, Nanning, China		
Product Designation	mini projector		
Brand Name	N/A		
Test Model	Q10		
Series Model	PA01, PA03, H3000, H5000, H6000, AN100, I100, A1, BPHW01J		
Model Difference	All the same except the model name.		
Date of test	May. 23, 2017~June. 1, 2017		
Deviation	None		
Condition of Test Sample	Normal		
Test Result	Pass		
Report Template	AGCRT-US-BR/RF		

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Tested by

Max Zhang(Zhang Yi)

June. 1, 2017

Reviewed by

Bart Xie(Xie Xiaobin))

Approved by

Solger Zhang(Zhang Hongyi)

Authorized Officer

June. 1, 2017

Page 5 of 31

### 2. GENERAL INFORMATION

### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

	0.400.011.4.0.400.011
Operation Frequency	2.402 GHz to 2.480GHz
Maximum field strength	89.71dBuV/m(AV)@3m
Bluetooth Version	V4.0
Modulation	GFSK for BLE
Number of channels	40
Antenna Gain	0dBi
Antenna Designation	Integrated Antenna (Met 15.203 Antenna requirement)
Hardware Version	V1.0
Software Version	5.90.195.89.13
Power Supply	DC 3.7V by battery or DC 5V by adapter

### 2.2. TABLE OF CARRIER FREQUENCY

**BLE Channel List** 

Frequency Band	Channel Number	Frequency	
	0	2402MHZ	
	1	2404MHZ	
2400~2483.5MHZ	:	:	
	38	2478 MHZ	
	39	2480 MHZ	

Page 6 of 31

### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y  $\pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %  $\circ$ 

No.	Item	Uncertainty
1	Conducted Emission Test	±3.18dB
2	All emissions,radiated	±3.91dB
3	Temperature	±0.5°C
4	Humidity	±2%

# 4. DESCRIPTION OF TEST MODES

Low channel GFSK
Middle channel GFSK
High channel GFSK

#### Note:


- 1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

Page 7 of 31

# **5. SYSTEM TEST CONFIGURATION**

# **5.1. CONFIGURATION OF EUT SYSTEM**

Configure:



### **5.2. EQUIPMENT USED IN EUT SYSTEM**

Item	m Equipment Model No.		ID or Specification	Remark	
1	Mini projector	Q10	2AF6A-Q10	EUT	
2	Adapter	WS2U050-200	AC100-240V 50/60Hz DC5V/1A	Accessory	
3	Battery	PACK(SEC-112990)	DC 3.7V 3300mAh	Accessory	

### **5.3. SUMMARY OF TEST RESULTS**

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249&15.209	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.215	20dB bandwidth	Compliant

Report No.: AGC08918170301FE03 Page 8 of 31

# **6. TEST FACILITY**

Site Dongguan Precise Testing Service Co., Ltd.	
Location  Building D, Baoding Technology Park, Guangming Road2, Dongcheng D Dongguan, Guangdong, China.	
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2014.

# ALL TEST EQUIPMENT LIST

Radiated Emission Test Site						
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration	
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 3, 2016	July 2, 2017	
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 3, 2016	July 2, 2017	
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 3, 2016	July 2, 2017	
RF Cable	SCHWARZBECK	AK9515E	96221	July 3, 2016	July 2, 2017	
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 3, 2016	June 2, 2017	
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A	
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 3, 2016	June 2, 2017	
Spectrum analyzer	Agilent	E4407B	MY46185649	June 3, 2016	June 2, 2017	
Power Sensor	Agilent	U2021XA	MY55050474	June 3, 2016	June 2, 2017	
Horn Antenna (1G-18GHz) SCHWARZ		BBHA9120D	9120D-1246	June 3, 2016	June 2, 2017	
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 3, 2016	June 2, 2017	

Conducted Emission Test Site							
Name of Equipment	Manufacturer	Model Number	Serial Number	Last Calibration	Due Calibration		
EMI Test Receiver	- Rohde & Schwarz	ESCI	101417	July 3, 2016	July 2, 2017		
Artificial Mains Network	Narda	L2-16B	000WX31025	July 3, 2016	July 2, 2017		
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 3, 2016	July 2, 2017		
RF Cable	SCHWARZBECK	AK9515E	96222	July 3, 2016	July 2, 2017		
Shielded Room	CHENGYU	843	PTS-002	July 3, 2016	July 2, 2017		

Page 9 of 31

### 7. RADIATED EMISSION

### 7.1TEST LIMIT

#### Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental	Field Strength of Harmonics		
	(millivolts/meter)	(microvolts/meter)		
900-928MHz	50	500		
2400-2483.5MHz	50	500		
5725-5875MHz	50	500		
24.0-24.25GHz	250	2500		

#### Standard FCC 15.209

Frequency	Distance	Field	Strengths Limit
(MHz)	Meters	μ V/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	
0.490 ~ 1.705	30	24000/F(kHz)	
1.705 ~ 30	30	30	
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(µV)/m	(Peak) 54.0 dB(µV)/m (Average)

Remark:

- (1) Emission level dB $\mu$  V = 20 log Emission level  $\mu$  V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Page 10 of 31

#### 7.2. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use minimum resolution bandwidth of 1 MHz. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Report No.: AGC08918170301FE03 Page 11 of 31

The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
	1GHz~26.5GHz
Start ~Stop Frequency	RBW 1.5MHz/ VBW 5MHz for Peak,
	RBW 1.5MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP


Page 12 of 31

#### 7.3. TEST SETUP


# Radiated Emission Test-Setup Frequency Below 30MHz



#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz



### RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Page 13 of 31


### 7.4. TEST RESULT

### **RADIATED EMISSION BELOW 30MHZ**

No emission found between lowest internal used/generated frequencies to 30MHz.

# **RADIATED EMISSION 30MHz-1GHZ**

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure:	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 1	Polarization :	Horizontal



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		148.0166	22.26	13.25	35.51	43.50	-7.99	peak			
2	Ţ	295.1333	26.72	14.58	41.30	46.00	-4.70	peak			
3	Ţ	367.8833	21.87	18.86	40.73	46.00	-5.27	peak			
4	*	442.2500	21.56	20.35	41.91	46.00	-4.09	peak			
5		479.4331	15.75	20.91	36.66	46.00	-9.34	peak			
6		896.5333	7.22	28.52	35.74	46.00	-10.26	peak		·	

**RESULT: PASS** 

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	<b>20</b> ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 1	Polarization :	Vertical

								Limit:	_
								Margi	in: —
	<u> </u>	3		4	_				
\\	, ii			Ť	5 *	1	6 X		
	1 ///\	1414			hill by the	ו למאלוו	Janhan	l Jun	Mushin
M L.J	W What	ANT No. Jun	₩, , ,	why lit	Malapata	CAN DAIL AND PARTY	A AMPRICA TORK	( Parkey	
	J I MM	l ik ir II dvideni	/ TWANT	T. W					
W ( ' ' ' '   Y	<i>[</i>								
// I									
.000 127.0	0 224	.00 <b>321</b> .	.00 418.	00 515.	.00 612	00 700	.00 806.	nn	1000.00

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	41.3166	26.97	8.81	35.78	40.00	-4.22	peak			
2	İ	173.8831	23.12	14.46	37.58	43.50	-5.92	peak			
3		220.7666	25.97	11.04	37.01	46.00	-8.99	peak			
4		442.2500	15.61	20.35	35.96	46.00	-10.04	peak			
5		589.3667	12.40	22.68	35.08	46.00	-10.92	peak			
6		773.6666	7.94	26.96	34.90	46.00	-11.10	peak			

### **RESULT: PASS**

#### Note:

Factor=Antenna Factor + Cable loss, Margin=Result-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

The mode 1 is the worst case, and only the data of the worst case recorded in this test report.

Page 15 of 31

### **RADIATED EMISSION ABOVE 1GHZ**

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure:	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 1	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
2402.013	103.65	-9.37	94.28	114	-19.72	peak			
2402.013	98.32	-9.37	88.95	94	-5.05	AVG			
4804.026	43.52	3.74	47.26	74	-26.74	peak			
4804.026	38.15	3.74	41.89	54	-12.11	AVG			
7206.039	39.42	8.14	47.56	74	-26.44	peak			
7206.039 34.05 8.14 42.19 54 -11.81 AVG									
Remark:									
actor = Ante	Factor = Antenna Factor + Cable Loss – Pre-amplifier.								

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 1	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
2402.013	102.55	-9.37	93.18	114	-20.82	peak
2402.013	97.31	-9.37	87.94	94	-6.06	AVG
4804.026	43.15	3.74	46.89	74	-27.11	peak
4804.026	37.84	3.74	41.58	54	-12.42	AVG
7206.039	39.05	8.14	47.19	74	-26.81	peak
7206.039	33.81	8.14	41.95	54	-12.05	AVG
Remark:						
Cotor - Anto	nna Factor + C	abla Laga Di	o amplifior			

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Report No.: AGC08918170301FE03 Page 16 of 31

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 2	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
2440.016	103.52	-9.63	93.89	114	-20.11	peak
2440.016	98.34	-9.63	88.71	94	-5.29	AVG
4880.032	43.17	3.76	46.93	74	-27.07	peak
4880.032	37.52	3.76	41.28	54	-12.72	AVG
7320.048	39.15	8.17	47.32	74	-26.68	peak
7320.048 33.85 8.17 42.02 54 -11.98 AVG						
Remark:						
Factor = Antenna Factor + Cable Loss – Pre-amplifier.						

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 2	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
2440.016	102.44	-9.63	92.81	114	-21.19	peak
2440.016	97.28	-9.63	87.65	94	-6.35	AVG
4880.032	43.25	3.76	47.01	74	-26.99	peak
4880.032	37.61	3.76	41.37	54	-12.63	AVG
7320.048	7320.048 38.54 8.17 46.71 74 -27.29 peak					
7320.048 33.51 8.17 41.68 54 -12.32 AVG						
Remark:						
Factor = Ante	Factor = Antenna Factor + Cable Loss – Pre-amplifier.					

Page 17 of 31

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 3	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
2480.021	104.64	-9.61	95.03	114	-18.97	peak
2480.021	99.32	-9.61	89.71	94	-4.29	AVG
4960.042	44.15	3.83	47.98	74	-26.02	peak
4960.042	38.64	3.83	42.47	54	-11.53	AVG
7440.063	39.52	8.21	47.73	74	-26.27	peak
7440.063 34.18 8.21 42.39 54 -11.61 AVG						
Remark:						
Factor = Ante	-actor = Antenna Factor + Cable Loss – Pre-amplifier.					

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 3	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
2480.021	103.55	-9.61	93.94	114	-20.06	peak
2480.021	98.42	-9.61	88.81	94	-5.19	AVG
4960.042	43.58	3.83	47.41	74	-26.59	peak
4960.042	38.16	3.83	41.99	54	-12.01	AVG
7440.063	38.42	8.21	46.63	74	-27.37	peak
7440.063 33.23 8.21 41.44 54 -12.56 AVG						
Remark:						
Factor = Ante	-actor = Antenna Factor + Cable Loss – Pre-amplifier.					

**Note:** Other emission from 8G to 25 GHz are considered as ambient noise. No recording in the test report. Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Page 18 of 31


#### 8. BAND EDGE EMISSION

#### **8.1. MEASUREMENT PROCEDURE**

- 1. The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
- (b) AVERAGE: RBW=1MHz; VBW=1/on time(1KHz) / Sweep=AUTO
- 3. Other procedures refer to clause 7.2.

#### **8.2 TEST SETUP**

#### RADIATED EMISSION TEST SETUP



#### **8.3 RADIATED TEST RESULT**

#### Note:

- 1. Factor=Antenna Factor + Cable loss Amplifier gain. Field Strength=Factor + Reading level
- 2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB( $\mu$ V) to represent the Amplitude. Use the F dB( $\mu$ V/m) to represent the Field Strength. So A=F.

EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 1	Polarization :	Horizontal

PK Value



**AV Value** 



EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 1	Polarization :	Vertical

#### PK Value




**AV Value** 



EUT:	MINI PROJECTOR	Model Name	Q10
Temperature:	20 ℃	Relative Humidtity:	48%
Pressure :	1010 hPa	Test Voltage :	Normal Voltage
Test Mode :	Mode 3	Polarization :	Horizontal

PK Value



**AV Value** 



Report No.: AGC08918170301FE03 Page 22 of 31

EUT:	MINI PROJECTOR	Model Name	Q10	
Temperature:	20 ℃	Relative Humidtity:	48%	
Pressure :	1010 hPa	Test Voltage :	Normal Voltage	
Test Mode :	Mode 3	Polarization :	Vertical	

PK Value



**AV Value** 




Page 23 of 31

#### 9. 20DB BANDWIDTH

#### 9.1. MEASUREMENT PROCEDURE

- 1. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- 2. The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- 3. Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level.
- 4. Set SPA Trace 1 Max hold, then View.

### 9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



Page 24 of 31

#### 9.3. MEASUREMENT RESULTS

TEST ITEM	20DB BANDWIDTH
TEST MODULATION	GFSK for BLE

Test Data (MHz)	Criteria			
Low Channel	1.133	PASS		
Middle Channel	1.128	PASS		
High Channel	1.128	PASS		

#### TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



Page 26 of 31

### 10. FCC LINE CONDUCTED EMISSION TEST


#### 10.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Francisco	Maximum RF Line Voltage							
Frequency	Q.P.( dBuV)	Average( dBuV)						
150kHz~500kHz	66-56	56-46						
500kHz~5MHz	56	46						
5MHz~30MHz	60	50						

#### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

### 10.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



Page 27 of 31

#### 10.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.

- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN..
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

#### 10.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.


# 10.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

# LINE CONDUCTED EMISSION TEST-L



No.	No. Freq.		Reading_Level (dBuV)		Correct Measurement Factor (dBuV)		Limit (dBuV)		Margin (dB)		P/F	Comment		
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1940	43.39		30.40	10.21	53.60		40.61	63.86	53.86	-10.26	-13.25	Р	
2	0.2620	37.78		19.69	10.27	48.05		29.96	61.36	51.36	-13.31	-21.40	Р	
3	0.4140	34.40		18.42	10.34	44.74		28.76	57.57	47.57	-12.83	-18.81	Р	
4	0.4980	34.66		11.85	10.40	45.06		22.25	56.03	46.03	-10.97	-23.78	Р	
5	0.7780	32.82		16.07	10.30	43.12		26.37	56.00	46.00	-12.88	-19.63	Р	
6	1.2740	32.07		11.96	10.38	42.45		22.34	56.00	46.00	-13.55	-23.66	Р	

# LINE CONDUCTED EMISSION TEST-N




No. Freq.				Correct Factor	1		Limit (dBuV)		Margin (dB)		P/F	Comment		
	(MHz)	Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1980	47.74		37.15	10.21	57.95		47.36	63.69	53.69	-5.74	-6.33	Р	
2	0.2620	40.83		30.26	10.27	51.10		40.53	61.36	51.36	-10.26	-10.83	Р	
3	0.3379	39.27		27.73	10.31	49.58		38.04	59.25	49.25	-9.67	-11.21	Р	
4	0.4260	36.69		22.37	10.35	47.04		32.72	57.33	47.33	-10.29	-14.61	Р	
5	0.7460	35.60		19.37	10.32	45.92		29.69	56.00	46.00	-10.08	-16.31	Р	
6	1.2740	33.68		15.07	10.38	44.06		25.45	56.00	46.00	-11.94	-20.55	Р	


**RESULT: PASS** 

# **APPENDIX A: PHOTOGRAPHS OF TEST SETUP**

FCC RADIATED EMISSION TEST SETUP BELOW 1GHZ



FCC RADIATED EMISSION TEST SETUP ABOVE 1GHZ



# FCC LINE CONDUCTED EMISSION TEST SETUP



----END OF REPORT----