



## FCC §15.247 (i), §2.1091 – RF Exposure

FCC ID: 2AF6VPERSONAL

### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

#### Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                   | 6  |
| 3.0-30                | 1842 / f                          | 4.89 / f                          | (900 / f)*                               | 6  |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | 6  |
| 300-1500              |                                   |                                   | F/300                                    | 6  |
| 1500-100,000          |                                   |                                   | 5  | 6  |

Note: f is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

#### Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                   | 30   |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                 | 30   |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | 30   |
| 300-1500              |                                   |                                   | F/1500                                   | 30   |
| 1500-100,000          |                                   |                                   | 1.0                                      | 30   |

Note: f = frequency in MHz

\* = Plane-wave equivalent power density

#### IEEE 802.11b

*max possible output power (AV,conducted) : 7±1dbm*

#### IEEE 802.11g

*max possible output power (AV,conducted) : 6±1dbm*

#### IEEE 802.11n(20/40)

*max possible output power (AV,conducted) : 5±1dbm*

*The max possible output power (AV,conducted) of All (IEEE 802.11b , IEEE 802.11g, IEEE 802.11n) is IEEE 802.11b.*



## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

## Test Result of RF Exposure Evaluation

|         | Target power W/ tolerance (dBm) | Max tune up power tolerance (dBm) | Total Output power to antenna (mW) | Antenna Gain(dBi) | Total Power Density at R=20cm (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) | Result |
|---------|---------------------------------|-----------------------------------|------------------------------------|-------------------|---|-----------------------------|--------|
| 802.11b | 7±1.0                           | 8.0                               | 6.31                               | 2.1<br>(1.622)    | 0.00203   | 1.0                         | Pass   |