



FCC Part 15, Subpart C, Section 15.247

Test Report

On

Outdoor Wifi Connected Home Security Camera
FCC ID: 2AF77-H1663003

Customer Name: Immedia Semiconductor

Customer P.O: 1003

Date of Report: March 9, 2017

Test Report No: R-6173N-1

Test Start Date: February 14, 2017

Test Finish Date: February 17, 2017

Test Technician: M. Seamans

Report Approved By: S. Wentworth

Report Prepared By: J. Ramsey

Our letters, procedures and reports are for the exclusive use of the customer to whom they are addressed and their communication or the use of the name of Retlif Testing Laboratories must receive our prior written approval. Our letters, procedures and reports apply only to the sample tested and are not necessarily indicative of the qualities of apparently identical or similar products. The letters, procedures and reports and the name of Retlif Testing Laboratories or insignia are not to be used under any circumstances in advertising to the general public. This test report shall not be reproduced, except in full, without the written approval of Retlif Testing Laboratories.

Technical Information

Report Number: R-6173N-1

Customer: Immedia Semiconductor

Address: 100 Burtt Road, Suite 100
Andover, MA 01810

Manufacturer: Immedia Semiconductor

Manufacturer Address: 100 Burtt Road, Suite 100
Andover, MA 01810

Test Sample: Outdoor Wifi Connected Home Security Camera

Model Number: BCM00600U

Serial Numbers: 670-000-043

FCC ID: 2AF77-H1663003

Type: Frequency Hopping Spread Spectrum Transmitter

Power Requirements: 5VDC via 120 VAC, 60 Hz AC/DC Power Adapter

Power Supply: AC Adapter, Sunun, Model: SA68-050100U

Frequency of Operation: 902.3 MHz to 927.6 MHz

Equipment Class: DSS

Antenna Type: Internal PCB Antenna – 2.0 dBi gain

Equipment Use: Used in a Home Monitoring System

Test Specification:

FCC Rules and Regulations Part 15, Subpart C, Section 15.247

Test Procedure:

ANSI C63.4:2014

ANSI C63.10:2013



Retlif Testing Laboratories

Report No. R-6173N-1

Test Facility:

Retlif Testing Laboratories
101 New Boston Road
Goffstown, NH 03045

FCC Registered Test Site Number: 90899

Table 1 – Tests Performed

FCC Part 15, Subpart C	Test Method
15.247(a)(1)	Channel Separation
15.247(a)(1)	20 dB Bandwidth
15.247(a)(1)(i)	Number of Channels and Occupancy Time
15.247(b)(2) and (4)	Peak Conducted Output Power
15.247(d)	Spurious Emissions, 30 MHz to 10 GHz
15.247(a)/15.209(a)	Field Strength of Spurious Emissions
15.207(a)	Conducted Emissions, Power Leads, 150 kHz to 30 MHz

Table 2 – Support Equipment

Description	Manufacturer	Model Number	Serial Number
Laptop PC	Toshiba	Satellite P55-A	00179-60817-80261-AA0EM
Sync Module	Immedia Semiconductor	BSM00200U	260-100-957
Test Board	Texas Instruments	CC31XXEMUB00ST	EM-400514-NA5000974
iPod	Apple	A1574	CCQQP2SWGGK4
Wireless Router	ASUS	RT-N66U	G51A08005445
Laptop PC	Lenovo	80Q7	PFOFMVOB



Retlif Testing Laboratories

Report No. R-6173N-1

Certification and Signatures

We certify that this report is a true representation of the results obtained from the tests of the equipment stated. We further certify that the measurements shown in this report were made in accordance with the procedures indicated and vouch for the qualifications of all Retlif Testing Laboratories personnel taking them.



Scott Wentworth
Branch Manager
NVLAP Approved Signatory



Todd Hannemann
EMC Test Engineer
iNARTE Certified ATL-0255-T

Non-Warranty Provision

The testing services have been performed, findings obtained and reports prepared in accordance with generally accepted laboratory principles and practices. This warranty is in lieu of all others, either expressed or implied.

Non-Endorsement

This test report contains only findings and results arrived at after employing the specific test procedures and standards listed herein. It is not intended to constitute a recommendation, endorsement or certification of the product or material tested. This test report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.



Retlif Testing Laboratories

Report No. R-6173N-1

Revision History

Revisions to this document are listed below; the latest revised document supersedes all previous issues of this document:

Revision	Date	Pages Affected
-	March 9, 2017	Original Release



Retlif Testing Laboratories

Report No. R-6173N-1

Requirements and Test Results

Requirement:

FCC Section 15.247 (a)(1)

Channel Separation and 20 dB Bandwidth

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- **Results:**

The carrier frequencies were separated by 404.53 kHz which exceeded the maximum 20 dB bandwidth of 404.5 kHz which complies with the requirements specified above.



Retlif Testing Laboratories

Report No. R-6173N-1

Requirements and Test Results (con't)

FCC Section 15.247 (a)(1)(i)

Number of Channels and Occupancy Time

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500.0 kHz.

- Results:**

The number of hopping frequencies used was 64 and the average time of occupancy was 360.7 msec which complied with the above requirements.



Retlif Testing Laboratories

Report No. R-6173N-1

Requirements and Test Results (con't)

FCC Section 15.247 (b)(2) and (4) Peak Conducted Output Power

(2) For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under Paragraph (a)(1)(i) of this section 15.247.

(4) The conducted output power limit specified in Paragraph (b) of Section 15.247 is based on the use of antenna with directional gains that do not exceed 6 dBi. Except as shown in Paragraph (c) of Section 15.247, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in Paragraph (b)(1), (b)(2) and (b)(3) of Section 15.247, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

- **Results:**

The frequency hopping system utilizes a transmitting antenna with a gain of 2.0 dBi. The maximum peak conducted output power was measured to be 22.387 milliwatts and the EIRP is less than 1W.



Retlif Testing Laboratories

Report No. R-6173N-1

Requirements and Test Results (con't)

FCC Section 15.247 (d)

Spurious Emissions

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under Paragraph (b)(3) of Section 15.247, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

- **Results:**

The antenna port conducted spurious emissions comply with the requirement that the radio frequency power be at least 20 dB below the highest in band level.

In addition, Harmonic and Spurious Emissions which were found to be within the restricted bands of operation, as defined in section 15.205 (a) were found to be in compliance with the general limits specified in section 15.209 (a).



Retlif Testing Laboratories

Report No. R-6173N-1

Requirements and Test Results (con't)

FCC Section 15.247 (a)

Field Strength of Spurious Radiation

Operation under the provisions of Section 15.247 is limited to frequency hopping and digitally modulated intentional radiators that comply with the provisions stated in Section 15.247(a)(1).

FCC Section 15.209(a)

Radiated Emission Limits, General Requirements

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 3.

Table 3 - Radiated Emission Limits

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 to 88	100	3
88 to 216	150	3
216 to 960	200	3
Above 960	500	3

- Results:**

The field strength of spurious radiated emissions did not exceed the limits specified in Table 3.



Retlif Testing Laboratories

Report No. R-6173N-1

Field Strength Calculation/Conversion:

The maximized field strength of the emission was obtained as follows:

$$C_R = M_R + C_F$$

Where:

C_R = Corrected Reading in dB μ V/m

M_R = Uncorrected Meter Reading in dB μ V

C_F = Correction Factor in dB (Antenna Factor, Pre-amp + Cable Loss)

Example:

$$M_R = 15.35 \text{ dB}\mu\text{V}$$

$$C_F = 16.85 \text{ dB}$$

$$C_R = 15.35 \text{ dB}\mu\text{V} + 16.85 = 32.2 \text{ dB}\mu\text{V/m}$$

dB μ V/M is converted to uV/M for comparison to the specified limit using the formula:

$$\text{invLog dB}\mu\text{V/M}/20$$

$$32.2 \text{ dB}\mu\text{V/m} = 40.74 \text{ uV/m}$$

RF Power Conversion:

Power readings in dBm may be converted to mW using the formula:

$$\text{InvLog dBm}/10$$

$$\text{Example: } 20 \text{ dBm} = 100 \text{ mW}$$



Retlif Testing Laboratories

Report No. R-6173N-1

Requirements and Test Results (con't)

FCC Section 15.247 (i)

RF Exposure Limits

Spread Spectrum Transmitters operating under 15.247 must be operated in a manner that ensures the public is not exposed to RF energy levels in excess of the commission's guidelines. Based on the transmitter power and maximum antenna gain (see calculation below) the minimum separation distance was calculated to determine the distance for acceptable MPE power density levels to meet both the Occupational/Controlled Exposure and the General Population/Uncontrolled Exposure requirements of FCC Part 1.1310. The calculation below uses the more stringent General Population MPE Limits.

$$S = \frac{PG}{4\pi Dsq}$$

D = Minimum Separation Distance in cm

S = Max allowed Power Density in mW/cmsq

Per 1.1310 For the Frequency of 928 MHz $S = 928 / 1500 = 0.618 \text{ mW/cmsq}$

Power = Max Power Input to Antenna = 22.39 mW

Gain = Max Power Gain of Antenna = 2.0 dBi = 1.58 numeric

$$0.618 \text{ mW/cmsq} = \frac{22.39 \times 1.58}{4 \times (3.14) \times D^2} = \frac{35.48}{12.56 \times D^2}$$

$$D^2 = \frac{35.48}{12.56 \times 0.618}$$

$$D = \sqrt{1.74} = 1.32 \text{ cm}$$

The test sample has an internal antenna and the minimum separation distance will always be maintained.



Retlif Testing Laboratories

Report No. R-6173N-1

Requirement:

FCC Section 15.207(a) - Conducted Limits

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits shown in Table 4, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of the paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Table 4 - Conducted Emission Limits

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

*Decreases due to logarithm of the frequency

- Results:**

The conducted emissions observed did not exceed the limits specified in Table 4.



Retlif Testing Laboratories

Report No. R-6173N-1

Equipment List

FCC Section 15.247(a)(1) Channel Separation

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5135	NARDA MICROWAVE ATTENUATOR, COAXIAL		10 dB, DC - 12.4 GHz	757C-10	11/23/2016	11/30/2017
R469	AGILENT / HP	ANALYZER, SPECTRUM	100 Hz - 26.5 GHz	E7405A;A	12/1/2016	12/31/2017

FCC Section 15.247(a)(1) 20 dB Bandwidth

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5135	NARDA MICROWAVE ATTENUATOR, COAXIAL		10 dB, DC - 12.4 GHz	757C-10	11/23/2016	11/30/2017
R469	AGILENT / HP	ANALYZER, SPECTRUM	100 Hz - 26.5 GHz	E7405A;A	12/1/2016	12/31/2017

FCC Section 15.247 (a)(1) (i) (i) Number of Channels and Occupancy Time

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5135	NARDA MICROWAVE ATTENUATOR, COAXIAL		10 dB, DC - 12.4 GHz	757C-10	11/23/2016	11/30/2017
R469	AGILENT / HP	ANALYZER, SPECTRUM	100 Hz - 26.5 GHz	E7405A;A	12/1/2016	12/31/2017

FCC Section 15.247 (b)(2) Peak Conducted Output Power

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5070	ROHDE & SCHWARZ	RECEIVER, EMI	20 Hz - 40 GHz	ESIB40	10/21/2016	10/31/2017
5135	NARDA MICROWAVE ATTENUATOR, COAXIAL		10 dB, DC - 12.4 GHz	757C-10	11/23/2016	11/30/2017

FCC Section 15.247 (d) Conducted Spurious Emissions, 30 MHz to 10 GHz

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5135	NARDA MICROWAVE ATTENUATOR, COAXIAL		10 dB, DC - 12.4 GHz	757C-10	11/23/2016	11/30/2017
R469	AGILENT / HP	ANALYZER, SPECTRUM	100 Hz - 26.5 GHz	E7405A;A	12/1/2016	12/31/2017



Retlif Testing Laboratories

Report No. R-6173N-1

**FCC Section 15.247 (a) / 15.209(a)
Field Strength of Spurious Radiated Emissions**

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
1232	AGILENT / HP	PRE-AMPLIFIER	1 - 26.5 GHz	8449B	6/16/2016	6/30/2017
3258	ETS / EMCO	ANTENNA, DOUBLE RIDGED GUIDE	1 - 18 GHz	3115	10/13/2016	4/30/2018
3427B	ETS / EMCO	ANTENNA, BICONICAL	20 - 200 MHz	3104	2/5/2016	8/31/2017
4029B	RETLIF	OPEN AREA TEST SITE, ATTENUATION	3 / 10 Meters	RNH	4/13/2016	4/30/2018
443	ELECTRO-METRICS	ANTENNA, LOG PERIODIC	200 MHz - 1000 MHz	LPA-25	10/6/2016	4/30/2018
5135	NARDA MICROWAVE	ATTENUATOR, COAXIAL	10 dB, DC - 12.4 GHz	757C-10	11/23/2016	11/30/2017
R469	AGILENT / HP	ANALYZER, SPECTRUM	100 Hz - 26.5 GHz	E7405A;A	12/1/2016	12/31/2017

**FCC Section 15.207 (a)
AC Line Conducted Emissions**

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5135	NARDA MICROWAVE	ATTENUATOR, COAXIAL	10 dB, DC - 12.4 GHz	757C-10	11/23/2016	11/30/2017
5209	SOLAR ELECTRONICS	LISN	50 uH, 150 kHz - 30 MHz	21106-50-BP-25-BNC	3/23/2016	3/31/2017
5210	SOLAR ELECTRONICS	LISN	50 uH, 150 kHz - 30 MHz	21106-50-BP-25-BNC	3/23/2016	3/31/2017
R469	AGILENT / HP	ANALYZER, SPECTRUM	100 Hz - 26.5 GHz	E7405A;A	12/1/2016	12/31/2017



Retlif Testing Laboratories

Report No. R-6173N-1

Test Photographs Channel Separation



Test Setup



Retlif Testing Laboratories

Report No. R-6173N-1

FCC Section 15.247(a)(1)
Channel Separation
Test Data





Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

Test Method:	Channel Carrier Frequency Separation		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting hopping frequency data		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (a)(1)		
Technician	M. Seamans	Date	February 14 th , 2017
Climatic Conditions	Temp: 18.8 °C Relative Humidity: 20.4 %		
Notes	Channel Carrier Frequency Separation: 404.53 kHz		

 Agilent 14:17:36 Feb 14, 2017



**Test Photographs
20 dB Bandwidth**



Test Setup



Retlif Testing Laboratories

Report No. R-6173N-1

**FCC Section 15.247(a)(1)
20 dB Bandwidth
Test Data**




Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

Test Method:	20dB Bandwidth		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (a)(1)(i)		
Technician	M. Seamans	Date	February 14 th , 2017
Climatic Conditions	Temp: 20.1 °C Relative Humidity: 19.2 %		
Notes	Transmit Frequency: 902.4 MHz 20dB Bandwidth: 404.5 kHz		


 **Agilent** 12:37:45 Feb 14, 2017



RETLIF TESTING LABORATORIES

Test Method:	20dB Bandwidth		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (a)(1)(i)		
Technician	M. Seamans	Date	February 14 th , 2017
Climatic Conditions	Temp: 20.1 °C Relative Humidity: 19.2 %		
Notes	Transmit Frequency: 915.2 MHz 20dB Bandwidth: 401.0 kHz		


 **Agilent** 12:43:20 Feb 14, 2017



RETLIF TESTING LABORATORIES

Test Method:	20dB Bandwidth		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (a)(1)(i)		
Technician	M. Seamans	Date	February 14 th , 2017
Climatic Conditions	Temp: 20.1 °C Relative Humidity: 19.2 %		
Notes	Transmit Frequency: 927.6 MHz 20dB Bandwidth: 401.0 kHz		

Agilent 12:47:36 Feb 14, 2017



Test Photographs
Number of Channels and Occupancy Time



Test Setup



Retlif Testing Laboratories

Report No. R-6173N-1

**FCC Section 15.247 (a)(1)(i)
Number of Channels and Occupancy Time
Test Data**



Retlif Testing Laboratories

Report No. R-6173N-1

**Number of Hopping Frequencies
Test Data**




Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

Test Method:	Number of Hopping Frequencies		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Part Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting hopping frequency data		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (a)(1)(i)		
Technician	M. Seamans	Date	February 14 th , 2017
Climatic Conditions	Temp: 20.1 °C Relative Humidity: 19.2 %		
Notes	Number of Hopping Frequencies: 64		

 **Agilent** 15:05:43 Feb 14, 2017



**Time of Occupancy
Test Data**




Retlif Testing Laboratories

Report No. R-6173N-1


RETLIF TESTING LABORATORIES

Test Method:	Time of Occupancy		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting hopping frequency data		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (a)(1)(i)		
Technician	M. Seamans	Date	February 14 th , 2017
Climatic Conditions	Temp: 21.5 °C Relative Humidity: 19.1 %		
Notes	Test Frequency: 902.4 MHz Pulse Width: 360.7 ms		

 Agilent 16:15:38 Feb 14, 2017



**Test Photographs
Peak Conducted Output Power**



Test Setup



Retlif Testing Laboratories

Report No. R-6173N-1

**FCC Section 15.247 (a)(1)
Peak Conducted Output Power
Test Data**




Retlif Testing Laboratories

Report No. R-6173N-1


RETLIF TESTING LABORATORIES

Test Method	Peak Power Output		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (b)(3)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 21.1 °C Relative Humidity: 19.0 %		
Notes	Transmit Frequency: 902.4 MHz Peak Power Output: 13.50 dBm (22.387mW)		




RETLIF TESTING LABORATORIES

Test Method	Peak Power Output		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C	Paragraph: 15.247 (b)(3)	
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 21.1 °C Relative Humidity: 19.0 %		
Notes	Transmit Frequency: 916 MHz Peak Power Output: 13.30 dBm (21.380mW)		



RETLIF TESTING LABORATORIES

Test Method	Peak Power Output		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (b)(3)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 21.1 °C Relative Humidity: 19.0 %		
Notes	Transmit Frequency: 927.5 MHz Peak Power Output: 13.03dBm (20.091mW)		



**Test Photographs
Conducted Spurious Emissions, 30 MHz to 10 GHz**



Test Setup



Retlif Testing Laboratories

Report No. R-6173N-1

**Unwanted Emissions into Non-Restricted Frequency Bands
25 MHz to 10 GHz
Conducted Spurious Emissions Test Data**




Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

Test Method	Unwanted Emissions into Non-Restricted Frequency Bands		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C	Paragraph: 15.247 (d)	
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 17.9 °C	Relative Humidity: 22.3 %	
Notes	Transmit Frequency: 902.4 MHz	Limit is 20dB down from the Fundamental Frequency Peak Power Density (100kHz)	


Agilent 10:43:02 Feb 15, 2017



RETLIF TESTING LABORATORIES

Test Method	Unwanted Emissions into Non-Restricted Frequency Bands		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (d)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 17.9 °C Relative Humidity: 22.3 %		
Notes	Transmit Frequency: 902.4 MHz	Limit is 20dB down from the Fundamental Frequency Peak Power Density (100kHz)	


Agilent 10:50:50 Feb 15, 2017



RETLIF TESTING LABORATORIES

Test Method	Unwanted Emissions into Non-Restricted Frequency Bands		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (d)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 17.9 °C Relative Humidity: 22.3 %		
Notes	Transmit Frequency: 915 MHz	Limit is 20dB down from the Fundamental Frequency Peak Power Density (100kHz)	


Agilent 10:59:01 Feb 15, 2017



RETLIF TESTING LABORATORIES

Test Method	Unwanted Emissions into Non-Restricted Frequency Bands		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (d)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 17.9 °C Relative Humidity: 22.3 %		
Notes	Transmit Frequency: 915 MHz Limit is 20dB down from the Fundamental Frequency Peak Power Density (100kHz)		


Agilent 10:53:24 Feb 15, 2017



RETLIF TESTING LABORATORIES

Test Method	Unwanted Emissions into Non-Restricted Frequency Bands		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (d)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 17.9 °C Relative Humidity: 22.3 %		
Notes	Transmit Frequency: 927.5 MHz	Limit is 20dB down from the Fundamental Frequency Peak Power Density (100kHz)	


Agilent 11:07:10 Feb 15, 2017



RETLIF TESTING LABORATORIES

Test Method	Unwanted Emissions into Non-Restricted Frequency Bands		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (d)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 17.9 °C Relative Humidity: 22.3 %		
Notes	Transmit Frequency: 927.5 MHz	Limit is 20dB down from the Fundamental Frequency Peak Power Density (100kHz)	

Agilent 11:16:23 Feb 15, 2017



**Band Edge Emissions Conducted
Test Data**




Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

Test Method	Band Edge Emissions Conducted		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (d)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 17.9 °C	Relative Humidity:	22.3 %
Notes	Transmit Frequency: 902.4 MHz		


 Agilent 11:25:59 Feb 15, 2017



RETLIF TESTING LABORATORIES

Test Method	Band Edge Emissions Conducted		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U	Serial No.	670-000-043
Operating Mode	Transmitting modulated signal		
Test Specification	FCC Part 15, Subpart C Paragraph: 15.247 (d)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 17.9 °C	Relative Humidity:	22.3 %
Notes	Transmit Frequency: 927.5 MHz		

 **Agilent** 11:18:45 Feb 15, 2017



**Test Photographs
Field Strength of Spurious Emissions**



Test Configuration



Retlif Testing Laboratories

Report No. R-6173N-1

**Test Photographs
Field Strength of Spurious Emissions**



Horizontal Antenna Polarization, 30 MHz – 200 MHz



Vertical Antenna Polarization, 30 MHz – 200 MHz



Retlif Testing Laboratories

Report No. R-6173N-1

Test Photographs
Field Strength of Spurious Emissions



Horizontal Antenna Polarization, 200 MHz – 1 GHz



Vertical Antenna Polarization, 200 MHz – 1 GHz



Retlif Testing Laboratories

Report No. R-6173N-1

Test Photographs
Field Strength of Spurious Emissions



Horizontal Antenna Polarization, 1 GHz – 10 GHz



Vertical Antenna Polarization, 1 GHz – 10 GHz



Retlif Testing Laboratories

Report No. R-6173N-1

**FCC Section 15.247 (a) / 15.209(a)
Field Strength of Spurious Emissions
Test Data**



Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands	
Customer	Immedia Semiconductor, Inc.	
Job Number	R-6173N-1	
Test Sample	Outdoor WiFi Connected Home Security Camera	
Model Number	BCM00600U	
Serial Number	670-000-043	
Test Specification	FCC Part 15 Subpart C	Paragraph: 15.247(d)
Operating Mode	Transmitting hopping frequency data at 902.37 MHz, 914.76 MHz and 927.59 MHz consecutively.	
Technician	M. Seamans	
Date	February 17 th , 2017	
Notes: Antenna Test Distance: 3 meters Detector: Quasi-Peak <1GHz, Average >1GHz		

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
37.50	-	-	-	-			-	100.00
	38.00	9.40	14.20	23.60	*		15.14	I
38.25	-	-	-	-			-	100.00
73.00	-	-	-	-			-	100.00
	74.00	16.94	8.36	25.30	*		18.41	I
74.60	-	-	-	-			-	100.00
74.80	-	-	-	-			-	100.00
	75.00	13.54	8.36	21.90	*		12.45	
75.20	-	-	-	-			-	100.00
108.00	-	-	-	-			-	150.00
	110.00	7.88	10.02	17.90	*		7.85	
	-	-	-	-			-	
121.94	-	-	-	-			-	150.00
123.00	-	-	-	-			-	150.00
	125.00	12.76	9.44	22.20	*		12.88	
	-	-	-	-			-	
138.00	-	-	-	-			-	150.00

EUT emissions observed throughout the given frequency spectrum were recorded and evaluated. Emission levels closest to the limit are listed on this data sheet. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).

Data Sheet 1 of 7



Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands	
Customer	Immedia Semiconductor, Inc.	
Job Number	R-6173N-1	
Test Sample	Outdoor WiFi Connected Home Security Camera	
Model Number	BCM00600U	
Serial Number	670-000-043	
Test Specification	FCC Part 15 Subpart C	Paragraph: 15.247(d)
Operating Mode	Transmitting hopping frequency data at 902.37 MHz, 914.76 MHz and 927.59 MHz consecutively.	
Technician	M. Seamans	
Date	February 17 th , 2017	
Notes: Antenna Test Distance: 3 meters Detector: Quasi-Peak <1GHz, Average >1GHz		

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
149.90	-	-	-	-			-	150.00
	150.00	6.93	11.17	18.10	*		8.04	
150.05	-	-	-	-			-	150.00
156.52	-	-	-	-			-	150.00
	156.52	4.12	12.08	16.20	*		6.46	
156.52	-	-	-	-			-	150.00
156.70	-	-	-	-			-	150.00
	156.80	3.78	12.12	15.90	*		6.24	
156.90	-	-	-	-			-	150.00
162.01	-	-	-	-			-	150.00
	165.00	4.92	12.68	17.60	*		7.59	
167.17	-	-	-	-			-	150.00
167.72	-	-	-	-			-	150.00
	170.00	6.10	12.80	18.90	*		8.81	
173.20	-	-	-	-			-	150.00

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum.

* This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).

Data Sheet 2 of 7



Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands	
Customer	Immedia Semiconductor, Inc.	
Job Number	R-6173N-1	
Test Sample	Outdoor WiFi Connected Home Security Camera	
Model Number	BCM00600U	
Serial Number	670-000-043	
Test Specification	FCC Part 15 Subpart C	Paragraph: 15.247(d)
Operating Mode	Transmitting hopping frequency data at 902.37 MHz, 914.76 MHz and 927.59 MHz consecutively.	
Technician	M. Seamans	
Date	February 17 th , 2017	

Notes: Antenna Test Distance: 3 meters Detector: Quasi-Peak <1GHz, Average >1GHz

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
240.00	-	-	-	-			-	200.00
	269.392	9.15	16.85	26.00			19.95	
285.00	-	-	-	-			-	200.00
322.80	-	-	-	-			-	200.00
	330.00	4.19	18.91	23.10	*		14.29	
335.40	-	-	-	-			-	200.00
399.90	-	-	-	-			-	200.00
	405.00	-0.99	21.49	20.50	*		10.59	
410.00	-	-	-	-			-	200.00
608.00	-	-	-	-			-	200.00
	611.00	-3.34	27.34	24.00	*		15.85	
614.00	-	-	-	-			-	200.00
960.00	-	-	-	-			-	500.00
	975.00	1.00	32.10	33.10	*		45.19	
1240.00	-	-	-	-			-	500.00
1300.00	-	-	-	-			-	500.00
	1350.00	34.92	-9.50	25.42	*		18.66	
1427.00	-	-	-	-			-	500.00

EUT emissions observed throughout the given frequency spectrum were recorded and evaluated. Emission levels closest to the limit are listed on this data sheet. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).

Data Sheet 3 of 7



Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands		
Customer	Immedia Semiconductor, Inc.		
Job Number	R-6173N-1		
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U		
Serial Number	670-000-043		
Test Specification	FCC Part 15 Subpart C		
Operating Mode	Transmitting hopping frequency data at 902.37 MHz, 914.76 MHz and 927.59 MHz consecutively.		
Technician	M. Seamans		
Date	February 17 th , 2017		

Notes: Antenna Test Distance: 3 meters Detector: Quasi-Peak <1GHz, Average >1GHz

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
1435.00	-	-	-	-			-	500.00
	1500.00	36.62	-9.40	27.22	*		22.96	
1646.50	-	-	-	-			-	500.00
1660.00	-	-	-	-			-	500.00
	1680.00	36.61	-9.04	27.58	*		23.93	
1710.00	-	-	-	-			-	500.00
1718.80	-	-	-	-			-	500.00
	1720.00	36.51	-8.64	27.87	*		24.75	
1722.20	-	-	-	-			-	500.00
2200.00	-	-	-	-			-	500.00
	2250.00	42.48	-6.76	35.72			61.09	
2300.00	-	-	-	-			-	500.00
2310.00	-	-	-	-			-	500.00
	2360.00	41.33	-6.51	34.82			55.08	
2390.00	-	-	-	-			-	500.00
2483.50	-	-	-	-			-	500.00
	2490.00	42.94	-6.11	36.83			69.42	
2500.00	-	-	-	-			-	500.00

EUT emissions observed throughout the given frequency spectrum were recorded and evaluated. Emission levels closest to the limit are listed on this data sheet. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).

Data Sheet 4 of 7



Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands	
Customer	Immedia Semiconductor, Inc.	
Job Number	R-6173N-1	
Test Sample	Outdoor WiFi Connected Home Security Camera	
Model Number	BCM00600U	
Serial Number	670-000-043	
Test Specification	FCC Part 15 Subpart C	Paragraph: 15.247(d)
Operating Mode	Transmitting hopping frequency data at 902.37 MHz, 914.76 MHz and 927.59 MHz consecutively.	
Technician	M. Seamans	
Date	February 17 th , 2017	
Notes: Antenna Test Distance: 3 meters	Detector: Quasi-Peak <1GHz, Average >1GHz	

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
2690.00	-	-	-	-			-	500.00
	2707.20	34.84	-5.40	29.44	*		29.65	
	2745.00	34.27	-5.40	28.87	*		27.77	
	2782.50	35.02	-5.40	29.62	*		30.27	
2900.00	-	-	-	-			-	500.00
3260.00	-	-	-	-			-	500.00
	3263.00	34.47	-3.30	31.17	*		36.18	
3267.00	-	-	-	-			-	500.00
3332.00	-	-	-	-			-	500.00
	3336.00	34.98	-3.10	31.88	*		39.26	
3339.00	-	-	-	-			-	500.00
3345.00	-	-	-	-			-	500.00
	3350.00	34.65	-3.05	31.60	*		38.02	
3358.00	-	-	-	-			-	500.00
3600.00	-	-	-	-			-	500.00
	3609.60	34.67	-1.50	33.17	*		45.55	
	3660.00	34.41	-1.25	33.16	*		45.50	
	3708.00	34.25	-1.05	33.20	*		45.71	

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum.

* This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).

Data Sheet 5 of 7



Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands		
Customer	Immedia Semiconductor, Inc.		
Job Number	R-6173N-1		
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model Number	BCM00600U		
Serial Number	670-000-043		
Test Specification	FCC Part 15 Subpart C		
Operating Mode	Transmitting hopping frequency data at 902.37 MHz, 914.76 MHz and 927.59 MHz consecutively.		
Technician	M. Seamans		
Date	February 17 th , 2017		

Notes: Antenna Test Distance: 3 meters Detector: Quasi-Peak <1GHz, Average >1GHz

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
	-	-	-	-			-	
4400.00	-	-	-	-			-	500.00
4500.00	-	-	-	-			-	500.00
	4512.00	33.30	0.05	33.35	*		46.51	
	4575.00	33.97	0.05	34.02	*		50.23	
	4637.50	34.18	0.20	34.38	*		52.86	
	-	-	-	-			-	
5150.00	-	-	-	-			-	500.00
5350.00	-	-	-	-			-	500.00
	5400.00	34.34	1.05	35.39	*		58.82	
5460.00	-	-	-	-			-	500.00
7250.00	-	-	-	-			-	500.00
	7500.00	35.42	3.75	39.17	*		90.89	
7750.00	-	-	-	-			-	500.00
8025.00	-	-	-	-			-	500.00
	8121.60	34.77	4.20	38.97	*		88.82	
	8235.00	34.64	4.30	38.64	*		85.54	
	8347.50	34.62	4.40	39.02	*		89.33	
	-	-	-	-			-	
8500.00	-	-	-	-			-	500.00

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum.

* This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).

Data Sheet 6 of 7



Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

UNINTENDED TEST DATA SHEET	
Test Method	Unwanted Emissions into Restricted Frequency Bands
Customer	Immedia Semiconductor, Inc.
Job Number	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera
Model Number	BCM00600U
Serial Number	670-000-043
Test Specification	FCC Part 15 Subpart C
Operating Mode	Transmitting hopping frequency data at 902.37 MHz, 914.76 MHz and 927.59 MHz consecutively.
Technician	M. Seamans
Date	February 17 th , 2017

Notes: Antenna Test Distance: 3 meters Detector: Quasi-Peak <1GHz, Average >1GHz

TEST PARAMETERS

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum.

* This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).

Data Sheet 7 of 7



Retrif Testing Laboratories

Report No. R-6173N-1

**Test Photographs
AC Line Conducted Emissions**



Test Configuration



Test Setup



Retlif Testing Laboratories

Report No. R-6173N-1

**FCC Section 15.207 (a)
AC Line Conducted Emissions
Test Data**




Retlif Testing Laboratories

Report No. R-6173N-1

RETLIF TESTING LABORATORIES

Test Method	Conducted Emissions 150 kHz to 30 MHz		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model No.	BCM00600U	Serial No.	670-000-043
Operating Mode	Live streaming video		
Test Specification	FCC Part 15. 207(a)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 23.2 °C	Relative Humidity: 19.7 %	
Lead Tested	120 VAC 60 Hz Hot	Peak Readings to Average Limits.	

Agilent 13:51:17 Feb 15, 2017



RETLIF TESTING LABORATORIES

Test Method	Conducted Emissions 150 kHz to 30 MHz		
Customer	Immedia Semiconductor, Inc.	Job No.	R-6173N-1
Test Sample	Outdoor WiFi Connected Home Security Camera		
Model No.	BCM00600U	Serial No.	670-000-043
Operating Mode	Live streaming video		
Test Specification	FCC Part 15. 207(a)		
Technician	M. Seamans	Date	February 15 th , 2017
Climatic Conditions	Temp: 23.2 °C Relative Humidity: 19.7 %		
Lead Tested	120 VAC 60 Hz Neutral Peak Readings to Average Limits.		

 **Agilent** 13:53:08 Feb 15, 2017

