



FCC Part 15, Subpart C, Section 15.247
Test Report

On

Blink Indoor/Outdoor Camera
FCC ID: 2AF77-H2041670

Customer Name: Immedia Semiconductor, LLC

Customer P.O.: 2D-03495230

Date of Report: July 15, 2020

Test Report No: R-6521H-1

Test Start Date: June 23, 2020

Test Finish Date: June 30, 2020

Test Engineer: T. Hannemann

Test Technician: M. Seamans

Approved By: S. Wentworth

Report Prepared By: D. Hull



Our letters, procedures and reports are for the exclusive use of the customer to whom they are addressed and their communication or the use of the name of Retlif Testing Laboratories must receive our prior written approval. Our letters, procedures and reports apply only to the sample tested and are not necessarily indicative of the qualities of apparently identical or similar products. The letters, procedures and reports and the name of Retlif Testing Laboratories or insignia are not to be used under any circumstances in advertising to the general public. This test report shall not be reproduced, except in full, without the written approval of Retlif Testing Laboratories.



40 YEARS OF TESTING EXCELLENCE

Technical Information

Report Number: R-6521H-1

Customer: Immedia Semiconductor, LLC

Address: 100 Riverpark Drive
North Reading, MA 01864

Manufacturer: Immedia Semiconductor, LLC

Manufacturer Address: 100 Riverpark Drive
North Reading, MA 01864

Test Sample: Blink Indoor/Outdoor Camera

Model Number: BCM00400U*
G8T1-GH00-0205-00KW (Conducted Testing)

Serial Number: G8T1-GH00-0205-0089 (Radiated Testing)

FCC ID: 2AF77- H2041670

Type: Frequency Hopping Spread Spectrum Transmitter
5 VDC via External 120 VAC power adapter or 3 VDC via internal batteries

Power Requirements:

Frequency of Operation: 902.4 MHz to 927.6 MHz

Equipment Class: DSS

Antenna Type: Internal PCB Antenna – 1.5 dBi Gain

Equipment Use: Used in a Home Monitoring System

Test Specification:

FCC Rules and Regulations Part 15, Subpart C, Section 15.247

*Note: The testing included in this test report is representative of Model Number: BCM00400U and Model Number: BCM00410U. The two models are electrically identical. The differences between these two models is the plastic external enclosure.

Test Procedure:

ANSI C63.4:2014

ANSI C63.10:2013

FCC 558074 D01 15.247 Meas Guidance v05r02, April 2, 2019

Test Facility:

Retlif Testing Laboratories

101 New Boston Road

Goffstown, NH 03045

FCC Designation Number: US5327



Retlif Testing Laboratories

Report No. R-6521H-1

Tests Performed

FCC Part 15, Subpart C	Test Method
15.247(a)(1)	Channel Separation
15.247(a)(1)	20 dB Bandwidth
15.247(a)(1)(i)	Number of Channels and Occupancy Time
15.247(b)(2) and (4)	Peak Conducted Output Power
15.247(d)	Spurious Emissions, 30 MHz to 10 GHz
15.247(d)	Field Strength of Spurious Emissions
Section 15.207 (a)	Conducted Emissions

EUT Operation:

The EUT is an outdoor Wi-Fi connected home security camera. The camera has a passive infrared motion sensor that can be used to trigger recording of video clips that are sent by Wi-Fi to internet based servers that relay the clips to the users' mobile device. The EUT can also receive commands from the user to start transmission of video or update status via 915 MHz FHSS radio.

Table 1 – Support Equipment

Description	Manufacturer	Model Number	Serial Number
Radiated Testing			
Blink Sync Module	Immedia Semiconductor	BSM00201U	244-148-306
iPad Tablet	Apple, Inc.	A1B22	FNVX7010HLF9
Conducted Testing			
Laptop PC	HP	Probook 450G5	5CD88466QTY
Sync Module	Immedia Semiconductor	BSM00203U	280-885-766



Retlif Testing Laboratories

Report No. R-6521H-1

Certification and Signatures

We certify that this report is a true representation of the results obtained from the tests of the equipment stated. We further certify that the measurements shown in this report were made in accordance with the procedures indicated and vouch for the qualifications of all Retlif Testing Laboratories personnel taking them.



Scott Wentworth
Branch Manager



Todd Hannemann
EMC Test Engineer
iNARTE Certified Technician ATL-0255-T

Non-Warranty Provision

The testing services have been performed, findings obtained and reports prepared in accordance with generally accepted laboratory principles and practices. This warranty is in lieu of all others, either expressed or implied.

Non-Endorsement

This test report contains only findings and results arrived at after employing the specific test procedures and standards listed herein. It is not intended to constitute a recommendation, endorsement or certification of the product or material tested. This report must not be used by the client to claim product endorsement by ANSI National Accreditation Board (ANAB).



Retlif Testing Laboratories

Report No. R-6521H-1

Revision History

Revisions to this document are listed below; the latest revised document supersedes all previous issues of this document:

Revision	Date	Pages Affected
-	July 15, 2020	Original Release



Retlif Testing Laboratories

Report No. R-6521H-1

Requirements and Test Results

Requirement:

FCC Section 15.247 (a)(1)

Channel Separation and 20 dB Bandwidth

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

- Results:**

The carrier frequencies were separated by 401.8 kHz which exceeded the maximum 20 dB bandwidth of 115.430 kHz which complies with the requirements specified above.

FCC Section 15.247 (a)(1)(i)

Number of Channels and Occupancy Time

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

- Results:**

The number of hopping frequencies used was 64 and the average time of occupancy was 9.619 msec which complied with the above requirements.



Retlif Testing Laboratories

Report No. R-6521H-1

Requirements and Test Results (con't)

FCC Section 15.247 (b)(2) and (4)

Peak Conducted Output Power

(1) For frequency hopping systems operating in the 902-928 MHz band employing at least 50 non-overlapping hopping channels: 1 watt. For systems employing less than 50 hopping channels, but at least 25 hopping channels: 0.25 watts.

(4) The conducted output power limit specified in Paragraph (b) of Section 15.247 is based on the use of antenna with directional gains that do not exceed 6 dBi. Except as shown in Paragraph (c) of Section 15.247, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in Paragraph (b)(1), (b)(2) and (b)(3) of Section 15.247, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

- Results:**

The frequency hopping system utilizes a transmitting antenna with a gain of 1.5 dBi. The maximum peak conducted output power was measured to be 16.98 milliwatts and the EIRP is less than 1W.

FCC Section 15.247 (d)

Spurious Emissions

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under Paragraph (b)(3) of Section 15.247, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a) must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

- Results:**

The antenna port conducted spurious emissions comply with the requirement that the radio frequency power be at least 20 dB below the highest in band level.

In addition, Harmonic and Spurious Emissions which were found to be within the restricted bands of operation, as defined in section 15.205 (a) were found to be in compliance with the general limits specified in section 15.209 (a).



Retlif Testing Laboratories

Report No. R-6521H-1

Requirements and Test Results (con't)

FCC Section 15.247 (a)

Field Strength of Spurious Radiation

Operation under the provisions of Section 15.247 is limited to frequency hopping and digitally modulated intentional radiators that comply with the provisions stated in Section 15.247(a)(1).

FCC Section 15.209(a)

Radiated Emission Limits, General Requirements

Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 3.

Table 2 - Radiated Emission Limits

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 to 88	100	3
88 to 216	150	3
216 to 960	200	3
Above 960	500	3

- Results:**

The field strength of spurious radiated emissions did not exceed the limits specified in Table 3.



Retlif Testing Laboratories

Report No. R-6521H-1

Field Strength Calculation/Conversion:

The maximized field strength of the emission was obtained as follows:

$$C_R = M_R + C_F$$

Where:

C_R = Corrected Reading in dB μ V/m

M_R = Uncorrected Meter Reading in dB μ V

C_F = Correction Factor in dB (Antenna Factor, Pre-amp + Cable Loss)

Example:

$$M_R = 15.35 \text{ dB}\mu\text{V}$$

$$C_F = 16.85 \text{ dB}$$

$$C_R = 15.35 \text{ dB}\mu\text{V} + 16.85 = 32.2 \text{ dB}\mu\text{V/m}$$

dB μ V/M is converted to uV/M for comparison to the specified limit using the formula:

$$\text{invLog dB}\mu\text{V/M}/20$$

$$32.2 \text{ dB}\mu\text{V/m} = 40.74 \text{ uV/m}$$

RF Power Conversion:

Power readings in dBm may be converted to mW using the formula:

$$\text{InvLog dBm}/10$$

$$\text{Example: } 20 \text{ dBm} = 100 \text{ mW}$$



Retlif Testing Laboratories

Report No. R-6521H-1

Requirements and Test Results (con't)

FCC Section 15.247 (i)

RF Exposure Limits

Spread Spectrum Transmitters operating under 15.247 must be operated in a manner that ensures the public is not exposed to RF energy levels in excess of the commission's guidelines. Based on the transmitter power and maximum antenna gain (see calculation below) the minimum separation distance was calculated to determine the distance for acceptable MPE power density levels to meet both the Occupational/Controlled Exposure and the General Population/Uncontrolled Exposure requirements of FCC Part 1.1310. The calculation below uses the more stringent General Population MPE Limits.

$$S = \frac{PG}{4\pi Dsq}$$

D = Minimum Separation Distance in cm

S = Max allowed Power Density in mW/cmsq

Per 1.1310 For the Frequency of 915 MHz S = 0.6 mW/cmsq

Power = Max Power Input to Antenna = 16.98mW

Gain = Max Power Gain of Antenna = 1.5 dBi = 1.41 numeric

$$0.61 \text{ mW/cmsq} = \frac{16.98 \times 1.41}{4 \times (3.14) \times D^2} = \frac{23.94}{12.56 \times D^2}$$

$$D^2 = \frac{23.94}{12.56 \times 0.61}$$

$$D = \sqrt{1.16} = 1.08 \text{ cm}$$

The test sample has an internal antenna and the minimum separation distance will always be maintained.



Retlif Testing Laboratories

Report No. R-6521H-1

Requirement:

FCC Section 15.207(a) - Conducted Limits

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits shown in Table 4, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of the paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Table 3 - Conducted Emission Limits

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15 to 0.5	66 to 56*	56 to 46*
0.5 to 5	56	46
5 to 30	60	50

*Decreases due to logarithm of the frequency

• **Results:**

The conducted emissions observed did not exceed the limits specified in Table 4.



Retlif Testing Laboratories

Report No. R-6521H-1

Equipment List

FCC Section 15.247(a)(1) Channel Separation

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5070	ROHDE & SCHWARZ	RECEIVER, EMI	20 Hz - 40 GHz	ESIB40	1/23/2020	1/31/2021
5134	NARDA MICROWAVE	ATTENUATOR, COAXIAL	10 dB, DC - 12.4 GHz, 2 W	757C-10	12/13/2019	12/31/2020
5229	FLORIDA RS TECHNOLOGY	CABLE, COAXIAL	DC - 40 GHz	FLRST-2.92 (102ö)	11/1/2019	11/30/2020
5250	DIGI-SENSE	HYGROMETER	0 - 50 deg. c, 10 - 90 % RH	20250-30	10/7/2019	10/31/2020

FCC Section 15.247(a)(1) 20 dB Bandwidth

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5070	ROHDE & SCHWARZ	RECEIVER, EMI	20 Hz - 40 GHz	ESIB40	1/23/2020	1/31/2021
5134	NARDA MICROWAVE	ATTENUATOR, COAXIAL	10 dB, DC - 12.4 GHz, 2 W	757C-10	12/13/2019	12/31/2020
5229	FLORIDA RS TECHNOLOGY	CABLE, COAXIAL	DC - 40 GHz	FLRST-2.92 (102ö)	11/1/2019	11/30/2020
5250	DIGI-SENSE	HYGROMETER	0 - 50 deg. c, 10 - 90 % RH	20250-30	10/7/2019	10/31/2020

FCC Section 15.247 (a)(1) (iii) Number of Channels and Occupancy Time

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5070	ROHDE & SCHWARZ	RECEIVER, EMI	20 Hz - 40 GHz	ESIB40	1/23/2020	1/31/2021
5134	NARDA MICROWAVE	ATTENUATOR, COAXIAL	10 dB, DC - 12.4 GHz, 2 W	757C-10	12/13/2019	12/31/2020
5229	FLORIDA RS TECHNOLOGY	CABLE, COAXIAL	DC - 40 GHz	FLRST-2.92 (102ö)	11/1/2019	11/30/2020
5250	DIGI-SENSE	HYGROMETER	0 - 50 deg. c, 10 - 90 % RH	20250-30	10/7/2019	10/31/2020

FCC Section 15.247 (a)(1) Peak Conducted Output Power

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5070	ROHDE & SCHWARZ	RECEIVER, EMI	20 Hz - 40 GHz	ESIB40	1/23/2020	1/31/2021
5134	NARDA MICROWAVE	ATTENUATOR, COAXIAL	10 dB, DC - 12.4 GHz, 2 W	757C-10	12/13/2019	12/31/2020
5229	FLORIDA RS TECHNOLOGY	CABLE, COAXIAL	DC - 40 GHz	FLRST-2.92 (102ö)	11/1/2019	11/30/2020
5250	DIGI-SENSE	HYGROMETER	0 - 50 deg. c, 10 - 90 % RH	20250-30	10/7/2019	10/31/2020



Retlif Testing Laboratories

Report No. R-6521H-1

FCC Section 15.247 (d)
Conducted Spurious Emissions, 30 MHz to 10 GHz

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5070	ROHDE & SCHWARZ	RECEIVER, EMI	20 Hz - 40 GHz	ESIB40	1/23/2020	1/31/2021
5134	NARDA MICROWAVE	ATTENUATOR, COAXIAL	10 dB, DC - 12.4 GHz, 2 W	757C-10	12/13/2019	12/31/2020
5229	FLORIDA RS TECHNOLOGY	CABLE, COAXIAL	DC - 40 GHz	FLRST-2.92 (102ö)	11/1/2019	11/30/2020
5250	DIGI-SENSE	HYGROMETER	0 - 50 deg. c, 10 - 90 % RH	20250-30	10/7/2019	10/31/2020

FCC Section 15.247 (a) / 15.209(a)
Field Strength of Spurious Radiated Emissions

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
1232	AGILENT / HP	PRE-AMPLIFIER	1 - 26.5 GHz	8449B	5/8/2020	5/31/2021
3258	ETS / EMCO	ANTENNA, DOUBLE RIDGED GUIDE	1 - 18 GHz	3115	12/2/2019	6/30/2021
3427B	ETS / EMCO	ANTENNA, BICONICAL	20 - 200 MHz	3104	4/25/2019	10/31/2020
4029B	RETLIF	OPEN AREA TEST SITE, ATTENUATION	3 / 10 Meters	RNH	9/30/2019	9/30/2021
443	ELECTRO-METRICS	ANTENNA, LOG PERIODIC	200 MHz - 1000 MHz	LPA-25	12/13/2019	6/29/2021
5070	ROHDE & SCHWARZ	RECEIVER, EMI	20 Hz - 40 GHz	ESIB40	1/23/2020	1/31/2021
5179B	MICRO-COAX	CABLE, COAXIAL	10 kHz - 18 GHz	UFB311A-1-036050U50U	11/6/2019	11/30/2020
5188	Cybertron	COMPUTER, CONTROL	N/A	TSVQJA2221	No Calibration Required	
5211	COM-POWER	GENERATOR, COMB	1 MHz - 1 GHz	CGO-501	5/22/2020	5/31/2021
5234	PASTERNACK	CABLE, COAXIAL	10 kHz - 18 GHz	PE302-230	8/14/2019	8/31/2020
5242	TELEDYNE MICROWAVE	CABLE, COAXIAL	10 kHz - 6 GHz	PR90-195-1275, 106'	9/12/2019	9/30/2020

FCC Section 15.207(a)
Conducted Limit

EN	Manufacturer	Description	Range	Model No.	Cal Date	Due Date
5070	ROHDE & SCHWARZ	RECEIVER, EMI	20 Hz - 40 GHz	ESIB40	1/23/2020	1/31/2021
5133	NARDA MICROWAVE	ATTENUATOR, COAXIAL	10 dB, DC - 12.4 GHz, 2 W	757C-10	11/8/2019	11/30/2020
5188	Cybertron	COMPUTER, CONTROL	N/A	TSVQJA2221	No Calibration Required	
5209	SOLAR ELECTRONICS	LISN	50 uH, 150 kHz - 30 MHz	21106-50-BP-25-BNC	5/26/2020	5/31/2021
5210	SOLAR ELECTRONICS	LISN	50 uH, 150 kHz - 30 MHz	21106-50-BP-25-BNC	5/26/2020	5/31/2021
5218	COM-POWER	GENERATOR, COMB	100 kHz - 400 MHz	CGC-510E	8/20/2019	8/31/2020
5250	DIGI-SENSE	HYGROMETER	0 - 50 deg. c, 10 - 90 % RH	20250-30	10/7/2019	10/31/2020



Retlif Testing Laboratories

Report No. R-6521H-1

Test Photographs Channel Separation



Test Setup



Retlif Testing Laboratories

Report No. R-6521H-1

FCC Section 15.247(a)(1)
Channel Separation
Test Data




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Channel Separation
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (a)(1)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.1 °C / 52.0 %
Result:	Channel Separation: 401.803 kHz



Retlif Testing Laboratories

Report No. R-6521H-1

**Test Photographs
20 dB Bandwidth**



Test Setup



Retlif Testing Laboratories

Report No. R-6521H-1

FCC Section 15.247(a)(1)
20 dB Bandwidth
Test Data




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Occupied Bandwidth	
Test Specification:	FCC Part 15, Subpart C	Paragraph: 15.247 (a)(i)
Job Number:	R-6521H-1	
Customer:	Immedia Semiconductor LLC	
Test Sample:	Blink Indoor/Outdoor Camera	
Model Number:	BCM00400U	
Serial Number:	G8T1-GH00-0205-00KW	
Operating Mode:	Transmitting modulated signal	
Technician:	M.Seamans	
Date(s):	June 24 th , 2020	
Temp/ Relative Humidity:	18.5 °C / 62.0 %	
Result:	20dB Bandwidth: 115.430 kHz	




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Occupied Bandwidth	
Test Specification:	FCC Part 15, Subpart C	Paragraph: 15.247 (a)(i)
Job Number:	R-6521H-1	
Customer:	Immedia Semiconductor LLC	
Test Sample:	Blink Indoor/Outdoor Camera	
Model Number:	BCM00400U	
Serial Number:	G8T1-GH00-0205-00KW	
Operating Mode:	Transmitting modulated signal	
Technician:	M.Seamans	
Date(s):	June 24 th , 2020	
Temp/ Relative Humidity:	18.5 °C / 62.0 %	
Result:	20dB Bandwidth: 114.228 kHz	




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Occupied Bandwidth	
Test Specification:	FCC Part 15, Subpart C	Paragraph: 15.247 (a)(i)
Job Number:	R-6521H-1	
Customer:	Immedia Semiconductor LLC	
Test Sample:	Blink Indoor/Outdoor Camera	
Model Number:	BCM00400U	
Serial Number:	G8T1-GH00-0205-00KW	
Operating Mode:	Transmitting modulated signal	
Technician:	M.Seamans	
Date(s):	June 24 th , 2020	
Temp/ Relative Humidity:	18.5 °C / 62.0 %	
Result:	20dB Bandwidth:114.829 kHz	



Retlif Testing Laboratories

Report No. R-6521H-1

Test Photographs
Number of Channels and Occupancy Time



Test Setup



Retlif Testing Laboratories

Report No. R-6521H-1

FCC Section 15.247 (a)(1)(i)
Number of Channels Separation and Occupancy Time
Test Data




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Channel Separation
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (a)(1)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.1 °C / 52.0 %
Result:	Channel Separation: 401.803 kHz




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Time of Occupancy
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (a)(iii)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	23.4 °C / 54.0 %
Result:	Time of Occupancy: (1 pulse in 20 second window)




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Time of Occupancy	
Test Specification:	FCC Part 15, Subpart C	Paragraph: 15.247 (a)(iii)
Job Number:	R-6521H-1	
Customer:	Immedia Semiconductor LLC	
Test Sample:	Blink Indoor/Outdoor Camera	
Model Number:	BCM00400U	
Serial Number:	G8T1-GH00-0205-00KW	
Operating Mode:	Transmitting modulated signal	
Technician:	M.Seamans	
Date(s):	June 24 th , 2020	
Temp/ Relative Humidity:	23.4 °C / 54.0 %	
Result:	Time of Occupancy: 9.619ms (1 pulse in 20 second window)	



Retlif Testing Laboratories

Report No. R-6521H-1

**Test Photographs
Number of Hopping Frequencies**



Test Setup



Retlif Testing Laboratories

Report No. R-6521H-1

**Number of Hopping Frequencies
Test Data**




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Number of Hopping Channels
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (a)(iii)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	23.7 °C / 54.0 %
Result:	Number of Hopping Channels: 64




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Number of Hopping Channels
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (a)(iii)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	23.7 °C / 54.0 %
Result:	Number of Hopping Channels: 64



Retlif Testing Laboratories

Report No. R-6521H-1

**Test Photographs
Peak Conducted Output Power**



Test Setup



Retlif Testing Laboratories

Report No. R-6521H-1

**FCC Section 15.247 (a)(1)
Peak Conducted Output Power
Test Data**




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Power Output
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (b)(1)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	22.8 °C / 55.0 %
Result:	Power Output: 12.30 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Power Output
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (b)(1)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	22.8 °C / 55.0 %
Result:	Power Output: 11.86 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Power Output
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (b)(1)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	22.8 °C / 55.0 %
Result:	Power Output: 11.50 dBm



Retlif Testing Laboratories

Report No. R-6521H-1

**Test Photographs
Conducted Spurious Emissions, 30 MHz to 10 GHz**



Test Setup



Retlif Testing Laboratories

Report No. R-6521H-1

**FCC Section 15.247 (d)
Conducted Spurious Emissions, 30 MHz to 10 GHz
Test Data**



Retlif Testing Laboratories

Report No. R-6521H-1

**Band Edge
Test Data**




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Band Edge
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Band Edge
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Band Edge
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal (while Hopping)
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Band Edge
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal (while Hopping)
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Conducted Out of Band
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Conducted Out of Band
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Conducted Out of Band
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Conducted Out of Band
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Method:	Conducted Out of Band
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET


Method:	Conducted Out of Band
Test Specification:	FCC Part 15, Subpart C Paragraph: 15.247 (d)
Job Number:	R-6521H-1
Customer:	Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-00KW
Operating Mode:	Transmitting modulated signal
Technician:	M.Seamans
Date(s):	June 24 th , 2020
Temp/ Relative Humidity:	24.3 °C / 53.0 %
Notes:	Limit: -7.70 dBm




Retlif Testing Laboratories

Report No. R-6521H-1

**Test Photographs
Field Strength of Spurious Emissions**



Horizontal Antenna Polarization, 30 to 200 MHz



Vertical Antenna Polarization, 30 to 200 MHz




Retlif Testing Laboratories

Report No. R-6521H-1

**Test Photographs
Field Strength of Spurious Emissions**



Horizontal Antenna Polarization, 200 MHz to 1 GHz



Vertical Antenna Polarization, 200 MHz to 1 GHz



Retlif Testing Laboratories

Report No. R-6521H-1

Test Photographs
Field Strength of Spurious Emissions



Horizontal Antenna Polarization, 1 GHz to 10 GHz



Vertical Antenna Polarization, 1 GHz to 10 GHz



Retlif Testing Laboratories

Report No. R-6521H-1

FCC Section 15.247 (d)
Field Strength of Spurious Emissions
Test Data



Retlif Testing Laboratories

Report No. R-6521H-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands		
Customer	Immedia Semiconductor LLC		
Job Number	R-6521H-1		
Test Sample	Blink Indoor/Outdoor Camera		
Model Number	BCM00400U		
Serial Number	G8T1-GH00-0205-0089		
Test Specification	FCC Part 15 Subpart C		
Operating Mode	Streaming video to Tablet		
Technician	M. Seamans		
Date	June 29 th , 2020		
Notes:	Antenna Test Distance: 3 meters Detector: Quasi-Peak <1GHz, Average >1GHz		

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
37.50	-	-	-	-			-	100.00
	38.00	6.85	12.35	19.20	*		9.12	
38.25	-	-	-	-			-	100.00
73.00	-	-	-	-			-	100.00
	74.00	12.17	8.63	20.80	*		10.96	
74.60	-	-	-	-			-	100.00
74.80	-	-	-	-			-	100.00
	75.00	8.01	8.60	16.60	*		6.76	
75.20	-	-	-	-			-	100.00
108.00	-	-	-	-			-	150.00
	115.00	7.24	14.56	21.80	*		12.30	
	-	-	-	-			-	
121.94	-	-	-	-			-	150.00
123.00	-	-	-	-			-	150.00
	130.00	6.83	14.67	21.50	*		11.89	
	-	-	-	-			-	
138.00	-	-	-	-			-	150.00

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).



Retlif Testing Laboratories

Report No. R-6521H-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands	
Customer	Immedia Semiconductor LLC	
Job Number	R-6521H-1	
Test Sample	Blink Indoor/Outdoor Camera	
Model Number	BCM00400U	
Serial Number	G8T1-GH00-0205-0089	
Test Specification	FCC Part 15 Subpart C	Paragraph: 15.247(d)
Operating Mode	Streaming video to Tablet	
Technician	M. Seamans	
Date	June 29 th , 2020	
Notes: Antenna Test Distance: 3 meters	Detector: Quasi-Peak <1GHz, Average >1GHz	

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
149.90	-	-	-	-			-	150.00
	150.00	8.33	14.37	22.70	*		13.65	
150.05	-	-	-	-			-	150.00
156.52	-	-	-	-			-	150.00
	156.52	8.53	15.27	23.80	*		15.49	
156.52	-	-	-	-			-	150.00
156.70	-	-	-	-			-	150.00
	156.80	8.49	15.31	23.80	*		15.49	
156.90	-	-	-	-			-	150.00
162.01	-	-	-	-			-	150.00
	165.00	8.70	16.50	25.20	*		18.20	
167.17	-	-	-	-			-	150.00
167.72	-	-	-	-			-	150.00
	170.00	8.64	17.26	25.90	*		19.72	
173.20	-	-	-	-			-	150.00

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).



Retlif Testing Laboratories

Report No. R-6521H-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands		
Customer	Immedia Semiconductor LLC		
Job Number	R-6521H-1		
Test Sample	Blink Indoor/Outdoor Camera		
Model Number	BCM00400U		
Serial Number	G8T1-GH00-0205-0089		
Test Specification	FCC Part 15 Subpart C		Paragraph: 15.247(d)
Operating Mode	Streaming video to Tablet		
Technician	M. Seamans		
Date	June 29 th , 2020		
Notes: Antenna Test Distance: 3 meters		Detector: Quasi-Peak <1GHz, Average >1GHz	

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
240.00	-	-	-	-			-	200.00
	260.00	6.75	15.25	22.00	*		12.59	
285.00	-	-	-	-			-	200.00
322.80	-	-	-	-			-	200.00
	330.00	6.53	17.47	24.00	*		15.85	
335.40	-	-	-	-			-	200.00
399.90	-	-	-	-			-	200.00
	405.00	6.68	19.22	25.90	*		19.72	
410.00	-	-	-	-			-	200.00
608.00	-	-	-	-			-	200.00
	611.00	7.51	23.49	31.00	*		35.48	
614.00	-	-	-	-			-	200.00
960.00	-	-	-	-			-	500.00
	975.00	8.49	29.71	38.20	*		81.28	
1240.00	-	-	-	-			-	500.00
1300.00	-	-	-	-			-	500.00
	1350.00	32.08	-7.75	24.33	*		16.46	
1427.00	-	-	-	-			-	500.00

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).



Retlif Testing Laboratories

Report No. R-6521H-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands		
Customer	Immedia Semiconductor LLC		
Job Number	R-6521H-1		
Test Sample	Blink Indoor/Outdoor Camera		
Model Number	BCM00400U		
Serial Number	G8T1-GH00-0205-0089		
Test Specification	FCC Part 15 Subpart C		Paragraph: 15.247(d)
Operating Mode	Streaming video to Tablet		
Technician	M. Seamans		
Date	June 29 th , 2020		
Notes: Antenna Test Distance: 3 meters	Detector: Quasi-Peak <1GHz, Average >1GHz		

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
1435.00	-	-	-	-			-	500.00
	1500.00	32.20	-6.91	25.79	*		19.48	
1646.50	-	-	-	-			-	500.00
1660.00	-	-	-	-			-	500.00
	1680.00	31.89	-6.00	25.89	*		19.70	
1710.00	-	-	-	-			-	500.00
1718.80	-	-	-	-			-	500.00
	1720.00	32.44	-5.81	26.63	*		21.45	
1722.20	-	-	-	-			-	500.00
2200.00	-	-	-	-			-	500.00
	2250.00	31.42	-3.72	27.70	*		24.47	
2300.00	-	-	-	-			-	500.00
2310.00	-	-	-	-			-	500.00
	2390.00	40.32	-3.27	37.05			71.20	
2390.00	-	-	-	-			-	500.00
2483.50	-	-	-	-			-	500.00
	2490.00	31.47	-2.96	28.51	*		26.64	
2500.00	-	-	-	-			-	500.00

EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).



Retlif Testing Laboratories

Report No. R-6521H-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands		
Customer	Immedia Semiconductor LLC		
Job Number	R-6521H-1		
Test Sample	Blink Indoor/Outdoor Camera		
Model Number	BCM00400U		
Serial Number	G8T1-GH00-0205-0089		
Test Specification	FCC Part 15 Subpart C		
Operating Mode	Streaming video to Tablet		
Technician	M. Seamans		
Date	June 29 th , 2020		
Notes: Antenna Test Distance: 3 meters	Detector: Quasi-Peak <1GHz, Average >1GHz		

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
2690.00	-	-	-	-			-	500.00
	-	-	-	-			-	
	2750.00	31.62	-2.21	29.41	*		29.55	
	-	-	-	-			-	
2900.00	-	-	-	-			-	500.00
3260.00	-	-	-	-			-	500.00
	3263.00	31.32	-0.46	30.86	*		34.91	
3267.00	-	-	-	-			-	500.00
3332.00	-	-	-	-			-	500.00
	3336.00	31.33	-0.17	31.16	*		36.14	
3339.00	-	-	-	-			-	500.00
3345.00	-	-	-	-			-	500.00
	3350.00	31.35	-0.11	31.24	*		36.48	
3358.00	-	-	-	-			-	500.00
3600.00	-	-	-	-			-	500.00
	-	-	-	-			-	
	3700.00	30.85	1.19	32.04	*		39.99	
	-	-	-	-			-	

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).



Retlif Testing Laboratories

Report No. R-6521H-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

Test Method	Unwanted Emissions into Restricted Frequency Bands	
Customer	Immedia Semiconductor LLC	
Job Number	R-6521H-1	
Test Sample	Blink Indoor/Outdoor Camera	
Model Number	BCM00400U	
Serial Number	G8T1-GH00-0205-0089	
Test Specification	FCC Part 15 Subpart C	Paragraph: 15.247(d)
Operating Mode	Streaming video to Tablet	
Technician	M. Seamans	
Date	June 29 th , 2020	
Notes: Antenna Test Distance: 3 meters		Detector: Quasi-Peak <1GHz, Average >1GHz

TEST PARAMETERS

Restricted Band	Measured Frequency	Meter Reading	Correction Factor	Corrected Reading			Converted Reading	Limit at 3M
MHz	MHz	dBuV	dB	dBuV/m			uV/m	uV/m
	-	-	-	-			-	
4400.00	-	-	-	-			-	500.00
4500.00	-	-	-	-			-	500.00
	4824.00	31.34	3.33	34.67			54.14	
5150.00	-	-	-	-			-	500.00
5350.00	-	-	-	-			-	500.00
	5400.00	30.30	4.30	34.60	*		53.70	
5460.00	-	-	-	-			-	500.00
7250.00	-	-	-	-			-	500.00
	7440.00	31.97	7.53	39.50	*		94.41	
7750.00	-	-	-	-			-	500.00
8025.00	-	-	-	-			-	500.00
	8300.00	32.19	8.57	40.76	*		109.14	
8500.00	-	-	-	-			-	500.00
9000.00	-	-	-	-			-	500.00
	9100.00	32.40	9.55	41.95	*		125.17	
9200.00	-	-	-	-			-	500.00

EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).



Retlif Testing Laboratories

Report No. R-6521H-1

RETLIF TESTING LABORATORIES

EMISSIONS TEST DATA SHEET

EMISSIONS TEST DATA SHEET		
Test Method	Unwanted Emissions into Restricted Frequency Bands	
Customer	Immedia Semiconductor LLC	
Job Number	R-6521H-1	
Test Sample	Blink Indoor/Outdoor Camera	
Model Number	BCM00400U	
Serial Number	G8T1-GH00-0205-0089	
Test Specification	FCC Part 15 Subpart C	Paragraph: 15.247(d)
Operating Mode	Streaming video to Tablet	
Technician	M. Seamans	
Date	June 29 th , 2020	
Notes: Antenna Test Distance: 3 meters	Detector: Quasi-Peak <1GHz, Average >1GHz	

TEST PARAMETERS

No EUT emissions within 10 dB of the specified test limit were observed at the specified test distance throughout the given frequency spectrum. * This emission is not from the EUT. It is a measurement of minimum measurement system sensitivity (Noise Floor).




Retlif Testing Laboratories

Report No. R-6521H-1

Test Photographs Conducted Limits



EUT Configuration



Test Setup



Retlif Testing Laboratories

Report No. R-6521H-1

FCC Part 15, Subpart B, Section 15.207 (a)
Conducted Emissions
150 kHz to 30 MHz
Test Data



Retlif Testing Laboratories

Report No. R-6521H-1

EMISSIONS TEST DATA SHEET

Test Specification:	FCC Part 15, Subpart B, Section 15.207(a), Conducted Emissions
Method:	ANSI C63.4, Section 7., AC power-line conducted emission measurements
Job Number/Customer:	R-6521H-1 / Immedia Semiconductor LLC
Test Sample:	Blink Indoor/Outdoor Camera
Model Number:	BCM00400U
Serial Number:	G8T1-GH00-0205-0089
Operating Mode:	Streaming video to tablet
Technician:	M. Seamans
Date(s):	June 29 th , 2020
Temp/ Relative Humidity:	22.3 °C / 58.0 %
Lead Tested:	120 VAC 60 Hz

Frequency	Lead Tested	Peak Meter Reading	Quasi-Peak Meter Reading	Average Meter Reading	Quasi-Peak Limit	Average Limit
MHz		dBuV	dBuV	dBuV	dBuV	dBuV
0.150	Hot	61.29	57.30	33.90	66.00	56.00
0.150	Neutral	71.24	58.80	34.50	66.00	56.00
0.229	Hot	67.40	45.90	27.10	62.49	52.49
0.161	Neutral	74.29	54.30	33.90	65.41	55.41
0.406	Hot	62.46	50.60	24.80	57.73	57.73
0.287	Neutral	68.21	59.30	29.60	60.61	50.61
0.496	Hot	59.09	37.50	23.00	56.07	46.07
0.373	Neutral	64.30	51.90	22.50	58.43	48.43
0.912	Hot	50.71	34.10	19.20	56	46
0.484	Neutral	59.72	35.80	21.10		
17.870	Hot	37.47	30.20	15.20	60	50
17.893	Neutral	37.13	29.50	18.60	60	50

The frequency range was scanned from 0.15 MHz to 30 MHz.

The six highest emissions relative to the limit are presented.

The emissions observed from the EUT do not exceed the specified limits.



Retlif Testing Laboratories

Report No. R-6521H-1