

RF EXPOSURE EVALUATION

Product Name	:	Bluetooth speaker	
Model Name	:	BS-201, BS-200	
FCC ID	:	2AF85-BS-201	
Bluetooth Version	•	Bluetooth LE Bluetooth Classical	
Operating frequency	:	2402-2480MHz	
Numbers of Channel	•	40 For BLE 79 For BT	
Antenna Type	:	PCB Print Antenna	
Antenna Gain	:	2dBi	
Type of Modulation		GFSK For BLE GFSK, Π/4-DQPSK, 8DPSK For BT	
Power supply	:	DC 3.7V, 4000mAh Battery	
Hardware Version	:	V1.1	
Software Version	:	V4.2	
Device category	:	Portable (<20cm separation)	

Standard Requirement

According to § 15.247(i) and § 1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v05, section 4. 3. 1.

The 1-g and 10-g SAR test exclusion thresholds for 100MHz to 6GHz at test separation distances \leq 50mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]*[$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g SAR extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison.



The test exclusions are applicable only when the minimum test separation distance is \leq 50mm and for transmission frequencies between 100MHz and 6GHz. When the minimum test separation distance is \leq 5mm, a distance of 5mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to quality for TCB approval.

One antenna is available for the EUT (BT product). The minimum separation distance is 5mm.

For Bluetooth Classical:

Channel	Mea	surement Peak Output	Power(dBm)
Frequency (MHz)	GFSK	П/4-DQPSK	8DPSK
(IVITIZ)			
2402	0.79	-0.57	-3.33
2441	-0.34	-2.89	-3.16
2480	-1.5	-2.33	-3.44

Channel Frequency (MHz)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Calculation Result	Limits
2402	1±1	2	1.58	0.49127	3
2441	0±1	1	1.26	0.39338	3
2480	-2±1	-1	0.79	0.25018	3
2402	-1±1	0	1.00	0.30997	3
2441	-3±1	-2	0.63	0.19716	3
2480	-2±1	-1	0.79	0.25018	3
2402	-3±1	-2	0.63	0.19558	3
2441	-3±1	-2	0.63	0.19716	3
2480	-3±1	-2	0.63	0.19873	3



For Bluetooth LE:

Channel Frequency	Measurement Peak Output Power(dBm)
(MHz)	GFSK
2402	-0.13
2440	0.42
2480	0.49

Channel Frequency (MHz)	Tune up tolerance (dBm)	Max tune up conducted power(dBm)	Output Peak power (mW)	Calculation Result	Limits
2402	0±1	1	1.26	0.39023	3
2440	0±1	1	1.26	0.39338	3
2480	0±1	1	1.26	0.39651	3

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.



Client's signature:

Client's name / title: Rain Tang/Manager

Telephone: 86-755-29100662 Fax No.: 86-755-29081870

Date: 2017-12-28

Contact information / address

Room B420B, Mingyou center, No.168 of Baoyuan Road, Bao'an district,

Shenzhen, China