

FCC TEST REPORT

APPLICANT

Jide Technology Co., Ltd.

PRODUCT NAME

Android Hybrid Laptop

MODEL NAME

: Remix Pro

TRADE NAME

: Remix OS, Remix Pro, JIDE

BRAND NAME

Remix OS, Remix Pro, JIDE

FCC ID

: 2AF86-RP1

STANDARD(S)

47 CFR Part 15 Subpart B

TEST DATE

2016-05-17 to 2016-07-11

ISSUE DATE

2017-01-06

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.

. Syste

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB GROUP

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555 Http://www.morlab.cn

Fax: 86-755-36698525 E-mail: service@morlab.cn



DIRECTORY

<u>1. I</u>	ECHN	NICAL INF	ORMATION	Į			 	 	5
1.1.	APPL	ICANT INFO	RMATION				 	 	5
1.2.	EQUII	PMENT UND	ER TEST (E	UT) DES	CRIPTION.		 	 	5
2. T	EST F	RESULTS					 	 	<u>7</u>
2.1.	APPL	IED REFER	ENCE DOCU	MENTS ···			 	 	7
3. T	EST (CONDITIO	NS SETTIN	IG			 		8
3.1.	TEST	MODE					 	 	8
3.2.	TEST	SETUP AND	EQUIPMEN	TS LIST.		<u></u>	 	 	9
3.2.1.	Co	NDUCTED E	MISSION				 	 	9
3.2.2.	RAI	DIATED EMI	SSION		<u>,</u>		 		10
<u>4. 47</u>	7 CFF	R PART 15	B REQUIR	EMENTS	3		 <u></u>	 	12
			ISSION						
4.1.1.	REG	QUIREMENT	••••••		,		 	 	12
			TION						
			SION						
			·						
			TION						
			ANGE OF ME						
4.2.4.	TES	ST RESULT .					 	 	16
ANNE	<u> X A</u>	PHOTOG	RAPHS O	F TEST S	SETUP		 	 	1 <u>9</u>
ANNE	EX B	TEST UN	CERTAINT	Ύ		9	 	 	23
ANNE	EX C	TESTING	LABORA	TORY IN	FORMAT	ION	 	 <u></u>	24



1.	IDENTIFICATION OF THE RESPONSIBLE TESTING LABORATORY24
2.	IDENTIFICATION OF THE RESPONSIBLE TESTING LOCATION24
3.	ACCREDITATION CERTIFICATE24
4.	TEST ENVIRONMENT CONDITIONS24

	Change History					
Issue	Issue Date Reason for change					
1.0	2017-01-06	First edition				



Test Report Declaration

Applicant	Jide Technology Co., Ltd.
Applicant Address	1801, Building 3, Crystal City, Tiansha Taoyian Road, Nanshan District, Shenzhen China
Manufacturer	Jide Technology Co., Ltd.
Manufacturer Address	1801, Building 3, Crystal City, Tiansha Taoyian Road, Nanshan District, Shenzhen China
Product Name	Android Hybrid Laptop
Model Name	Remix Pro
Brand Name	Remix OS, Remix Pro, JIDE
HW Version	B1.1
SW Version	Wanlong_B2
Test Standards	47 CFR Part 15 Subpart B
Test Result	PASS

Tested by	date.	Wang Dalong
, a	100	Wang Dalong (Test Engineer)

Reviewed by : Xian Xiang

Xīao Xīong Xiao Xiong (EMC Manager)

Approved by : ______ Andy Jah

Andy Yeh (Technology Manager)



1. Technical Information

Note: Provided by applicant

1.1. Applicant Information

Company: Jide Technology Co., Ltd.

Address: 1801, Building 3, Crystal City, Tiansha Taoyian Road,

Nanshan District, Shenzhen China

1.2. Equipment under Test (EUT) Description

EUT Type:	Android Hybrid Laptop
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	B1.1
Software Version:	Wanlong_B2
Working Voltage:	3.8V
Working current:	4.5A

Battery	E WALLE OFFICE MORE WAS		
Brand Name:	N/A		
Model No.:	24107130		
Serial No.:	(N/A, marked #1 by test site)		
Capacity:	4600mAh		
Rated Voltage:	3.8V		
Charge Limit:	4.35V		
AC Adapter (Ch	arger for Battery)		
Brand Name:	N/A		
Model No.:	KSA-20W-090200HC		
Serial No.:	(N/A, marked #1 by test site)		
Rated Input:	~ 100-240V, 50/60Hz, 500mA		
Rated Output:	= 9V, 2000mA		
	Brand Name: Model No.: Serial No.: Capacity: Rated Voltage: Charge Limit: AC Adapter (Charden Name: Model No.: Serial No.: Rated Input:		

NOTE:

- The EUT is an Android Hybrid Laptop which supports ISM 2.4GHz and WIFI 802.11(a/b/g/n/ac) band.
- 2. The EUT was equipped with a SD card slot and two USB ports which can be connected to the



ancillary equipments.

3. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer.



2. Test Results

2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15(July 07, 2016	Radio Frequency Devices
	Edition)	The State work was

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Result
1	15.107	Conducted Emission	2016.07.10	PASS
2	15.109	Radiated Emission	2016.07.10	PASS

NOTE: The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.



3. Test Conditions Setting

3.1. Test Mode


1 , 18	The first test mode
	The EUT configuration of the emission tests was EUT + Battery + SD Card + PC.
	During the test, the EUT embedded with a SD Card was connected with a PC, the data
	was transmitted between the PC and the SD Card of the EUT.
2	The second test mode
	The EUT configuration of the emission tests was EUT + AC adapter.
	During the measurement, the EUT was charged by the AC adapter, the EUT was
,	working normally as an intentional device.
Note: A	I test modes were preformed, only the worse mode(first) was recorded in the report.



3.2. Test Setup and Equipments List

3.2.1. Conducted Emission

A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu H$ of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity in maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.

B. Equipments List:


Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
Receiver	Narda	PMM 9010	001WX11001	2016.01.13	2017.01.12
Receiver	Narda	PMM 9060	595WX11007	2016.01.13	2017.01.12
LISN	Schwarzbeck	NSLK 8127	812744	2016.01.13	2017.01.12
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9537	2016.01.13	2017.01.12
PC	Apple	A1370	C02FQ2PYDDQW	N/A	N/A




3.2.2. Radiated Emission

A. Test Setup:

1. For radiated emissions from 30MHz to1GHz



2. For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Due. Date
MXE EMI Receiver	Agilent	N9038A	MY54130016	2016.01.13	2017.01.12
Semi-Anechoic Chamber	Albatross	9m*6m*6m	N/A	2016.01.13	2017.01.12
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2016.01.13	2017.01.12
PC	Apple	A1370	C02FQ2PYDD QW	N/A	N/A



4.47 CFR Part 15B Requirements

4.1. Conducted Emission

4.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a $50\mu\text{H}/50\Omega$ line impedance stabilization network (LISN).

Frequency range	Conducted L	.imit (dΒμV)
(MHz)	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- a) The limit subjects to the Class B digital device.
- b) The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 0.50MHz.

4.1.2. Test Description


See section 3.2.1 of this report.

4.1.3. Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.


A. Test Plot and Suspicious Points:





NO.	Fre.	Emission Le	vel (dBµV)	Limit (dBμV)		Power-line	Verdict	
	(MHz)	Quai-peak	Average	Quai-peak	Average			
1	0.15	53.20	34.31	66.00	56.00	ORLA	PASS	
2	0.315	37.88	17.70	61.29	51.29	, me	PASS	
3	0.61	42.81	32.53	56.00	46.00	Lina	PASS	
4	1.12	36.92	27.45	56.00	46.00	Line	PASS	
5	1.485	35.97	29.00	56.00	46.00	Jen Bur	PASS	
6	1.915	36.15	28.71	56.00	46.00	ORLAN	PASS	





NO. Fre.		Emission Le	vel (dBµV)	Limit (dBµV)		Power-line	Verdict	
	(MHz)	Quai-peak	Average	Quai-peak	Average		7 0 1 0 1 0 1	
1	0.15	45.45	21.11	66.00	56.00	ORLA	PASS	
2	0.19	51.75	33.09	64.86	54.86	e me	PASS	
3	0.215	50.45	17.32	64.14	54.14	Mauritral	PASS	
4	0.285	43.92	10.99	62.14	52.14	Neutral	PASS	
5	0.61	43.96	26.58	56.00	46.00	Okr. B W	PASS	
6	1.065	38.17	27.29	56.00	46.00	ORLAN	PASS	

Test Result: PASS



4.2. Radiated Emission

4.2.1. Requirement

According to FCC section 15.109(a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency	Field Strength Limita	ation at 3m Measurement Dist
range (MHz)	(μV/m)	(dBµV/m)
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dBμV/m is calculated by 20log Emission Level(μV/m).
- 3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of Ld1 = Ld2 * (d2/d1)^{2.}

Example:

F.S Limit at 30m distance is $30\mu\text{V/m}$, then F.S Limitation at 3m distance is adjusted as Ld1 = L1 = $30\mu\text{V/m}$ * $(10)^2$ = 100 * $30\mu\text{V/m}$

4.2.2. Test Description

See section 3.2.2 of this report.



4.2.3. Frequency range of measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:

40	
Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measure- ment range (MHz)
Below 1.705	30. 1000. 2000. 5000. 5th harmonic of the highest frequency or 40 GHz, whichever is lower.


4.2.4. Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.





							0.76		
No.	Fre.	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	ANT	Verdict
	MHz	dBµV/m	dBµV/m	dBµV/m	dBµV/m	dBµV/m	dBµV/m	le.	9 111
1	33.880	N.A.	25.38	N.A.	N.A.	40.00	N.A.	V	PASS
2	173.560	N.A.	35.94	N.A.	N.A.	43.50	N.A.	V	PASS
3	480.080	N.A.	34.75	N.A.	N.A.	46.00	N.A.	V	PASS
4	960.230	N.A.	41.52	N.A.	N.A.	54.00	N.A.	V	PASS
5	1440.533	44.16	N.A.	36.88	74.00	N.A.	54.00	V	PASS
6	3882.560	44.69	N.A.	37.15	74.00	N.A.	54.00	V	PASS





No.	Fre.	Pk	QP	AV	Limit-PK	Limit-QP	Limit-AV	ANT	Verdict
	MHz	dBµV/m	dBµV/m	dBµV/m	dBµV/m	dBµV/m	dBµV/m	LAB	ORL
10	49.400	N.A.	10.43	N.A.	N.A.	40.00	N.A.	Н	PASS
2	171.620	N.A.	23.74	N.A.	N.A.	43.50	N.A.	Hel	PASS
3	241.460	N.A.	33.38	N.A.	N.A.	46.00	N.A.	Н	PASS
4	479.110	N.A.	25.84	N.A.	N.A.	46.00	N.A.	Н	PASS
5	724.520	N.A.	28.99	N.A.	N.A.	46.00	N.A.	Ĥ	PASS
6	2798.400	45.22	N.A.	38.47	74.00	N.A.	54.00	Н	PASS

Test Result: PASS



Annex A Photographs of Test Setup


1. Mains Terminal Disturbance Voltage Measurement













2. Radiated Field Strength Measurement(30MHz - 1GHz)







3. Radiated Field Strength Measurement(Above 1GHz)







Annex B Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	±1.8dB
Uncertainty of Radiated Emission:	±3.1dB





Annex C <u>Testing Laboratory Information</u>

1. Identification of the Responsible Testing Laboratory

Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Department:	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Responsible Test Lab Manager:	Mr. Su Feng
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	Morlab Laboratory FL.3, Building A, FeiYang Science Park, No.8 LongChang
RLE MORE AS ME	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

3. Accreditation Certificate

Accredited Testing Laboratory: The FCC registration number is 695796.

(Shenzhen Morlab Communications Technology Co., Ltd.)

4. Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

"**** END OF REPORT *****

