



# FCC Part 15C Test Report

## FCC ID: 2AF8KRF1-1

Product Name:	<b>Remote control</b>
Trademark:	<b>N/A</b>
Model Name :	<b>JQH15ARF1-1, JQH15ARF1-2, JQH15ARF1-3</b>
Prepared For :	<b>KOOLi Inc.</b>
Address :	10 Corporate Park, Suite 330 Irvine, California 92606, USA
Prepared By :	<b>Shenzhen BCTC Technology Co., Ltd.</b>
Address :	No.101, Yousong Road, Longhua New District, Shenzhen, China
Test Date:	<b>Nov. 5 – Nov. 9, 2015</b>
Date of Report :	<b>Nov. 10, 2015</b>
Report No.:	<b>BCTC-151013503</b>



## VERIFICATION OF COMPLIANCE

**Applicant's name** ..... : **KOOLi Inc.**

Address ..... : 10 Corporate Park, Suite 330 Irvine, California 92606, USA

**Manufacture's Name** ..... : **Shenzhen Jinquanhui Technologe Co., Ltd.**

Address ..... : 5 floor, building D, Lonada Industrial Area, Huating RD, Dalang, Longhua, Shenzhen

### Product description

Product name ..... : Remote control

Trademark:

Model Name: JQH15ARF1-1, JQH15ARF1-2, JQH15ARF1-3

Test procedure FCC Part15.249

Standards ANSI C63.10-2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Test Result.....: **Pass**

Testing Engineer : \_\_\_\_\_

(Eric Yang)

Technical Manager : \_\_\_\_\_

(Sophia Lee)

Authorized Signatory :

(Carson. Zhang)





Table of Contents	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>4</b>
<b>1.1 TEST FACILITY</b>	<b>4</b>
<b>1.2 MEASUREMENT UNCERTAINTY</b>	<b>4</b>
<b>2 . GENERAL INFORMATION</b>	<b>5</b>
<b>2.1 GENERAL DESCRIPTION OF EUT</b>	<b>5</b>
<b>2.2 DESCRIPTION OF TEST MODES</b>	<b>6</b>
<b>2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING</b>	<b>6</b>
<b>2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b>	<b>6</b>
<b>2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS</b>	<b>7</b>
<b>3 . EMC EMISSION TEST</b>	<b>8</b>
<b>3.1 RADIATED EMISSION MEASUREMENT</b>	<b>10</b>
<b>3.1.1 RADIATED EMISSION LIMITS</b>	<b>10</b>
<b>3.1.2 TEST PROCEDURE</b>	<b>11</b>
<b>3.1.3 DEVIATION FROM TEST STANDARD</b>	<b>11</b>
<b>3.1.4 TEST SETUP</b>	<b>12</b>
<b>3.1.5 EUT OPERATING CONDITIONS</b>	<b>13</b>
<b>3.1.6 TEST RESULTS</b>	<b>14</b>
<b>4 . BANDWIDTH TEST</b>	<b>18</b>
<b>4.1 APPLIED PROCEDURES / LIMIT</b>	<b>18</b>
<b>4.1.1 TEST PROCEDURE</b>	<b>18</b>
<b>4.1.2 DEVIATION FROM STANDARD</b>	<b>18</b>
<b>4.1.3 TEST SETUP</b>	<b>18</b>
<b>4.1.4 EUT OPERATION CONDITIONS</b>	<b>18</b>
<b>4.1.5 TEST RESULTS</b>	<b>19</b>
<b>5 . BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>21</b>
<b>5.1 DEVIATION FROM STANDARD</b>	<b>21</b>
<b>5.2 TEST SETUP</b>	<b>21</b>
<b>5.3 EUT OPERATION CONDITIONS</b>	<b>21</b>
<b>5.4 TEST RESULTS</b>	<b>22</b>
<b>6 . ANTENNA REQUIREMENT</b>	<b>23</b>
<b>6.1 STANDARD REQUIREMENT</b>	<b>23</b>
<b>6.2 EUT ANTENNA</b>	<b>23</b>
<b>7 . EUT TEST PHOTO</b>	<b>24</b>



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.249	Radiated Spurious Emission	PASS	
15.249	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

### 1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Address: No.101, Yousong Road, Longhua New District, Shenzhen, China

FCC Registration No.: 187086

### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$  , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  , providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Remote control									
Trade Name	N/A									
Model Name	JQH15ARF1-1, JQH15ARF1-2, JQH15ARF1-3									
Product Description	<table border="1"><tr><td>Operation Frequency:</td><td>2405~2470 MHz</td></tr><tr><td>Modulation Type:</td><td>FSK</td></tr><tr><td>Number Of Channel</td><td>14 CH</td></tr><tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr></table> <p>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</p>		Operation Frequency:	2405~2470 MHz	Modulation Type:	FSK	Number Of Channel	14 CH	Antenna Designation:	Please see Note 3.
Operation Frequency:	2405~2470 MHz									
Modulation Type:	FSK									
Number Of Channel	14 CH									
Antenna Designation:	Please see Note 3.									
Channel List	Please refer to the Note 2.									
Adapter	N/A									
Battery	DC 3V									
Connecting I/O Port(s)	Please refer to the User's Manual									
hardware version	--									
Software version	--									
Serial number	--									

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2405	07	2440		
01	2410	08	2445		
02	2415	09	2450		
03	2420	10	2455		
04	2425	11	2460		
05	2430	12	2465		
06	2435	13	2470		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	N/A	0	



## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Frequency	2405 MHz	2430 MHz	2470 MHz
Channel	Low	Middle	High


Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Fully-charged battery is used during the test

## 2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

None.

## 2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



## 2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Remote control	N/A	JQH15ARF1-1	01	EUT

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	0.5M	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in『Length』 column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



## 2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	1166.5950K 03-101165- ha	2015.06.06	2016.06.05	1 year
2	LISN	R&S	NSLK81 26	812646 6	2015.08.24	2016.08.23	1 year
3	LISN	R&S	NSLK81 26	812648 7	2015.08.24	2016.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2015.06.06	2016.06.05	1 year
5	RF cables	R&S	R204	R20X	2015.06.06	2016.06.05	1 year

### Radiation test, Band-edge test and 20db bandwidth test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY4510804 0	2015.06.06	2016.06.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.06	2016.06.05	1 year
3	Bilog Antenna	R&S	VULB 9168	VULB91 68-438	2015.06.06	2016.06.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2015.06.06	2016.06.05	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.06	2016.06.05	1 year
6	Horn Antenna	R&S	HF906	10027	2015.06.06	2016.06.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.06.06	2016.06.05	1 year
8	Amplifier	R&S	BBV9743	9743-01 9	2014.12.22	2015.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.06	2016.06.05	1 year
10	RF cables	R&S	R203	R20X	2015.06.06	2016.06.05	1 year
11	Antenna connector	Florida RFLabs	Lab-Fle	RF 01#	2015.06.06	2016.06.05	1 year



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quas -peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


#### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

The data only show the worst mode.

### 3.1.6 TEST RESULTS

The product's power provide by battery, is no requirement for this item.



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

#### FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 <sup>th</sup> harmonic of the highest frequency or 40 GHz, whichever is lower



Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1.5 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- f. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


#### (A) Radiated Emission Test-Up Frequency Below 30MHz



#### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (C) Radiated Emission Test-Up Frequency Above 1GHz

**3.2.5 EUT OPERATING CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



### 3.2.6 TEST RESULTS

#### Radiated Spurious Emission (Below 30MHz )

EUT :	Remote control	Model Name :	JQH15ARF1-1
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Polarization :	---
Test Voltage :	DC 3V		
Test Mode :	TX		

Freq. (MHz)	Reading (dBuV/m)	Limit (dBuV/m)	Margin (dB)	State
--	--	--	--	PASS
--	--	--	--	PASS

**NOTE:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);  
Limit line = specific limits(dBuV) + distance extrapolation factor.



## Radiated Spurious Emission (Between 30MHz – 1GHz)

EUT :	Remote control	Model Name :	JQH15ARF1-1
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 3V		
Test Mode :	TX Low Channel (Worst)		


No.	Mk.	Freq. MHz	Reading Level	Correct Factor	Measure- ment	Limit	Over	Antenna Height cm	Table Degree	Comment
			dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	
1		119.8555	34.89	-14.72	20.17	43.50	-23.33	QP		
2	*	210.7860	40.56	-15.89	24.67	43.50	-18.83	QP		
3		339.5887	32.76	-11.57	21.19	46.00	-24.81	QP		
4		480.5276	34.99	-8.42	26.57	46.00	-19.43	QP		
5		768.7481	23.16	-3.04	20.12	46.00	-25.88	QP		
6		955.4380	26.57	-0.45	26.12	46.00	-19.88	QP		

## Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Pretest all mode, the data only show the worst mode.

If peak level comply with Quasi-Peak limit, then the Quasi-Peak level is deemed to comply with Quasi-Peak limit.






EUT :	Remote control	Model Name :	JQH15ARF1-1
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 3V		
Test Mode :	TX Low Channel (Worst)		

No.	Mk.	Reading Freq. MHz	Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Detector	Height cm	Table degree	Comment
1		107.8876	26.63	-15.83	10.80	43.50	-32.70	QP			
2		197.8926	30.03	-16.07	13.96	43.50	-29.54	QP			
3		211.5264	28.93	-15.87	13.06	43.50	-30.44	QP			
4		392.0951	24.75	-10.38	14.37	46.00	-31.63	QP			
5		593.0497	24.06	-5.88	18.18	46.00	-27.82	QP			
6	*	955.4380	23.73	-0.45	23.28	46.00	-22.72	QP			

Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
Pretest all mode, the data only show the worst mode.  
If peak level comply with Quasi-Peak limit, then the Quasi-Peak level is deemed to comply with Quasi-Peak limit.





## Radiated Spurious Emission ( 1GHz to 25GHz)

	Freq.	Receiver Reading	Detector	Polar	Corrected Factor	Emission Level	Limit	Result
	(MHz)	(dB $\mu$ V)	(PK/QP/Ave)	(H/V)	(dB)	(dB $\mu$ V/m)	(dB $\mu$ V/m)	
	2405.00	103.88	PK	H	1.35	105.23	114.00	Pass
Lower Channel 2405MHz	2405.00	91.55	Ave	H	1.35	92.90	94.00	Pass
	4810.00	58.12	PK	H	-1.01	57.11	74.00	Pass
	4810.00	49.07	Ave	H	-1.01	48.06	54.00	Pass
	2405.00	102.80	PK	V	1.35	104.15	114.00	Pass
	2405.00	90.83	Ave	V	1.35	92.18	94.00	Pass
	4810.00	59.14	PK	V	-1.01	58.13	74.00	Pass
	4810.00	47.58	Ave	V	-1.01	46.57	54.00	Pass
	2430.00	103.73	PK	H	0.79	104.52	114.00	Pass
	2430.00	91.09	Ave	H	0.79	91.88	94.00	Pass
	4860.00	54.93	PK	H	-0.61	54.32	74.00	Pass
Middle Channel 2430MHz	4860.00	44.01	Ave	H	-0.61	43.40	54.00	Pass
	2430.00	101.42	PK	V	0.79	102.21	114.00	Pass
	2430.00	89.54	Ave	V	0.79	90.33	94.00	Pass
	4860.00	54.65	PK	V	-0.61	54.04	74.00	Pass
	4860.00	44.13	Ave	V	-0.61	43.52	54.00	Pass
	2470.00	101.72	PK	H	0.49	102.21	114.00	Pass
	2470.00	90.22	Ave	H	0.49	90.71	94.00	Pass
	4940.00	51.90	PK	H	-0.18	51.72	74.00	Pass
Upper Channel 2470.00 Hz	4940.00	42.97	Ave	H	-0.18	42.79	54.00	Pass
	2470.00	100.88	PK	V	0.49	101.37	114.00	Pass
	2470.00	89.51	Ave	V	0.49	90.00	94.00	Pass
	4940.00	54.05	PK	V	-0.18	53.87	74.00	Pass
	4940.00	43.17	Ave	V	-0.18	42.99	54.00	Pass

## Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Emission Level = Meter Reading + Factor

Margin = Emission Level - Limit

Other harmonics emissions are lower than 20dB below the allowable limit.



## 4. BANDWIDTH TEST

### 4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.249	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	100KHz
VB	$\geq$ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW $\geq$  RBW, Sweep time = Auto.

#### 4.1.2 DEVIATION FROM STANDARD

No deviation.

#### 4.1.3 TEST SETUP



#### 4.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.




#### 4.1.5 TEST RESULTS

EUT :	Remote control	Model Name :	JQH15ARF1-1
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3V
Test Mode :	CH low/Middle/High		

Frequency	20dB Bandwidth (MHz)	Result
2405 MHz	0.398	PASS
2430 MHz	0.420	PASS
2470 MHz	0.443	PASS







## 5. BANDWIDTH OF FREQUENCY BAND EDGE

### APPLICABLE STANDARD

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

### TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1.5 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- f. For the radiated emission test above 1GHz:  
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.  
The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- g. Spectrum Setting : RBW= 1MHz, VBW=3MHz, Sweep time = Auto for peak  
RBW= 1MHz, VBW=10Hz, Sweep time = Auto for average

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 5.1 DEVIATION FROM STANDARD

No deviation.

### 5.2 TEST SETUP

### 5.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## 5.4 TEST RESULTS

EUT :	Remote control	Model Name :	JQH15ARF1-1	
Temperature :	25 °C	Relative Humidity :	60%	
Pressure :	1012 hPa	Test Voltage :	DC 3V	
Test Mode :	CH Low/High			

Frequency (MHz)	Antenna polarization (H/V)	Emission	Band edge Limit		Result
		(dBuV/m)	PK	PK	
<2400	H	50.40	74.00	54.00	Pass
<2400	V	49.64	74.00	54.00	Pass
>2483.5	H	49.52	74.00	54.00	Pass
>2483.5	V	50.08	74.00	54.00	Pass

If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



## 6. ANTENNA REQUIREMENT

### 6.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



### 6.2 EUT ANTENNA

The EUT antenna is PCB antenna. It complies with the standard requirement.



## 7. EUT TEST PHOTO

**Radiated Measurement Photos**



## 8. PHOTO OF THE EUT

