



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20180400041E-03

Applicant: 1MORE INC.

Address of Applicant: Tianliao Building F14 East Block (New Materials Industrial Park), Xueyuan Road, Nanshan District, Shenzhen, China

Manufacturer: 1MORE Shen Zhen Acoustic Technology Co., Ltd.

Address of Manufacturer: Tianliao Building 1403-1411, Zone A Tianliao Industrial Park, Taoyuan Street, Nanshan District, Shenzhen, P.R. China

Equipment Under Test (EUT):

Product: 1MORE Dual Driver BT ANC In-Ear Headphones

Model No.: E1004BA

Brand Name: 1MORE

FCC ID: 2AF8ZE1004BA

Standards: 47 CFR Part 1.1307

47 CFR Part 2.1093


KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-04-25 to 2018-07-04

Date of Issue: 2018-07-04

Test Result : PASS*

Tested By:


(Aaron Ma)

Reviewed By:


(Owen Zhou)

Approved By:


(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

2 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20180400041E-03	Rev.01	Initial report	2018-07-04

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT	4
5 SAR EVALUATION	5
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
5.1.1 <i>Standard Requirement</i>	5
5.1.2 <i>Limits</i>	5
5.1.3 <i>EUT RF Exposure</i>	5

4 General Information

4.1 Client Information

Applicant:	1MORE INC.
Address of Applicant:	Tianliao Building F14 East Block (New Materials Industrial Park), Xueyuan Road, Nanshan District, Shenzhen, China
Manufacturer:	1MORE Shen Zhen Acoustic Technology Co., Ltd.
Address of Manufacturer:	Tianliao Building 1403-1411, Zone A Tianliao Industrial Park, Taoyuan Street, Nanshan District, Shenzhen, P.R. China

4.2 General Description of EUT

Product Name:	1MORE Dual Driver BT ANC In-Ear Headphones
Model No.:	E1004BA
Trade Mark:	N/A
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.1
Modulation Type:	BT classic: GFSK, π/4DQPSK, 8DPSK BLE: GFSK
Number of Channel:	BT classic:79 BLE:40
Sample Type:	portable production
Test Software of EUT:	Non Signaling Test Tool (manufacturer declare)
Antenna Type:	Ceramic antenna
Antenna Gain:	1.72dBi
Power Supply:	lithium battery:DC3.7V 160mAh, Charge by DC5.0V

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

For BT: Measurement Data

GFSK mode	
Test channel	Peak Output Power (dBm)
Lowest	1.650
Middle	1.560
Highest	-0.160
$\pi/4$ DQPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	1.610
Middle	1.530
Highest	-0.150
8DPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	1.710
Middle	1.530
Highest	-0.190

Remark: The Conducted Peak Output Power data refer to report Report No.: CQASZ20180400041E-01

For BLE:**Measurement Data**

GFSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-1.00
Middle	-1.21
Highest	-2.98

Remark: The Conducted Peak Output Power data refer to report Report No.: CQASZ20180400041E-02

BDR, EDR and BLE can not simultaneous transmitting at same time.

The worst case data: 8DPSK_lowest channel

The Max Conducted Peak Output Power is 1.71dBm in lowest channel(2.402GHz);

The best case gain of the antenna is 1.72dBi.

EIRP= 1.71dBm + 1.72dBi= 3.43dBm

3.34dBm logarithmic terms convert to numeric result is nearly 2.2mW

According to the formula. calculate the EIRP test result:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] · [$\sqrt{f(\text{GHz})}$]General RF Exposure = $(2.2\text{mW} / 5 \text{ mm}) \times \sqrt{2.402\text{GHz}} = 0.68$ ①

SAR requirement:

S= 3.0

② ;

① < ②.

So the SAR report is not required.