

FCC Test Report

Report No.: AGC01040250606FR02

FCC ID : 2AF9HCS600

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: Smart Cycling Computer

BRAND NAME : COOSPO

MODEL NAME : CS600, CS600se, CS600lite, CS610, CS620, CS630, CS650,

CS660, CS670, CS680, CS690

APPLICANT: Shenzhen CooSpo Tech Co., Ltd

DATE OF ISSUE : Jul. 10, 2025

STANDARD(S) : FCC Part 15 Subpart C §15.249

REPORT VERSION: V1.0

Attestation Of Global Concellance (Shenzhen) Co., Ltd



Page 2 of 35


Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Jul. 10, 2025	Valid	Initial Release	



Table of Contents

1. General Information	4
2. Product Information	5
2.1 Product Technical Description	5
2.2 Test Frequency List	5
2.3 Related Submittal(S) / Grant (S)	6
2.4 Test Methodology	6
2.5 Antenna Requirement	6
3. Test Environment	7
3.1 Address of the Test Laboratory	7
3.2 Test Facility	7
3.3 Environmental Conditions	8
3.4 Measurement Uncertainty	8
3.5 List of Equipment Use	9
4. System Test Configuration	11
4.1 EUT Configuration	11
4.2 EUT Exercise	11
4.3 Configuration of Tested System	11
4.4 Equipment Used In Tested System	12
4.5 Summary of Test Results	12
5. Description of Test Modes	13
6. Duty Cycle Measurement	14
7. 20dB Bandwidth Measurement	15
7.1 Provisions Applicable	15
7.2 Measurement Procedure	15
7.3 Measurement Setup (Block Diagram of Configuration)	15
7.4 Measurement Results	16
8. Field Strength of Fundamental and Radiated Spurious Emission	17
8.1 Measurement Limit	17
8.2 Measurement Procedure	18
8.3 Measurement Setup (Block Diagram of Configuration)	21
8.4 Measurement Results	22
9. AC Power Line Conducted Emission	30
9.1 Measurement Limit	30
9.2 Measurement Setup (Block Diagram of Configuration)	30
9.3 Preliminary Procedure of Line Conducted Emission Test	31
9.4 Final Procedure of Line Conducted Emission Test	31
9.5 Measurement Result	31
Appendix I: Photographs of Test Setup	34
Appendix II: Photographs of Test EUT	34





1. General Information

Applicant	Shenzhen CooSpo Tech Co., Ltd
Address	Room 602, 1# building, Lingyun Factory, Liufang Road 2nd, Xingdong Community, Bao'an District, Shenzhen, Guangdong, China
Manufacturer	Shenzhen CooSpo Tech Co., Ltd
Address	Room 602, 1# building, Lingyun Factory, Liufang Road 2nd, Xingdong Community, Bao'an District, Shenzhen, Guangdong, China
Factory	Shenzhen CooSpo Tech Co., Ltd
Address	Room 602, 1# building, Lingyun Factory, Liufang Road 2nd, Xingdong Community, Bao'an District, Shenzhen, Guangdong, China
Product Designation	Smart Cycling Computer
Brand Name	COOSPO
Test Model	CS600
Series Model(s)	CS600se, CS600lite, CS610, CS620, CS630, CS650, CS660, CS670, CS680, CS690
Difference Description	All the same except for the model name.
Date of receipt of test item	Jun. 25, 2025
Date of Test	Jun. 25, 2025 to Jul. 10, 2025
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-ANT+-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By	Thea Huang	
	Thea Huang (Project Engineer)	Jul. 10, 2025
Reviewed By	Bibo zhang	
Approved By	Bibo Zhang (Reviewer) Angolo li	Jul. 10, 2025
	Angela Li (Authorized Officer)	Jul. 10, 2025



Page 5 of 35

2. Product Information

2.1 Product Technical Description

Equipment Specification	Low Power Short Range Equipment (ANT ⁺)
Frequency Band	2400MHz-2483.5MHz
Operation Frequency	2457MHz
Modulation Type	GFSK
Field Strength of Fundamental	94.15dBµV/m @3m (Peak)
Hardware Version	BC680_MB_V1.3
Software Version	V1.0
Antenna Designation	PCB Antenna
Antenna Gain	1.94dBi
Power Supply	DC 3.85V by battery or DC 5V by adapter

2.2 Test Frequency List

Frequency Band	Channel Number	Test Frequency		
2400~2483.5MHz	1	2457 MHz		



Page 6 of 35

2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2AF9HCS600**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

2.5 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 1.94dBi.



Page 7 of 35

3. Test Environment

3.1 Address of the Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories).

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



Page 8 of 35


3.3 Environmental Conditions

	Normal Conditions
Temperature range (℃)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 3.85V by battery or DC 5V by adapter

3.4 Measurement Uncertainty

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$		
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$		
Uncertainty of Duty Cycle	$U_c = \pm 2 \%$		





3.5 List of Equipment Use

•	RF Conducted Test System								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2025-01-14	2026-01-13		
\boxtimes	AGC-ER-A007	6dB Fixed Attenuator	Mini circuits	BW-S6-2W263A+	N/A	2025-01-30	2026-01-29		
\boxtimes	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A		
\boxtimes	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A		
\boxtimes	AGC-ER-E091	DC Power Supply	AIDEKESI	IT6720	800103030787810080	2024-03-28	2026-03-27		

• F	Radiated Spurious Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	100096	2025-01-14	2026-01-13		
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2025-05-08	2026-05-07		
\boxtimes	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2025-05-08	2026-05-07		
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04		
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2025-03-14	2027-03-13		
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2025-03-27	2026-03-26		
\boxtimes	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23		
\boxtimes	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23		
\boxtimes	AGC-EM-A119	2.4GHz Filter	SongYi	N/A	N/A	2025-05-16	2026-05-15		
\boxtimes	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2025-05-16	2027-05-15		
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2025-05-16	2027-05-15		

• A	AC Power Line Conducted Emission								
Illsed I Equipment No. 1 Test Equipment Manufacturer Model No. 1 Serial No. 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1							Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2025-05-08	2026-05-07		
\boxtimes	AGC-EM-A171	Attenuator	Mini-Circuits	UNAT-10A+	DC-6GZ	2024-02-01	2026-01-31		
\boxtimes	AGC-EM-E023	AMN	R&S	ESH2-Z5	100086	2025-05-08	2026-05-07		





• Tes	● Test Software							
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information			
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71			
\boxtimes	AGC-EM-S003	RE Test System	FARA	EZ-EMC	VRA-03A			
	AGC-EM-S004	RE Test System	Tonscend	TS ⁺ Ver2.1(JS32-RE)	4.0.0.0			
\boxtimes	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6			
\boxtimes	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0			



4. System Test Configuration

4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



AC Power Line Conducted Emission Configure:





Page 12 of 35

4.4 Equipment Used In Tested System

The following peripheral devices and interface cables were connected during the measurement:

☐ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Adapter	XIAOMI	MDY-16-EA	Input(AC):100-240V 50/60Hz 2.5A Output(DC):5V3A/9V3A/11V6.1A/20V5A/20 V6A	N/A

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	USB Cable	N/A	N/A	N/A	0.5m unshielded

4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203	Antenna Equipment	Pass
2	§15.249(a)	Field Strength of Fundamental	Pass
3	§15.209&§15.249(d)	Radiated Emission& Band Edge	Pass
4	§15.205	Restricted Bands of Operation	Pass
5	§15.215	20dB Bandwidth	Pass
6	§15.207	AC Power Line Conducted Emission	Pass




Page 13 of 35

5. Description of Test Modes

	Summary Table of Test Cases				
Test Item	Equipment type / Modulation				
rest item	Short Distance and Low Power Consumption/ GFSK				
Radiated Test Cases	Mode 1: ANT ⁺ Tx_2457MHz(Battery powered)				
RF Conducted Test Cases	Mode 1: ANT ⁺ Tx_2457MHz (Powered by DC source)				
AC Conducted Emission	Mode 1: ANT ⁺ Normal transmission (2457MHz) (Charging from AC/DC adapter)				

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. The battery is full-charged during the test.
- For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 4. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
- The fixed-frequency transmission of the prototype is debugged through the buttons declared by the manufacturer.
- The manufacturer of RF external cable claims that the cable loss is 0.5dB, and the cable loss and attenuator have been compensated into the Corrections Configuration of measuring equipment.
- Input correction factor includes external cable loss and attenuator amplitude compensation. The formula is: Input compensation coefficient (dB) = Cable Loss (dB) + Attenuator attenuation value (dB)





6. Duty Cycle Measurement


The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector =Peak. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Operating mode	T(µs)	Duty Cycle (%)	Duty Cycle Factor (dB)	
GFSK_2457MHz	N/A	100%	N/A	

Remark:

Duty Cycle factor = 10 * log (1/ Duty cycle)

The test plots as follows:





Page 15 of 35

7. 20dB Bandwidth Measurement


7.1 Provisions Applicable


N/A

7.2 Measurement Procedure

- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss
 was compensated to the results for each measurement.
- 2. Set to the maximum power setting and enable the EUT transmit continuously.
- 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 30 kHz. Set the Video bandwidth (VBW) = 100 kHz. In order to make an accurate measurement.
- For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
- 5. Measure and record the results in the test report.

7.3 Measurement Setup (Block Diagram of Configuration)








7.4 Measurement Results

Test Data of Occupied Bandwidth and -20dB Bandwidth								
Test Mode	Test Mode Test Frequency (MHz) Occupied Bandwidth (MHz) -20dB Bandwidth (MHz) Limits (MHz) Pass or Fai							
GFSK	2457	0.93892	1.029	N/A	Pass			

Test Graphs of Occupied Bandwidth and -20dB Bandwidth





Page 17 of 35

8. Field Strength of Fundamental and Radiated Spurious Emission

8.1 Measurement Limit

15.249 Limit in the below table has to be followed:

Frequency Range	Field Strength of Fundamental	Field Strength of Harmonics
2 η 1 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2	(millivolts/meter)	(microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

15.209 Limit in the below table has to be followed:

Frequency Range	Distance	Field Strengths Limit		
(MHz)	Meters	μV/m	dB(μV)/m	
0.009 ~ 0.490	300	2400/F(kHz)		
0.490 ~ 1.705	30	24000/F(kHz)		
1.705 ~ 30	30	30		
30 ~ 88	3	100	40.0	
88 ~ 216	3	150	43.5	
216 ~ 960	3	200	46.0	
960 ~ 1000	3	500	54.0	
Above 1000	3	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)		

Remark:

- 1) Emission level dB μ V = 20 log Emission level μ V/m.
- 2) The smaller limit shall apply at the cross point between two frequency bands.
- 3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.



Page 18 of 35

8.2 Measurement Procedure

- The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



Page 19 of 35

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting		
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP		
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP		
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average		

Receiver Parameter	Setting		
Start ~Stop Frequency	9kHz~150kHz/RB 200Hz for QP		
Start ~Stop Frequency	150kHz~30MHz/RB 9kHz for QP		
Start ~Stop Frequency	30MHz~1000MHz/RB 120kHz for QP		

- The following is the test setup of Field Strength of Fundamental:
 - > Peak detection: RBW is greater than the main frequency OBW, VBW=50MHz / Sweep=AUTO
 - Average detection: RBW is greater than the main frequency OBW, VBW=50MHz / Sweep=AUTO
- The following is the test setup of Band Edge:

The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

- Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - Peak detection: RBW=1MHz, VBW=3MHz / Sweep=AUTO
 - > Average detection: RBW=1MHz; VBW=1/T / Sweep=AUTO (Duty cycle is less than 98%)
 - Average detection: RBW=1MHz; VBW=3M / Sweep=AUTO
 - Other procedures refer to clause 7.2.



Report No.: AGC01040250606FR02 Page 20 of 35

Quasi-Peak Measurements below 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

Peak Measurements above 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

• Average Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW ≥ [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.






8.3 Measurement Setup (Block Diagram of Configuration)


Radiated Emission Test Setup 9kHz-30MHz



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 22 of 35


8.4 Measurement Results

Field Strength of Fundamental

EUT Name		Smart Cycling Computer		Model Name	Model Name		CS600	
Temperature		26.9℃		Relative Humic	Relative Humidity 57.0		57.0%	
Pressure		960hPa		Test Voltage		DC 3.85V	by battery	
Test Mode		Mode 1		Antenna		Horizontal	/Vertical	
			Peal	< Value				
Frequency (MHz)	Measured Level@3m (dBµV/m)		Correction Factor dB/m	Field Strength (dBµV/m)	Limit @3m (dBµV/m)		Polarity	
2457		104.17	-10.06	94.11	114		Horizontal	
2457		104.21	-10.06	94.15	114		Vertical	
			Avera	ge Value				
Frequency (MHz)			Correction Factor dB/m	Field Strength (dBµV/m)		it @3m sµV/m)	Polarity	
2457	103.94		-10.06	93.88		94	Horizontal	
2457		103.86	-10.06	93.80		94	Vertical	

RESULT: Pass

Note: Corr. Factor= Antenna Factor (dB/m) + Cable Loss (dB) - Pre-amplifier.






Radiated Emission Below 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20dB below the permissible value need not be reported.

Radiated Emission Test Results at 30MHz-1GHz					
EUT Name	Smart Cycling Computer	Model Name	CS600		
Temperature	23.2℃	Relative Humidity	53.9%		
Pressure	960hPa	Test Voltage	DC 3.85V by battery		
Test Mode	Mode 1	Antenna Polarity	Horizontal		




Final Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	67.2022	14.58	-25.26	40.00	25.42	100	60	Horizontal
2	166.0680	18.74	-21.00	43.50	24.76	100	124	Horizontal
3	294.1137	21.43	-19.72	46.00	24.57	100	108	Horizontal
4	330.1949	26.63	-18.66	46.00	19.37	100	79	Horizontal
5	798.9797	30.90	-9.95	46.00	15.1	100	123	Horizontal
6	863.0562	31.40	-9.35	46.00	14.6	100	215	Horizontal





Radiated Emission Test Results at 30MHz-1GHz					
EUT Name	Smart Cycling Computer	Model Name	CS600		
Temperature	23.2℃	Relative Humidity	53.9%		
Pressure	960hPa	Test Voltage	DC 3.85V by battery		
Test Mode	Mode 1	Antenna Polarity	Vertical		



Final Data List

NO.	Freq. [MHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity
1	210.0482	22.04	-22.69	43.50	21.46	100	124	Vertical
2	330.1949	27.50	-17.93	46.00	18.5	100	95	Vertical
3	378.5843	29.38	-17.04	46.00	16.62	100	136	Vertical
4	520.8882	32.12	-13.75	46.00	13.88	100	215	Vertical
5	601.4265	34.00	-11.51	46.00	12.0	100	124	Vertical
6	679.9600	33.84	-10.14	46.00	12.16	100	80	Vertical

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Limit-Level.

2. All test modes had been pre-tested. The mode 1 is the worst case and recorded in the report.



Page 25 of 35

Radiated Emissions Test Results for Above 1GHz

EUT Name	Smart Cycling Computer	Model Name	CS600
Temperature	23.2℃	Relative Humidity	53.9%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4914.000	45.26	0.08	45.34	74	-28.66	peak
4914.000	39.22	0.08	39.3	54	-14.7	AVG
7371.000	41.35	2.21	43.56	74	-30.44	peak
7371.000	32.51	2.21	34.72	54	-19.28	AVG

Remark:

Factor = Antenna Factor + Cable Loss - Pre-amplifier.

EUT Name	Smart Cycling Computer	Model Name	CS600
Temperature	23.2℃	Relative Humidity	53.9%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4914.000	46.59	0.08	46.67	74	-27.33	peak
4914.000	38.38	0.08	38.46	54	-15.54	AVG
7371.000	42.22	2.21	44.43	74	-29.57	peak
7371.000	31.41	2.21	33.62	54	-20.38	AVG


Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: Pass

Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.






EUT Name	Smart Cycling Computer	Model Name	CS600
Temperature	26.9℃	Relative Humidity	57.0%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal


Test Graph for Peak Measurement







RESULT: PASS






EUT Name	Smart Cycling Computer	Model Name	CS600
Temperature	26.9℃	Relative Humidity	57.0%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Test Graph for Peak Measurement








RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/






EUT Name	Smart Cycling Computer	Model Name	CS600
Temperature	26.9℃	Relative Humidity	57.0%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	Mode 1	Antenna Polarity	Horizontal


Test Graph for Peak Measurement








RESULT: PASS






EUT Name	Smart Cycling Computer	Model Name	CS600
Temperature	26.9℃	Relative Humidity	57.0%
Pressure	960hPa	Test Voltage	DC 3.85V by battery
Test Mode	Mode 1	Antenna Polarity	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss - Amplifier gain. Field Strength=Factor + Reading level

2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μ V) to represent the Amplitude. Use the F dB(μ V/m) to represent the Field Strength. So A=F.



9. AC Power Line Conducted Emission


9.1 Measurement Limit

F	Maximum RF Line Voltage				
Frequency	Q.P. (dBμV)	Average (dBµV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

9.2 Measurement Setup (Block Diagram of Configuration)





Page 31 of 35

9.3 Preliminary Procedure of Line Conducted Emission Test

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

9.4 Final Procedure of Line Conducted Emission Test

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.
- 4. A conducted emission is calculated by the following equation:
 - Measurement Level (dBµV) = Receiver reading (dBµV) + Transd (dB)
 - Transd (dB)= AMN Factor(dB)+Cable Loss(dB)+Attenuation(dB)
 - Margin= Limit-Level

9.5 Measurement Result





MEASUREMENT RESULT: "agc_fin"

2025/	6/27 13:4	17					
Fr	equency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0	.350000	24.20	9.9	59	34.8	QP	L1
0	.778000	26.40	9.9	56	29.6	QP	L1
1	.098000	24.10	9.9	56	31.9	QP	L1
2	.174000	18.70	9.9	56	37.3	QP	L1
10	.834000	12.20	10.3	60	47.8	QP	L1
13	.562000	13.30	10.5	60	46.7	QP	L1

MEASUREMENT RESULT: "agc fin2"


2025/6/27	13:47						
Frequen M	cy 1 Hz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.3540	00 2	20.10	9.9	49	28.8	AV	L1
0.7780	00 2	21.60	9.9	46	24.4	AV	L1
1.2140	00	19.10	9.9	46	26.9	AV	L1
2.1700	00	14.20	9.9	46	31.8	AV	L1
5.9180	00	7.60	10.0	50	42.4	AV	L1
13.5580	00	7.50	10.5	50	42.5	AV	L1


RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/







MEASUREMENT RESULT: "agc fin"

2025/6/27 13:51

2023/0/2/ 13.	JI					
Frequency MHz	Level dBµV		Limit dBµV	Margin dB	Detector	Line
0.358000	23.60	9.9	59	35.2	QP	N
0.594000	22.60	9.9	56	33.4	QP	N
1.074000	23.90	9.9	56	32.1	QP	N
2.154000	18.60	9.9	56	37.4	QP	N
13.018000	12.90	10.4	60	47.1	QP	N
14.286000	13.10	10.5	60	46.9	OP	N

MEASUREMENT RESULT: "agc fin2"

2025/6/27 13:51

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.358000	20.10	9.9	49	28.7	AV	N
0.502000	19.50	9.9	46	26.5	AV	N
1.162000	19.10	9.9	46	26.9	AV	N
2.150000	14.20	9.9	46	31.8	AV	N
6.050000	7.50	10.0	50	42.5	AV	N
15.718000	7.60	10.6	50	42.4	AV	N

RESULT: PASS



Page 34 of 35

Appendix I: Photographs of Test Setup

Refer to the Report No.: AGC01040250606AP02

Appendix II: Photographs of Test EUT

Refer to the Report No.: AGC01040250606AP03





Conditions of Issuance of Test Reports

- 1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
- 2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
- 3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
- 4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
- 5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
- 6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
- 7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
- 8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.
- 9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

----End of Report----