

JianYan Testing Group Shenzhen Co., Ltd.

Report No.: JYTSZ-R12-2201859

RF Exposure Evaluation Report

Applicant: Inepro BV

Address of Applicant: Pondweg 7, 2153 PK Nieuw-Vennep, The Netherlands

Equipment Under Test (EUT)

Product Name: Red Spider

Model No.: Red Spider Desktop HF

Trade mark: Red Spider

FCC ID: 2AFBFRSDHF1

Applicable standards: FCC CFR Title 47 Part 2 (§2.1091)

Date of sample receipt: 08 Sep., 2022

Date of Test: 09 Sep., to 02 Nov., 2022

Date of report issue: 21 Feb., 2023

Test Result: PASS

Tested by: _____ Date: ____ 21 Feb., 2023

Reviewed by: Date: 21 Feb., 2023

Approved by: Date: 21 Feb., 2023

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in above the application standard version. Test results reported herein relate only to the item(s) tested.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.





1 Version

| Version No. | Date | Description |
|-------------|---------------|-----------------|
| 00 | 23 Nov., 2022 | Original |
| 01 | 21 Feb., 2023 | Update page 4/6 |
| | | |
| | | |

Remark: Please refer to FCC ID: 2AFBFRSHF01, report No.: JYTSZ-R12-2201853 issue by JianYan Testing Group Shenzhen Co., Ltd. The Red Spider Desktop HF and the Red Spider HF model are the same internally, including circuit design, layout, components used and internal wiring. The differences between them are as follows: The Red Spider Desktop HF have four electrical cables. So no need retest.





2 Contents

| | | | Page |
|---|---------|---------------------------------------------------------|------|
| C | over Pa | age | 1 |
| 1 | Vers | sion | 2 |
| 2 | Con | ntents | 3 |
| 3 | Gen | neral Information | 4 |
| | 3.1 | Client Information | 4 |
| | 3.2 | General Description of E.U.T. | 4 |
| | 3.3 | Operating Modes | 4 |
| | 3.4 | Additions to, deviations, or exclusions from the method | |
| | 3.5 | Laboratory Facility | 5 |
| | 3.6 | Laboratory Location | 5 |
| 4 | Tec | chnical Requirements Specification | 6 |
| | 4.1 | Limits | 6 |
| | 4.2 | Result | 6 |
| | 4.3 | Conclusion | 6 |





3 General Information

3.1 Client Information

| Applicant: | Inepro BV |
|-----------------------|--------------------------------------------------|
| Address: | Pondweg 7, 2153 PK Nieuw-Vennep, The Netherlands |
| Manufacturer/Factory: | Inepro BV |
| Address: | Pondweg 7, 2153 PK Nieuw-Vennep, The Netherlands |

3.2 General Description of E.U.T.

| <u> </u> | |
|------------------------|-------------------------------------------------------------------------------|
| Product Name: | Red Spider |
| Model No.: | Red Spider Desktop HF |
| Operation Frequency: | BLE: 2402MHz~2480MHz |
| | NFC: 13.56MHz |
| Modulation technology: | BLE: GFSK |
| | NFC: ASK |
| Antenna Type: | Internal Antenna |
| Antenna gain: | BLE: 0.5 dBi; NFC: 0dBi |
| Test Sample Condition: | The test samples were provided in good working order with no visible defects. |

3.3 Operating Modes

| Operating mode | Detail description |
|----------------|-------------------------------------------------------|
| BLE mode | Keep the EUT in continuously transmitting in BLE mode |
| NFC mode | Keep the EUT in continuously transmitting in NFC mode |

3.4 Additions to, deviations, or exclusions from the method

No



Report No.: JYTSZ-R12-2201859

3.5 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC - Designation No.: CN1211

JianYan Testing Group Shenzhen Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● ISED - CAB identifier.: CN0021

The 3m Semi-anechoic chamber and 10m Semi-anechoic chamber of JianYan Testing Group Shenzhen Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

• CNAS - Registration No.: CNAS L15527

JianYan Testing Group Shenzhen Co., Ltd. is accredited to ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L15527.

• A2LA - Registration No.: 4346.01

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

3.6 Laboratory Location

JianYan Testing Group Shenzhen Co., Ltd.

Address: No.101, Building 8, Innovation Wisdom Port, No.155 Hongtian Road, Huangpu Community, Xingiao Street, Bao'an District, Shenzhen, Guangdong, People's Republic of China.

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info-JYTee@lets.com, Website: http://jyt.lets.com



Report No.: JYTSZ-R12-2201859

4 Technical Requirements Specification

4.1 Limits

RF Exposure Test Exemptions for Single Source

1-mW Test Exemption

Per § 1.1307(b)(3)(i)(A), a single RF source is *exempt RF device* (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance.

This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

4.2 Result

According to the calculation formula of power:

EIRP = P*G = $(E*d)^2/30$, So P = $(E*d)^2/(30 *G)$.

Where:

P = transmitter output power in watts,

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator (unitless),

E = electric field strength in V/m, --- $10^{((dBuV/m)/20)}/10^6$.

d = measurement distance in meters (m)---3m,

Reference report JYTSZ-R12-2201853, FCC ID: 2AFBFRSHF01.

4.3 Conclusion

Reference report JYTSZ-R12-2201853, FCC ID: 2AFBFRSHF01.

-----End of report-----