

FCC / ISED Canada Test Report

FOR:

iRhythm Technologies, Inc.

Model Name:

A101A5001

Product Description:

Zio AT ECG Patch

FCC ID: 2AFBP-AT17P IC ID: N/A

Applied Rules and Standards: 47 CFR Part 15.247 (DTS) RSS-247 Issue 1 (DTSs) RSS-Gen Issue 4

REPORT #: EMC_IRHYT-008-17001_15.247_DTS_PATCH

DATE: 2017-05-09



A2LA Accredited

IC recognized # 3462B-1

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: +1 (408) 586 6200 • Fax: +1 (408) 586 6299 • E-mail: info@cetecom.com • http://www.cetecom.com CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

IC ID: N/A



TABLE OF CONTENTS

| 1 | Α | SSESSMENT | 3 |
|----|---------------------------------|---|--------|
| 2 | Α | DMINISTRATIVE DATA | 4 |
| | 2.1 2.2 2.3 | IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT. IDENTIFICATION OF THE CLIENT | 4 4 |
| 3 | E | QUIPMENT UNDER TEST (EUT) | 5 |
| | 3.1 3.2 3.3 3.4 3.5 | EUT SPECIFICATIONS EUT SAMPLE DETAILS ACCESSORY EQUIPMENT (AE) DETAILS. TEST SAMPLE CONFIGURATION WORST CASE MODE OF OPERATION | 6 6 |
| 4 | S | UBJECT OF INVESTIGATION | 8 |
| 5 | M | IEASUREMENT RESULTS SUMMARY | 8 |
| 6 | M | IEASUREMENTS | 9 |
| | 6.1 6.2 6.3 | MEASUREMENT UNCERTAINTY | 9 |
| 7 | M | IEASUREMENT PROCEDURES | 10 |
| | 7.1 7.2 7.3 7.4 | RADIATED MEASUREMENT POWER LINE CONDUCTED MEASUREMENT PROCEDURE RF CONDUCTED MEASUREMENT PROCEDURE CONDUCTED SETUP BLOCK DIAGRAM | 12 |
| 8 | T | EST RESULT DATA | 13 |
| | 8.1 8.2 | EMISSION BANDWIDTH | |
| 9 | P | OWER SPECTRAL DENSITY | 27 |
| | 9.2 9.3 | BAND EDGE AND RESTRICTED BAND COMPLIANCE | |
| 10 | T | EST SETUP PHOTOS | 51 |
| 11 | T | EST EQUIPMENT AND ANCILLARIES USED FOR TESTING | 51 |
| 40 | _ | EVICION LICTORY | |

FCC ID: 2AFBP-AT17P



Date of Report 2017-05-09 Page 3 of 52 IC ID: N/A

1 Assessment

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and the relevant ISED Canada standard RSS-247 Issue 1, and RSS-Gen Issue 4. No deviations have been ascertained in the course of testing.

| Company | Description | Model # | |
|----------------------------|------------------|-----------|--|
| iRhythm Technologies, Inc. | Zio AT ECG Patch | A101A5001 | |

Responsible for Testing Laboratory:

Dr. Peter Nevermann

| 2017-05-09 | RC&E | (Director Radio Communications and EMC) | |
|------------|---------|---|-----------|
| Date | Section | Name | Signature |

Responsible for the Report:

Cindy Li

| 2017-05-09 | RC&E | (EMC Engineer) | |
|------------|---------|----------------|-----------|
| Date | Section | Name | Signature |

The test results of this test report relate exclusively to the test item specified in Section3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

Page 4 of 52

FCC ID: 2AFBP-AT17P IC ID: N/A



2 Administrative Data

Date of Report 2017-05-09

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

| Company Name: | CETECOM Inc. |
|------------------------------|------------------------|
| Department: | Compliance |
| Street Address: | 411 Dixon Landing Road |
| City/Zip Code | Milpitas, CA 95035 |
| Country | USA |
| Telephone: | +1 (408) 586 6200 |
| Fax: | +1 (408) 586 6299 |
| Director Radio Com. and EMC: | Peter Nevermann |
| Responsible Project Leader: | Cindy Li |

2.2 Identification of the Client

| Applicant's Name: | iRhythm Technologies, Inc. |
|-------------------|----------------------------|
| Street Address: | 650 Townsend St # 500 |
| City/Zip Code | San Francisco, CA 94103 |
| Country | USA |
| Contact Person: | Matt Ho, Chase Hathaway |

2.3 Identification of the Manufacturer

| Manufacturer's Name: | Same as Applicant |
|------------------------|-------------------|
| Manufacturers Address: | |
| City/Zip Code | |
| Country | |

Page 5 of 52 IC ID: N/A

FCC ID: 2AFBP-AT17P



3 Equipment Under Test (EUT)

Date of Report 2017-05-09

3.1 EUT Specifications

| Model No: | A101A5001 | | | | |
|--|---|--|--|--|--|
| HW Version : | A101A6001.02 | | | | |
| SW Version : | Application firmware: 170407 Patch MAX32621 Production 2.1.4.4.hex BLE firmware: 160914 Patch CC2640 Production 2.1.1.8.hex | | | | |
| FCC-ID: | 2AFBP-AT17P | | | | |
| IC-ID: | N/A | | | | |
| HVIN: | N/A | | | | |
| PMN: | N/A | | | | |
| Product Description: | Zio AT ECG Patch | | | | |
| Frequency Range / number of channels: | Nominal band: 2402 MHz – 2480 MHz; Center to center: 2402 MHz (Ch 0) – 2480 MHz (Ch 39), 40 channels | | | | |
| Type(s) of Modulation: | Bluetooth version 4.0, Low Energy, GFSK modulation. | | | | |
| Modes of Operation: | Bluetooth LE. Based on TI chip CC2640 | | | | |
| Antenna Information: | PCB trace antenna. Gain -1.1dBi for 2480MHz. Gain determined from measured EIRP and measured conducted power | | | | |
| Max. declared Output Powers conducted: | 2dBm declared in operational description and used during testing. | | | | |
| Power Supply/ Rated Operating Voltage Range: | 2 Lithium Manganese Dioxide Coin Cells (2.7V – 3.2V) | | | | |
| Operating Temperature Range | 2 °C to 40 °C | | | | |
| Other Radios included in the device: | N/A | | | | |
| Sample Revision | ■Prototype Unit □Production Unit □Pre-Production | | | | |

Page 6 of 52 IC ID: N/A

FCC ID: 2AFBP-AT17P



3.2 EUT Sample details

Date of Report 2017-05-09

| EUT# | Serial Number | HW Version | SW Version | Notes/Comments |
|------|---------------|--------------|--|-------------------|
| 1 | AJNPI00014 | A101A6001.02 | Application firmware: 170407 Patch MAX32621 Production 2.1.4.4.hex BLE firmware: 160914 Patch CC2640 Production 2.1.1.8.hex | Conducted testing |
| 2 | NPI41402 | A101A6001.02 | Application firmware: 170407 Patch MAX32621 Production 2.1.4.4.hex BLE firmware: 160914 Patch CC2640 Production 2.1.1.8.hex | Radiated testing |

3.3 Accessory Equipment (AE) details

| AE# | Туре | Model | Manufacturer | Serial Number |
|-----|------|-------|--------------|---------------|
| 1 | N/A | N/A | N/A | N/A |

3.4 Test Sample Configuration

| EUT Set-up # | Combination of AE used for test set up | Comments | | |
|--------------|--|-------------------|--|--|
| 1 AJNPI00014 | | Conducted testing | | |
| 2 NPI41402 | | Radiated testing | | |

Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH FCC ID: 2AFBP-AT17P

Date of Report 2017-05-09 Page 7 of 52 IC ID: N/A



3.5 Worst Case Mode of Operation

During the testing process the EUT was tested with transmitter sets on low, mid and high channels. For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

The channels and modulation scheme of the EUT was set with diagnostic software (not available to the end user), and the transmitter output power was measured using spectrum analyzer (Peak Power).

The applications "AT Patch controller v1.03" and "HCITester - BLE_2dBm_TX_Test", were used to program the sample to low, mid and high carrier channel with the following parameters that were declared by the customer.

- Output power set to +2 dBm which is the maximum power used according to customer declaration in operational description.
- Data Rate to 1Mb/s, the standard for Bluetooth Low Energy.

These settings are considered worst case for all measurements in scope of this report.

Date of Report 2017-05-09 Page 8 of 52

FCC ID: 2AFBP-AT17P

IC ID: N/A



4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 Issue 1 of ISED Canada.

This test report is to support a request for new equipment authorization.

Testing procedures are based on 558074 D01 DTS Meas Guidance v04 – "GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER §15.247; April 5, 2017" by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

5 Measurement Results Summary

| Test Specification | Test Case | Temperature and Voltage Conditions | Mode | Pass | Fail | NA | NP | Result |
|--|---|------------------------------------|------|------|------|----|----|----------|
| §15.247(a)(1) RSS-247 5.2(1) | Emission Bandwidth | Nominal | BTLE | • | | | | Complies |
| §15.247(e) RSS-247 5.2(2) | Power Spectral Density | Nominal | BTLE | | | | | Complies |
| §15.247(b)(1) RSS-247 5.4(4) | Maximum Conducted Output Power and EIRP | Nominal | BTLE | | | | | Complies |
| §15.247(d) RSS-247 5.5 | Band edge compliance Unrestricted Band Edges | Nominal | BTLE | | | | | Complies |
| §15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10 | Band edge compliance Restricted Band Edges | Nominal | BTLE | | | | | Complies |
| §15.247(d); §15.209 RSS-Gen 6.13 | TX Spurious emissions- Radiated | Nominal | BTLE | | | | | Complies |
| §15.207(a) RSS Gen 8.8 | AC Conducted Emissions | Nominal | BTLE | | | | | Complies |

Note: NA= Not Applicable; NP= Not Performed.

Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH FCC ID: 2AFBP-AT17P

Date of Report 2017-05-09 Page 9 of 52 IC ID: N/A



6 <u>Measurements</u>

6.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor k=1.

Radiated measurement

9 kHz to 30MHz ±2.5 dB (Magnetic Loop Antenna) 30 MHz to 1000 MHz ±2.0 dB (Biconilog Antenna) 1 GHz to 40 GHz ±2.3 dB (Horn Antenna)

Conducted measurement

150 kHz to 30 MHz ± 0.7 dB (LISN)

RF conducted measurement ±0.5 dB

6.2 Environmental Conditions during Testing:

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25°C
- Relative humidity: 40-60%

6.3 Dates of Testing:

4/20/2017 - 5/02/2017



7 Measurement Procedures


Date of Report 2017-05-09

7.1 Radiated Measurement

The radiated measurement is performed according to: ANSI C63.10 (2013)

- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.

Radiated Emissions Test Setup below 30MHz Measurements





FCC ID: 2AFBP-AT17P

Page 11 of 52 IC ID: N/A



Radiated Emissions Test Setup 30MHz-1GHz Measurements





FCC ID: 2AFBP-AT17P



Date of Report 2017-05-09 Page 12 of 52 IC ID: N/A

7.1.1 **Sample Calculations for Field Strength Measurements**

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

- Measured reading in dBµV
- 2. Cable Loss between the receiving antenna and SA in dB and
- 3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

FS $(dB\mu V/m)$ = Measured Value on SA $(dB\mu V)$ - Cable Loss (dB)+ Antenna Factor (dB/m)

Example:

| Frequency (MHz) | Measured SA (dBμV) | Cable Loss (dB) | Antenna Factor Correction (dB) | Field Strength Result (dBµV/m) |
|--------------------|-----------------------|--------------------|--------------------------------------|-----------------------------------|
| 1000 | 80.5 | 3.5 | 14 | 98.0 |


7.2 **Power Line Conducted Measurement Procedure**

AC Power Line conducted emissions measurements performed according to: ANSI C63.10 (2013)

7.3 **RF Conducted Measurement Procedure**

Reference: 558074 D01 DTS Meas Guidance v03r05 - "GUIDANCE FOR PERFORMING COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEMS (DTS) OPERATING UNDER §15.247; April 8, 2016" by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

7.4 **Conducted Setup Block diagram**



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.

Page 13 of 52 IC ID: N/A

FCC ID: 2AFBP-AT17P



8 Test Result Data

8.1 Emission Bandwidth

8.1.1 Measurement according to FCC KDB 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

Date of Report 2017-05-09

- Set RBW = 100 kHz
- Set the video bandwidth (VBW) ≥ 3 x RBW
- Detector = Peak
- Trace mode = max hold
- Sweep = auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two
 outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the
 maximum level measured in the fundamental emission.

8.1.2 Limits:

FCC §15.247(a)(1) and RSS-247 5.2(1)

• Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test conditions and setup:

| Ambient Temperature | EUT Set-Up# | EUT operating mode | Power Input | Measurement Path Loss (dB) | Antenna Gain (dBi) |
|------------------------|-------------|--------------------|-------------|----------------------------|-----------------------|
| 24° C | 1 | BT LE | 3 VDC | 1.4 | 1.8 |


8.1.4 Measurement result:

| Plot # | Frequency (MHz) | 6dB DTS Bandwidth (MHz) | Limit (MHz) | Result |
|--------|-----------------|-------------------------|-------------|--------|
| 1 | 2402 | 0.7 | > 0.5 | Pass |
| 2 | 2442 | 0.7 | > 0.5 | Pass |
| 3 | 2480 | 0.72 | > 0.5 | Pass |

| Plot # | Frequency (MHz) | 99% Bandwidth (MHz) | Limit (MHz) | Result |
|--------|-----------------|---------------------|-------------|--------|
| 4 | 2402 | 1.29 | > 0.5 | Pass |
| 5 | 2442 | 1.33 | > 0.5 | Pass |
| 6 | 2480 | 1.30 | > 0.5 | Pass |




8.1.5 Measurement Plots:




Page 15 of 52 IC ID: N/A





Page 16 of 52 IC ID: N/A






Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH
Date of Report 2017-05-09 Page 17 of 52

FCC ID: 2AFBP-AT17P IC ID: N/A






Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH
Date of Report 2017-05-09 Page 18 of 52


Page 18 of 52 IC ID: N/A





Page 19 of 52 IC ID: N/A







FCC ID: 2AFBP-AT17P

IC ID: N/A

8.2 Maximum Peak Conducted Output Power and EIRP

8.2.1 Measurement according to FCC KDB 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings:

- Span = approximately 5 times the 20 dB bandwidth
- RBW > the 20 dB bandwidth of the emission being measured
- VBW ≥ RBW
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Use the marker-peak function to set the marker to the peak of the emission.

8.2.2 Limits:

Maximum Peak Output Power:

• FCC §15.247 (b): 1W

• IC RSS-247: 1W

8.2.3 Test conditions and setup:


| Ambient Temperature | EUT Set-Up# | EUT operating mode | Power Input | Measurement Path Loss (dB) | Antenna Gain (dBi) |
|------------------------|-------------|--------------------|----------------|----------------------------|-----------------------|
| 22° C | 1 | BT LE | 3 VDC | 1.4 | -1.1 |

8.2.4 Measurement result:

| Plot # | Frequency (MHz) | Maximum Peak Conducted Output Power (dBm) | EIRP Peak (dBm) | Gain calculated (dBm) | Limit conducted output power (dBm) peak | Result |
|--------|--------------------|--|--------------------|-----------------------------|---|--------|
| 1 | 2402 | 4.03 | - | 1.4 - 4.03 = -2.6 | 30 | Pass |
| 2 | 2442 | 3.83 | - | 1.6 - 3.83 = -2.2 | 30 | Pass |
| 3 | 2480 | 3.51 | - | 3.51 – 2.4 = -1.1 | 30 | Pass |
| 4 | 2402 | - | 1.4 | | 36 | Pass |
| 5 | 2442 | - | 1.6 | | 36 | Pass |
| 6 | 2480 | - | 2.4 | | 36 | Pass |




8.2.5 **Measurement Plots:**



FCC ID: 2AFBP-AT17P

IC ID: N/A






FCC ID: 2AFBP-AT17P

CETECOM


Date of Report 2017-05-09 Page 23 of 52 IC ID: N/A



FCC ID: 2AFBP-AT17P


IC ID: N/A





IC ID: N/A





FCC ID: 2AFBP-AT17P IC ID: N/A



Plot #6 Modulation/Packet Type: Bluetooth LE EIRP 2480 MHz 2.479807692 GHz 2.342 dBm Level in dBm 2485 2475 2480 2490 Frequency in MHz MaxPeak-ClearWrite-PK+ - MaxPeak-MaxHold-PK+

FCC ID: 2AFBP-AT17P



8.3 **Power Spectral Density**

8.3.1 Measurement according to FCC KDB 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings for Peak PSD method:

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth
- Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
- Set the VBW \geq 3 x RBW.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

8.3.2 Limits:

FCC§15.247(e) & RSS-247 5.2(2)

For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test conditions and setup:

| Ambient Temperature | EUT Set-Up# | EUT operating mode | Power Input | Measurement Path Loss (dB) | Antenna Gain (dBi) |
|------------------------|-------------|--------------------|-------------|----------------------------|-----------------------|
| 22° C | 1 | BT LE | 3 VDC | 1.4 | 1.8 |


8.3.4 Measurement result:

| Plot # | Frequency (MHz) | Maximum Power Spectral Density (dBm / 3kHz) | Limit (dBm / 3kHz) | Result |
|--------|-----------------|---|-------------------------|--------|
| 1 | 2402 | -12.18 | 8 | Pass |
| 2 | 2440 | -12.6 | 8 | Pass |
| 3 | 2480 | -13.27 | 8 | Pass |

Note: PSD results were adjusted to include antenna gain.




8.3.5 Measurement Plots:



Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH
Date of Report 2017-05-09 Page 29 of 52

Page 29 of 52 IC ID: N/A





Page 30 of 52 IC ID: N/A

FCC ID: 2AFBP-AT17P



Plot #3 2480 MHz Modulation/Packet Type: Bluetooth LE **P**S *RBW 3 kHz Marker 1 [T1] VBW 10 kHz Ref 31.4 dBm Att 55 dB SWT 120 ms 2.479954567 GHz 30 Offset 1.4 dB A 1 PK MAXH Center 2.48 GHz 105 kHz/ Span 1.05 MHz Date: 20.APR.2017 18:15:01



8.4 **Band Edge and Restricted Band Compliance**

8.4.1 Measurement according to FCC KDB 558074 D01 DTS Meas Guidance v04

Spectrum Analyzer settings for non-restricted band edge:

- Span: wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
- RBW ≥ 1% of the span
- VBW ≥ RBW
- Sweep Time: Auto
- Detector = peak
- Trace = max hold
- Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge.

8.4.2 Limits non restricted band:

FCC§15.247 (d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 5/5

 In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

Spectrum Analyzer settings for restricted band:

Peak measurements are made using a peak detector and RBW=1 MHz, VBW ≥ RBW

Date of Report 2017-05-09 Page 32 of 52 IC ID: N/A



8.4.3 Limits restricted band §15.247/15.209/15.205 and RSS-Gen 8.9/8.10

- *PEAK LIMIT= 74dBµV/m @3m =-21.23dBm
- *AVG. LIMIT= 54dBµV/m @3m =-41.23dBm
- Start frequency & stop frequency according to frequency range specified in the restricted band table in FCC section 15.205 & RSS-Gen 8.10
- Measurements with a peak detector were used to show compliance to average limits, thus showing compliance to both peak and average limits.
- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| 10.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | Above 38.6 |
| 13.36-13.41 | | | |

8.4.4 Test conditions and setup:

| Ambient Temperature | EUT Set-Up# | EUT operating mode | Power Input | Measurement Path Loss (dB) | Antenna Gain (dBi) |
|---------------------|-------------|--------------------|----------------|----------------------------|-----------------------|
| 22° C | 3 | BT LE | 3 VDC | 1.4 | -1.1 |

8.4.5 Measurement result:

| Plot# | Band Edge | Band Edge Delta (dBc) | Limit (dBc) | Result |
|-------|----------------------|-----------------------|-------------|--------|
| 1 | Lower non restricted | 30.76 | > 20 | Pass |


| Plot | # EUT operating mode | Band Edge | Measured Value (dBm) | Corrected by Ant. Gain (dBm) - min 2dBi | Limit (dBm) | Result |
|------|----------------------|--------------------------|-------------------------|---|---------------|--------|
| 2 | BT LE | Upper restricted peak | -24.48 | -22.48 | PEAK = -21.23 | Pass |
| 3 | BT LE | Upper restricted average | -49.29 | -47.29 | AVG = -41.23 | Pass |

Page 33 of 52 IC ID: N/A

FCC ID: 2AFBP-AT17P



BT LE Continuous Transmit Mode Measured Duty cycle 8.4.6




Date: 20.APR.2017 16:28:16

Duty Cycle= 412.5/627.2=0.658= 65.8% Duty Cycle Correction Factor = 10*log(1/0.658) = 1.8 dB



8.4.7 Measurement Plots:



Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH Date of Report 2017-05-09

Page 35 of 52






Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH Date of Report 2017-05-09

Page 36 of 52







8.5 Radiated Transmitter Spurious Emissions

8.5.1 Measurement according to ANSI C63.10 (2013)

Spectrum Analyzer Settings:

- Frequency = 9 KHz 30 MHz
- RBW = 9 KHz
- Detector: Peak
- Frequency = 30 MHz 1 GHz
- Detector = Peak / Quasi-Peak
- RBW=120 KHz (<1GHz)
- Frequency > 1 GHz
- Detector = Peak / Average
- RBW= 1MHz
- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate
 for the lowest, middle and highest channel in each frequency band of operation and for the highest gain
 antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing at distance other than the specified in the standard, the limit conversion is calculated by using 40 dB/decade extrapolation factor as follow: Conversion factor (CF) = 40 log (D/d) = 40 log (300m / 3m) = 80dB

8.5.2 Limits:

FCC §15.247

• In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH FCC ID: 2AFBP-AT17P

Date of Report 2017-05-09 Page 38 of 52 IC ID: N/A



FCC §15.209 & RSS-Gen 8.9

• Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency of emission (MHz) | Field strength (μV/m) | Measurement Distance (m) | Field strength @ 3m (dBµV/m) |
|-----------------------------|-----------------------|--------------------------|------------------------------|
| 0.009-0.490 | 2400/F(kHz) / | 300 | - |
| 0.490-1.705 | 24000/F(kHz) / | 30 | - |
| 1.705–30.0 | 30 / (29.5) | 30 | - |
| 30–88 | 100 | 3 | 40 dBμV/m |
| 88–216 | 150 | 3 | 43.5 dBµV/m |
| 216–960 | 200 | 3 | 46 dBμV/m |
| Above 960 | 500 | 3 | 54 dBμV/m |

FCC §15.205 & RSS-Gen 8.10

• Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| 10.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | Above 38.6 |
| 13.36-13.41 | | | |

• Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

*PEAK LIMIT= 74dBµV/m

*AVG. LIMIT= 54dBµV/m

Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH FCC ID: 2AFBP-AT17P

Date of Report 2017-05-09 Page 39 of 52 IC ID: N/A



8.5.3 Test conditions and setup:

| Ambient Temperature | EUT Set-Up# | EUT operating mode | Power Input | Antenna Gain (dBi) | |
|---------------------|-------------|--------------------|-------------|--------------------|--|
| 23° C | 1 | BT LE | 3 VDC | -1.1 | |

8.5.4 Measurement result:

| Plot # | Channel # | EUT Set-Up# | Scan Frequency | Limit | Result |
|--------|-----------|-------------|-----------------|-------------------|--------|
| 1-3 | Low | 1 | 30 MHz – 18 GHz | See section 8.6.2 | Pass |
| 4-5 | Mid | 1 | 9 kHz – 1 GHz | See section 8.6.2 | Pass |
| 6-8 | Mid | 1 | 1 GHz – 40 GHz | See section 8.6.2 | Pass |
| 9-11 | High | 1 | 30 MHz – 18 GHz | See section 8.6.2 | Pass |

Note: As the off times of the 66% DC signal was 200us and thus much shorter than the scan time of 2ms the average trace in the plots below are valid without correction.

Page 40 of 52


FCC ID: 2AFBP-AT17P IC ID: N/A



8.5.5 Measurement Plots:

Date of Report 2017-05-09


Plots reported here represent the worst case emissions for horizontal and vertical antenna polarizations and for three orientations of the EUT. Unless mentioned otherwise, the emissions outside the limit lines in the plots are from the transmit signal.



Page 41 of 52

FCC ID: 2AFBP-AT17P IC ID: N/A






FCC ID: 2AFBP-AT17P

Date of Report 2017-05-09 Page 42 of 52 IC ID: N/A





Page 43 of 52

FCC ID: 2AFBP-AT17P

IC ID: N/A




Plot # 4 Radiated Emissions: 9 KHz - 30 MHz

Channel: Mid Modulation: BT LE

Final Measurement Result

| Frequency (MHz) | MaxPeak (dBµV/m) | Meas. Time (ms) | Bandwidth (kHz) | Height (cm) | Polarization | Azimuth (deg) | Corr. (dB) | Margin (dB) | Limit (dBµV/m) |
|--------------------|---------------------|-----------------------|--------------------|----------------|--------------|------------------|---------------|----------------|-------------------|
| 0.035040 | 106.1 | 2.0 | 0.200 | 260.0 | Н | 148.0 | 75.2 | 10.6 | 116.7 |



Page 44 of 52

FCC ID: 2AFBP-AT17P IC ID: N/A



Plot #5 Radiated Emissions: 30 MHz - 1GHz Modulation: BT LE Channel: Mid 70-65 60 FCC 1<u>5</u> 55 50 45 Level in dBµV/m 30 25 10 30M 50 60 80 100M 200 300 400 500 800 1G Frequency in Hz FCC 15 Preview Result 1-PK+ Data Reduction Result 1 [2]-PK+

Page 45 of 52 IC ID: N/A

FCC ID: 2AFBP-AT17P



Plot #6 Radiated Emissions: 1-3 GHz Modulation: BT LE Channel: Mid 100 95 2.440000000 GHz 93.133 dBµV/m 85 80 74 dBuV perm 70 Level in dBµV/m 65 In the plant with the second s 55 45 40 35 30-1500 2500 1000 2000 3000 Frequency in MHz 74 dBuV per m 54 dBuV per m Preview Result 1-PK+ Preview Result 2-RMS Data Reduction Result 1 [4]-PK+ Data Reduction Result 2 [4]-RMS

IC ID: N/A

FCC ID: 2AFBP-AT17P

CETECOM


Plot #7 Radiated Emissions: 3-18 GHz Modulation: BT LE Channel: Mid 90_T 85 80 74 dBuV per m 75 70 65 60 55 Level in dBµV/m 50 35 30 25 20 15-10-5-0+ 3G 5G 6 8 10G 18G Frequency in Hz 74 dBuV per m 54 dBuV per m Preview Result 1-PK+ Preview Result 2-RMS Data Reduction Result 1 [5]-PK+ Data Reduction Result 2 [5]-RMS

Page 47 of 52

FCC ID: 2AFBP-AT17P

IC ID: N/A






Page 48 of 52

FCC ID: 2AFBP-AT17P IC ID: N/A





Date of Report 2017-05-09

Page 49 of 52 IC ID: N/A

FCC ID: 2AFBP-AT17P




Plot # 10 Radiated Emissions: 1-3 GHz and Restricted Bands Modulation: BT LE Channel: High 100 2.478000000 GHz 95 94.457 dBµV/m 90 85 80 75 74 dBuV perm 70 Level in dBµV/m 65 man hadin di kinin da man da mangan pada ka ka a mala man ka kinin da ka pada man ka ka ka ka ka ka ka ka ka k 40 35 30-1000 1500 2000 2500 3000 Frequency in MHz 74 dBuV per m 54 dBuV per m Preview Result 1-PK+ Preview Result 2-RMS Data Reduction Result 1 [4]-PK+ Data Reduction Result 2 [4]-RMS

FCC ID: 2AFBP-AT17P

Date of Report 2017-05-09 Page 50 of 52 IC ID: N/A





Date of Report 2017-05-09 Page 51 of 52 IC ID: N/A



FCC ID: 2AFBP-AT17P

9 Test setup photos

Setup photos are included in supporting file name: "EMC_IRHYT-008-17001_15.247_DTS_PATCH_Setup_Photos.pdf"

10 Test Equipment And Ancillaries Used For Testing

| Item Name | Equipment Type | Manufacturer | Model | Serial # | Calibration Cycle | Last Calibration Date |
|----------------------------|---------------------------|--------------------|-----------|----------|----------------------|-----------------------------|
| Antenna Biconilog 3142E | Biconlog Antenna | EMCO | 3142E | 166067 | 3 years | 6/14/2014 |
| Antenna Horn 3115 SN 35111 | Horn Antenna | EMCO | 3115 | 35111 | 3 years | 7/24/2015 |
| Antenna Horn 3116 | Horn Antenna | ETS Lindgren | 3116 | 70497 | 3 years | 7/22/2015 |
| Digital Barometer | Compact Digital Barometer | Control Company | 35519-055 | 91119547 | 2 Years | 4/7/2015 |
| FSU26 | Spectrum Analyzer | R&S | FSU26 | 200065 | 3 years | 7/4/2015 |
| FSU26 | Spectrum Analyzer | R&S | FSU26 | 200302 | 3 years | 7/4/2015 |
| Thermometer Humidity TM320 | Thermometer Humidity | Dickson | AY1072 | 0528 | 1 Year | 11/2/2016 |

Note:

- 1. Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels.
- 2. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

Test Report #: EMC_IRHYT-008-17001_15.247_DTS_PATCH FCC ID: 2AFBP-AT17P

Date of Report 2017-05-09 Page 52 of 52 IC ID: N/A



11 Revision History

| Date | Report Name | Changes to report | Report prepared by | |
|------------|--------------------------------------|-------------------|--------------------|--|
| 2017-04-25 | EMC IRHYT-008-17001 15.247 DTS PATCH | Initial Version | Cindy Li | |