

**FCC 47 CFR PART 15 SUBPART C**

**CERTIFICATION TEST REPORT**

*For*

**WiSound**

**MODEL No.:**

**WSK-5-XYY, WSK-9-XYY, WSS-5-XYY, WSS-6-XYY, SW-3-XYY, WSK-4-XYY**  
(X-> B: Black, R: Red, W: White YY-> EU: Europe plug, UK: UK plug)

**FCC ID: 2AFBR-TEEVY**

**REPORT NO: ES150515146E2**

**ISSUE DATE: July 03, 2015**

*Prepared for*

**Crystal Audio S.A.  
Aiantos 3A, Athens, Greece**

*Prepared by*

**SHENZHEN EMTEK CO., LTD.**

**Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,  
Guangdong, China  
TEL: 86-755-26954280  
FAX: 86-755-26954282**

## Table of Contents

1	TEST RESULT CERTIFICATION .....	3
2	EUT TECHNICAL DESCRIPTION.....	4
3	SUMMARY OF TEST RESULT .....	5
4	TEST METHODOLOGY .....	6
4.1	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	6
4.2	MEASUREMENT EQUIPMENT USED.....	6
4.3	DESCRIPTION OF TEST MODES .....	7
5	FACILITIES AND ACCREDITATIONS .....	8
5.1	FACILITIES .....	8
5.2	LABORATORY ACCREDITATIONS AND LISTINGS.....	8
6	TEST SYSTEM UNCERTAINTY .....	9
7	SETUP OF EQUIPMENT UNDER TEST .....	10
7.1	RADIO FREQUENCY TEST SETUP 1.....	10
7.2	RADIO FREQUENCY TEST SETUP 2.....	10
7.3	CONDUCTED EMISSION TEST SETUP .....	11
7.4	SUPPORT EQUIPMENT .....	12
8	FREQUENCY HOPPING SYSTEM REQUIREMENTS .....	13
8.1	STANDARD APPLICABLE.....	13
8.2	EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	13
8.3	EQUAL HOPPING FREQUENCY USE .....	14
8.4	FREQUENCY HOPPING SYSTEM.....	14
9	TEST REQUIREMENTS.....	15
9.1	20DB & 99% BANDWIDTH.....	15
9.2	CARRIER FREQUENCY SEPARATION .....	21
9.3	NUMBER OF HOPPING FREQUENCIES.....	27
9.4	AVERAGE TIME OF OCCUPANCY (DWELL TIME) .....	29
9.5	MAXIMUM PEAK CONDUCTED OUTPUT POWER .....	32
9.6	CONDUCTED SPURIOUS EMISSION .....	38
9.7	RADIATED SPURIOUS EMISSION .....	45
9.8	CONDUCTED EMISSION TEST .....	58
9.9	ANTENNA APPLICATION.....	61

## 1 TEST RESULT CERTIFICATION

Applicant:	Crystal Audio S.A.
Manufacturer:	Crystal Audio S.A.
Product Description:	WiSound
Model Number:	WSK-5-XYY, WSK-9-XYY, WSS-5-XYY, WSS-6-XYY, SW-3-XYY, WSK-4-XYY (X-> B: Black, R: Red, W: White YY-> EU: Europe plug, UK: UK plug) (Note: These models are identical in circuitry and electrical, mechanical and physical construction; the only differences are the color and plug. We prepare WSS-6 for test, and the worst result recorded in the report.)
File Number:	ES150515146E2
Date of Test:	May 25, 2015 to June 02, 2015

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J	
FCC 47 CFR Part 15, Subpart C	PASS

The above equipment was tested by SHENZHEN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Date of Test : May 15, 2015 to July 03, 2015



KingKong /Tester



Yaping Shen/Editor



Lisa Wang/Manager

Prepared by :

Approve & Authorized Signer :

## 2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
<b>Data Rate</b>	WIFI: 802.11 b:1,2,5.5,11Mbps; 802.11 g:6,9,12,18,24,36,48,54Mbps; 802.11n(HT20):MCS0-MCS7; 802.11n(HT40):MCS8-MCS15; Bluetooth: 1Mbps for BT V3.0 BR GFSK modulation 2Mbps for BT V3.0 EDR pi/4-DQPSK modulation 3Mbps for BT V3.0 EDR 8DPSK modulation
<b>Modulation:</b>	WIFI: DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n; Bluetooth: GFSK modulation (1Mbps) pi/4-DQPSK modulation (2Mbps) 8DPSK modulation (3Mbps)
<b>Operating Frequency Range(s):</b>	WIFI: 2412-2462MHz for 802.11b/g; 2412-2462MHz for 802.11n(HT20); 2422-2452MHz for 802.11n(HT40); Bluetooth: 2402-2480MHz
<b>Number of Channels:</b>	WIFI: 11 channels for 802.11b/g; 11 channels for 802.11n(HT20); 7 channels for 802.11n(HT40); Bluetooth DSS: 79 channels Bluetooth DTS: 40 channels
<b>Transmit Power Max:</b>	WIFI: 14.91 dBm for 802.11b; 15.27 dBm for 802.11g; 14.55 dBm for 802.11n(HT20); 15.36 dBm for 802.11n(HT40); Bluetooth: 7.195 dBm for BT DSS; 7.643 dBm for BT DTS;
<b>Antenna Type :</b>	PCB antenna
<b>Antenna Gain:</b>	2dBi for Bluetooth antenna 2dBi for WIFI antenna
<b>Power supply:</b>	<input type="checkbox"/> DC supply: <input checked="" type="checkbox"/> Adapter supply: Model: TP06-240250W INPUT: 100-240V~50/60Hz 1.5A MAX OUTPUT: DC 24V 2.5A
<b>Temperature Range</b>	-20°C ~ +55°C

**Note:** for more details, please refer to the User's manual of the EUT.

### 3 SUMMARY OF TEST RESULT

FCC Part Clause	IC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(1)	RSS-247.5.1(2)	20 dB Bandwidth	PASS	
15.247(a)(1)	RSS-247.5.1(4)	Carrier Frequency Separation	PASS	
15.247(a)(1)	RSS-247.5.1(4)	Number of Hopping Frequencies	PASS	
15.247(a)(1)	RSS-247.5.1(5)	Average Time of Occupancy (Dwell Time)	PASS	
15.247(b)(1)	RSS-247.5.4(4)	Maximum Peak Conducted Output Power	PASS	
15.247(c)	RSS-Gen 8.8	Conducted Spurious Emissions	PASS	
15.247(d) 15.209	RSS-Gen.6.13	Radiated Spurious Emissions	PASS	
15.207	RSS-Gen 8.8	Conducted Emission	PASS	
15.247(b)	RSS-Gen.6.7	Antenna Application	PASS	
	RSS-Gen.6.6	99% Bandwidth	PASS	
		NOTE1: N/A (Not Applicable)		

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AFBR-TEEVY filing to comply with Section 15.247 of the FCC Part 15, Subpart C.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:  
 FCC 47 CFR Part 2, Subpart J  
 FCC 47 CFR Part 15, Subpart C  
 DA 00-705

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/16/2015	05/15/2016
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/16/2015	05/15/2016
50Ω Coaxial Switch	Anritsu	MP59B	M20531	N/A	05/15/2016
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/16/2015	05/15/2016
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/16/2015	05/15/2016
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/16/2015	05/15/2016

#### 4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	05/16/2015	05/15/2016
Pre-Amplifier	HP	8447D	2944A07999	05/16/2015	05/15/2016
Bilog Antenna	Schwarzbeck	VULB9163	142	05/16/2015	05/15/2016
Loop Antenna	ARA	PLA-1030/B	1029	05/16/2015	05/15/2016
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	05/16/2015	05/15/2016
Horn Antenna	Schwarzbeck	BBHA 9120	D143	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	ACRX1	05/16/2015	05/15/2016
Cable	Rosenberger	N/A	FP2RX2	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	CRPX1	05/16/2015	05/15/2016
Cable	Schwarzbeck	AK9513	CRRX2	05/16/2015	05/15/2016

#### 4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
Spectrum Analyzer	Agilent	E4407B	88156318	05/16/2015	05/15/2016
Signal Analyzer	Agilent	N9010A	My53470879	05/16/2015	05/15/2016
Power meter	Anritsu	ML2495A	0824006	05/16/2015	05/15/2016
Power sensor	Anritsu	MA2411B	0738172	05/16/2015	05/15/2016

**Remark:** Each piece of equipment is scheduled for calibration once a year.

#### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (1Mbps for Bluetooth V3.0 BR GFSK modulation; 2Mbps for Bluetooth V3.0 EDR pi/4-DQPSK modulation; 3Mbps for Bluetooth V3.0 EDR 8DPSK modulation ) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Frequency and Channel list for Bluetooth V3.0:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	...	...
1	2403	40	2442	76	2478
2	2404	41	2443	77	2479
...	...	...	...	78	2480

Note:  $fc = 2402\text{MHz} + (k-1) \times 1\text{MHz}$  k=1 to 79

Test Frequency and channel for Bluetooth V3.0:

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	39	2441	78	2480

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2013.10.29  
The certificate is valid until 2016.10.28  
The Laboratory has been assessed and proved to be in compliance with CNAS-CL01: 2006(identical to ISO/IEC17025: 2005)  
The Certificate Registration Number is L2291

: Accredited by TUV Rheinland Shenzhen, 2010.5.25  
The Laboratory has been assessed according to the requirements ISO/IEC 17025.

: Accredited by FCC, July 24, 2013  
The Certificate Registration Number is 406365.

: Accredited by FCC, April 17, 2013  
The Certificate Registration Number is 709623.

: Accredited by Industry Canada, November 29, 2012  
The Certificate Registration Number is 4480A-2

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0 \text{dB}$
Conducted Emissions Test	$\pm 2.0 \text{dB}$
Radiated Emission Test	$\pm 2.0 \text{dB}$
Occupied Bandwidth Test	$\pm 1.0 \text{dB}$
Band Edge Test	$\pm 3 \text{dB}$
All emission, radiated	$\pm 3 \text{dB}$
Antenna Port Emission	$\pm 3 \text{dB}$
Temperature	$\pm 0.5 \text{ }^{\circ}\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The Bluetooth V3.0 component's antenna port(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2009 and CAN/CSA-CEI/IEC CISPR 22.


Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


Above 30GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


#### (a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (Game fitness board) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2009 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



#### 7.4 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Note
	iPhone	Apple	A1526	N/A

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 8 FREQUENCY HOPPING SYSTEM REQUIREMENTS

### 8.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.


### 8.2 EUT Pseudorandom Frequency Hopping Sequence

The channel is represented by a pseudo-random hopping sequence hopping through the 79 RF channels. The hopping sequence is unique for the piconet and is determined by the Bluetooth device address of the master; the phase in the hopping sequence is determined by the Bluetooth clock of the master. The channel is divide into time slots where each slot corresponds to an RF hop frequency. Consecutive hops correspond to different RF hop frequencies. The normal hop is 1 600 hops/s.


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones. Number of shift register stages: 9

Length of pseudo-random sequence:  $2^9 - 1 = 524$  bits

Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*



Each frequency used equally on the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

### **8.3 Equal Hopping Frequency Use**

All Bluetooth units participating in the piconet are time and hop-synchronized to the channel.

Example of a 79 hopping sequence in data mode:

35, 27, 6, 44, 14, 61, 74, 32, 1, 11, 23, 2, 55, 65, 29, 3, 9, 52, 78, 58, 40, 25, 0, 7, 18, 26, 76, 60, 47, 50, 2, 5, 16, 37, 70, 63, 66, 54, 20, 13, 4, 8, 15, 21, 26, 10, 73, 77, 67, 69, 43, 24, 57, 39, 46, 72, 48, 33, 17, 31, 75, 19, 41, 62, 68, 28, 51, 66, 30, 56, 34, 59, 71, 22, 49, 64, 38, 45, 36, 42, 53

Each Frequency used equally on the average by each transmitter

### **8.4 Frequency Hopping System**

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH- enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

## 9 TEST REQUIREMENTS

### 9.1 20DB & 99% BANDWIDTH

#### 9.1.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

#### 9.1.2 Conformance Limit

No limit requirement.

#### 9.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 9.1.4 Test Procedure

The EUT was operating in Bluetooth V3.0 mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 30 kHz.

Set the video bandwidth (VBW) =100 kHz.

Set Span= approximately 2 to 3 times the 20 dB bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the markerdelta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.


Measure and record the results in the test report.


### Test Results


Temperature:	24°C	Test Date:	July 01, 2015
Humidity:	53 %	Test By:	KK


Modulation Mode	Channel Number	Channel Frequency (MHz)	20dB Bandwidth (kHz)	99% Bandwidth (kHz)
GFSK	00	2402	863.052	834.589
	39	2441	857.903	826.055
	78	2480	860.005	829.299
pi/4-DQPSK	00	2402	1216.0	1158.6
	39	2441	1223.0	1162.3
	78	2480	1221.0	1159.2
8DPSK	00	2402	1212.0	1146.7
	39	2441	1218.0	1143.0
	78	2480	1227.0	1145.9
Note: N/A (Not Applicable)				











## 9.2 CARRIER FREQUENCY SEPARATION

### 9.2.1 Applicable Standard

According to FCC Part 15.247(a)(1) and DA 00-705

### 9.2.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall have hopping channel carrier frequencies separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

In case of an output power less than 125mW, the frequency hopping system may have channels separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of the hopping channel, whichever is greater.

### 9.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.2.4 Test Procedure

■ According to FCC Part15.247(a)(1)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Set the RBW =100kHz. Set VBW =300kHz.

Set the span = wide enough to capture the peaks of two adjacent channels

Set Sweep time = auto couple.


Set Detector = peak. Set Trace mode = max hold.

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.



### Test Results


Temperature:	24 °C	Test Date:	July 01, 2015
Humidity:	53 %	Test By:	KK

Modulation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (kHz)	Limit (kHz)	Verdict
GFSK	0	2402	1000	>575.368	PASS
	39	2441	1000	>571.935	PASS
	78	2480	1000	>573.337	PASS
pi/4-DQPSK	0	2402	1000	>810.667	PASS
	39	2441	1000	>815.333	PASS
	78	2480	1000	>814.000	PASS
8DPSK	0	2402	1000	>808.000	PASS
	39	2441	1000	>812.000	PASS
	78	2480	1000	>818.000	PASS
Note: Limit = 20dB bandwidth*2/3, if it is greater than 25kHz and the output power is less than 125mW (21dBm).					



Test Model	Carrier Frequency Separation	
	Bluetooth v3.0	
	Channel 78: 2480MHz	GFSK Modulation
<div style="display: flex; justify-content: space-between;"> <div style="flex: 1;"> <p>Agilent</p> <p>Ref 20 dBm      Atten 30 dB</p> <p>Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.479500000 GHz</p> <p>Mkr1 <math>\Delta</math> 1.0000 MHz 0.044 dB</p> <p>Marker 1R Trace (1) Type Freq 2.4790000 GHz X Axis 2.4790000 GHz Amplitude 6.807 dBm</p> <p>Marker 1a Trace (1) Type Freq 1.0000 MHz 1.0000 MHz 0.044 dB</p> </div> <div style="flex: 1; border: 1px solid black; padding: 5px;"> <p><b>Freq/Channel</b></p> <p>Center Freq 2.47950000 GHz</p> <p>Start Freq 2.47800000 GHz</p> <p>Stop Freq 2.48100000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p> </div> </div>		
Test Model	Carrier Frequency Separation	
	Bluetooth v3.0	pi/4-DQPSK Modulation
<div style="display: flex; justify-content: space-between;"> <div style="flex: 1;"> <p>Agilent</p> <p>Ref 20 dBm      Atten 30 dB</p> <p>Peak Log 10 dB/Offset 1 dB</p> <p>Center 2.402500000 GHz</p> <p>Mkr1 <math>\Delta</math> 1.0000 MHz 1.285 dB</p> <p>Marker 1R Trace (1) Type Freq 2.4020000 GHz X Axis 2.4020000 GHz Amplitude 0.699 dBm</p> <p>Marker 1a Trace (1) Type Freq 1.0000 MHz 1.0000 MHz 1.285 dB</p> </div> <div style="flex: 1; border: 1px solid black; padding: 5px;"> <p><b>Freq/Channel</b></p> <p>Center Freq 2.40250000 GHz</p> <p>Start Freq 2.40100000 GHz</p> <p>Stop Freq 2.40400000 GHz</p> <p>CF Step 300.000000 kHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p> </div> </div>		

Test Model	Carrier Frequency Separation																
	Bluetooth v3.0																
	Channel 39: 2441MHz	pi/4-DQPSK Modulation															
 <p><b>Agilent</b></p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 <math>\Delta</math> 1.0000 MHz      0.004 dB</p> <p>Peak Log 10 dB/Offst 1 dB</p> <p>Center 2.441500000 GHz</p> <p>Center 2.442 GHz      #Res BW 100 kHz      #VBW 300 kHz      Sweep 5 ms (401 pts)</p> <table border="1"> <tr> <td>Marker</td> <td>Trace</td> <td>Type</td> <td>X Axis</td> <td>Amplitude</td> </tr> <tr> <td>1R</td> <td>(1)</td> <td>Freq</td> <td>2.4410000 GHz</td> <td>3.883 dBm</td> </tr> <tr> <td>1<math>\Delta</math></td> <td>(1)</td> <td>Freq</td> <td>1.0000 MHz</td> <td>0.004 dB</td> </tr> </table> <p>Freq/Channel</p> <p>Center Freq 2.44150000 GHz</p> <p>Start Freq 2.44000000 GHz</p> <p>Stop Freq 2.44300000 GHz</p> <p>CF Step 300.000000 kHz</p> <p>Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>			Marker	Trace	Type	X Axis	Amplitude	1R	(1)	Freq	2.4410000 GHz	3.883 dBm	1 $\Delta$	(1)	Freq	1.0000 MHz	0.004 dB
Marker	Trace	Type	X Axis	Amplitude													
1R	(1)	Freq	2.4410000 GHz	3.883 dBm													
1 $\Delta$	(1)	Freq	1.0000 MHz	0.004 dB													
Test Model	Carrier Frequency Separation																
	Bluetooth v3.0																
	Channel 78: 2480MHz	pi/4-DQPSK Modulation															
 <p><b>Agilent</b></p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 <math>\Delta</math> 1.0000 MHz      0.015 dB</p> <p>Peak Log 10 dB/Offst 1 dB</p> <p>Center 2.479500000 GHz</p> <p>Center 2.479 GHz      #Res BW 100 kHz      #VBW 300 kHz      Sweep 5 ms (401 pts)</p> <table border="1"> <tr> <td>Marker</td> <td>Trace</td> <td>Type</td> <td>X Axis</td> <td>Amplitude</td> </tr> <tr> <td>1R</td> <td>(1)</td> <td>Freq</td> <td>2.4790000 GHz</td> <td>4.354 dBm</td> </tr> <tr> <td>1<math>\Delta</math></td> <td>(1)</td> <td>Freq</td> <td>1.0000 MHz</td> <td>0.015 dB</td> </tr> </table> <p>Freq/Channel</p> <p>Center Freq 2.47950000 GHz</p> <p>Start Freq 2.47800000 GHz</p> <p>Stop Freq 2.48100000 GHz</p> <p>CF Step 300.000000 kHz</p> <p>Auto Man</p> <p>Freq Offset 0.0000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>			Marker	Trace	Type	X Axis	Amplitude	1R	(1)	Freq	2.4790000 GHz	4.354 dBm	1 $\Delta$	(1)	Freq	1.0000 MHz	0.015 dB
Marker	Trace	Type	X Axis	Amplitude													
1R	(1)	Freq	2.4790000 GHz	4.354 dBm													
1 $\Delta$	(1)	Freq	1.0000 MHz	0.015 dB													





### 9.3 NUMBER OF HOPPING FREQUENCIES

#### 9.3.1 Applicable Standard

According to FCC Part 15.247(a)(1) (iii)and DA 00-705

#### 9.3.2 Conformance Limit

Frequency hopping systems operating in the 2400-2483.5MHz band shall use at least 15 channels.

#### 9.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 9.3.4 Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation (2390-2440MHz) and(2440-2490MHz)

RBW  $\geq$  1% of the span

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak


Trace = max hold

Allow the trace to stabilize. It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

#### Test Results

Temperature: 24°C      Test Date: July 01, 2015  
Humidity: 53 %      Test By: KK

Hopping Channel Frequency Range	Quantity of Hopping Channel	Quantity of Hopping Channel limit
2402-2480	79	>15



## 9.4 AVERAGE TIME OF OCCUPANCY (DWELL TIME)

### 9.4.1 Applicable Standard

According to FCC Part 15.247(a)(1)(iii) and DA 00-705

### 9.4.2 Conformance Limit

For frequency hopping systems operating in the 2400-2483.5MHz band, the average time of occupancy on any channel shall not be greater than 0.4s within a period of 0.4s multiplied by the number of hopping channels employed.

### 9.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.4.4 Test Procedure

- According to FCC Part15.247(a)(1)(iii)

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = zero span, centered on a hopping channel

RBW = 1 MHz

VBW  $\geq$  RBW

Sweep = as necessary to capture the entire dwell time per hopping channel

Detector function = peak

Trace = max hold



If possible, use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.),


repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section.

### 9.4.5 Test Results

Temperature: 24°C      Test Date: July 01, 2015  
 Humidity: 53 %      Test By: KK

Modulation Mode	Channel Number	Packet type	Pluse width (ms)	Number per channel in 31.6s	dwell time (ms)	Limit (ms)	Verdict
GFSK	0	DH1	0.39	320.00	124.8	<400	PASS
	0	DH3	1.60	160.00	256.0	<400	PASS
	0	DH5	2.90	106.67	309.3	<400	PASS
Note:							

Test Model	Average Time Of Occupancy (Dwell Time)		
	Bluetooth v3.0		
	CH 0: 2402MHz	GFSK	DH1
 <p>Agilent</p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 <math>\Delta</math> 390 <math>\mu</math>s Peak      1.292 dB</p> <p>Log 10 dB/ Offst 1 dB</p> <p>Center 2.402000000 GHz</p> <p>W1 S2 S3 FS AA</p> <p>Center 2.402 GHz      Span 0 Hz Res BW 1 MHz      *VBW 3 MHz      Sweep 4 ms (401 pts)</p> <p>Freq/Channel Center Freq Start Freq Stop Freq CF Step Freq Offset Signal Track Scale Type</p>			
Test Model	Average Time Of Occupancy (Dwell Time)		
	Bluetooth v3.0		
	CH 0: 2402MHz	GFSK	DH3
 <p>Agilent</p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 <math>\Delta</math> 1.64 ms Peak      0.013 dB</p> <p>Log 10 dB/ Offst 1 dB</p> <p>Center 2.402000000 GHz</p> <p>W1 S2 S3 FS AA</p> <p>Center 2.402 GHz      Span 0 Hz Res BW 1 MHz      *VBW 3 MHz      Sweep 8 ms (401 pts)</p> <p>Freq/Channel Center Freq Start Freq Stop Freq CF Step Freq Offset Signal Track Scale Type</p>			



## 9.5 MAXIMUM PEAK CONDUCTED OUTPUT POWER

### 9.5.1 Applicable Standard

According to FCC Part 15.247(b)(1) and DA 00-705

### 9.5.2 Conformance Limit

The max For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

### 9.5.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.5.4 Test Procedure

- According to FCC Part15.247(b)(1)

As an alternative to a peak power measurement, compliance with the limit can be based on a measurement of the maximum conducted output power.

Use the following spectrum analyzer settings:

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel (about 10MHz)

Set RBW > the 20 dB bandwidth of the emission being measured (about 3MHz)

Set VBW  $\geq$  RBW

Set Sweep = auto

Set Detector function = peak



Set Trace = max hold



Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission to determine the peak amplitude level.



## Test Results



Temperature:	24°C	Test Date:	July 01, 2015
Humidity:	53 %	Test By:	KK


Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
GFSK	0	2402	4.355	30	PASS
	39	2441	6.778	30	PASS
	78	2480	<b>7.195</b>	30	PASS
pi/4-DQPSK	0	2402	2.065	30	PASS
	39	2441	5.220	30	PASS
	78	2480	5.724	30	PASS
8DPSK	0	2402	2.657	30	PASS
	39	2441	5.548	30	PASS
	78	2480	6.002	30	PASS
Note: N/A					

Test Model	Maximum Peak Conducted Output Power				
	Bluetooth v3.0				
	Channel 0: 2402MHz	GFSK			
 <p><b>Agilent</b></p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 2.402200 GHz 4.355 dBm</p> <p>Peak      Log      10 dB/Offst 1 dB</p> <p>Center 2.402000000 GHz</p> <p>M1 S2      S3 FC      AA</p> <p>Center 2.402 GHz      #Res BW 3 MHz      *VBW 3 MHz      Span 10 MHz      Sweep 4 ms (401 pts)</p> <p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.40200000 GHz</p> <p><b>Start Freq</b> 2.39700000 GHz</p> <p><b>Stop Freq</b> 2.40700000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>					
Test Model	Maximum Peak Conducted Output Power				
	Bluetooth v3.0				
	Channel 39: 2441MHz	GFSK			
 <p><b>Agilent</b></p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 2.440775 GHz 6.778 dBm</p> <p>Peak      Log      10 dB/Offst 1 dB</p> <p>Center 2.441000000 GHz</p> <p>M1 S2      S3 FC      AA</p> <p>Center 2.441 GHz      #Res BW 3 MHz      *VBW 3 MHz      Span 10 MHz      Sweep 4 ms (401 pts)</p> <p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.44100000 GHz</p> <p><b>Start Freq</b> 2.43600000 GHz</p> <p><b>Stop Freq</b> 2.44600000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>					

Test Model	Maximum Peak Conducted Output Power		
	Bluetooth v3.0		
	Channel 78: 2480MHz	GFSK	
 <p><b>Agilent</b></p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 2.479850 GHz 7.195 dBm</p> <p>Peak Log 10 dB/ Offst 1 dB</p> <p>Center 2.480000000 GHz</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.48 GHz      Span 10 MHz #Res BW 3 MHz      *VBW 3 MHz      Sweep 4 ms (401 pts)</p> <p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.48000000 GHz</p> <p><b>Start Freq</b> 2.47500000 GHz</p> <p><b>Stop Freq</b> 2.48500000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto      Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On      Off</p> <p><b>Scale Type</b> Log      Lin</p>			
Test Model	Maximum Peak Conducted Output Power	Bluetooth v3.0	pi/4-DQPSK
	Channel 0: 2402MHz		
 <p><b>Agilent</b></p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 2.402250 GHz 2.065 dBm</p> <p>Peak Log 10 dB/ Offst 1 dB</p> <p>Center 2.402000000 GHz</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.402 GHz      Span 10 MHz #Res BW 3 MHz      *VBW 3 MHz      Sweep 4 ms (401 pts)</p> <p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.40200000 GHz</p> <p><b>Start Freq</b> 2.39700000 GHz</p> <p><b>Stop Freq</b> 2.40700000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto      Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On      Off</p> <p><b>Scale Type</b> Log      Lin</p>			

Test Model	Maximum Peak Conducted Output Power		
	Bluetooth v3.0		
	Channel 39: 2441MHz	pi/4-DQPSK	
 <p><b>Agilent</b></p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 2.440750 GHz 5.22 dBm</p> <p>Peak      Log</p> <p>10 dB/Offst 1 dB</p> <p>Center 2.441000000 GHz</p> <p>M1 S2      S3 FC      AA</p> <p>Center 2.441 GHz      #Res BW 3 MHz      *VBW 3 MHz      Span 10 MHz      Sweep 4 ms (401 pts)</p> <p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.44100000 GHz</p> <p><b>Start Freq</b> 2.43600000 GHz</p> <p><b>Stop Freq</b> 2.44600000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>			
Maximum Peak Conducted Output Power			
Bluetooth v3.0		pi/4-DQPSK	
Channel 78: 2480MHz			
 <p><b>Agilent</b></p> <p>Ref 20 dBm      Atten 30 dB      Mkr1 2.479850 GHz 5.724 dBm</p> <p>Peak      Log</p> <p>10 dB/Offst 1 dB</p> <p>Center 2.480000000 GHz</p> <p>M1 S2      S3 FC      AA</p> <p>Center 2.48 GHz      #Res BW 3 MHz      *VBW 3 MHz      Span 10 MHz      Sweep 4 ms (401 pts)</p> <p><b>Freq/Channel</b></p> <p><b>Center Freq</b> 2.48000000 GHz</p> <p><b>Start Freq</b> 2.47500000 GHz</p> <p><b>Stop Freq</b> 2.48500000 GHz</p> <p><b>CF Step</b> 1.00000000 MHz Auto Man</p> <p><b>Freq Offset</b> 0.00000000 Hz</p> <p><b>Signal Track</b> On Off</p> <p><b>Scale Type</b> Log Lin</p>			

Test Model	Maximum Peak Conducted Output Power				
	Bluetooth v3.0				
	Channel 0: 2402MHz	8DPSK			
 <p>Agilent</p> <p>Ref 20 dBm Atten 30 dB Mkr1 2.402025 GHz 2.657 dBm</p> <p>Peak Log 10 dB/Offst 1 dB</p> <p>Center 2.402000000 GHz</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.402 GHz #Res BW 3 MHz *VBW 3 MHz Span 10 MHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.40200000 GHz</p> <p>Start Freq 2.39700000 GHz</p> <p>Stop Freq 2.40700000 GHz</p> <p>CF Step 1.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>					
Test Model	Maximum Peak Conducted Output Power				
	Bluetooth v3.0				
	Channel 39: 2441MHz	8DPSK			
 <p>Agilent</p> <p>Ref 20 dBm Atten 30 dB Mkr1 2.440975 GHz 5.548 dBm</p> <p>Peak Log 10 dB/Offst 1 dB</p> <p>Center 2.441000000 GHz</p> <p>M1 S2 S3 FC AA</p> <p>Center 2.441 GHz #Res BW 3 MHz *VBW 3 MHz Span 10 MHz Sweep 4 ms (401 pts)</p> <p>Freq/Channel</p> <p>Center Freq 2.44100000 GHz</p> <p>Start Freq 2.43600000 GHz</p> <p>Stop Freq 2.44600000 GHz</p> <p>CF Step 1.00000000 MHz Auto Man</p> <p>Freq Offset 0.00000000 Hz</p> <p>Signal Track On Off</p> <p>Scale Type Log Lin</p>					



## 9.6 CONDUCTED SUPRIOUS EMISSION

### 9.6.1 Applicable Standard

According to FCC Part 15.247(d) and DA 00-705

### 9.6.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted, provided the transmitter demonstrates compliance with the peak conducted power limits.

### 9.6.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 9.6.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

#### ■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DSS channel center frequency.

Set Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel.

Set the RBW = 100 kHz. Set the VBW  $\geq$  3 x RBW.

Set Detector = peak. Set Sweep time = auto couple.

Set Trace mode = max hold. Allow trace to fully stabilize.

Use the peak marker function to determine the maximum Maximum conducted level.

Note that the channel found to contain the maximum conducted level can be used to establish the reference level.

#### ■ Band-edge Compliance of RF Conducted Emissions

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the emission operating on the channel closest to the band-edge, as well as any modulation products which fall outside of the authorized band of operation

Set RBW  $\geq$  1% of the span=100kHz Set VBW  $\geq$  RBW

Set Sweep = auto Set Detector function = peak Set Trace = max hold

Allow the trace to stabilize. Set the marker on the emission at the bandedge, or on the highest modulation product outside of the band, if this level is greater than that at the bandedge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.

The marker-delta value now displayed must comply with the limit specified in this Section.

Now, using the same instrument settings, enable the hopping function of the EUT. Allow the trace to stabilize. Follow the same procedure listed above to determine if any spurious emissions caused by the hopping function also comply with the specified limit.

#### ■ Conducted Spurious RF Conducted Emission

Use the following spectrum analyzer settings:


Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic.(30MHz to 25GHz). Set RBW = 100 kHz Set VBW  $\geq$  RBW


Set Sweep = auto Set Detector function = peak Set Trace = max hold


Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this Section.


### 9.6.5 Test Results



Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:










Test Model	Maximum Conducted Level RBW=100kHz		
	Bluetooth v3.0		
	Hopping Mode		GFSK
			
Test Model	Conducted Spurious RF Conducted Emission		
	Bluetooth v3.0		
	Hopping Mode		GFSK
			



## 9.7 RADIATED SPURIOUS EMISSION

### 9.7.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and DA 00-705

### 9.7.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength ( $\mu$ V/m)	Field Strength ( $\text{dB}\mu$ V/m)	Measurement Distance
0.009-0.490	2400/F(KHz)	20 log ( $\mu$ V/m)	300
0.490-1.705	2400/F(KHz)	20 log ( $\mu$ V/m)	30
1.705-30	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

### 9.7.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 9.7.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz(1GHz to 25GHz), 100 kHz for  $f < 1$  GHz(30MHz to 1GHz)

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2009 respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

### 9.7.5 Test Results

#### ■ Spurious Emission below 30MHz (9KHz to 30MHz)

Temperature:	24°C	Test Date:	July 01, 2015
Humidity:	53 %	Test By:	KK
Test mode:	TX Mode		

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor = $40\log(\text{Specific distance/ test distance})(\text{ dB})$ ;  
Limit line=Specific limits(dBuV) + distance extrapolation factor

#### ■ Spurious Emission Above 1GHz (1GHz to 25GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:

Temperature:	24°C	Test Date:	July 01, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3179.73	V	60.86	45.58	74.00	54.00	-13.14	-8.42
4199.73	V	64.48	46.62	74.00	54.00	-9.52	-7.38
7565.73	V	66.44	45.94	74.00	54.00	-7.56	-8.06
3043.73	H	62.58	45.40	74.00	54.00	-11.42	-8.60
4165.73	H	63.94	46.61	74.00	54.00	-10.06	-7.39
6919.73	H	64.14	45.90	74.00	54.00	-9.86	-8.10

Temperature: 24°C      Test Date: July 01, 2015  
 Humidity: 53 %      Test By: KK  
 Test mode: GFSK      Frequency: Channel 39: 2441MHz

Freq. (MHz)	Ant.Po. l. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
2567.73	V	61.00	44.58	74.00	54.00	-13.00	-9.42
4148.73	V	63.95	45.63	74.00	54.00	-10.05	-8.37
9248.73	V	68.83	47.67	74.00	54.00	-5.17	-6.33
2516.73	H	60.20	45.40	74.00	54.00	-13.80	-8.60
4267.73	H	63.83	45.90	74.00	54.00	-10.17	-8.10
9656.73	H	67.83	46.69	74.00	54.00	-6.17	-7.31

Temperature: 24°C      Test Date: July 01, 2015  
 Humidity: 53 %      Test By: KK  
 Test mode: GFSK      Frequency: Channel 78: 2480MHz

Freq. (MHz)	Ant.Po. l. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
3145.73	V	62.11	45.62	74.00	54.00	-11.89	-8.38
4369.73	V	63.28	46.91	74.00	54.00	-10.72	-7.09
8466.73	V	67.56	47.75	74.00	54.00	-6.44	-6.25
1428.73	H	58.86	45.58	74.00	54.00	-15.14	-8.42
4165.73	H	63.44	48.01	74.00	54.00	-10.56	-5.99
9622.73	H	67.28	46.90	74.00	54.00	-6.72	-7.10

**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).  
 (2) Emission Level= Reading Level+Probe Factor +Cable Loss.  
 (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK, Hopping) mode have been tested, and the worst result(GFSK, Hopping) was report as below:

Temperature:	24°C	Test Date:	July 01, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Channel 0: 2402MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)
2389.12	H	43.09	74	-30.91	29.83	54	-24.17
2387.68	V	46.36	74	-27.64	32.73	54	-21.27

Temperature:	24°C	Test Date:	July 01, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Channel 78: 2480MHz

Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)
2484.11	H	38.78	74	-35.22	25.38	54	-28.62
2484.24	V	41.27	74	-32.73	27.49	54	-26.51


Temperature:	24°C	Test Date:	July 01, 2015
Humidity:	53 %	Test By:	KK
Test mode:	GFSK	Frequency:	Hopping


Frequency (MHz)	Polarity H/V	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)	AV(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Over(dB)
2382.20	H	45.07	74	-28.93	31.59	54	-22.41
2399.68	H	50.73	74	-23.27	37.69	54	-16.31
2483.50	H	55.36	74	-18.64	42.48	54	-11.52
2397.97	V	47.96	74	-26.04	33.68	54	-20.32
2400.00	V	60.44	74	-13.56	42.65	54	-11.35
2483.50	V	51.49	74	-22.51	38.43	54	-15.27


**Note:** (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.









■ Spurious Emission below 1GHz (30MHz to 1GHz)

Bluetooth (GFSK, pi/4-DQPSK, 8DPSK) mode have been tested, and the worst result(GFSK) was report as below:




\*:Maximum data    x:Over limit    !:over margin

Operator: KK




\*:Maximum data    x:Over limit    !:over margin

Operator: KK



\*:Maximum data    x:Over limit    !:over margin


Operator: KK



No.	Mk.	Freq. MHz	Reading	Correct	Measure-	Limit	Over	Antenna Height cm	Table Degree	Comment
			Level dBuV	Factor dB	ment dBuV/m					
1	*	30.0000	51.61	-16.46	35.15	40.00	-4.85	QP		
2		39.7000	40.49	-13.03	27.46	40.00	-12.54	QP		
3		118.2700	38.64	-15.97	22.67	43.50	-20.83	QP		
4		288.9900	32.68	-13.13	19.55	46.00	-26.45	QP		
5		385.0200	29.51	-9.71	19.80	46.00	-26.20	QP		
6		421.8800	29.68	-9.60	20.08	46.00	-25.92	QP		

\*:Maximum data    x:Over limit    !:over margin


Operator: KK



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1	*	196.8400	42.66	-16.68	25.98	43.50	-17.52	QP		
2		236.6100	39.87	-14.26	25.61	46.00	-20.39	QP		
3		242.4300	39.80	-13.71	26.09	46.00	-19.91	QP		
4		271.5300	40.52	-12.67	27.85	46.00	-18.15	QP		
5		292.8700	40.52	-13.39	27.13	46.00	-18.87	QP		
6		378.2300	35.29	-10.06	25.23	46.00	-20.77	QP		

\*:Maximum data   x:Over limit   !:over margin

Operator: KK



\*:Maximum data    x:Over limit    !:over margin

Operator: KK

## **9.8 CONDUCTED EMISSION TEST**

### **9.8.1 Applicable Standard**

According to FCC Part 15.207(a)

### **9.8.2 Conformance Limit**

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.


### **9.8.3 Test Configuration**

Test according to clause 7.3 conducted emission test setup

### **9.8.4 Test Procedure**

The EUT was placed on a table which is 0.8m above ground plane.  
Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
Repeat above procedures until all frequency measured were complete.

### **9.8.5 Test Results**



Site Conduction #1

Phase: **L1**

Temperature: 26

Limit: (CE)FCC PART 15 C

Power: AC 120V/60Hz


Humidity: 60 %

Mode: BT ON

Note:

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
			MHz	dBuV	dB	dBuV	dB		
1	*	0.1500	58.00	0.00	58.00	66.00	-8.00	QP	
2		0.1500	30.95	0.00	30.95	56.00	-25.05	AVG	
3		0.2000	50.86	0.00	50.86	63.61	-12.75	QP	
4		0.2000	24.61	0.00	24.61	53.61	-29.00	AVG	
5		0.3850	39.59	0.00	39.59	58.17	-18.58	QP	
6		0.3850	25.69	0.00	25.69	48.17	-22.48	AVG	
7		0.5050	41.95	0.00	41.95	56.00	-14.05	QP	
8		0.5050	26.99	0.00	26.99	46.00	-19.01	AVG	
9		4.0300	31.76	0.00	31.76	56.00	-24.24	QP	
10		4.0300	16.24	0.00	16.24	46.00	-29.76	AVG	
11		12.7000	32.64	0.00	32.64	60.00	-27.36	QP	
12		12.7000	31.24	0.00	31.24	50.00	-18.76	AVG	

\*:Maximum data   x:Over limit   !:over margin   Comment: Factor build in receiver.   Operator: XY



Site Conduction #1

Limit: (CE)FCC PART 15 C

Mode: BT ON

Note:

Phase: **N**

Power: AC 120V/60Hz

Temperature: 26

Humidity: 60 %

No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV	dBuV	dB		
1	*	0.1550	58.22	0.00	58.22	65.73	-7.51	QP	
2		0.1550	30.76	0.00	30.76	55.73	-24.97	AVG	
3		0.3450	40.18	0.00	40.18	59.08	-18.90	QP	
4		0.3450	25.44	0.00	25.44	49.08	-23.64	AVG	
5		0.5000	41.87	0.00	41.87	56.00	-14.13	QP	
6		0.5000	28.14	0.00	28.14	46.00	-17.86	AVG	
7		1.6550	32.07	0.00	32.07	56.00	-23.93	QP	
8		1.6550	26.60	0.00	26.60	46.00	-19.40	AVG	
9		12.7000	32.58	0.00	32.58	60.00	-27.42	QP	
10		12.7000	30.75	0.00	30.75	50.00	-19.25	AVG	
11		23.3500	32.74	0.00	32.74	60.00	-27.26	QP	
12		23.3500	20.37	0.00	20.37	50.00	-29.63	AVG	

\*:Maximum data

x:Over limit

!:over margin

Comment: Factor build in receiver.

Operator: XY

## 9.9 ANTENNA APPLICATION

### 9.9.1 Antenna Requirement

Standard	Requirement
FCC CRF Part 15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

The EUT'S antenna is PCB antenna. The antenna's gain is 2dBi, and the antenna can't be replaced by the user which in accordance to section 15.203, please refer to the photos.

### 9.9.2 Result

PASS.