

FCC Test Report

Report No.: RF150722C10-4

FCC ID: 2AFD7-P3301

Test Model: P3301

Received Date: Jul. 22, 2015

Test Date: Aug. 01, 2015 ~ Aug. 07, 2015

Issued Date: Aug. 25, 2015

Applicant: Poynt Co.

Address: 490 S California Avenue Suite 200 Palo Alto, CA 94306 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C)

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan

Hsien 333, Taiwan, R.O.C.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: RF150722C10-4 Page No. 1 / 32 Report Format Version: 6.1.1



Table of Contents

Release Control Record					
1	Cer	tificate of Conformity	. 5		
2	Sun	nmary of Test Results	. 6		
	21	Measurement Uncertainty	6		
		Modification Record			
3		neral Information			
3					
		General Description of EUT			
	3.2	Description of Test Modes			
	2 2	3.2.1 Test Mode Applicability and Tested Channel Detail Description of Support Units			
	3.3	3.3.1 Configuration of System under Test			
	3.4	General Description of Applied Standards			
4		t Types and Results			
•		•••			
	4.1	Radiated Emission and Bandedge Measurement			
		4.1.1 Limits of Radiated Emission and Bandedge Measurement			
		4.1.3 Test Procedures			
		4.1.4 Deviation from Test Standard			
		4.1.5 Test Set Up			
		4.1.6 EUT Operating Conditions	15		
		4.1.7 Test Results			
	4.2	Conducted Emission Measurement			
		4.2.1 Limits of Conducted Emission Measurement			
		4.2.3 Test Procedures			
		4.2.4 Deviation from Test Standard			
		4.2.5 TEST SETUPW			
		4.2.6 EUT Operating Conditions			
		4.2.7 Test Results			
	4.3	6dB Bandwidth Measurement			
		4.3.1 Limits of 6dB Bandwidth Measurement			
		4.3.2 Test Setup			
		4.3.4 Test Procedure			
		4.3.5 Deviation fromTest Standard			
		4.3.6 EUT Operating Conditions			
		4.3.7 Test Result			
	4.4	Conducted Output Power Measurement			
		4.4.1 Limits OF Conducted Output Power Measurement			
		4.4.2 Test Setup			
		4.4.3 Test Instruments			
		4.4.4 Test Procedures			
		4.4.6 EUT Operating Conditions			
		4.4.7 Test Results			
	4.5	Power Spectral Density Measurement			
		4.5.1 Limits of Power Spectral Density Measurement			
		4.5.2 Test Setup			
		4.5.3 Test Instruments			
		4.5.4 Test Procedure			
		4.5.6 EUT Operating Condition			
		4.5.7 Test Results			
			_5		



4.6 Conducted Out of Band Emission Measurement	29
4.6.1 Limits of Conducted Out of Band Emission Measurement	29
4.6.2 Test Setup	29
4.6.3 Test Instruments	29
4.6.4 Test Procedure	29
4.6.5 Deviation from Test Standard	
4.6.6 EUT Operating Condition	
4.6.7 TEST RESULTS	30
5 Pictures of Test Arrangements	31
Appendix – Information on the Testing Laboratories	32



Release Control Record

Issue No.	Description	Date Issued
RF150722C10-4	Original Release	Aug. 25, 2015

Report No.: RF150722C10-4 Page No. 4 / 32 Report Format Version: 6.1.1



1 Certificate of Conformity

Product: POS

Brand: POYNT

Test Model: P3301

Sample Status: Production Unit

Applicant: Poynt Co.

Test Date: Aug. 01, 2015 ~ Aug. 07, 2015

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : _______, Date: _______, Aug. 25, 2015

Ivonne Wu / Supervisor

Approved by : , **Date:** Aug. 25, 2015

Kay Wu / Supervisor



2 Summary of Test Results

	47 CFR FCC Part 15, Subpart C (SECTION 15.247) LE						
FCC Clause	Test Item	Result	Remarks				
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.74dB at 0.15811MHz.				
15.205 & 209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -12.82dB at 479.90MHz.				
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.				
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.				
15.247(a)(2)	15.247(a)(2) 6dB bandwidth		Meet the requirement of limit.				
15.247(b)	Conducted power	PASS	Meet the requirement of limit.				
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.				
15.203	Antenna Requirement	PASS	No antenna connector is used.				

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Padiated Emissions up to 1 CH7	30MHz ~ 200MHz	2.93 dB
Radiated Emissions up to 1 GHz	200MHz ~1000MHz	2.95 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.26 dB
Radiated Emissions above 1 GHZ	18GHz ~ 40GHz	1.94 dB

2.2 Modification Record

There were no modifications required for compliance.

Report No.: RF150722C10-4 Page No. 6 / 32 Report Format Version: 6.1.1



3 General Information

3.1 General Description of EUT

Product	POS		
Brand	POYNT		
Test Model	P3301		
Status of EUT	Production Unit		
Dower Supply Poting	12Vdc (adapter)		
Power Supply Rating	3.7Vdc (Li-ion battery)		
Modulation Type	GFSK		
Transfer Rate	1 Mbps		
Operating Frequency	2402 ~ 2480 MHz		
Number of Channel	40		
Output Power	1.774 mW		
Antenna Type	PIFA antenna with 3.2 dBi gain		
Antenna Connector	N/A		
Accessory Device	Refer to Note as below		
Data Cable Supplied	Refer to Note as below		

Note:

1. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	FSP GROUP INC.	FSP040-RHBN2	I/P: 100-240Vac, 50/60Hz, 1.5A O/P: 12Vdc, 3.33A 1.2m shielded cable with one core
Battery	Formosa Electronic Industries IN	P61	3.7Vdc, 14.8Wh
LCD Panel 1	LG	LD070WX7-SMN4	7"
LCD Panel 2	LG	LH430WV1-SD07	4.3"
Photo Camera	LITE-ON CORP.	5BA502T2A	
Video Camera	NingBo Sunny Opotech	Q034C-200	
Main Board	Quanta	DA0P61MBAB0	
eMMC	kingston	EMMC16G-V100-C50	16GB
CPU	nV	T40s	
WLAN Module	Azurewave	AW-AH640	
Docking	Quanta	DA0P61TB6B0	

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 Description of Test Modes

LE 4.0

40 channels are provided to this EUT:

Channel	Freq. (MHz)						
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

Report No.: RF150722C10-4 Page No. 8 / 32 Report Format Version: 6.1.1



3.2.1 Test Mode Applicability and Tested Channel Detail

LE 4.0

EUT Configure		Applica	able To	Description	
Mode	RE≥1G	RE<1G	PLC	APCM	Description
-	V	V	V	√	-

Where

RE≥1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	1

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)	
-	0 to 39	0	GFSK	1	

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0	GFSK	1

Report No.: RF150722C10-4 Page No. 9 / 32 Report Format Version: 6.1.1



Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Type	Data Rate (Mbps)
-	0 to 39	0, 19, 39	GFSK	1

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
PLC	25deg. C, 68%RH	120Vac, 60Hz	Toby Tian
APCM	21deg. C, 60%RH	3.7Vdc	Howard Kao


Report No.: RF150722C10-4 Page No. 10 / 32 Report Format Version: 6.1.1



3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units.

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
FCC Public Notice DA 00-705
558074 D01 DTS Meas Guidance v03r02

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

Report No.: RF150722C10-4 Page No. 11 / 32 Report Format Version: 6.1.1



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Report No.: RF150722C10-4 Page No. 12 / 32 Report Format Version: 6.1.1



4.1.2 Test Instruments

Description & Manaufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Jan. 21, 2015	Jan. 21, 2016
Spectrum Analyzer Agilent	N9010A	MY52220314	Sep. 03, 2014	Sep. 02, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 09, 2015	Feb. 09, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Feb. 04, 2015	Feb. 04, 2016
Loop Antenna	EM-6879	269	Jul. 31, 2015	Jul. 30, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 12, 2014	Dec. 11, 2015
Preamplifier EMCI	EMC 184045	980116	Jan. 09, 2015	Jan. 08, 2016
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2014	Dec. 26, 2015
Power Meter Anritsu	ML2495A	1232002	Sep. 17, 2014	Sep. 16, 2015
Power Sensor Anritsu	MA2411B	1207325	Sep. 17, 2014	Sep. 16, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2014	Oct. 17, 2015
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Nov. 07, 2014	Nov. 06, 2015
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 10.
- 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 690701.
- 5. The IC Site Registration No. is IC7450F-10.

Report No.: RF150722C10-4 Page No. 13 / 32 Report Format Version: 6.1.1



4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
- The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
- 5. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4	Deviation from	Test Standard


No deviation.

Report No.: RF150722C10-4 Page No. 14 / 32 Report Format Version: 6.1.1




4.1.5 Test Set Up

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- a. Placed the EUT on the testing table.
- b. Set the EUT under transmission condition continuously at specific channel frequency.

Report No.: RF150722C10-4 Page No. 15 / 32 Report Format Version: 6.1.1



4.1.7 Test Results

ABOVE 1GHz DATA:

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 0	FREQUENCY RANGE	1GHz ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2386	35.7	42.21	54	-18.3	26.91	4.08	37.5	139	82	Average
2386	58.22	64.73	74	-15.78	26.91	4.08	37.5	139	82	Peak
2402	96.61	103.13			26.91	4.09	37.52	139	82	Average
2402	97.35	103.87			26.91	4.09	37.52	139	82	Peak
2492	35.82	41.71	54	-18.18	27.2	4.16	37.25	139	82	Average
2492	57.61	63.5	74	-16.39	27.2	4.16	37.25	139	82	Peak
		ANTEN	INA POLA	RITY & T	EST DIST	ANCE: V	ERTICAL	AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2360	35.54	42.17	54	-18.46	26.81	4.05	37.49	102	18	Average
2360	57.63	64.26	74	-16.37	26.81	4.05	37.49	102	18	Peak
2402	92.52	99.04			26.91	4.09	37.52	102	18	Average
2402	93.24	99.76			26.91	4.09	37.52	102	18	Peak
2494	35.72	41.61	54	-18.28	27.2	4.16	37.25	102	18	Average
2494	57.61	63.5	74	-16.39	27.2	4.16	37.25	102	18	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2402MHz: Fundamental frequency.

Report No.: RF150722C10-4 Page No. 16 / 32 Report Format Version: 6.1.1



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 19	FREQUENCY RANGE	1GHz ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2358	35.22	41.85	54	-18.78	26.81	4.05	37.49	106	92	Average
2358	57.15	63.78	74	-16.85	26.81	4.05	37.49	106	92	Peak
2440	96.56	102.84			27.06	4.12	37.46	106	92	Average
2440	97.32	103.6			27.06	4.12	37.46	106	92	Peak
2488	35.6	41.56	54	-18.4	27.2	4.16	37.32	106	92	Average
2488	56.96	62.92	74	-17.04	27.2	4.16	37.32	106	92	Peak
		ANTEN	NA POLA	RITY & T	EST DIST	ANCE: V	ERTICAL	AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2384	35.1	41.66	54	-18.9	26.86	4.08	37.5	101	32	Average
2384	56.64	63.2	74	-17.36	26.86	4.08	37.5	101	32	Peak
2440	92.62	98.9	_		27.06	4.12	37.46	101	32	Average
2440	93.41	99.69			27.06	4.12	37.46	101	32	Peak
2488	35.4	41.36	54	-18.6	27.2	4.16	37.32	101	32	Average
2488	56.6	62.56	74	-17.4	27.2	4.16	37.32	101	32	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2440MHz: Fundamental frequency.

Report No.: RF150722C10-4 Page No. 17 / 32 Report Format Version: 6.1.1



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 39	FREQUENCY RANGE	1GHz ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2386	35.79	42.3	54	-18.21	26.91	4.08	37.5	103	86	Average
2386	56.49	63	74	-17.51	26.91	4.08	37.5	103	86	Peak
2480	96.59	102.61			27.15	4.15	37.32	103	86	Average
2480	97.39	103.41			27.15	4.15	37.32	103	86	Peak
2498	36.56	42.45	54	-17.44	27.2	4.16	37.25	103	86	Average
2498	58.12	64.01	74	-15.88	27.2	4.16	37.25	103	86	Peak
		ANTEN	NA POLA	RITY & T	EST DISTA	ANCE: V	ERTICAL	AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2346	35.46	42.13	54	-18.54	26.77	4.05	37.49	100	3	Average
2346	57.02	63.69	74	-16.98	26.77	4.05	37.49	100	3	Peak
2480	92.35	98.37	_		27.15	4.15	37.32	100	3	Average
2480	93.13	99.15			27.15	4.15	37.32	100	3	Peak
2498	36.09	41.98	54	-17.91	27.2	4.16	37.25	100	3	Average
2498	57.04	62.93	74	-16.96	27.2	4.16	37.25	100	3	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2480MHz: Fundamental frequency.

Report No.: RF150722C10-4 Page No. 18 / 32 Report Format Version: 6.1.1



BELOW 1GHz WORST-CASE DATA:

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 0	FREQUENCY RANGE	30MHz ~ 1GHz	
INPUT POWER	120Vac, 60 Hz		Peak (PK) Quasi-peak (QP)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
201.72	26.93	47.93	43.5	-16.57	9.44	1.3	31.74	110	231	Peak
211.71	30.28	50.68	43.5	-13.22	9.85	1.35	31.6	120	149	Peak
250.05	32.81	51.78	46	-13.19	11.48	1.49	31.94	110	340	Peak
360.2	26.79	42.58	46	-19.21	14.38	1.8	31.97	115	73	Peak
479.9	26.72	39.59	46	-19.28	16.93	2.05	31.85	124	153	Peak
637.4	28.11	37.82	46	-17.89	20.06	2.33	32.1	126	74	Peak
		ANTEN	INA POLA	RITY & T	EST DISTA	ANCE: V	ERTICAL	AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
59.16	25.42	43.93	40	-14.58	12.04	0.8	31.35	104	149	Peak
220.35	25.7	45.81	46	-20.3	10.22	1.38	31.71	100	136	Peak
250.05	28.29	47.26	46	-17.71	11.48	1.49	31.94	122	48	Peak
479.9	33.18	46.05	46	-12.82	16.93	2.05	31.85	128	229	Peak
500.9	28.78	40.98	46	-17.22	17.33	2.09	31.62	110	200	Peak
637.4	30.52	40.23	46	-15.48	20.06	2.33	32.1	109	246	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor

Margin value = Emission level – Limit value

Report No.: RF150722C10-4 Page No. 19 / 32 Report Format Version: 6.1.1



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Fraguency (MHz)	Conducted Limit (dBuV)			
Frequency (MHz)	Quasi-peak	Average		
0.15 - 0.5	66 - 56	56 - 46		
0.50 - 5.0	56	46		
5.0 - 30.0	60	50		

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 11, 2014	Nov. 10, 2015
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 26, 2014	Dec. 25, 2015
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 26, 2015	Feb. 25, 2016
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 24, 2015	Jul. 23, 2016
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-2040.

4.2.3 Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.


4.2.4 Deviation from Test Standard

No deviation.

Report No.: RF150722C10-4 Page No. 20 / 32 Report Format Version: 6.1.1



4.2.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

4.2.6 EUT Operating Conditions

Same as 4.1.6.



4.2.7 Test Results


CONDUCTED WORST-CASE DATA

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Toby Tian	Test Date	2015/8/1

	Phase Of Power : Line (L)									
	Frequency	Correction		Reading Value		nission Level Lir		nit	Margin	
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17022	0.05	48.05	28.23	48.10	28.28	64.95	54.95	-16.85	-26.67
2	0.19400	0.06	44.27	25.82	44.33	25.88	63.86	53.86	-19.53	-27.98
3	0.21406	0.06	41.29	26.15	41.35	26.21	63.05	53.05	-21.70	-26.84
4	0.26221	0.06	34.73	20.64	34.79	20.70	61.36	51.36	-26.57	-30.66
5	0.53686	0.06	34.66	25.25	34.72	25.31	56.00	46.00	-21.28	-20.69
6	3.08600	0.16	31.21	19.62	31.37	19.78	56.00	46.00	-24.63	-26.22

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value



Report No.: RF150722C10-4 Page No. 22 / 32 Report Format Version: 6.1.1




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Toby Tian	Test Date	2015/8/1

	Phase Of Power : Neutral (N)										
	Frequency	Correction	Readin	g Value	Emissic	mission Level Li		Limit		Margin	
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.15811	0.05	50.77	36.79	50.82	36.84	65.56	55.56	-14.74	-18.72	
2	0.20577	0.05	42.89	27.95	42.94	28.00	63.37	53.37	-20.43	-25.37	
3	0.23000	0.05	39.08	24.30	39.13	24.35	62.45	52.45	-23.32	-28.10	
4	0.27786	0.05	31.18	11.75	31.23	11.80	60.88	50.88	-29.65	-39.08	
5	0.53124	0.06	34.17	23.12	34.23	23.18	56.00	46.00	-21.77	-22.82	
6	2.90594	0.15	31.19	19.53	31.34	19.68	56.00	46.00	-24.66	-26.32	

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value



Report No.: RF150722C10-4 Page No. 23 / 32 Report Format Version: 6.1.1




4.3 6dB Bandwidth Measurement

4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) \geq 3 x RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 Deviation fromTest Standard

No deviation.

4.3.6 EUT Operating Conditions


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF150722C10-4 Page No. 24 / 32 Report Format Version: 6.1.1



4.3.7 Test Result

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	714.63	0.5	Pass
19	2440	704.26	0.5	Pass
39	2480	715.45	0.5	Pass






4.4 Conducted Output Power Measurement

4.4.1 Limits OF Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

A peak / average power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the power level.

4.4.5 Deviation from Test Standard

No deviation.

4.4.6 EUT Operating Conditions

Same as 4.3.6.

4.4.7 Test Results

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass / Fail
0	2402	1.734	2.39	30	Pass
19	2440	1.774	2.49	30	Pass
39	2480	1.770	2.48	30	Pass

Report No.: RF150722C10-4 Page No. 26 / 32 Report Format Version: 6.1.1




4.5 Power Spectral Density Measurement

4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition


Same as 4.3.6

Report No.: RF150722C10-4 Page No. 27 / 32 Report Format Version: 6.1.1



4.5.7 Test Results

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass / Fail
0	2402	-11.75	8	Pass
19	2440	-11.45	8	Pass
39	2480	-11.66	8	Pass






4.6 Conducted Out of Band Emission Measurement

4.6.1 Limits of Conducted Out of Band Emission Measurement

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

MEASUREMENT PROCEDURE REF

- Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOBE

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep = auto couple.
- 5. Trace Mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 Deviation from Test Standard


No deviation.

4.6.6 EUT Operating Condition

Same as 4.3.6

Report No.: RF150722C10-4 Page No. 29 / 32 Report Format Version: 6.1.1







5 Pictures of Test Arrangements
Please refer to the attached file (Test Setup Photo).

Report No.: RF150722C10-4 Page No. 31 / 32 Report Format Version: 6.1.1



Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF Lab/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-5935343 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: RF150722C10-4 Page No. 32 / 32 Report Format Version: 6.1.1