

FCC Test Report

Report No.: RF150722C10-3

FCC ID: 2AFD7-P3301

Test Model: P3301

Received Date: Jul. 22, 2015

Test Date: Aug. 01, 2015 ~ Aug. 07, 2015

Issued Date: Aug. 25, 2015

Applicant: Poynt Co.

Address: 490 S California Avenue Suite 200 Palo Alto, CA 94306 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C)

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan

Hsien 333, Taiwan, R.O.C.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Report No.: RF150722C10-3 Page No. 1 / 42 Report Format Version: 6.1.1



Table of Contents

Release Control Record4						
1	Cert	tificate of Conformity	5			
2	Sun	nmary of Test Results	6			
	2.1	•				
		Modification Record				
_						
3	Gen	eral Information	7			
	3.1	General Description of EUT	7			
		Description of Test Modes	8			
		3.2.1 Test Mode Applicability and Tested Channel Detail				
	3.3	Description of Support Units				
		3.3.1 Configuration of System under Test				
	3.4 General Description of Applied Standards					
4		t Types and Results				
	4.1	Radiated Emission and Bandedge Measurement	13			
		4.1.1 Limits of Radiated Emission and Bandedge Measurement				
		4.1.2 Test Instruments				
		4.1.3 Test Procedures				
		4.1.4 Deviation from Test Standard				
		4.1.5 Test Set Up				
		4.1.6 EUT Operating Conditions				
	12	Conducted Emission Measurement				
	7.2	4.2.1 Limits of Conducted Emission Measurement				
		4.2.2 Test Instruments				
		4.2.3 Test Procedures				
		4.2.4 Deviation From Test Standard	22			
		4.2.5 Test Setup				
		4.2.6 EUT Operating Condition				
		4.2.7 Test Results				
	4.3	Number of Hopping Frequency Used				
		4.3.1 Limits of Hopping Frequency Used Measurement				
		4.3.2 Test Setup				
		4.3.4 Test Procedure				
		4.3.5 Deviation fromTest Standard	25			
		4.3.6 Test Results				
	4.4	Dwell Time on Each Channel	27			
		4.4.1 Limits of Dwell Time on Each Channel Measurement	27			
		4.4.2 Test Setup				
		4.4.3 Test Instruments				
		4.4.4 Test Procedures				
		4.4.5 Deviation from Test Standard				
	4.5	4.4.6 Test Results				
	4.5	4.5.1 Limits of Channel Bandwidth Measurement				
		4.5.2 Test Setup				
		4.5.3 Test Instruments				
		4.5.4 Test Procedure				
		4.5.5 Deviation from Test Standard				
		4.5.6 EUT Operating Condition	31			
		4.5.7 Test Results				
	4.6	Hopping Channel Separation				
		4.6.1 Limits of Hopping Channel Separation Measurement	33			



4.6.2 Test Setup	33
4.6.3 Test Instruments	
4.6.4 Test Procedure	33
4.6.5 Deviation From Test Standard	
4.6.6 Test Results	34
4.7 Maximum Output Power	35
4.7.1 Limits of Maximum Output Power Measurement	35
4.7.2 Test Setup	35
4.7.3 Test Instruments	
4.7.4 Test Procedure	
4.7.5 Deviation fromTest Standard	
4.7.6 EUT Operating Condition	
4.7.7 Test Results	
4.8 Conducted Out of Band Emission Measurement	
4.8.1 Limits Of Conducted Out Of Band Emission Measurement	
4.8.2 Test Instruments	
4.8.3 Test Procedure	
4.8.4 Deviation from Test Standard	
4.8.5 EUT Operating Condition	
4.8.6 Test Results	37
5 Pictures of Test Arrangements	41
Appendix – Information on the Testing Laboratories	42



Release Control Record

Issue No.	Description	Date Issued
RF150722C10-3	Original Release	Aug. 25, 2015

Report No.: RF150722C10-3 Page No. 4 / 42 Report Format Version: 6.1.1



1 Certificate of Conformity

Product: POS

Brand: POYNT

Test Model: P3301

Sample Status: Production Unit

Applicant: Poynt Co.

Test Date: Aug. 01, 2015 ~ Aug. 07, 2015

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Ivonne Wu / Supervisor

Kay Wu / Supervisor



2 Summary of Test Results

	47 CFR FCC Part 15, Subpart C (SECTION 15.247)							
FCC Clause	Test Item	Result	Remarks					
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.03dB at 0.15811MHz.					
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.					
15.247(a)(1) (iii)	I Dwell time on Fach Channel I		Meet the requirement of limit.					
15.247(a)(1)	Hopping Channel Separation Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.					
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.					
15.205 & 209	Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -13.02dB at 479.90MHz.					
15.247(d) Band Edge Measurement		PASS	Meet the requirement of limit.					
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.					
15.203 Antenna Requirement		PASS	No antenna connector is used.					

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT:

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	2.93 dB
Radiated Effissions up to 1 GHz	200MHz ~1000MHz	2.95 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.26 dB
Radiated Effissions above 1 GHz	18GHz ~ 40GHz	1.94 dB

2.2 Modification Record

There were no modifications required for compliance.

Report No.: RF150722C10-3 Page No. 6 / 42 Report Format Version: 6.1.1



3 General Information

3.1 General Description of EUT

Product	POS
Brand	POYNT
Test Model	P3301
Status of EUT	Production Unit
Dower Cumply Dating	12Vdc (adapter)
Power Supply Rating	3.7Vdc (Li-ion battery)
Modulation Type	GFSK, π/4-DQPSK, 8DPSK
Transfer Rate	1/2/3 Mbps
Operating Frequency	2402 ~ 2480 MHz
Number of Channel	79
Output Power	2.291 mW
Antenna Type	PIFA antenna with 3.2 dBi gain
Antenna Connector	N/A
Accessory Device	Refer to Note as below
Data Cable Supplied	Refer to Note as below

Note:

1. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	FSP GROUP INC.	FSP040-RHBN2	I/P: 100-240Vac, 50/60Hz, 1.5A O/P: 12Vdc, 3.33A 1.2m shielded cable with one core
Battery	Formosa Electronic Industries IN	P61	3.7Vdc, 14.8Wh
LCD Panel 1	LG	LD070WX7-SMN4	7"
LCD Panel 2	LG	LH430WV1-SD07	4.3"
Photo Camera	LITE-ON CORP.	5BA502T2A	
Video Camera	NingBo Sunny Opotech	Q034C-200	
Main Board	Quanta	DA0P61MBAB0	
eMMC	kingston	EMMC16G-V100-C50	16GB
CPU	nV	T40s	
WLAN Module	Azurewave	AW-AH640	
Docking	Quanta	DA0P61TB6B0	

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.



3.2 Description of Test Modes

79 channels are provided to this EUT:

Channel	Freq. (MHz)						
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		_

Report No.: RF150722C10-3 Page No. 8 / 42 Report Format Version: 6.1.1



3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure		Applica	able To		Description
Mode	RE≥1G	RE<1G	PLC	APCM	Description
-	V	V	V	V	-

Where

RE≥1G: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE:

- 1. For Radiated emission test, pre-tested GFSK, π /4-DQPSK, 8DPSK modulation type and found GFSK was the worse, therefore chosen for the final test and presented in the test report.
- 2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.
- 3. "-" means no effect.

Radiated Emission Test (Above 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5

Radiated Emission Test (Below 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	0	FHSS	GFSK	DH5

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	0	FHSS	GFSK	DH5

Report No.: RF150722C10-3 Page No. 9 / 42 Report Format Version: 6.1.1



Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	π/4-DQPSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	DH5

Test Condition:

TOOL COMMITTEE			
Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
RE<1G	25deg. C, 65%RH	120Vac, 60Hz	Anson Lin
PLC	25deg. C, 68%RH	120Vac, 60Hz	Toby Tian
APCM	21deg. C, 60%RH	3.7Vdc	Howard Kao

Report No.: RF150722C10-3 Page No. 10 / 42 Report Format Version: 6.1.1



3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
A.	Bluetooth Tester	R&S	CBT	100980	N/A

Note:

- 1. All power cords of the above support units are non-shielded (1.8m).
- 2. Item A acted as communication partners to transfer data.


No.	Signal Cable Description Of The Above Support Units
1.	N/A

Note:

- 1. All power cords of the above support units are non-shielded (1.8m).
- 2. Item 1 acted as communication partners to transfer data.

3.3.1 Configuration of System under Test

*Kept in remote area



Report No.: RF150722C10-3 Page No. 11 / 42 Report Format Version: 6.1.1



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247) FCC Public Notice DA 00-705 ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

Report No.: RF150722C10-3 Page No. 12 / 42 Report Format Version: 6.1.1



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Report No.: RF150722C10-3 Page No. 13 / 42 Report Format Version: 6.1.1



4.1.2 Test Instruments

Description & Manaufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent	N9038A	MY51210203	Jan. 21, 2015	Jan. 21, 2016
Spectrum Analyzer Agilent	N9010A	MY52220314	Sep. 03, 2014	Sep. 02, 2015
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Dec. 10, 2014	Dec. 09, 2015
BILOG Antenna SCHWARZBECK	VULB9168	9168-472	Feb. 04, 2015	Feb. 04, 2016
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-969	Feb. 09, 2015	Feb. 09, 2016
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Feb. 04, 2015	Feb. 04, 2016
Loop Antenna	EM-6879	269	Jul. 31, 2015	Jul. 30, 2016
Preamplifier EMCI	EMC 012645	980115	Dec. 12, 2014	Dec. 11, 2015
Preamplifier EMCI	EMC 184045	980116	Jan. 09, 2015	Jan. 08, 2016
Preamplifier EMCI	EMC 330H	980112	Dec. 27, 2014	Dec. 26, 2015
Power Meter Anritsu	ML2495A	1232002	Sep. 17, 2014	Sep. 16, 2015
Power Sensor Anritsu	MA2411B	1207325	Sep. 17, 2014	Sep. 16, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	309219/4 2950114	Oct. 18, 2014	Oct. 17, 2015
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	250130/4	Oct. 18, 2014	Oct. 17, 2015
RF Coaxial Cable Worken	8D-FB	Cable-Ch10-01	Nov. 07, 2014	Nov. 06, 2015
Software BV ADT	E3 6.120103	NA	NA	NA
Antenna Tower MF	MFA-440H	NA	NA	NA
Turn Table MF	MFT-201SS	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Chamber 10.
- 3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 4. The FCC Site Registration No. is 690701.
- 5. The IC Site Registration No. is IC7450F-10.

Report No.: RF150722C10-3 Page No. 14 / 42 Report Format Version: 6.1.1



4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
- 4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
- 5. All modes of operation were investigated and the worst-case emissions are reported.

				<u> </u>
4.1.4	Deviation	trom	Test	Standard


No deviation.

Report No.: RF150722C10-3 Page No. 15 / 42 Report Format Version: 6.1.1




4.1.5 Test Set Up

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

Set the EUT under transmission condition continuously at specific channel frequency.

Report No.: RF150722C10-3 Page No. 16 / 42 Report Format Version: 6.1.1



4.1.7 Test Results

ABOVE 1GHz DATA:

GFSK

EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL	Channel 0	FREQUENCY RANGE	1GHz ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2328	33.13	39.84	54	-20.87	26.72	4.04	37.47	107	79	Average
2328	56.29	63	74	-17.71	26.72	4.04	37.47	107	79	Peak
2402	87.05	93.57			26.91	4.09	37.52	107	79	Average
2402	98.02	104.54			26.91	4.09	37.52	107	79	Peak
2486	33.76	39.78	54	-20.24	27.15	4.15	37.32	107	79	Average
2486	56.33	62.35	74	-17.67	27.15	4.15	37.32	107	79	Peak
		ANTEN	INA POLA	RITY & T	EST DISTA	ANCE: V	ERTICAL	AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2350	33.21	39.88	54	-20.79	26.77	4.05	37.49	105	338	Average
2350	56.99	63.66	74	-17.01	26.77	4.05	37.49	105	338	Peak
2402	84	90.52			26.91	4.09	37.52	105	338	Average
2402	94.45	100.97		-	26.91	4.09	37.52	105	338	Peak
2488	33.88	39.84	54	-20.12	27.2	4.16	37.32	105	338	Average
2488	57.09	63.05	74	-16.91	27.2	4.16	37.32	105	338	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor
 Margin value = Emission level Limit value
- 2. 2402MHz: Fundamental frequency.

Report No.: RF150722C10-3 Page No. 17 / 42 Report Format Version: 6.1.1



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL Channel 39		FREQUENCY RANGE	1GHz ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2380	33.32	39.88	54	-20.68	26.86	4.08	37.5	105	90	Average
2380	56.87	63.43	74	-17.13	26.86	4.08	37.5	105	90	Peak
2441	88.04	94.25			27.06	4.12	37.39	105	90	Average
2441	98.9	105.11			27.06	4.12	37.39	105	90	Peak
2492	33.85	39.74	54	-20.15	27.2	4.16	37.25	105	90	Average
2492	57	62.89	74	-17	27.2	4.16	37.25	105	90	Peak
		ANTEN	INA POLA	RITY & T	EST DIST	ANCE: V	ERTICAL	AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2330	33.07	39.78	54	-20.93	26.72	4.04	37.47	101	29	Average
2330	56.66	63.37	74	-17.34	26.72	4.04	37.47	101	29	Peak
2441	84.83	91.04			27.06	4.12	37.39	101	29	Average
2441	95.05	101.26	_		27.06	4.12	37.39	101	29	Peak
2484	33.79	39.81	54	-20.21	27.15	4.15	37.32	101	29	Average
2484	56.77	62.79	74	-17.23	27.15	4.15	37.32	101	29	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2441MHz: Fundamental frequency.

Report No.: RF150722C10-3 Page No. 18 / 42 Report Format Version: 6.1.1



EUT TEST CONDITION		MEASUREMENT DETAIL		
CHANNEL Channel 78		FREQUENCY RANGE	1GHz ~ 25GHz	
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Average (AV)	
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin	

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2360	33.14	39.77	54	-20.86	26.81	4.05	37.49	104	83	Average
2360	56.92	63.55	74	-17.08	26.81	4.05	37.49	104	83	Peak
2480	88.21	94.23			27.15	4.15	37.32	104	83	Average
2480	98.94	104.96			27.15	4.15	37.32	104	83	Peak
2496	34.14	40.03	54	-19.86	27.2	4.16	37.25	104	83	Average
2496	56.51	62.4	74	-17.49	27.2	4.16	37.25	104	83	Peak
		ANTEN	NA POLA	RITY & T	EST DISTA	ANCE: V	ERTICAL	AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
2368	33.39	40.01	54	-20.61	26.81	4.07	37.5	102	360	Average
2368	55.54	62.16	74	-18.46	26.81	4.07	37.5	102	360	Peak
2480	84.75	90.77	_		27.15	4.15	37.32	102	360	Average
2480	94.95	100.97			27.15	4.15	37.32	102	360	Peak
2500	34	39.89	54	-20	27.2	4.16	37.25	102	360	Average
2500	56.84	62.73	74	-17.16	27.2	4.16	37.25	102	360	Peak

REMARKS:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2480MHz: Fundamental frequency.

Report No.: RF150722C10-3 Page No. 19 / 42 Report Format Version: 6.1.1



BELOW 1GHz WORST-CASE DATA:

EUT TEST CONDITION		MEASUREMENT DETAIL			
CHANNEL	Channel 0	FREQUENCY RANGE	30MHz ~ 1GHz		
INPUT POWER	120Vac, 60 Hz	DETECTOR FUNCTION	Peak (PK) Quasi-peak (QP)		
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH	TESTED BY	Anson Lin		

	F	ANTENN	A POLAR	ITY & TE	ST DISTAN	ICE: HO	RIZONTA	L AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
200.64	25.58	46.64	43.5	-17.92	9.4	1.29	31.75	110	194	Peak
219	30.52	50.67	46	-15.48	10.18	1.37	31.7	115	176	Peak
250.05	32.54	51.51	46	-13.46	11.48	1.49	31.94	136	55	Peak
360.2	26.14	41.93	46	-19.86	14.38	1.8	31.97	119	327	Peak
479.9	27.57	40.44	46	-18.43	16.93	2.05	31.85	104	151	Peak
637.4	27.67	37.38	46	-18.33	20.06	2.33	32.1	135	349	Peak
		ANTEN	INA POLA	RITY & T	EST DIST	ANCE: V	ERTICAL	AT 3 M		
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB/m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
59.43	24.91	43.42	40	-15.09	12.04	0.8	31.35	128	309	Peak
211.98	25.19	45.56	43.5	-18.31	9.89	1.35	31.61	104	38	Peak
250.05	28.24	47.21	46	-17.76	11.48	1.49	31.94	101	249	Peak
479.9	32.98	45.85	46	-13.02	16.93	2.05	31.85	105	59	Peak
498.8	28.37	40.64	46	-17.63	17.29	2.09	31.65	108	98	Peak
637.4	31.05	40.76	46	-14.95	20.06	2.33	32.1	103	52	Peak

REMARKS: Emission Level = Read Level + Antenna Factor + Cable Loss - Preamp Factor Margin value = Emission level – Limit value

Report No.: RF150722C10-3 Page No. 20 / 42 Report Format Version: 6.1.1



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)				
	Quasi-peak	Average			
0.15 - 0.5	66 - 56	56 - 46			
0.50 - 5.0	56	46			
5.0 - 30.0	60	50			

Note: 1. The lower limit shall apply at the transition frequencies.

- 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
- 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration	Due Date Of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 11, 2014	Nov. 10, 2015
RF signal cable Woken	5D-FB	Cable-HYC01-01	Dec. 26, 2014	Dec. 25, 2015
LISN ROHDE & SCHWARZ (EUT)	ESH3-Z5	835239/001	Feb. 26, 2015	Feb. 25, 2016
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Jul. 24, 2015	Jul. 23, 2016
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-2040.

Report No.: RF150722C10-3 Page No. 21 / 42 Report Format Version: 6.1.1



4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 Deviation From Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Same as 4.1.6.

Report No.: RF150722C10-3 Page No. 22 / 42 Report Format Version: 6.1.1



4.2.7 Test Results


CONDUCTED WORST-CASE DATA: GFSK

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Toby Tian	Test Date	2015/8/1

	Phase Of Power : Line (L)									
	Frequency Correction Reading Value		Emission Level		Limit		Margin			
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15811	0.05	51.48	36.78	51.53	36.83	65.56	55.56	-14.03	-18.73
2	0.19400	0.06	44.71	26.35	44.77	26.41	63.86	53.86	-19.09	-27.45
3	0.24200	0.06	37.35	21.26	37.41	21.32	62.03	52.03	-24.62	-30.71
4	0.26850	0.06	33.72	18.43	33.78	18.49	61.16	51.16	-27.38	-32.67
5	0.53828	0.06	34.55	25.63	34.61	25.69	56.00	46.00	-21.39	-20.31
6	3.11000	0.16	31.26	19.73	31.42	19.89	56.00	46.00	-24.58	-26.11

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value



Report No.: RF150722C10-3 Page No. 23 / 42 Report Format Version: 6.1.1




Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Toby Tian	Test Date	2015/8/1

	Phase Of Power : Neutral (N)										
No	Frequency	Correction Factor	Readin	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	
1	0.15800	0.05	51.15	36.53	51.20	36.58	65.57	55.57	-14.37	-18.99	
2	0.17384	0.05	47.44	26.84	47.49	26.89	64.77	54.77	-17.28	-27.88	
3	0.20631	0.05	42.49	26.72	42.54	26.77	63.35	53.35	-20.81	-26.58	
4	0.23000	0.05	39.03	24.04	39.08	24.09	62.45	52.45	-23.37	-28.36	
5	0.53404	0.06	34.30	24.00	34.36	24.06	56.00	46.00	-21.64	-21.94	
6	2.59800	0.13	30.02	19.75	30.15	19.88	56.00	46.00	-25.85	-26.12	

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value



Report No.: RF150722C10-3 Page No. 24 / 42 Report Format Version: 6.1.1




4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation fromTest Standard


No deviation.

4.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

Report No.: RF150722C10-3 Page No. 25 / 42 Report Format Version: 6.1.1








4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.

Report No.: RF150722C10-3 Page No. 27 / 42 Report Format Version: 6.1.1



4.4.6 Test Results

GFSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
DH1	10.20	457.00	0.15	0.4
DH3	5.40	1690.00	0.29	0.4
DH5	3.60	2996.00	0.34	0.4

NOTE:

- 1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
- 2. 79 channels come from the Hopping Channel number
- 3. Average Hopping Channel = hops/sweep time
- 4. t: Package Transfer Time(us)
- 5. Test plots of the transmitting time slot are shown as below.





Π/4-DQPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
2DH1	10.00	471.00	0.15	0.4
2DH3	5.40	1722.00	0.29	0.4
2DH5	3.40	2972.00	0.32	0.4

NOTE:

- 1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
- 2. 79 channels come from the Hopping Channel number
- 3. Average Hopping Channel = hops/sweep time
- 4. t: Package Transfer Time(us)
- 5. Test plots of the transmitting time slot are shown as below.






8DPSK

Mode	Average Hopping Channel	Package Transfer Time (usec)	Result (sec)	Limit (sec)
3DH1	10.00	447.00	0.14	0.4
3DH3	5.40	1698.00	0.29	0.4
3DH5	3.20	2972.00	0.30	0.4

NOTE:

- 1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
- 2. 79 channels come from the Hopping Channel number
- 3. Average Hopping Channel = hops/sweep time
- 4. t: Package Transfer Time(us)
- 5. Test plots of the transmitting time slot are shown as below.






4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

Report No.: RF150722C10-3 Page No. 31 / 42 Report Format Version: 6.1.1



4.5.7 Test Results

Oh a sa a a l	Frequency (MHz)	20dB Bandwidth (MHz)				
Channel		GFSK	π/4-DQPSK	8DPSK		
0	2402	1.20	1.35	1.31		
39	2441	1.40	1.35	1.31		
78	2480	1.20	1.35	1.30		






4.6 Hopping Channel Separation

4.6.1 Limits of Hopping Channel Separation Measurement

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 Test Setup



4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.6.4 Test Procedure

Measurement Procedure REF

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.6.5 Deviation From Test Standard

No deviation.

Report No.: RF150722C10-3 Page No. 33 / 42 Report Format Version: 6.1.1




4.6.6 Test Results

Channel	Freq. (MHz)	Adjacent Channel Separation (MHz)			20dB Bandwidth (MHz)			Minimum Limit (MHz)			Pass / Fail
	GFSK π/4-DQPSK 8DPSK		8DPSK	GFSK	π/4-DQPSK	8DPSK	GFSK	π/4-DQPSK	8DPSK	/ I all	
0	2402	1.10	1.10	1.00	1.20	1.35	1.31	0.800	0.900	0.873	Pass
39	2441	1.10	1.10	1.00	1.40	1.35	1.31	0.933	0.900	0.873	Pass
78	2480	1.00	1.10	1.10	1.20	1.35	1.30	0.800	0.900	0.867	Pass

NOTE:

1. The minimum limit is two-third 20dB bandwidth.






4.7 Maximum Output Power

4.7.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

4.7.5 Deviation fromTest Standard

No deviation.

4.7.6 EUT Operating Condition


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

Report No.: RF150722C10-3 Page No. 35 / 42 Report Format Version: 6.1.1



4.7.7 Test Results

Channel	Frequency	Output Power (mW)			(Output Powe (dBm)	Power Limit	Pass /	
	(MHz)	GFSK	π/4-DQPSK	8DPSK	GFSK	π/4-DQPSK	8DPSK	(mW)	Fail
0	2402	1.786	1.380	1.445	2.52	1.40	1.60	125	PASS
39	2441	2.291	1.377	1.538	3.60	1.39	1.87	125	PASS
78	2480	2.061	1.300	1.476	3.14	1.14	1.69	125	PASS





4.8 Conducted Out of Band Emission Measurement

4.8.1 Limits Of Conducted Out Of Band Emission Measurement

Below –20dB of the highest emission level of operating band (in 100kHz RBW).

4.8.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 Deviation from Test Standard

No deviation.

4.8.5 EUT Operating Condition


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 Test Results

The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

Report No.: RF150722C10-3 Page No. 37 / 42 Report Format Version: 6.1.1
















5 Pictures of Test Arrangements
Please refer to the attached file (Test Setup Photo).

Report No.: RF150722C10-3 Page No. 41 / 42 Report Format Version: 6.1.1



Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF Lab/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-5935343 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: RF150722C10-3 Page No. 42 / 42 Report Format Version: 6.1.1