

SUNVALLEYTEK INTERNATIONAL, INC.

46724 Lakeview Blvd, Fremont, California, United States, 94538-6529.

2018.05.02

To: Federal Communications Commission  
7435 Oakland Mills Road  
Columbia, MD


FCC ID: 2AFDGVA-DK001

To Whom It May Concern:

This letter is to ascertain that SUNVALLEYTEK INTERNATIONAL, INC. Product VAVA Docking Station, Model: VA-DK001, has been the units used for conducting FCC compliance testing, and it meets KDB 680106 D01 RF Exposure Wireless Charging App v03 Clause 5(b) 6 conditions.

|   |  |
|---|--|
| 1 | Power transfer frequency is less than 1 MHz  |
|   | YES; the device operated in the frequency range from 126.5 kHz.  |
| 2 | Output power from each primary coil is less than or equal to 15 watts.   |
|   | YES; the maximum output power of the primary coil is 9W.   |
| 3 | The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils. |
|   | YES; the transfer system includes only single primary and secondary coils.   |
| 4 | Client device is placed directly in contact with the transmitter.  |
|   | YES; Client device is placed directly in contact with the transmitter.   |
| 5 | Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).  |
|   | YES  |
| 6 | The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.  |
|   | YES; The EUT field strength levels are 50% x MPE limits.   |

If you have any question or concerns, pls. contact us.



Client's signature :

Client's name / title : Lion.Liao/ Approbation Manager

Telephone: +01 4089809679

Fax: +01 4089809699

Contact information / address: 46724 Lakeview Blvd, Fremont, California, United States, 94538-6529.