



Shenzhen Huatongwei International Inspection Co., Ltd.

Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Phone:86-755-26748019 Fax:86-755-26748089 <http://www.szhtw.com.cn>



TEST REPORT

Report Reference No. : **TRE1507005701** **R/C** : **83723**
FCC ID : **2AFEE-E-B10**
Applicant's name : **Nanjing Xijian Information Technology Co., Ltd.**
Address : Floor 3, Jinjvlong building,9 Gaohu Road, Jiangning District,Nanjing,China
Manufacturer : Nanjing Xijian Information Technology Co., Ltd.
Address : Floor 3, Jinjvlong building,9 Gaohu Road, Jiangning District,Nanjing,China
Test item description : **ECG Recorder**
Trade Mark : SnapECG
Model/Type reference : E-B10
Listed Model(s) : --
Standard : **FCC CFR Title 47 Part 15 Subpart C Section 15.247**
Date of receipt of test sample : July 8, 2015
Date of testing : July 9, 2015 ~ July 28, 2015
Date of issue : July 28, 2015
Result : **PASS**

Compiled by
(position+printed name+signature) : File administrators Shayne Zhu

Supervised by
(position+printed name+signature) : Project Engineer Hans Hu

Approved by
(position+printed name+signature) : RF Manager Hans Hu

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd**

Address : Bldg3, Hongfa Hi-tech Industrial Park, Genyu Road, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS AND TEST DESCRIPTION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Test Description	3
<u>2.</u>	<u>SUMMARY</u>	<u>4</u>
2.1.	Client Information	4
2.2.	Product Description	4
2.3.	Operation state	4
2.4.	EUT configuration	5
2.5.	Modifications	5
<u>3.</u>	<u>TEST ENVIRONMENT</u>	<u>6</u>
3.1.	Address of the test laboratory	6
3.2.	Test Facility	6
3.3.	Environmental conditions	7
3.4.	Statement of the measurement uncertainty	7
3.5.	Equipments Used during the Test	8
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>9</u>
4.1.	Antenna requirement	9
4.2.	Conducted Emission (AC Main)	10
4.3.	Conducted Peak Output Power	15
4.4.	20dB Emission Bandwidth	18
4.5.	Carrier Frequencies Separation	21
4.6.	Hopping Channel Number	25
4.7.	Dwell Time	27
4.8.	Pseudorandom Frequency Hopping Sequence	30
4.9.	Restricted band (radiated)	31
4.10.	Bandedge and Spurious Emission (conducted)	36
4.11.	Spurious Emission (radiated)	46
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	<u>52</u>
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	<u>53</u>

1. **TEST STANDARDS AND TEST DESCRIPTION**

1.1. **Test Standards**

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

[ANSI C63.10-2013](#): American National Standard for Testing Unlicensed Wireless Devices

1.2. **Test Description**

Report Section	Test Item	Section in CFR 47	Result
4.1	Antenna Requirement	15.203/15.247 (c)	Pass
4.2	AC Power Line Conducted Emission	15.207	Pass
4.3	Conducted Peak Output Power	15.247 (b)(1)	Pass
4.4	20dB Occupied Bandwidth	15.247 (a)(1)	Pass
4.5	Carrier Frequencies Separation	15.247 (a)(1)	Pass
4.6	Hopping Channel Number	15.247 (a)(1)	Pass
4.7	Dwell Time	15.247 (a)(1)	Pass
4.8	Pseudorandom Frequency Hopping Sequence	15.247(b)(4)&TCB Exclusion List (7 July 2002)	Pass
4.9	Restricted band	15.247(d)/15.205	Pass
4.10/4.11	Radiated Emission	15.247(d)/15.209	Pass

Remark: The measurement uncertainty is not included in the test result.

2. SUMMARY

2.1. Client Information

Applicant:	Nanjing Xijian Information Technology Co., Ltd.
Address:	Floor 3, Jinjvlong building,9 Gaohu Road, Jiangning District,Nanjing,China
Manufacturer:	Nanjing Xijian Information Technology Co., Ltd.
Address:	Floor 3, Jinjvlong building,9 Gaohu Road, Jiangning District,Nanjing,China

2.2. Product Description

Name of EUT	ECG Recorder
Trade Mark:	SnapECG
Model No.:	E-B10
Listed Model(s):	--
Power supply:	DC 3.7V From internal battery
Bluetooth	
Version:	Supported BT3.0+EDR
Modulation:	GFSK, π/4DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Internal Antenna
Antenna gain:	1.0 dBi

2.3. Operation state

◆ Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channel which were tested. the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the above gray bottom.

Channel	Frequency (MHz)
0	2402
1	2403
:	:
39	2441
:	:
77	2479
78	2480

◆ Test mode

For RF test items:

The engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions:

The EUT was charging mode by USB port of PC.

2.4. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- supplied by the lab

<input type="radio"/>	Power Cable	Length (m) :	/
		Shield :	/
		Detachable :	/
<input type="radio"/>	Multimeter	Manufacturer :	/
		Model No. :	/

2.5. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Laboratory: Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming)
Address: Bldg3, Hongfa Hi-tech Industrial Park, Genyu Road, Shenzhen, China
Phone: 86-755-26748019 Fax: 86-755-26748089

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: February 28, 2015. Valid time is until February 27, 2018.

A2LA-Lab Cert. No. 2243.01

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is until Sept 30, 2015.

FCC-Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date Jul. 01, 2012, valid time is until Jun. 01, 2015.

FCC-Registration No.: 317478

Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming EMC Laboratory) has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 317478, Renewal date July 18, 2014, valid time is until July. 18, 2017.

IC-Registration No.: 5377A

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377A on Dec. 31, 2013, valid time is until Dec. 31, 2016.

IC-Registration No.: 5377B

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd. (Gongming EMC Laboratory) has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377B on September 3, 2014, valid time is until September 3, 2017.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd. EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

VCCI

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.:R-2484. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 29, 2015.

Radiated disturbance above 1GHz measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-292. Date of Registration: Dec. 24, 2013. Valid time is until Dec. 23, 2016.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: Dec. 20, 2012. Valid time is until Dec. 19, 2015.

Telecommunication Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: T-1837. Date of Registration: May 07, 2013. Valid time is until May 06, 2016.

DNV

Shenzhen Huatongwei International Inspection Co., Ltd. has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025 (2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until Aug. 24, 2016.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15~35°C
Relative Humidity:	30~60 %
Air Pressure:	950~1050mba

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics;Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics;Part 2" and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)
Transmitter power Radiated	2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	1.60 dB	(1)
Radiated spurious emission 9KHz-40 GHz	2.20 dB	(1)
Conducted Emission 9KHz-30MHz	3.39 dB	(1)
Radiated Emission 30~1000MHz	4.24 dB	(1)
Radiated Emissio 1~18GHz	5.16 dB	(1)
Radiated Emissio 18-40GHz	5.54 dB	(1)
Occupied Bandwidth	-----	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=1.96$.

3.5. Equipments Used during the Test

Conducted Emission (AC Main)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Artificial Mains	Rohde&Schwarz	ESH2-Z5	100028	2014/11/01
2	EMI Test Receiver	Rohde&Schwarz	ESCI3	100038	2014/11/01
3	Pulse Limiter	Rohde&Schwarz	ESHSZ2	100044	2014/11/01
4	EMI Test Software	Rohde&Schwarz	ES-K1 V1.71	N/A	N/A

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Ultra-Broadband Antenna	ShwarzBeck	VULB9163	538	2014/11/01
2	EMI TEST RECEIVER	Rohde&Schwarz	ESI 26	100009	2014/11/01
3	EMI TEST Software	Audix	E3	N/A	N/A
4	TURNTABLE	ETS	2088	2149	N/A
5	ANTENNA MAST	ETS	2075	2346	N/A
6	EMI TEST Software	Rohde&Schwarz	ESK1	N/A	N/A
7	HORN ANTENNA	ShwarzBeck	9120D	1011	2014/11/01
8	Amplifier	Sonoma	310N	E009-13	2014/11/01
9	JS amplifier	Rohde&Schwarz	JS4-00101800-28-5A	F201504	2014/11/01
10	High pass filter	Compliance Direction systems	BSU-6	34202	2014/11/01
11	HORN ANTENNA	ShwarzBeck	9120D	1012	2014/11/01
12	Amplifier	Compliance Direction systems	PAP1-4060	120	2014/11/01
13	Loop Antenna	Rohde&Schwarz	HFH2-Z2	100020	2014/11/01
14	TURNTABLE	MATURO	TT2.0	----	N/A
15	ANTENNA MAST	MATURO	TAM-4.0-P	----	N/A
16	Horn Antenna	SCHWARZBECK	BBHA9170	25841	2014/11/01
17	ULTRA-BROADBAND ANTENNA	Rohde&Schwarz	HL562	100015	2014/11/01

Maximum Peak Output Power / Power Spectral Density / 6dB Bandwidth / Band Edge Compliance of RF Emission / Spurious RF Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal
1	Spectrum Analyzer	Rohde&Schwarz	FSP	1164.4391.40	2014/11/01

The Cal.Interval was one year

4. **TEST CONDITIONS AND RESULTS**

4.1. Antenna requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

Test Result:

The antenna is integral antenna, the best case gain of the antenna is 1.0dBi



4.2. Conducted Emission (AC Main)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE


1. The EUT was setup and tested according to ANSI C63.10: 2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedance stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.

TEST RESULTS

@120VAC 60Hz

Test mode:	BT	Polarization	L1
------------	----	--------------	----

SCAN TABLE: "Voltage (9K-30M) FIN"
 Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "GMR0813502_fin"

8/13/2015 3:35PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.505500	26.50	10.2	56	29.5	QP	L1	GND
2.026500	23.90	10.2	56	32.1	QP	L1	GND
2.089500	22.40	10.2	56	33.6	QP	L1	GND
2.364000	22.40	10.3	56	33.6	QP	L1	GND
2.476500	24.50	10.3	56	31.5	QP	L1	GND
2.535000	23.10	10.3	56	32.9	QP	L1	GND


MEASUREMENT RESULT: "GMR0813502_fin2"

8/13/2015 3:35PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.505500	26.20	10.2	46	19.8	AV	L1	GND
1.468500	17.70	10.2	46	28.3	AV	L1	GND
1.977000	18.60	10.2	46	27.4	AV	L1	GND
1.981500	13.70	10.2	46	32.3	AV	L1	GND
2.062500	18.90	10.2	46	27.1	AV	L1	GND
2.485500	21.20	10.3	46	24.8	AV	L1	GND

Test mode:	BT	Polarization	N
------------	----	--------------	---

SCAN TABLE: "Voltage (9K-30M) FIN"
Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "GMR0813501_fin"

8/13/2015 3:32PM


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.505500	26.50	10.2	56	29.5	QP	N	GND
1.963500	25.60	10.2	56	30.4	QP	N	GND
2.026500	25.10	10.2	56	30.9	QP	N	GND
2.044500	20.60	10.2	56	35.4	QP	N	GND
2.472000	26.90	10.3	56	29.1	QP	N	GND
2.548500	21.30	10.3	56	34.7	QP	N	GND

MEASUREMENT RESULT: "GMR0813501_fin2"

8/13/2015 3:32PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.505500	25.80	10.2	46	20.2	AV	N	GND
1.464000	16.00	10.2	46	30.0	AV	N	GND
1.972500	20.80	10.2	46	25.2	AV	N	GND
1.977000	21.30	10.2	46	24.7	AV	N	GND
2.067000	16.90	10.2	46	29.1	AV	N	GND
2.476500	21.00	10.3	46	25.0	AV	N	GND

@240VAC 60Hz

**MEASUREMENT RESULT: "GMR0813506_fin"**


8/13/2015 3:48PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.150000	33.40	10.2	66	32.6	QP	L1	GND
1.666500	22.90	10.2	56	33.1	QP	L1	GND
2.454000	23.80	10.3	56	32.2	QP	L1	GND
3.556500	13.20	10.3	56	42.8	QP	L1	GND
3.610500	10.90	10.3	56	45.1	QP	L1	GND
4.096500	23.70	10.3	56	32.3	QP	L1	GND

MEASUREMENT RESULT: "GMR0813506_fin2"

8/13/2015 3:48PM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.496500	23.60	10.2	46	22.5	AV	L1	GND
0.537000	21.60	10.2	46	24.4	AV	L1	GND
2.067000	18.00	10.2	46	28.0	AV	L1	GND
2.562000	18.30	10.3	46	27.7	AV	L1	GND
3.561000	7.10	10.3	46	38.9	AV	L1	GND
3.637500	0.90	10.3	46	45.1	AV	L1	GND

**MEASUREMENT RESULT: "GMR0813505_fin"**

8/13/2015 3:44PM

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.154500	32.00	10.2	66	33.0	QP	N	GND
1.846500	22.70	10.2	56	33.3	QP	N	GND
2.409000	25.20	10.3	56	30.8	QP	N	GND
2.571000	20.90	10.3	56	35.1	QP	N	GND
2.616000	24.30	10.3	56	31.7	QP	N	GND
3.115500	19.50	10.3	56	36.5	QP	N	GND

MEASUREMENT RESULT: "GMR0813505_fin2"

8/13/2015 3:44PM


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Detector	Line	PE
0.496500	24.50	10.2	46	21.6	AV	N	GND
0.501000	18.20	10.2	46	27.8	AV	N	GND
2.031000	16.30	10.2	46	29.7	AV	N	GND
2.427000	19.60	10.3	46	26.4	AV	N	GND
2.566500	22.40	10.3	46	23.6	AV	N	GND
3.102000	17.00	10.3	46	20.2	AV	N	GND

4.3. Conducted Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): **30dBm**

TEST CONFIGURATION




TEST PROCEDURE


Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

TEST RESULTS

Modulation type	Channel	Output power (dBm)	Limit (dBm)	Result
GFSK	00	-4.350	30.00	Pass
	39	-4.734		
	78	-4.100		
$\pi/4$ DQPSK	00	-4.255	21.00	Pass
	39	-4.634		
	78	-3.994		
8DPSK	00	-5.169	21.00	Pass
	39	-4.476		
	78	-3.955		

Test plot as follows:






4.4. 20dB Emission Bandwidth

LIMIT

N/A

TEST CONFIGURATION




TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with $RBW \geq 1\%$ of the 20 dB bandwidth and $VBW \geq RBW$.
3. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

TEST RESULTS

Modulation type	Channel	20dB Bandwidth (MHz)	Limit (MHz)	Result
GFSK	00	0.561	/	Pass
	39	0.564		
	78	0.578		
$\pi/4$ DQPSK	00	1.220	/	Pass
	39	1.216		
	78	1.214		
8DPSK	00	1.232	/	Pass
	39	1.247		
	78	1.253		

Test plot as follows:






4.5. Carrier Frequencies Separation

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the 2/3*20dB bandwidth of the hopping channel, whichever is greater.

TEST CONFIGURATION




TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=30 KHz and VBW=100KHz.


TEST RESULTS

Modulation type	Channel	Carrier Frequencies Separation (MHz)	Limit (MHz)	Result
GFSK	00	1.000	0.561	Pass
	39	1.000	0.564	
	78	1.000	0.578	
$\pi/4$ DQPSK	00	1.005	0.813	Pass
	39	1.005	0.811	
	78	1.005	0.809	
8DPSK	00	1.005	0.821	Pass
	39	1.000	0.831	
	78	1.005	0.835	

Test plot as follows:








4.6. Hopping Channel Number

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least **15** channels.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. The bandwidth of the fundamental frequency was measured by spectrum analyzer with RBW=1MHz and VBW=3MHz.

TEST RESULTS

Modulation type	Channel number	Limit (MHz)	Result
GFSK	79	15	Pass
$\pi/4$ DQPSK	79		
8DPSK	79		

Test plot as follows:




4.7. Dwell Time

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Set center frequency of spectrum analyzer=operating frequency with RBW=1MHz and VBW=1MHz,Span=0Hz.


TEST RESULTS


Modulation type	Channel	Dwell time (Second)	Limit (Second)	Result
GFSK	DH1	0.125	0.40	Pass
	DH3	0.260		
	DH5	0.312		
$\pi/4$ DQPSK	2-DH1	0.131	0.40	Pass
	2-DH3	0.266		
	2-DH5	0.312		
8DPSK	3-DH1	0.128	0.40	Pass
	3-DH3	0.266		
	3-DH5	0.308		

Note:

1. We have tested all mode at high,middle and low channel, and recorded worst case at middle channel.
2. Dwell time=Pulse time (ms) \times $(1600 \div 2 \div 79) \times 31.6$ Second for DH1, 2-DH1, 3-DH1
Dwell time=Pulse time (ms) \times $(1600 \div 4 \div 79) \times 31.6$ Second for DH3, 2-DH3, 3-DH3
Dwell time=Pulse time (ms) \times $(1600 \div 6 \div 79) \times 31.6$ Second for DH5, 2-DH5, 3-DH5

Test plot as follows:





4.8. Pseudorandom Frequency Hopping Sequence

LIMIT


FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

TEST RESULTS


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.


4.9. Restricted band (radiated)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dB _u V/m @3m)	Value
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION




TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10:2013 for compliance to FCC 47CFR 15.247 requirements.
2. The EUT is placed on a turn table which is 0.8 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.
5. The receiver set as follow:
RBW=1MHz, VBW=3MHz for Peak value
RBW=1MHz, VBW=10Hz for Average value.
6. The frequency range from 2310MHz to 2483.5MHz harmonic is checked.


TEST RESULTS

Worst mode:	GFSK Modulation	Test Channel:	00
Detector:	Peak	Polarization:	Horizontal




Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2386.75	46.69	27.53	6.80	37.57	43.45	74.00	-30.55	Peak
2	2390.02	44.04	27.53	6.81	37.57	40.81	74.00	-33.19	Peak
3	2402.09	98.76	27.57	6.83	37.58	95.58	74.00	21.58	Peak

Worst mode:	GFSK Modulation	Test Channel:	00
Detector:	Peak	Polarization:	Vertical




Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2385.40	46.88	27.53	6.80	37.57	43.64	74.00	-30.36	Peak
2	2390.02	42.75	27.53	6.81	37.57	39.52	74.00	-34.48	Peak
3	2402.09	98.93	27.57	6.83	37.58	95.75	74.00	21.75	Peak

Worst mode:	GFSK Modulation	Test Channel:	00
Detector:	Average	Polarization:	Horizontal




Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2385.98	32.09	27.53	6.80	37.57	28.85	54.00	-25.15	Average
2	2390.02	28.91	27.53	6.81	37.57	25.68	54.00	-28.32	Average
3	2402.09	96.52	27.57	6.83	37.58	93.34	54.00	39.34	Average

Worst mode:	GFSK Modulation	Test Channel:	00
Detector:	Average	Polarization:	Vertical




Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2386.08	30.79	27.53	6.80	37.57	27.55	54.00	-26.45	Average
2	2390.02	29.16	27.53	6.81	37.57	25.93	54.00	-28.07	Average
3	2402.09	91.99	27.57	6.83	37.58	88.81	54.00	34.81	Average

Worst mode:	GFSK Modulation	Test Channel:	78
Detector:	Peak	Polarization:	Horizontal




Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2483.50	57.63	27.85	6.96	37.65	54.79	74.00	-19.21	Peak
2	2492.57	50.64	27.88	6.97	37.65	47.84	74.00	-26.16	Peak

Worst mode:	GFSK Modulation	Test Channel:	78
Detector:	Peak	Polarization:	Vertical




Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2479.98	94.16	27.83	6.94	37.64	91.29	74.00	17.29	Peak
2	2483.50	53.50	27.85	6.96	37.65	50.66	74.00	-23.34	Peak
3	2496.03	49.96	27.88	6.97	37.65	47.16	74.00	-26.84	Peak

Worst mode:	GFSK Modulation	Test Channel:	78
Detector:	Average	Polarization:	Horizontal



Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2480.06	92.96	27.83	6.94	37.64	90.09	54.00	36.09	Average
2	2483.50	51.95	27.85	6.96	37.65	49.11	54.00	-4.89	Average
3	2496.18	30.63	27.88	6.97	37.65	27.83	54.00	-26.17	Average

Worst mode:	GFSK Modulation	Test Channel:	78
Detector:	Average	Polarization:	Vertical



Mark	Frequency	Reading	Antenna	Cable	Preamp	Level	Limit	Over	Remark
	MHz	dBuV/m	dB	dB	dB	dBuV/m	dBuV/m	limit	
1	2480.01	93.29	27.83	6.94	37.64	90.42	54.00	36.42	Average
2	2483.50	51.78	27.85	6.96	37.65	48.94	54.00	-5.06	Average
3	2496.01	27.36	27.88	6.97	37.65	24.56	54.00	-29.44	Average

Note: Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report and the Peak Level result is lower than the AV limit, so the AV result is not required.


4.10. Bandedge and Spurious Emission (conducted)

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION






TEST PROCEDURE


1. The transmitter output was connected to the spectrum analyzer through an attenuator.
2. Conducted spurious emission the bandwidth of the fundamental frequency was measured by spectrum analyzer with $RBW=100$ KHz and $VBW=300$ KHz.
3. Below -20dB of the highest emission level in operating band.

TEST RESULTS




Test plot as follows:





Modulation:	GFSK	Test channel:	39
		30MHz~3GHz	
3GHz~15GHz			
15GHz~26.5GHz			



Modulation:	π/4DQPSK	Test channel:	00
		Bandedge- no hopping mode	
		Bandedge- hopping mode	
		30MHz~3GHz	
		3GHz~15GHz	
		15GHz~26.5GHz	

Modulation:	π/4DQPSK	Test channel:	39		
					
30MHz~3GHz			3GHz~15GHz		
					
15GHz~26.5GHz					





Modulation:	8DPSK	Test channel:	39
		30MHz~3GHz	
		3GHz~15GHz	
		15GHz~26.5GHz	

Modulation:	8DPSK	Test channel:	78
Bandedge- no hopping mode		Bandedge- hopping mode	
30MHz~3GHz		3GHz~15GHz	
15GHz~26.5GHz			

4.11. Spurious Emission (radiated)


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209


Frequency	Limit (dBuV/m @3m)	Value
30MHz-88MHz	40.00	Quasi-peak
88MHz-216MHz	43.50	Quasi-peak
216MHz-960MHz	46.00	Quasi-peak
960MHz-1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- ◆ Below 30MHz



- ◆ 30MHz~1000MHz



- ◆ Above 1GHz



TEST PROCEDURE

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1GHz, RBW=120KHz, VBW=300KHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Above 1GHz, RBW=1MHz, VBW=3MHz for Peak value
RBW=1MHz, VBW=10Hz for Average value.

TEST RESULTS

Noted:

Have pre-scan all modulation mode, found the GFSK modulation which it was worst case, so only the worst case's data on the test report.

Measurement data:


■ 9kHz ~ 30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

■ 30MHz ~ 1GHz

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength			
Start Frequency	Stop Frequency	Detector	Meas.	IF	Transducer
30.0 MHz	1.2 GHz	MaxPeak	Coupled	100 kHz	VULB9163 2014


***MEASUREMENT RESULT: "GM0805609_red"***

8/5/2015 11:30AM

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det. ---	Height cm	Azimuth deg	Polarization
71.710000	25.00	-17.2	40.0	15.0	---	100.0	41.00	HORIZONTAL
198.780000	26.20	-13.7	43.5	17.3	---	100.0	82.00	HORIZONTAL
207.510000	24.50	-13.9	43.5	19.0	---	100.0	98.00	HORIZONTAL
279.290000	30.10	-14.4	46.0	15.9	---	100.0	82.00	HORIZONTAL
540.220000	28.10	-5.3	46.0	17.9	---	100.0	269.00	HORIZONTAL
930.160000	34.30	3.3	46.0	11.7	---	100.0	252.00	HORIZONTAL

SWEEP TABLE: "test (30M-1G)"

Short Description:		Field Strength		
Start Frequency	Stop Frequency	Detector	Meas.	IF
30.0 MHz	1.2 GHz	MaxPeak	Coupled	100 kHz
				Transducer
				VULB9163 2014

**MEASUREMENT RESULT: "GM0805608_red"**

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det. ---	Height cm	Azimuth deg	Polarization
71.710000	22.60	-17.2	40.0	17.4	---	100.0	78.00	VERTICAL
199.750000	25.10	-13.6	43.5	18.4	---	100.0	261.00	VERTICAL
208.480000	24.00	-13.9	43.5	19.5	---	100.0	333.00	VERTICAL
498.510000	27.10	-7.4	46.0	18.9	---	100.0	23.00	VERTICAL
540.220000	34.30	-5.3	46.0	11.7	---	100.0	359.00	VERTICAL
944.710000	34.00	3.6	46.0	12.0	---	100.0	205.00	VERTICAL

■ Above 1GHz

CH00 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4804.00	38.37	31.28	5.66	35.29	40.02	74.00	-33.98	Vertical	Peak
7206.00	36.84	36.22	6.87	35.15	44.78	74.00	-29.22	Vertical	
9608.00	36.95	37.85	8.80	35.55	48.05	74.00	-25.95	Vertical	
12010.00	*							Vertical	
4804.00	38.60	31.28	5.66	35.29	40.25	74.00	-33.75	Horizontal	
7206.00	37.39	36.22	6.87	35.15	45.33	74.00	-28.67	Horizontal	
9608.00	36.74	37.85	8.80	35.55	47.84	74.00	-26.16	Horizontal	
12010.00	*							Horizontal	
4804.00	32.93	31.28	5.66	35.29	34.58	54.00	-19.42	Vertical	Average
7206.00	28.65	36.22	6.87	35.15	36.59	54.00	-17.41	Vertical	
9608.00	26.76	37.85	8.80	35.55	37.86	54.00	-16.14	Vertical	
12010.00	*							Vertical	
4804.00	33.07	31.28	5.66	35.29	34.72	54.00	-19.28	Horizontal	
7206.00	29.00	36.22	6.87	35.15	36.94	54.00	-17.06	Horizontal	
9608.00	26.75	37.85	8.80	35.55	37.85	54.00	-16.15	Horizontal	
12010.00	*							Horizontal	

CH39 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4882.00	39.94	30.88	5.70	35.27	41.25	74.00	-32.75	Vertical	Peak
7323.00	37.29	35.82	6.91	35.13	44.89	74.00	-29.11	Vertical	
9764.00	37.76	37.45	8.84	35.53	48.52	74.00	-25.48	Vertical	
12205.00	*							Vertical	
4882.00	39.44	30.88	5.70	35.27	40.75	74.00	-33.25	Horizontal	
7323.00	38.08	35.82	6.91	35.13	45.68	74.00	-28.32	Horizontal	
9764.00	37.71	37.45	8.84	35.53	48.47	74.00	-25.53	Horizontal	
12205.00	*							Horizontal	
4882.00	33.44	30.88	5.70	35.27	34.75	54.00	-19.25	Vertical	Average
7323.00	29.29	35.82	6.91	35.13	36.89	54.00	-17.11	Vertical	
9764.00	27.12	37.45	8.84	35.53	37.88	54.00	-16.12	Vertical	
12205.00	*							Vertical	
4882.00	33.66	30.88	5.70	35.27	34.97	54.00	-19.03	Horizontal	
7323.00	29.15	35.82	6.91	35.13	36.75	54.00	-17.25	Horizontal	
9764.00	27.70	37.45	8.84	35.53	38.46	54.00	-15.54	Horizontal	
12205.00	*							Horizontal	

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
- “*”, means this data is the too weak instrument of signal is unable to test.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

CH78 for GFSK									
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin Limit (dB)	Polarization	Test value
4960.00	39.29	30.98	5.73	35.32	40.68	74.00	-33.32	Vertical	Peak
7440.00	36.90	35.92	6.94	35.18	44.58	74.00	-29.42	Vertical	
9920.00	37.05	37.55	8.87	35.58	47.89	74.00	-26.11	Vertical	
12400.00	*							Vertical	
4960.00	38.86	30.98	5.73	35.32	40.25	74.00	-33.75	Horizontal	
7440.00	37.06	35.92	6.94	35.18	44.74	74.00	-29.26	Horizontal	
9920.00	36.84	37.55	8.87	35.58	47.68	74.00	-26.32	Horizontal	
12400.00	*							Horizontal	
4960.00	33.18	30.98	5.73	35.32	34.57	54.00	-19.43	Vertical	Average
7440.00	29.27	35.92	6.94	35.18	36.95	54.00	-17.05	Vertical	
9920.00	26.98	37.55	8.87	35.58	37.82	54.00	-16.18	Vertical	
12400.00	*							Vertical	
4960.00	33.55	30.98	5.73	35.32	34.94	54.00	-19.06	Horizontal	
7440.00	29.34	35.92	6.94	35.18	37.02	54.00	-16.98	Horizontal	
9920.00	27.75	37.55	8.87	35.58	38.59	54.00	-15.41	Horizontal	
12400.00	*							Horizontal	

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. “*”, means this data is the too weak instrument of signal is unable to test.
3. The emission levels of other frequencies are very lower than the limit and not show in test report.

5. Test Setup Photos of the EUT

Radiated Emission




Conducted Emission (AC Mains)



6. External and Internal Photos of the EUT


External Photos










Internal Photos









.....End of Report.....