

74, Seoicheon-ro 578beon-gil, Majang-myeon, Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA
TEL: +82-31-645-6300 FAX: +82-31-645-6401

FCC MPE REPORT

FCC Certification

Applicant Name:
FRTEK CO., LTD.

Address:
11-25, Simin-daero 327beon-gil, Dongan-gu, Anyang-si,
Gyeonggi-do, Republic of Korea

Date of Issue:
March 20, 2019

Location of test lab:
HCT CO., LTD.,
74, Seoicheon-ro 578beon-gil, Majang-myeon,
Icheon-si, Gyeonggi-do, 17383, Rep. of KOREA

Report No.: HCT-RF-1904-FC003

FCC ID: 2AFEG-23-25-21-24


APPLICANT: FRTEK CO., LTD.

Model: GTS2325FRT

EUT Type: INOVA ERU

The measurements shown in this report were made in accordance with the procedures specified in §2.947. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them.

HCT CO., LTD. Certifies that no party to this application has subject to a denial of Federal benefits that includes FCC benefits pursuant to section 5301 of the Anti-Drug Abuse Act of 1998,21 U.S. C.853(a)



Report prepared by : Kyung Soo Kang
Engineer of Telecommunication testing center

Approved by : Yong Hyun Lee
Manager of Telecommunication testing center

This report only responds to the tested sample and may not be reproduced, except in full, without written approval of the HCT Co., Ltd.

Version

TEST REPORT NO.	DATE	DESCRIPTION
HCT-RF-1904-FC003	March 20, 2019	- First Approval Report

RF Exposure Statement

1. LIMITS

According to §1.1310 and §2.1091 RF exposure is calculated.

(B) Limits for General Population/Uncontrolled Exposures

Frequency range (MHz)	Electric field Strength (V/m)	Magnetic field Strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
0.3 - 1.34.....	614	1.63	*(100)	30
1.34 - 30.....	824/f	2.19/f	*(180/ f ²)	30
30 - 300.....	27.5	0.073	0.2	30
300 - 1500.....	f/1500	30
1500 - 100.000.....	1.0	30

F = frequency in MHz

* = Plane-wave equivalent power density

2. MAXIMUM PERMISSIBLE EXPOSURE Prediction

Prediction of MPE limit at a given distance

$$S = PG/4\pi R^2$$

S = Power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

3. RESULTS

- WCS

Max Peak output Power at antenna input terminal	22.000	dBm
Max Peak output Power at antenna input terminal	158.49	mW
Prediction distance	20.00	cm
Prediction frequency	2 355.00	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency(S)	0.126	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²

- BRS

Max Peak output Power at antenna input terminal	25.00	dBm
Max Peak output Power at antenna input terminal	316.23	mW
Prediction distance	20.00	cm
Prediction frequency	2 593.00	MHz
Antenna Gain(typical)	6.000	dBi
Antenna Gain(numeric)	3.981	-
Power density at prediction frequency(S)	0.250	mW/cm ²
MPE limit for uncontrolled exposure at prediction frequency	1.000	mW/cm ²