



FCC CERTIFICATION TEST REPORT

Applicant:	Guangzhou Shirui Electronics Co.,Ltd
Address:	192 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, Guangdong, China
Manufacturer:	Guangzhou Shirui Electronics Co.,Ltd
Address:	192 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, Guangdong, China
Product Description:	Speakerphone
Brand Name:	NA
Tested Model:	BM41
FCC ID:	2AFG6-BM41
Report No.:	JCF220826201-003
Received Date:	Aug. 26, 2022
Tested Date:	Aug. 26, 2022~Sep. 10, 2022
Issued Date:	Sep. 13, 2022
Test Standards:	FCC Rules and Regulations Part 15 Subpart C
Test Procedure :	ANSI C63.10:2013
Test Result:	Pass
Prepared By:  <u>Roger/Engineer</u>	
 Date: Sep. 13, 2022	
Reviewed By:  <u>Jone Lv/Engineer</u>	
Date: Sep. 13, 2022	
Approved By:  <u>Talent Zhang/Engineer</u>	
Date: Sep. 13, 2022	

Note: The test results in this report apply exclusively to the tested model / sample. Without written approval of Guangzhou Jingce Testing Technology Co., Ltd. the test report shall not be reproduced except in full.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Sep. 13, 2022	Original Report	/

Table of Contents

1. Test Report Declare	5
2. Summary of Test Results	6
3. Test Laboratory	6
4. Equipment Under Test	7
4.1. Description of EUT	7
4.2. Channel List	7
4.3. Packet Type Configuration	8
4.4. Test Channel Configuration	8
4.5. Test Environment Conditions	8
4.6. The Worse Case Power Setting Parameter	8
4.7. Description of Available Antennas	9
5. Description of Test Setup	9
5.1. Accessory	9
5.2. Support Equipment	9
5.3. Test Setup	9
5.4. Setup Diagram for Tests	9
6. Measurement Uncertainty	10
7. Measuring Instrument and Software Used	10
8. On Time and Duty Cycle	12
8.1. Block Diagram of Test Setup	12
8.2. Limits	12
8.3. Results	12
8.4. Original Test Data	13
9. 20 dB Occupied Bandwidth	16
9.1. Block Diagram of Test Setup	16
9.2. Limit	16
9.3. Test Procedure	16
9.4. Results	16
9.5. Original Test Data	17
10. Conducted Output Power	20
10.1. Block Diagram of Test Setup	20
10.2. Limits	20
10.3. Test Procedure	20
10.4. Results	20
10.5. Original Test Data	21
11. Carrier Hopping Channel Separation	24
11.1. Block Diagram of Test Setup	24
11.2. Limits	24
11.3. Test Procedure	24
11.4. Results	24
11.5. Original Test Data	25
12. Number of Hopping Frequency	26
12.1. Block Diagram of Test Setup	26
12.2. Limits	26
12.3. Test Procedure	26
12.4. Results	26

12.5. Original Test Data	27
13. Time of Occupancy (Dwell Time)	28
13.1. Block Diagram of Test Setup	28
13.2. Limits	28
13.3. Test Procedure	28
13.4. Results	29
13.5. Original Test Data	30
14. Conducted Spurious Emission	33
14.1. Block Diagram of Test Setup	33
14.2. Limits	33
14.3. Test Procedure	33
14.4. Results	34
14.5. Original Test Data	35
15. Radiated Emission	43
15.1. Block Diagram of Test Setup	43
15.2. Limit	44
15.3. Test Procedure	46
15.4. Results	49
15.5. Original Test Data	49
16. AC Power Line Conducted Emissions	50
16.1. Block Diagram of Test Setup	50
16.2. Limits	50
16.3. Test Procedure	50
16.4. Test Result	51
16.5. Original Test Data	51
17. Antenna Requirements	52
17.1. Limits	52
17.2. Result	52
APPENDIX A – Radiated Emission Below 1GHz Test Data	53
APPENDIX B – Radiated Emission Above 1GHz Test Data	55
APPENDIX C – AC Power Line Conducted Emission Test Data	75

1. Test Report Declare

Applicant:	Guangzhou Shirui Electronics Co.,Ltd
Address:	192 Kezhu Road, Scienteck Park, Guangzhou Economic & Technology Development District, Guangzhou, Guangdong, China
Manufacturer:	Guangzhou Shirui Electronics Co.,Ltd
Address:	192 Kezhu Road, Scienteck Park, Guangzhou Economic & Technology Development District, Guangzhou, Guangdong, China
Product Name:	Speakerphone
Brand Name:	NA
Model Name:	BM41, BMxx(x: 0~9, A~Z, Blank)
Difference Description:	The products with all the models covered in this report are the same as each other, except for different model number and market region.

We Declare:

The equipment described above is tested by Guangzhou Jingce Testing Technology Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained this test report and Guangzhou Jingce Testing Technology Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

2. Summary of Test Results

Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Result
1	20 dB Bandwidth	FCC 15.247 (a) (1)	Pass
2	Conducted Output Power	FCC 15.247 (b) (1)	Pass
3	Carrier Hopping Channel Separation	FCC 15.247 (a) (1)	Pass
4	Number of Hopping Frequency	15.247 (a) (1) III	Pass
5	Time of Occupancy (Dwell Time)	15.247 (a) (1) III	Pass
6	Conducted Band edge	FCC 15.247 (d)	Pass
7	Radiated Band edge and Spurious	FCC 15.247 (d) FCC 15.209 FCC 15.205	Pass
8	Conducted Emission Test For AC Power Port	FCC 15.207	Pass
9	Antenna Requirement	FCC 15.203	Pass

3. Test Laboratory

Guangzhou Jingce Testing Technology Co., Ltd.

Add.: No.192, Kezhu Road, Huangpu District, Guangzhou, Guangdong, China

Association for Laboratory Accreditation(A2LA). Certificate Number: 6594.01

FCC Designation Number:CN1331. Test Firm Registration Number: 360543

IC Test Firm Registration Number: 28796

Conformity Assessment Body identifier: CN0138

4. Equipment Under Test

4.1. Description of EUT

EUT Name:	Speakerphone
Model Number:	BM41
EUT Function Description:	Please reference user's manual
Power Supply:	DC 5V from Adapter DC 3.7V from Battery
Hardware Version:	V1.1
Software Version:	220805180611_BT1_V6.8
Radio Specification:	Bluetooth V5.3
Operation Frequency:	2402 MHz - 2480 MHz
Modulation:	GFSK, $\pi/4$ -DQPSK
Data Rate:	1Mbps,2Mbps
Antenna Type:	PCB Antenna, -4.86 dBi

Note 1: EUT is the ab. of equipment under test.

Note 2: The antenna gain is declared by the customer and the laboratory is not responsible for the accuracy of the antenna gain.

4.2. Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	/	/

4.3. Packet Type Configuration

Test Mode	Packet Type	Setting(Packet Length)
GFSK	DH1	27
	DH3	183
	DH5	339
$\pi/4$ -DQPSK	2-DH1	54
	2-DH3	367
	2-DH5	679

4.4. Test Channel Configuration

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
GFSK hopping on Tx mode	CH0 to CH78	2402 to 2480
$\pi/4$ -DQPSK hopping on Tx mode	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	LCH: CH0	2402
	MCH: CH39	2441
	HCH: CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	LCH: CH0	2402
	MCH: CH39	2441
	HCH: CH78	2480

4.5. Test Environment Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25 °C
Humidity range:	40-75%
Pressure range:	86-106 kPa

4.6. The Worse Case Power Setting Parameter

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		FCC Assist 1.0.2.2		
Modulation Type	Transmit Antenna Number	Test Software Setting Value		
		CH 0	CH 39	CH 78
GFSK	1	9	8	8
$\pi/4$ -DQPSK	1	9	9	8

4.7. Description of Available Antennas

Test Mode	Transmit and Receive Mode	Description
GFSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
$\pi/4$ -DQPSK	☒ 1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

5. Description of Test Setup

5.1. Accessory

Description of Accessories	Manufacturer	Model Number	Description	Remark
USB-C Cable	/	/	1.0m	Shielded

5.2. Support Equipment

Equipment	Brand Name	Model Name	P/N
PC	Lenovo	T480	/
Adapter	FlyPower	PS10K050K2000CU	/

5.3. Test Setup

The EUT can work in fixed frequency.

5.4. Setup Diagram for Tests



6. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
AC Power Conduction emission	1.37 dB
All Radiated emissions	5.4dB
Conducted emissions	3.09 dB
Occupied Channel Bandwidth	1.1%
Conducted Output power	0.82dB
Power Spectral Density	0.82dB
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level using a coverage factor of k = 2.	


7. Measuring Instrument and Software Used

TS Test System						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	Spectrum Analyzer	Keysight	N9030B	MY56320512	Jul.25,2022	Jul.24,2023
☒	Vector Signal Generator	Keysight	N5182B	MY57300334	Dec.03,2021	Dec.02,2022
☒	Signal Generator	Keysight	N5171B	MY57280639	Dec.03,2021	Dec.02,2022
☒	DC POWER	Keysight	E342A	MY59020356	Jul.25,2022	Jul.24,2023
☒	Incubator thermometer	GWS	EL-02JA	21107288	Nov.05,2021	Nov.04,2022
☒	Control unit(Power sensor)	Tonscend	JS0806-2	/	Aug.25,2021	Aug.24,2022
Software						
Used	Description	Manufacturer	Name		Version	
☒	Test software	TS+	JS1120-3		V3.2.11	
RSE Test System						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	EMI Receiver	R&S	ESW	101685	Jul.24,2022	Jul.23,2023
☒	Bilog Antenna	Schwarzbeck	VULB 9163	01416	Feb.22,2022	Feb.21,2023
☒	Horn Antenna 1	Schwarzbeck	BBHA 9120 D	02411	May.30,2022	May.29,2023
☒	Horn Antenna 2	ETS	3116C	00217677	Aug.27,2022	Aug.26,2023
☒	Signal Pre-Amplifier	Tonscend	TAP01018050	AP21C806122	Aug.08,2022	Aug.07,2023
☒	Signal Pre-Amplifier	Tonscend	TAP9K3G32	AP20K806104	Aug.08,2022	Aug.07,2023
☒	Signal Pre-Amplifier	ETS	3116C-PA	00217677	Sep.29,2021	Sep.28,2022

☒	Wideband radio communication tester	R&S	CMW500	163478	Jul.25,2022	Jul.24,2023
☒	3m Fully-anechoic Chamber	ETS	RFD-100	/	Apr.24,2021	Apr.23,2024
Software						
Used	Description	Manufacturer	Name		Version	
☒	Test software	TS+	TS+		V3.0.0.4	
Conducted Emission Test For AC Power Port						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	LISN	R&S	ENV216	102154	Jul.24,2022	Jul.23,2023
☒	EMI Receiver	R&S	ESR3	102509	Jul.24,2022	Jul.23,2023
Software						
Used	Description	Manufacturer	Name		Version	
☒	Test software	EZ	EZ-EMC		EMEC-3A1	
Other Instrument						
Used	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
☒	Temperature & Humidity	Temperature	HTC-1	/	Jan.24,2022	Jan.23,2023

8. On Time and Duty Cycle

8.1. Block Diagram of Test Setup



8.2. Limits

None; for reporting purposes only

8.3. Results

Test Mode	Ant.	Freq. (MHz)	ON Time (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Factor(dB)
DH5	Ant1	2402	2.89	3.75	77.07	1.13
		2441	2.89	3.75	77.07	1.13
		2480	2.89	3.75	77.07	1.13
2DH5	Ant1	2402	2.89	3.75	77.07	1.13
		2441	2.89	3.75	77.07	1.13
		2480	2.89	3.75	77.07	1.13

Note: Duty Cycle Correction Factor= $10\log(1/x)$.

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

8.4. Original Test Data





2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480



9. 20 dB Occupied Bandwidth

9.1. Block Diagram of Test Setup

Same as section 8.1

9.2. Limit

CFR 47 FCC Part15 (15.247) Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1)	20 dB Occupied Bandwidth	N/A	2400-2483.5

9.3. Test Procedure

Connect the UUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 20 dB Occupied Bandwidth: 1 % to 5 % of the 20 dB bandwidth
VBW	For 20 dB Occupied Bandwidth: approximately 3×RBW
Span	approximately 2 to 3 times the 20 dB bandwidth
Trace	Max hold
Sweep	Auto couple

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

9.4. Results

20 dB Occupied Bandwidth:

Test Mode	Ant.	Freq. (MHz)	20db EBW (MHz)	FL (MHz)	FH (MHz)
DH5	Ant1	2402	0.957	2401.550	2402.507
		2441	0.942	2440.559	2441.501
		2480	0.951	2479.550	2480.501
2DH5	Ant1	2402	1.323	2401.355	2402.678
		2441	1.311	2440.364	2441.675
		2480	1.278	2479.388	2480.666

9.5. Original Test Data

20 dB Occupied Bandwidth:





2DH5_Ant1_2402



2DH5_Ant1_2441



2DH5_Ant1_2480



10. Conducted Output Power

10.1. Block Diagram of Test Setup

Same as section 8.1

10.2. Limits

CFR 47 FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (b) (1)	Peak Conducted Output Power	Hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel: 1 watt or 30dBm; Hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel : 125 mW or 21dBm	2400-2483.5

10.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.


(2) Measure the maximum output power of EUT by spectrum analyzer with PK detector and RBW=3 MHz (above 20 dB bandwidth of measured signal), VBW=8 MHz


Note: The attenuator loss was inputted into spectrum analyzer as amplitude offset.

10.4. Results

Test Mode	Ant.	Freq. (MHz)	Conducted Peak Power (dBm)	Conducted Limit (dBm)	Verdict
DH5	Ant1	2402	-0.97	≤20.97	PASS
		2441	-2.57	≤20.97	PASS
		2480	-1.85	≤20.97	PASS
2DH5	Ant1	2402	-0.09	≤20.97	PASS
		2441	1.25	≤20.97	PASS
		2480	-1	≤20.97	PASS

10.5. Original Test Data







11. Carrier Hopping Channel Separation

11.1. Block Diagram of Test Setup

Same as section 8.1

11.2. Limits

CFR 47 FCC Part15 (15.247) , Subpart C			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247 (a) (1)	Carrier Hopping Channel Separation	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel.	2400-2483.5

11.3. Test Procedure

Connect the UUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Span	wide enough to capture the peaks of two adjacent channels
Detector	Peak
RBW	Start with the RBW set to approximately 30 % of the channel spacing; adjust as necessary to best identify the center of each individual channel.
VBW	≥ RBW
Trace	Max hold
Sweep time	Auto couple

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Compliance of an EUT with the appropriate regulatory limit shall be determined.

A plot of the data shall be included in the test report.

11.4. Results

Test Mode	Ant.	Freq. (MHz)	Result (MHz)	Limit (MHz)	Verdict
DH5	Ant1	Hop	0.706	≥0.638	PASS
2DH5	Ant1	Hop	0.986	≥0.882	PASS

11.5. Original Test Data



12. Number of Hopping Frequency

12.1. Block Diagram of Test Setup

Same as section 8.1

12.2. Limits

CFR 47 FCC Part15 (15.247), Subpart C		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III	Number of Hopping Frequency	at least 15 hopping channels

12.3. Test Procedure

Connect the EUT to the spectrum Analyzer and use the following settings:

Detector	Peak
RBW	To identify clearly the individual channels, set the RBW to less than 30 % of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW	≥RBW
Span	The frequency band of operation
Trace	Max hold
Sweep time	Auto couple

Set EUT to transmit maximum output power and switch on frequency hopping function. then set enough count time (larger than 5000 times) to get all the hopping frequency channel displayed on the screen of spectrum analyzer.

Count the quantity of peaks to get the number of hopping channels.

FHSS Mode: 79 Channels observed.

AFHSS Mode: 20 Channels declared.

12.4. Results

Test Mode	Ant.	Freq. (MHz)	Result (Num)	Limit (Num)	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS

12.5. Original Test Data



13. Time of Occupancy (Dwell Time)

13.1. Block Diagram of Test Setup

Same as section 8.1

13.2. Limits

CFR 47 FCC Part15 (15.247), Subpart C		
Section	Test Item	Limit
CFR 47 15.247 (a) (1) III	Time of Occupancy (Dwell Time)	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed.

13.3. Test Procedure

Connect the UUT to the spectrum Analyzer and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Average
RBW	1 MHz
VBW	≥ RBW
Span	zero span
Trace	Clear Write
Sweep time	As necessary to capture the entire dwell time per hopping channel

Connect the UUT to the spectrum Analyzer and use the following settings:

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1 MHz and VBW to 3 MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.

f. Measure the maximum time duration of one single pulse.

g. Set the EUT for DH5, DH3 and DH1 packet transmitting.

h. Measure the maximum time duration of one single pulse.

A Period Time = (channel number)*0.4

For FHSS Mode (79 Channel):

DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)

DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)

DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

13.4. Results

Test Mode	Ant.	Freq. (MHz)	Burst Width (ms)	Total Hops (Num)	Result (s)	Limit (s)	Verdict
DH1	Ant1	Hop	0.36	320	0.115	≤0.4	PASS
DH3	Ant1	Hop	1.62	160	0.259	≤0.4	PASS
DH5	Ant1	Hop	2.86	106.67	0.305	≤0.4	PASS
2DH1	Ant1	Hop	0.38	320	0.122	≤0.4	PASS
2DH3	Ant1	Hop	1.63	160	0.261	≤0.4	PASS
2DH5	Ant1	Hop	2.87	106.67	0.306	≤0.4	PASS

13.5. Original Test Data





2DH1 Ant1 Hop



2DH3 Ant1 Hop



2DH5 Ant1 Hop



14. Conducted Spurious Emission

14.1. Block Diagram of Test Setup

Same as section 8.1

14.2. Limits

CFR 47 FCC Part15 (15.247), Subpart C		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d)	Conducted Spurious Emission	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

14.3. Test Procedure

Please refer to the ANSI C63.10 section 6.10.

For Band edge use the following settings:

Detector	Peak
RBW	100 kHz
VBW	300 kHz
Span	wide enough to fully capture the emission being measured
Trace	Max hold
Sweep time	Auto couple.

For Spurious Emission use the following settings:

Detector	Peak
RBW	100 kHz
VBW	300 kHz
Span	wide enough to fully capture the emission being measured
Trace	Max hold
Sweep time	Auto couple.

Use the peak marker function to determine the maximum amplitude level.

14.4. Results

Band edge:

Test Mode	Ant.	Ch Name	Freq. (MHz)	Ref Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
DH5	Ant1	Low	2402	-1.28	-55.6	≤-21.28	PASS
		High	2480	-2.26	-56.89	≤-22.26	PASS
		Low	Hop_2402	-1.87	-55.34	≤-21.87	PASS
		High	Hop_2480	0.30	-56.46	≤-19.7	PASS
2DH5	Ant1	Low	2402	-1.31	-55.59	≤-21.31	PASS
		High	2480	-2.32	-56.85	≤-22.32	PASS
		Low	Hop_2402	-2.94	-55.52	≤-22.94	PASS
		High	Hop_2480	0.05	-56.83	≤-19.95	PASS

Spurious Emission:

Test Mode	Ant.	Freq. (MHz)	Freq Range (MHz)	Ref Level (dBm)	Result (dBm)	Limit (dBm)	Verdict
DH5	Ant1	2402	30~1000	-1.28	-64.48	≤-21.28	PASS
			1000~26500	-1.28	-51.66	≤-21.28	PASS
		2441	30~1000	-2.97	-64.51	≤-22.97	PASS
			1000~26500	-2.97	-54.41	≤-22.97	PASS
		2480	30~1000	-2.26	-63.78	≤-22.26	PASS
			1000~26500	-2.26	-52.43	≤-22.26	PASS
2DH5	Ant1	2402	30~1000	-1.31	-64.67	≤-21.31	PASS
			1000~26500	-1.31	-52.28	≤-21.31	PASS
		2441	30~1000	0.13	-64.6	≤-19.87	PASS
			1000~26500	0.13	-51.72	≤-19.87	PASS
		2480	30~1000	-2.32	-64.29	≤-22.32	PASS
			1000~26500	-2.32	-54.03	≤-22.32	PASS

14.5. Original Test Data

Band edge:





DH5 Ant1 High Hop 2480



2DH5 Ant1 Low 2402



2DH5 Ant1 High 2480



2DH5 Ant1 Low Hop 2402




2DH5 Ant1 High Hop 2480



Spurious Emission:






DH5 Ant1 2441 1000~26500



DH5 Ant1 2480 30~1000



DH5 Ant1 2480 1000~26500



2DH5_Ant1_2402_30~1000



2DH5_Ant1_2402_1000~26500



2DH5_Ant1_2441_30~1000







15. Radiated Emission

15.1. Block Diagram of Test Setup


In 3m Anechoic Chamber, test setup diagram for 9kHz - 30MHz:



In 3m Anechoic Chamber, test setup diagram for 30 MHz - 1 GHz:



In 3m Anechoic Chamber, test setup diagram for frequency above 1 GHz:



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

15.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6

(2) FCC 15.209 Limit.

Frequency MHz	Distance Meters	Field Strengths Limit	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	$2400/F(\text{kHz})$	$67.6-20\log(F)$
0.490 ~ 1.705	30	$24000/F(\text{kHz})$	$87.6-20\log(F)$
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.

About Restricted bands of operation please refer to FCC § 15.205 (a),

15.3. Test Procedure

Below 30 MHz:

The setting of the spectrum Analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of 1 meter height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore, sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

Below 1 GHz and above 30 MHz:

The setting of the spectrum Analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz:

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013.

2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

3. The EUT was placed on a turntable with 1.5m above ground.

4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.

5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.

6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for AVG measurements. For the Duty Cycle please refer to clause 7.1.On Time And Duty Cycle.

7. Restriction band: Investigated frequency range from 2310 MHz to 2410 MHz and 2470MHz to 2500 MHz.

All restriction band should comply with 15.209, other emission should be at least 20 dB below the fundamental.

Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT does not support simultaneous transmission.

Note 3: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

15.4. Results

Pass. (See below detailed test result)

All the emissions except fundamental emission from 9 kHz to 25 GHz were comply with 15.209 limits.

Note1: According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz, so the final test was performed with frequency range from 30 MHz to 26 GHz and recorded in below.

Note2: For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in GFSK, TX 2402 MHz mode.

Note3: For emissions above 1 GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.


15.5. Original Test Data

Below 1 GHz and above 30 MHz test data Refer to appendix A

Above 1 GHz test data Refer to appendix B

16. AC Power Line Conducted Emissions

16.1. Block Diagram of Test Setup



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through an Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

16.2. Limits

Please refer to CFR 47 FCC § 15.207 (a) .

Frequency (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

16.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

16.4. Test Result

Pass. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.

Note2: Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worse case.

16.5. Original Test Data

Refer to appendix C

17. Antenna Requirements

17.1. Limits

Please refer to FCC § 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC § 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

17.2. Result

The antenna used for this product is PCB antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is -4.86 dBi


APPENDIX A – Radiated Emission Below 1GHz Test Data

Test Report

Project Information			
EUT:	Speakerphone	Environment:	25℃/58%
Model:	BM41	SN:	
Mode:	BT_DH5_2402	Voltage:	AC120V/60Hz
Customer:		Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 22:38:11

Test Graph




Suspected Data List								
NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	58.0358	31.22	-22.21	40.00	8.78	100	267	Horizontal
2	83.9374	34.68	-26.79	40.00	5.32	100	191	Horizontal
3	155.918	34.16	-25.55	43.50	9.34	100	152	Horizontal
4	215.967	39.67	-22.55	43.50	3.83	100	164	Horizontal
5	312.007	41.22	-19.76	46.00	4.78	100	228	Horizontal
6	371.959	38.67	-18.01	46.00	7.33	100	221	Horizontal

Test Report

Project Information			
EUT:	Speakerphone	Environment:	25℃/58%
Model:	BM41	SN:	
Mode:	BT_DH5_2402	Voltage:	AC120V/60Hz
Customer:		Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 22:38:47

Test Graph



Suspected Data List

NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Polarity
1	57.0657	32.60	-22.07	40.00	7.40	100	216	Vertical
2	74.3334	29.43	-26.43	40.00	10.57	100	340	Vertical
3	83.9374	31.32	-26.79	40.00	8.68	100	359	Vertical
4	215.967	34.74	-22.55	43.50	8.76	100	28	Vertical
5	263.987	33.34	-21.02	46.00	12.66	100	28	Vertical
6	312.007	32.51	-19.76	46.00	13.49	100	28	Vertical


APPENDIX B – Radiated Emission Above 1GHz Test Data

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2402	Voltage:	AC120V/60Hz
Environment:	25℃/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-05 20:16:12

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2402.1402	7.13	47.26	74.00	26.74	150	253	Horizontal
2	2959.3959	8.65	45.47	74.00	28.53	150	14	Horizontal
3	5020.7021	-8.45	38.35	74.00	35.65	150	350	Horizontal
4	9608.1608	3.01	52.46	74.00	21.54	150	64	Horizontal
5	14296.1296	11.60	49.54	74.00	24.46	150	150	Horizontal
6	17882.9883	14.73	51.21	74.00	22.79	150	279	Horizontal

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2402.1402	7.13	42.81	54.00	11.19	150	253	Horizontal
2	2959.3959	8.65	38.68	54.00	15.32	150	14	Horizontal
3	5020.7021	-8.45	31.24	54.00	22.76	150	350	Horizontal
4	9608.1608	3.01	47.44	54.00	6.56	150	64	Horizontal
5	14296.1296	11.60	43.42	54.00	10.58	150	150	Horizontal
6	17882.9883	14.73	45.69	54.00	8.31	150	279	Horizontal

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2402	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-05 20:17:37

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2401.9402	7.13	45.51	74.00	28.49	150	26	Vertical
2	2933.5934	8.52	45.39	74.00	28.61	150	20	Vertical
3	9608.1608	3.01	54.68	74.00	19.32	150	158	Vertical
4	12297.9298	7.00	47.60	74.00	26.40	150	74	Vertical
5	14642.6643	12.29	48.89	74.00	25.11	150	226	Vertical
6	17939.9940	14.66	50.54	74.00	23.46	150	66	Vertical

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2401.9402	7.13	41.30	54.00	12.70	150	26	Vertical
2	2933.5934	8.52	39.12	54.00	14.88	150	20	Vertical
3	9608.1608	3.01	48.09	54.00	5.91	150	158	Vertical
4	12297.9298	7.00	42.19	54.00	11.81	150	74	Vertical
5	14642.6643	12.29	44.32	54.00	9.68	150	226	Vertical
6	17939.9940	14.66	46.22	54.00	7.78	150	66	Vertical

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2441	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-05 20:21:10

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2475.5476	7.64	45.04	74.00	28.96	150	93	Horizontal
2	2997.3997	8.85	45.39	74.00	28.61	150	33	Horizontal
3	7272.4272	-1.37	42.53	74.00	31.47	150	82	Horizontal
4	9764.1764	3.11	49.00	74.00	25.00	150	340	Horizontal
5	14729.6730	11.74	49.38	74.00	24.62	150	356	Horizontal
6	17881.4881	14.72	51.71	74.00	22.29	150	133	Horizontal

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2475.5476	7.64	39.37	54.00	14.63	150	93	Horizontal
2	2997.3997	8.85	38.98	54.00	15.02	150	33	Horizontal
3	7272.4272	-1.37	36.21	54.00	17.79	150	82	Horizontal
4	9764.1764	3.11	44.24	54.00	9.76	150	340	Horizontal
5	14729.6730	11.74	43.93	54.00	10.07	150	356	Horizontal
6	17881.4881	14.72	45.98	54.00	8.02	150	133	Horizontal

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2441	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-05 20:22:35

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2419.5420	7.26	44.54	74.00	29.46	150	294	Vertical
2	2893.9894	8.33	45.78	74.00	28.22	150	83	Vertical
3	7152.4152	-1.77	41.58	74.00	32.42	150	244	Vertical
4	9764.1764	3.11	51.15	74.00	22.85	150	236	Vertical
5	12888.9889	9.49	48.46	74.00	25.54	150	351	Vertical
6	16678.3678	11.25	50.00	74.00	24.00	150	286	Vertical

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2419.5420	7.26	38.76	54.00	15.24	150	294	Vertical
2	2893.9894	8.33	39.47	54.00	14.53	150	83	Vertical
3	7152.4152	-1.77	35.16	54.00	18.84	150	244	Vertical
4	9764.1764	3.11	47.21	54.00	6.79	150	236	Vertical
5	12888.9889	9.49	43.47	54.00	10.53	150	351	Vertical
6	16678.3678	11.25	44.29	54.00	9.71	150	286	Vertical

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2480	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-05 20:24:51

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2485.5486	7.71	45.18	74.00	28.82	150	79	Horizontal
2	2893.9894	8.33	44.97	74.00	29.03	150	358	Horizontal
3	4959.1959	-8.84	41.61	74.00	32.39	150	256	Horizontal
4	9920.1920	3.89	49.55	74.00	24.45	150	68	Horizontal
5	13526.5527	10.57	48.73	74.00	25.27	150	118	Horizontal
6	17851.4851	14.50	51.58	74.00	22.42	150	360	Horizontal

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2485.5486	7.71	39.64	54.00	14.36	150	79	Horizontal
2	2893.9894	8.33	39.73	54.00	14.27	150	358	Horizontal
3	4959.1959	-8.84	33.49	54.00	20.51	150	256	Horizontal
4	9920.1920	3.89	44.47	54.00	9.53	150	68	Horizontal
5	13526.5527	10.57	44.27	54.00	9.73	150	118	Horizontal
6	17851.4851	14.50	46.13	54.00	7.87	150	360	Horizontal

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2480	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-05 20:26:17

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2510.5511	7.88	44.49	74.00	29.51	150	242	Vertical
2	3505.5506	-15.06	32.91	74.00	41.09	150	214	Vertical
3	4959.1959	-8.84	40.17	74.00	33.83	150	74	Vertical
4	9920.1920	3.89	51.76	74.00	22.24	150	74	Vertical
5	13516.0516	10.59	49.03	74.00	24.97	150	196	Vertical
6	17830.4830	14.35	53.10	74.00	20.90	150	169	Vertical

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2510.5511	7.88	39.57	54.00	14.43	150	242	Vertical
2	3505.5506	-15.06	27.28	54.00	26.72	150	214	Vertical
3	4959.1959	-8.84	35.80	54.00	18.20	150	74	Vertical
4	9920.1920	3.89	46.97	54.00	7.03	150	74	Vertical
5	13516.0516	10.59	43.70	54.00	10.30	150	196	Vertical
6	17830.4830	14.35	45.66	54.00	8.34	150	169	Vertical

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2402	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 19:09:28

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2401.9402	7.13	45.44	74.00	28.56	150	96	Horizontal
2	2869.3869	8.27	46.29	74.00	27.71	150	285	Horizontal
3	7911.4911	-0.16	43.23	74.00	30.77	150	106	Horizontal
4	9608.1608	3.01	51.84	74.00	22.16	150	99	Horizontal
5	13765.0765	10.45	50.17	74.00	23.83	150	114	Horizontal
6	17794.4794	14.07	51.74	74.00	22.26	150	322	Horizontal

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2401.9402	7.13	41.72	54.00	12.28	150	96	Horizontal
2	2869.3869	8.27	40.22	54.00	13.78	150	285	Horizontal
3	7911.4911	-0.16	37.54	54.00	16.46	150	106	Horizontal
4	9608.1608	3.01	45.88	54.00	8.12	150	99	Horizontal
5	13765.0765	10.45	44.18	54.00	9.82	150	114	Horizontal
6	17794.4794	14.07	45.53	54.00	8.47	150	322	Horizontal

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2402	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 19:10:54

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2402.3402	7.14	44.83	74.00	29.17	150	31	Vertical
2	2962.5963	8.67	45.15	74.00	28.85	150	265	Vertical
3	8732.0732	1.90	44.37	74.00	29.63	150	136	Vertical
4	9608.1608	3.01	53.54	74.00	20.46	150	136	Vertical
5	12968.4969	9.50	49.64	74.00	24.36	150	156	Vertical
6	17861.9862	14.58	53.05	74.00	20.95	150	295	Vertical

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2402.3402	7.14	39.89	54.00	14.11	150	31	Vertical
2	2962.5963	8.67	39.07	54.00	14.93	150	265	Vertical
3	8732.0732	1.90	39.28	54.00	14.72	150	136	Vertical
4	9608.1608	3.01	48.74	54.00	5.26	150	136	Vertical
5	12968.4969	9.50	43.58	54.00	10.42	150	156	Vertical
6	17861.9862	14.58	46.38	54.00	7.62	150	295	Vertical

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2441	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 19:14:05

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2480.3480	7.68	44.66	74.00	29.34	150	306	Horizontal
2	2999.1999	8.86	44.42	74.00	29.58	150	159	Horizontal
3	4881.1881	-9.49	41.76	74.00	32.24	150	290	Horizontal
4	9764.1764	3.11	50.26	74.00	23.74	150	102	Horizontal
5	12911.4911	9.51	49.26	74.00	24.74	150	243	Horizontal
6	17905.4905	14.82	51.94	74.00	22.06	150	169	Horizontal

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2480.3480	7.68	38.81	54.00	15.19	150	306	Horizontal
2	2999.1999	8.86	39.75	54.00	14.25	150	159	Horizontal
3	4881.1881	-9.49	35.15	54.00	18.85	150	290	Horizontal
4	9764.1764	3.11	44.59	54.00	9.41	150	102	Horizontal
5	12911.4911	9.51	43.88	54.00	10.12	150	243	Horizontal
6	17905.4905	14.82	46.20	54.00	7.80	150	169	Horizontal

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2441	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 19:15:31

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2487.9488	7.73	45.16	74.00	28.84	150	359	Vertical
2	2985.3985	8.79	45.77	74.00	28.23	150	352	Vertical
3	4881.1881	-9.49	40.10	74.00	33.90	150	69	Vertical
4	9764.1764	3.11	54.43	74.00	19.57	150	210	Vertical
5	12966.9967	9.50	48.50	74.00	25.50	150	320	Vertical
6	17990.9991	14.41	52.63	74.00	21.37	150	344	Vertical

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2487.9488	7.73	39.70	54.00	14.30	150	359	Vertical
2	2985.3985	8.79	39.12	54.00	14.88	150	352	Vertical
3	4881.1881	-9.49	32.32	54.00	21.68	150	69	Vertical
4	9764.1764	3.11	49.37	54.00	4.63	150	210	Vertical
5	12966.9967	9.50	43.44	54.00	10.56	150	320	Vertical
6	17990.9991	14.41	46.31	54.00	7.69	150	344	Vertical

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2480	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-07 19:20:24

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2480.1480	7.68	45.42	74.00	28.58	150	16	Horizontal
2	5083.7084	-8.32	37.45	74.00	36.55	150	280	Horizontal
3	8579.0579	1.98	44.48	74.00	29.52	150	113	Horizontal
4	9920.1920	3.89	49.93	74.00	24.07	150	113	Horizontal
5	13516.0516	10.59	51.26	74.00	22.74	150	296	Horizontal
6	17840.9841	14.43	53.24	74.00	20.76	150	1	Horizontal

AV Final Data List


NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2480.1480	7.68	39.89	54.00	14.11	150	16	Horizontal
2	5083.7084	-8.32	31.93	54.00	22.07	150	280	Horizontal
3	8579.0579	1.98	38.10	54.00	15.90	150	113	Horizontal
4	9920.1920	3.89	44.45	54.00	9.55	150	113	Horizontal
5	13516.0516	10.59	44.36	54.00	9.64	150	296	Horizontal
6	17840.9841	14.43	46.54	54.00	7.46	150	1	Horizontal

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2480	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-07 19:21:49

Test Graph



PK Final Data List

NO.	Freq. (MHz)	Factor (dB)	PK Value (dBμV/m)	PK Limit (dBμV/m)	PK Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2414.7415	7.22	44.04	74.00	29.96	150	346	Vertical
2	2997.1997	8.85	45.98	74.00	28.02	150	46	Vertical
3	4959.1959	-8.84	39.56	74.00	34.44	150	240	Vertical
4	9920.1920	3.89	51.77	74.00	22.23	150	345	Vertical
5	13544.5545	10.53	49.31	74.00	24.69	150	123	Vertical
6	17851.4851	14.50	53.03	74.00	20.97	150	337	Vertical

AV Final Data List

NO.	Freq. (MHz)	Factor (dB)	AV Value (dBμV/m)	AV Limit (dBμV/m)	AV Margin (dB)	Height (cm)	Angle (°)	Polarity
1	2414.7415	7.22	39.40	54.00	14.60	150	346	Vertical
2	2997.1997	8.85	39.33	54.00	14.67	150	46	Vertical
3	4959.1959	-8.84	32.64	54.00	21.36	150	240	Vertical
4	9920.1920	3.89	47.56	54.00	6.44	150	345	Vertical
5	13544.5545	10.53	44.49	54.00	9.51	150	123	Vertical
6	17851.4851	14.50	45.86	54.00	8.14	150	337	Vertical


Restriction Band Emission

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2402	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 19:45:47

Test Graph



Suspected Data List


NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Detector	Polarity
1	2370.8716	46.21	6.43	74.00	27.79	150	319	PK	Horizont
2	2390.0193	45.35	6.47	74.00	28.65	150	228	PK	Horizont

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2402	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 19:46:35

Test Graph



Suspected Data List


NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Detector	Polarity
1	2345.9020	46.91	6.37	74.00	27.09	150	287	PK	Vertical
2	2390.0193	45.10	6.47	74.00	28.90	150	19	PK	Vertical

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2480	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-07 20:00:06

Test Graph



Suspected Data List


NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Detector	Polarity
1	2483.5038	45.92	7.09	74.00	28.08	150	256	PK	Horizont
2	2487.6218	47.42	7.12	74.00	26.58	150	227	PK	Horizont

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_DH5_2480	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-07 20:00:51

Test Graph



Suspected Data List


NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Detector	Polarity
1	2483.5038	45.54	7.09	74.00	28.46	150	138	PK	Vertical
2	2485.1726	47.22	7.10	74.00	26.78	150	293	PK	Vertical

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2480	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-07 20:02:43

Test Graph



Suspected Data List


NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Detector	Polarity
1	2483.5038	44.54	7.09	74.00	29.46	150	13	PK	Horizont
2	2484.1161	47.37	7.10	74.00	26.63	150	57	PK	Horizont

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2480	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 8		
Test Standard:			

Start of Test: 2022-09-07 20:03:35

Test Graph



Suspected Data List


NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Detector	Polarity
1	2483.5038	45.32	7.09	74.00	28.68	150	25	PK	Vertical
2	2491.0075	46.85	7.15	74.00	27.15	150	217	PK	Vertical

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2402	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 20:07:13

Test Graph



Suspected Data List


NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Detector	Polarity
1	2360.3274	46.70	6.40	74.00	27.30	150	19	PK	Horizont
2	2390.0193	45.12	6.47	74.00	28.88	150	11	PK	Horizont

Test Report

Project Information			
Customer:		EUT:	Speakerphone
Model:	BM41	SN:	
Mode:	BT_2DH5_2402	Voltage:	AC120V/60Hz
Environment:	25°C/58%	Engineer:	Roger
Remark:	Power set : 9		
Test Standard:			

Start of Test: 2022-09-07 20:08:02


Test Graph




Suspected Data List

NO.	Freq. (MHz)	Level (dBμV/m)	Factor (dB)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Angle (°)	Detector	Polarity
1	2329.3741	46.30	6.33	74.00	27.70	150	150	PK	Vertical
2	2390.0193	45.06	6.47	74.00	28.94	150	225	PK	Vertical

APPENDIX C – AC Power Line Conducted Emission Test Data





END OF REPORT