

TEST REPORT

Report No.: SHATBL2402001W07

Applicant : HAMATON AUTOMOTIVE TECHNOLOGY CO.,LTD

Product Name : Vehicle Communication Interface

Brand Name : Hamaton

Model Name : RXT003

FCC ID : 2AFH7RXT003

Test Standard : 47 CFR Part 2.1093

Date of Test : 2024.02.08-2024.02.21

Report Prepared by :

Jack Suo

(Jack Suo)

Report Approved by :

Ghost Li.

(Ghost Li)

Authorized Signatory :

Terry Yang

(Terry Yang)



TABLE OF CONTENTS

REVISION HISTORY	3
DECLARATION OF REPORT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Factory	5
1.4. General Information of EUT	6
1.5. Equipment Specification	7
1.6. Modification of EUT	8
1.7. Laboratory Information	8
1.8. Applicable Standards	8
2. RF EXPOSURE EVALUATION	9
2.1. Limits for Maximum Permissible Exposure (MPE)	9
2.2. Formula	9
2.3. MPE Result	10

REVISION HISTORY

Rev.	Issue Date	Revisions	Revised by
00	2024.02.23	Initial Release	Ghost Li

DECLARATION OF REPORT

1. The device has been tested by ATBL, and the test results show that the equipment under test (EUT) is in compliance with the requirements of 47 CFR Part 2.1093. And it is applicable only to the tested sample identified in the report.
2. This report shall not be reproduced except in full, without the written approval of ATBL, this document only be altered or revised by ATBL, personal only, and shall be noted in the revision of the document.
3. The general information of EUT in this report is provided by the customer or manufacture, ATBL is only responsible for the test data but not for the information provided by the customer or manufacture.
4. The results in this report is only apply to the sample as tested under conditions. The customer or manufacturer is responsible for ensuring that the additional production units of this model have the same electrical and mechanical components.

1. GENERAL DESCRIPTION

1.1. Applicant

Name : HAMATON AUTOMOTIVE TECHNOLOGY CO.,LTD
Address : 12 East Zhenxing Road, Linping, Yuhang, Hangzhou, Zhejiang, China

1.2. Manufacturer

Name : HAMATON AUTOMOTIVE TECHNOLOGY CO.,LTD
Address : 12 East Zhenxing Road, Linping, Yuhang, Hangzhou, Zhejiang, China

1.3. Factory

Name : HAMATON AUTOMOTIVE TECHNOLOGY CO.,LTD
Address : 12 East Zhenxing Road, Linping, Yuhang, Hangzhou, Zhejiang, China

1.4. General Information of EUT

General Information	
Equipment Name	Vehicle Communication Interface
Brand Name	Hamaton
Model Name	RTX003
Series Model	RTX001
Model Difference	Only the model name is different.
SN or IMEI Code	202312080005003
Adapter	N/A
Battery	Model:HYY802050 Rated Voltage: 3.7V Charge Limit Voltage: 4.2±0.03V Capacity:800mAh
Hardware version	V1.0.4
Software version	0009
Connecting I/O Port(s)	Refer to the remark below.

Remark:

The above information of EUT was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.5. Equipment Specification

Equipment Specification		
WLAN	2.4GHz	2400 - 2483.5
Antenna Information	Antenna Type:	PCB Antenna
	Antenna Gain:	The antenna gain of all bands is 2.3 dBi.

Equipment Specification		
	433.92MHz	433.92
	315MHz	315
Antenna Information	Antenna Type:	Internal Antenna Antenna
	Antenna Gain:	The antenna gain of all bands is 1.3 dBi.

1.6. Modification of EUT

No modifications are made to the EUT during all test items.

1.7. Laboratory Information

Company Name	: Shanghai ATBL Technology Co., Ltd.
Address	: Building 8, No.160 Basheng Road, Waigaoqiao Free Trade Zone, Pudong New Area, Shanghai
Telephone	: +86(0)21-51298625

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

Standard	Description
47 CFR Part 15.247	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
47 CFR Part 2.1093	Radio frequency radiation exposure evaluation: mobile devices.
KDB 447498 D01 V06	Rf Exposure Procedures And Equipment Authorization Policies For Mobile And Portable Devices

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.

2. RF EXPOSURE EVALUATION

2.1. Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1,500			f/300	<6
1,500–100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1,500			f/1500	<30
1,500–100,000			1.0	<30

Note:

f = frequency in MHz.

* = Plane-wave equivalent power density.

2.2. Formula

Below method describes a theoretical approach to calculate possible exposure to electromagnetic radiation around a base station transceiver antenna. Precise statements are basically only possible either with measurements or complex calculations considering the complexity of the environment (e.g. soil conditions, near buildings and other obstacles) which causes reflections, scattering of electromagnetic fields. The maximum output power (given in EIRP) of a base station is usually limited by license conditions of the network operator. A rough estimation of the expected exposure in power flux density on a given point can be made with the following equation.

$$Pd_{(mW/cm^2)} = \frac{P_{(mW)} * G_{numeric}}{4 * r^2_{(cm)} * \pi}$$

Pd = Power Density

P = Maximum output power

$G_{numeric}$ = Numeric gain of the antenna relative to isotropic antenna

r = distance between the antenna and the point of exposure

2.3. MPE Result

2.3.1. For 433.92MHz,315MHz

Operating Band	Frequency (MHz)	Ant. Gain (dBi)	Max The field strength Power (dBμV/m)	EIRP/ERP (dBm)	EIRP/ERP Limit (dBm)	EIRP/ERP (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Result
433.92	433.92	1.30	71.0	-24.2	-15.06	0.0038019	7.56364E-7	0.289	Pass
315	315	1.30	56.5	-38.7	-20.98	0.0001349	2.68375E-8	0.210	Pass

Note: EIRP(dBm) = The field strength value(dBμV/m) - 95.2

2.3.2. For BLE

Operating Band	Frequency (MHz)	Ant. Gain (dBi)	EIRP/ERP (dBm)	EIRP/ERP Limit (dBm)	EIRP/ERP (mW)	Power Density at R = 20 cm (mW/cm ²)	Limit (mW/cm ²)	Result
BLE	2402	2.30	3.49	36.00	2.23	0.0044387	1.000	Pass

Note:The DUT can not realize synchronous transmission function

*****END OF THE REPORT*****