

FCC PART 15B, CLASS B TEST REPORT

For

Foream Network Technology Co, Ltd.

RM1101, Block A, building 5, Shenzhen Software Industry Base, Shenzhen, China

FCC ID: 2AFHKFD9965

Report Type:		Product Type:	
Original Report		Foream X1 wearable s	port camera
Test Engineer:	Joson Xiao	Joson	. Xiao
Report Number:	RSZ15072700	05-00	
Report Date:	2015-08-28		
Dondono d Don	Jimmy Xiao	Jimm)	/ xiao
Reviewed By:	KF Engineer		
Prepared By:	6/F, the 3rd Pl ShiHua Road,	-33320008	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

Report No.: RSZ150727005-00

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	
Objective	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST FACILITY	
SYSTEM TEST CONFIGURATION	4
DESCRIPTION OF TEST CONFIGURATION	
EUT Exercise Software	
SPECIAL ACCESSORIES	
EQUIPMENT MODIFICATIONS	
SUPPORT EQUIPMENT LIST AND DETAILS	4
External I/O Cable	5
BLOCK DIAGRAM OF TEST SETUP	5
SUMMARY OF TEST RESULTS	6
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	
APPLICABLE STANDARD	
MEASUREMENT UNCERTAINTY	
EUT Setup	
EMI TEST RECEIVER SETUP	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
CORRECTED FACTOR & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
TEST DATA	9
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	12
APPLICABLE STANDARD	12
Measurement Uncertainty	
EUT Setup	
EMI TEST RECEIVER SETUP.	
TEST PROCEDURE	
TEST EQUIPMENT LIST AND DETAILS	
CORRECTED AMPLITUDE & MARGIN CALCULATION	
TEST RESULTS SUMMARY	
Tege Data	15

TABLE OF CONTENTS

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The Foream Network Technology Co, Ltd. 's product, model number: FD9965 (FCC ID: 2AFHKFD9965) or the "EUT" in this report was a Foream X1 wearable sport camera, which was measured approximately: 177 mm (L) \times 177 mm (W) \times 27 mm (H), rated with input voltage: DC 3.7 V rechargeable Li-ion battery. The highest operating frequency is 430MHz.

Report No.: RSZ150727005-00

*All measurement and test data in this report was gathered from production sample serial number: 1505874 (Assigned by Shenzhen BACL). The EUT supplied by the applicant was received on 2015-07-27.

Objective

This test report is prepared on behalf of *Foream Network Technology Co,Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submissions with FCC ID: 2AFHKFD9965

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2013. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

FCC Part 15B, Class B Page 3 of 17

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: Downloading (data transfer with computer)

EUT Exercise Software

"BurnIn test v5.3" exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
N/A	earphone	N/A	2365284
Kingston	Micro SD card	4 GB	N/A
TCL	Monitor	TFT1560PS	ALA560S05C180409
DELL	PC	DCSCSF	127BP2X
ECOM	Modem	56000bps	21654684
LISTED	Modem adapter	TYP60-1207000Z	326703
Microsoft	Keyboard	1406	0200706128743
Microsoft	Mouse	1405	0204608630856

Report No.: RSZ150727005-00

FCC Part 15B, Class B Page 4 of 17

External I/O Cable


Cable Description	Length (m)	From / Port	То
Un-Shielded detachable AC cable	1.5	Monitor	Mains
Shielded detachable VGA cable	1.5	PC	Monitor
Un-Shielded detachable AC cable	1.2	PC	Mains
Un-Shielded Un-detachable earphone cable	1.5	Earphone	EUT
Shielded detachable USB cable	0.93	PC	EUT
Un-Shielded detachable RS232 cable	1.8	PC	Modem
Un-Shielded Un-detachable DC cable	1.7	Modem	Modem adapter
Un-Shielded detachable AC cable	1.6	Modem adapter	mains
Shielded Un-detachable USB cable	1.5	Keyboard	PC
Shielded Un-detachable USB cable	1.5	Mouse	PC

Report No.: RSZ150727005-00

Block Diagram of Test Setup

For Radiated emission:

Test Mode: Downloading



FCC Part 15B, Class B Page 5 of 17

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Spurious Emissions	Compliance

Report No.: RSZ150727005-00

FCC Part 15B, Class B Page 6 of 17

FCC §15.107 - AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.107

Measurement Uncertainty


Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between LISN/ISN and receiver, LISN/ISN voltage division factor, LISN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Report No.: RSZ150727005-00

Port	Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

The host PC, LCD Monitor and Modern Adapter were connected to a 120 VAC/60 Hz power source.

FCC Part 15B, Class B Page 7 of 17

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W	
150 kHz – 30 MHz	9 kHz	

Report No.: RSZ150727005-00

Test Procedure

During the conducted emission test, the host PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2015-06-03	2016-06-03
Rohde & Schwarz	LISN	ENV216	3560.6650.12- 101613-Yb	2014-12-01	2015-12-01
Rohde & Schwarz	LISN	ESH2-Z5	892107/021	2015-06-09	2016-06-09
Rohde & Schwarz	Transient Limitor	ESH3Z2	DE25985	2015-05-14	2016-05-14
Rohde & Schwarz	CE Test software	EMC 32	V8.53	NCR	NCR

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss + Transient Limiter Attenuation

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15B, Class B Page 8 of 17

Test Results Summary

According to the recorded data in following table, the EUT complied with the <u>FCC Part 15.107</u>, the worst margin as below:

Report No.: RSZ150727005-00

5.2 dB at 8.849190 MHz in the Line conducted mode

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{(L{\rm m})} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	26 ℃
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Joson Xiao on 2015-08-22.


FCC Part 15B, Class B Page 9 of 17

EUT operation mode: Downloading

AC 120V/60 Hz, Line

EMI Auto Test L

Report No.: RSZ150727005-00




Frequency (MHz)	Corrected Amplitude (dBµV)	Corrected Factor (dB)	Limit (dBµV)	Margin (dB)	Remark (PK/QP/Ave.)
8.849190	46.1	20.1	60.0	13.9	QP
8.849190	44.8	20.1	50.0	5.2	Ave.
8.854810	43.3	20.1	60.0	16.7	QP
8.854810	38.8	20.1	50.0	11.2	Ave.
9.247190	47.2	20.1	60.0	12.8	QP
9.247190	36.8	20.1	50.0	13.2	Ave.
9.253630	44.7	20.1	60.0	15.3	QP
9.253630	43.1	20.1	50.0	6.9	Ave.
9.549190	43.5	20.1	60.0	16.5	QP
9.549190	39.8	20.1	50.0	10.2	Ave.
9.647690	44.9	20.1	60.0	15.1	QP
9.647690	34.4	20.1	50.0	15.6	Ave.

FCC Part 15B, Class B Page 10 of 17

AC 120V/60 Hz, Neutral

EMI Auto Test N

Report No.: RSZ150727005-00



Frequency (MHz)	Corrected Amplitude (dBµV)	Corrected Factor (dB)	Limit (dBµV)	Margin (dB)	Remark (PK/QP/Ave.)
1.105410	38.4	20.0	56.0	17.6	QP
1.105410	38.8	20.0	46.0	7.2	Ave.
8.440870	43.5	20.1	60.0	16.5	QP
8.440870	41.9	20.1	50.0	8.1	Ave.
9.243310	43.9	20.1	60.0	16.1	QP
9.243310	40.4	20.1	50.0	9.6	Ave.
9.754250	40.4	20.1	60.0	19.6	QP
9.754250	37.7	20.1	50.0	12.3	Ave.
16.394470	41.0	20.1	60.0	19.0	QP
16.394470	31.5	20.1	50.0	18.5	Ave.
18.592710	39.1	20.1	60.0	20.9	QP
18.592710	34.7	20.1	50.0	15.3	Ave.

Note:

FCC Part 15B, Class B Page 11 of 17

¹⁾ Correction Factor =LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation The corrected factor has been input into the transducer of the test software.

²⁾ Corrected Amplitude = Reading + Correction Factor
3) Margin = Limit – Corrected Amplitude

FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard

FCC §15.109

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Report No.: RSZ150727005-00

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown in below table. And the uncertainty will not be taken into consideration for the test data recorded in the report

Frequency	Polarity	Measurement uncertainty
30 MHz~200 MHz	Horizontal	4.62 dB (k=2, 95% level of confidence)
30 MHZ~200 MHZ	Vertical	4.54 dB (k=2, 95% level of confidence)
200 MHz∼1 GHz	Horizontal	4.84 dB (k=2, 95% level of confidence)
200 MHZ~1 GHZ	Vertical	5.91 dB (k=2, 95% level of confidence)
1 GHz~6 GHz	Horizontal/Vertical	4.68 dB (k=2, 95% level of confidence)
Above 6 GHz	Horizontal/Vertical	4.92 dB (k=2, 95% level of confidence)


EUT Setup

Below 1GHz:



FCC Part 15B, Class B Page 12 of 17

Above 1GHz:



Report No.: RSZ150727005-00

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The host PC, LCD Monitor and Modem Adapter wre connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 2 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector	
30 MHz – 1000 MHz	MHz 100 kHz 300 kHz		120 kHz	QP	
Above 1 GHz	1MHz	3 MHz	/	PK	
	1MHz	10 Hz	/	Ave.	

FCC Part 15B, Class B Page 13 of 17

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Report No.: RSZ150727005-00

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK and average detector modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date	
НР	Amplifier	HP8447E	1937A01046	2015-05-06	2016-05-06	
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2014-11-03	2015-11-03	
Sunol Sciences	Bi-log Antenna	ЈВ1	A040904-2	2014-12-07	2017-12-06	
A.H. System	Horn Antenna	SAS-200/571	135	2015-02-10	2018-02-10	
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2014-12-11	2015-12-11	
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2015-04-23	2016-04-23	
TDK	Chamber	Chamber A	2#	2015-10-15	2018-10-15	
TDK	Chamber	Chamber B	1#	2015-07-22	2018-07-22	
R&S	Auto test Software	EMC32	V9.10	NCR	NCR	

^{*} Statement of Traceability: Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

FCC Part 15B, Class B Page 14 of 17

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B, the worst margin reading as below:

Report No.: RSZ150727005-00

4.23 dB at 30.013125 MHz in the Vertical polarization

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_{\rm m} + U_{\rm (Lm)} \leq L_{\rm lim} + U_{\rm cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	26 ℃		
Relative Humidity:	55 %		
ATM Pressure:	101.0 kPa		

The testing was performed by Joson Xiao on 2015-08-22.


FCC Part 15B, Class B Page 15 of 17

EUT operation mode: Downloading

30 MHz~1 GHz

Full Spectrum

Report No.: RSZ150727005-00



Frequency (MHz)	Corrected Amplitude (dBµV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (deg)	Correction Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
30.013125	35.77	383.0	V	304.0	-5.9	40.00	4.23
35.621875	24.97	114.0	V	287.0	-10.6	40.00	15.03
240.077625	33.97	117.0	Н	136.0	-14.8	46.00	12.03
287.994875	40.40	126.0	Н	251.0	-12.6	46.00	5.60
336.009000	40.69	117.0	Н	152.0	-12.0	46.00	5.31
432.007125	37.65	108.0	Н	303.0	-10.0	46.00	8.35

FCC Part 15B, Class B Page 16 of 17

Above 1G:

Frequency (MHz)	Reading (dBµV)	Detector (PK/QP/Ave.)	Turntable Degree	Height (m)	Polar (H/V)	Correction Factor (dB/m)	Corrected Amplitude (dBµV/m)	Limit (dBμV/m)	Margin (dB)
1899.79	30.09	PK	291	1.2	Н	2.63	32.72	74	41.28
1899.79	19.94	Ave.	291	1.2	Н	2.63	22.57	54	31.43
1601.20	30.57	PK	192	1.5	V	1.7	32.27	74	41.73
1601.20	21.25	Ave.	192	1.5	V	1.7	22.95	54	31.05

Report No.: RSZ150727005-00

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss amplifier factor
- 2) Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit Corrected Amplitude

***** END OF REPORT *****

FCC Part 15B, Class B Page 17 of 17