



BUREAU
VERITAS

Test Report No.: FS170111N040

RF EXPOSURE REPORT

Applicant	INNOVATIVE TECHNOLOGY ELECTRONICS LLC
Address	1 CHANNEL DRIVE, PORT WASHINGTON, NY 11050, USA

Manufacturer or Supplier	Guangdong Leetac Electronics Technology Co., Ltd.
Address	No.15 Danli Road, South District, Zhongshan, Guangdong, China.
Product	BRIGHT TUNES
Brand Name	Innovative Technology, Victrola, Bright Tunes
Model	BRT-401-WEE-12
Additional Model & Model Difference	BRT-401-EEE-12, BRT-401-xy-z, see item 1.
Date of tests	Jan. 11, 2017 ~ Mar. 28, 2017

FCC Part 2 (Section 2.1091)

KDB 447498 D01

IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Tom Chen Project Engineer / EMC Department	Approved by Glyn He Supervisor/ EMC Department

Date: Apr. 01, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



BUREAU
VERITAS

Test Report No.: FS170111N040

Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



**BUREAU
VERITAS** Test Report No.: FS170111N040

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS170111N040	Original release	Apr. 01, 2017



1. CERTIFICATION

FCC ID:	2AFHW-BRTUN
PRODUCT:	BRIGHT TUNES
BRAND NAME:	Innovative Technology, Victrola, Bright Tunes
MODEL NO.:	BRT-401-WEE-12
ADDITIONAL NO.:	BRT-401-EEE-12, BRT-401-xy-z
APPLICANT:	INNOVATIVE TECHNOLOGY ELECTRONICS LLC
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

NOTE:

1. Additional models BRT-401-EEE-12, BRT-401-xy-z are identical with the test model BRT-401-WEE-12 except with different the color of the light string, the color or the shape of cosmetic decoration that is attached to strand and the numbers of lamps
No., brand name for trading purpose.
 1. Basic model: BRT-401-WEE-12
 2. Alternative model: BRT-401-EEE-12, BRT-401-xy-z
(where "x" can be replaced by digit 0-1 or letter A-Z indicate the color of the light string;
"y" can be replaced by 1 or 2 digit alphanumeric (0-9, A-Z) to indicate the color or shape of cosmetic decoration that is attached to strand;
"z" can be replaced by digit 7 or above indicate the numbers of lamps.)
3. Innovative Technology, Victrola and Bright Tunes can be used for all the models.



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$Pd = (Pout * G) / (4 * \pi * r^2)$$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	0	Integral PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
2402-2480	-5	+2	-7	-3

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
GFSK	2402	-4.24
8DPSK	2402	-4.99

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2402-2480	-3	0	20	0.0001	1.0

--- END ---