## RF Exposure evaluation

According to KDB 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] • [ $\sqrt{f(GHz)}$ ]  $\leq$  3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- ${}^{\bullet}$  Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

```
eirp = pt x gt = (EXd)^2/30

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10^6

d = measurement distance in meters (m)---3m

So pt = (EXd)^2/30 x gt
```

Field strength = 95.87 dBuV/m @3m

Ant gain OdBi; so Ant numeric gain=1

So pt={ $[10^{(95.87/20)}/10^6x3]^2/30x1$ }x1000mW =1.16 mWSo (1.16 mW/5mm) x  $\sqrt{2.402GHz}$  = 0.36<3

Then SAR evaluation is not required