

## SAR evaluation

MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well

as the gain of the used antenna, the RF power density can be obtained.

Calculated Result and Limit (WORSE CASE IS AS BELOW)

### WIFI

Directional AntennaGain (Numeric)	Peak Output Power (mW)	Power Density (S)(mW/cm <sup>2</sup> )	Limit of Power Density (S)(mW/cm <sup>2</sup> )	Test Result
1.55 (1.91dBi)	147.231 (21.68dBm)	0.045	1	Compiles

### ZIGBEE

Directional AntennaGain (Numeric)	Peak Output Power (mW)	Power Density (S)(mW/cm <sup>2</sup> )	Limit of Power Density (S)(mW/cm <sup>2</sup> )	Test Result
1.585 (2dBi)	2.972 (4.73dBm)	0.000938	1	Compiles

$$0.045 + 0.000938 = 0.045938 < 1$$